Accepted Manuscript

Title: The potential of manganese nitride based materials as nitrogen transfer reagents for nitrogen chemical looping

Authors: Said Laassiri, Constantinos D. Zeinalipour-Yazdi, C. Richard A. Catlow, Justin S.J. Hargreaves



Please cite this article as: Said Laassiri, Constantinos D.Zeinalipour-Yazdi, C.Richard A.Catlow, Justin S.J.Hargreaves, The potential of manganese nitride based materials as nitrogen transfer reagents for nitrogen chemical looping, Applied Catalysis B, Environmentalhttp://dx.doi.org/10.1016/j.apcatb.2017.04.073

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



The potential of manganese nitride based materials as nitrogen transfer reagents for nitrogen chemical looping

Said Laassiri^a, Constantinos D. Zeinalipour-Yazdi^b, C. Richard A. Catlow^b and Justin S. J. Hargreaves.*^a

^aWestCHEM, School of Chemistry, University of Glasgow, Glasgow G12 8QQ, UK

^bKathleen Lonsdale Materials Chemistry, Department of Chemistry, University College London, 20 Gordon Street, London, WC1H 0AJ, UK

*Corresponding author: <u>Justin.Hargreaves@glasgow.ac.uk</u>

Graphical abstract



Highlights

- Manganese nitride materials were prepared using a molten salt technique
- Lattice nitrogen reactivity was studied using the ammonia synthesis reaction
- Ammonia synthesis occurs via a mechanism akin to the Mars van Krevelen mechanism
- Adding lithium to the system improved the reactivity of lattice nitrogen

Abstract.

A systematic study was carried out to investigate the potential of manganese nitride related materials for ammonia production. A-Mn-N (A= Fe, Co, K, Li) materials were synthesised by nitriding their oxide counterparts at low temperature using NaNH₂ as a source of reactive nitrogen. The reactivity of lattice nitrogen was assessed using ammonia synthesis as a model reaction. In the case of Mn_3N_2 , limited reactivity was observed and only 3.1% of the available

lattice nitrogen was found to be reactive towards hydrogen to yield ammonia while most of the lattice nitrogen was lost as N_2 . However, the presence of a co-metal played a key role in shaping the nitrogen transfer properties of manganese nitride and impacted strongly upon its reactivity. In particular, doping manganese nitride with low levels of lithium resulted in enhanced reactivity at low temperature. In the case of the Li-Mn-N system, the fraction of ammonia formed at 400°C corresponded to the reaction of 15% of the total available lattice nitrogen towards hydrogen. Li-Mn-N presented high thermochemical stability after reduction with hydrogen which limited the regeneration step using N_2 from the gas phase. However, the results presented herein demonstrate the Li-Mn-N system to be worthy of further attention.

Keywords

Manganese nitride, ammonia production, nitrogen mobility, chemical looping

1. Introduction

The production of the vast majority of nitrogen containing organic products requires the use of nitrogen building blocks such as HCN, HNO₃ or NH₃ as a source of reactive nitrogen. (*e.g.* aniline synthesis [1, 2], Paal-Knorr pyrrole synthesis [3, 4]). During the last century, major breakthroughs in reactive nitrogen production have been achieved through the development of several industrial processes: the Haber-Bosch Process [5], the Andrussow Process [6] and the Ostwald Process [7]. However, producing reactive nitrogen is highly demanding in energy and requires the construction of centralized, capital intensive plants. The Haber-Bosch Process, the industrial process for ammonia generation from H₂ and N₂, is probably the most explicit example. Due to the low equilibrium conversion at ambient pressure, the process is conducted under intensive energy consuming conditions (temperature ca. 400-500°C and pressure ca.150-200 atm) to ensure acceptable process rates [8]. Even in such extreme conditions, dinitrogen and

dihydrogen conversion is only partial and un-reacted gases need to be re-circulated. Moreover, the process requires the use of highly purified reactant to avoid catalyst deactivation which adds greater complexity. Considering the environmental and energetic costs of nitrogen fixation reactions, developing more sustainable and economical routes which could be applied in more local context is of critical interest.

In this context, the development of nitrogen transfer reactions from metal nitrides to generate "on demand" in-situ reactive nitrogen under mild conditions constitutes a tantalizing alternative. This approach is based on the mobility of lattice nitrogen and its possible transfer through mechanisms analogous to the Mars-van Krevelen one. Lattice nitrogen reactivity is precedented and studies on nitrogen reactivity of binary nitride metals and their reduction using dihydrogen to yield ammonia at ambient pressure are established in the literature [9, 10]. Ternary cobalt molybdenum nitride was also reported for its high nitrogen mobility and its ability to be reduced from Co₃Mo₃N to Co₆Mo₆N under H₂ atmosphere to generate ammonia under ambient pressure [11]. Related to this concept, Mg₃N₂ has been studied as source of in-situ reactive nitrogen in order to circumvent the use of an external supply of ammonia for the Paal-Knorr pyrrole reaction [12, 13]. The ability of some metals to accommodate nitrogen in their structure that could afterwards be available for reaction is of interest for diverse processes including catalytic [14], photocatalytic [15-17] and electrocatalytic [18] ammonia synthesis, particularly if that lattice N-can derived from an N₂ source.

Nitrogen chemical looping using nitride materials as nitrogen transfer reagents is an attractive approach to develop combined nitrogen production in a decentralized manner. In this approach lattice nitrogen can be discharged upon reaction and recharged in a second separated step under different reaction conditions which could alleviate thermodynamic limitations. In such a scheme

lattice nitrogen mobility and reactivity under mild conditions are decisive factors for the appropriate choice of the looping material. In recent work, tantalum nitride has been reported as a highly active nitrogen transfer reagent when doped with cobalt. 52% of the total available lattice nitrogen was found to be reactive to hydrogen at ambient pressure to yield ammonia. Post reaction elemental analysis confirmed the reduction of N- content in this material from 8.54 wt.% to 3.04 wt.%. Thus, almost 80% of N- lost during the reaction reacted with H₂ to produce ammonia [19]. Manganese nitride was studied for solar ammonia production where the metal nitride is obtained by dinitrogen reduction at high temperature and subsequently hydrolysed to yield ammonia [20]. The ability of manganese to activate N₂ under ambient pressure to form a range of manganese nitrides [21-22] as presented in Figure 1 is of relevant interest for the possible development to nitrogen chemical looping reactions. Although manganese nitride is better described as a regenerable reagent in this context, very recent work has reported manganese nitride to be a highly active catalyst for ammonia synthesis at 350°C when LiH is added as a co-catalyst [23]. However, to date, there is little data relating to the reactivity of the lattice nitrogen in manganese nitride based materials available and the present study aims to address this issue.

Direct reduction using H₂ to yield ammonia has been targeted and the role of dopant metals assessed. The results presented are therefore of interest in both context of development of manganese nitride based N- chemical looping as well as ammonia synthesis catalysed by manganese nitride based systems.

2. Experimental section

2.1. Materials synthesis

2.1.1. Preparation of Mn_3N_2

Manganese nitride was prepared using a NaNH₂ molten salt synthesis procedure as described in reference [24]. In a typical reaction 0.3g of Mn₂O₃ (Sigma Aldrich, 99 %) and 1.0g of NaNH₂ (Sigma Aldrich, 98 %) were loaded into a Teflon-lined steel autoclave inside a nitrogen-filled glovebox. The autoclave was tightly closed and kept in an oven at 240°C for 36 h. The product was then collected by filtration, and washed with ethanol and water, and dried overnight at room temperature.

2.1.2. Preparation of A-Mn-N materials (A = Li, K, Fe and Co)

A-Mn-O, A= Li, K, Fe and Co systems, with A/Mn molar ratios equal to 1, were prepared by a conventional co-precipitation route, using ammonia as precipitation agent, followed by calcination under static air at 800°C for 8h [25]. The nitride phase was then prepared in a similar manner to Mn_3N_2 .

2.2. Physical and textural characterisation

Elemental analysis. Nitrogen analysis was undertaken by combustion using an Exeter Analytical CE-440 Elemental Analyser. Error calculations have been performed statistically by repeating the measurement at least twice.

X-ray diffraction. Diffraction patterns were collected on a Siemens D5000 instrument, using CuK α radiation ($\lambda = 0.154$ nm) as X-ray source. Recording was performed for between 10° and 80° 2θ (step time = 120 s; step size = 0.02°). Samples were prepared by compaction into Si sample holders. Phase identification is obtained by comparison with JCPDS database files.

Surface area measurement. Surface areas were determined from N₂ physisorption measurements at -196°C upon samples previously degassed at 120°C under vacuum for 12h. The specific

surface areas, S_{BET}, were calculated by applying the Brunauer-Emmett-Teller equation.

Scanning electron microscopy. Scanning electron microscopy was performed on Philips XLSEMand FEI Quanta 200F Environmental instruments operating at 20 kV. Samples were coated using Au/Pd alloy before SEM imaging.

2.3. Nitrogen transfer properties

The nitrogen transfer properties of manganese based materials were evaluated using ammonia synthesis as a model reaction.

In a typical reaction test, 0.3 g of nitride was placed in the reactor and was pre-treated for 2h at 400°C under a 75 vol.% H₂ in N₂ (BOC, 99.98%) gas mixture. The reaction was then performed under a flow composed either of 75 vol.% H₂ in N₂ or 75 vol.% H₂ in Ar (BOC, 99.98%) at a total gas feed of 60 NTP ml min⁻¹. Ammonia production was determined by measurement of the decrease in conductivity of a 200 ml 0.0018 M H₂SO₄ solution through which the reactor effluent stream flowed. The NH₃ yield is reported as the molar ratio of NH₃ generated after a given time (t) relative to the total lattice nitrogen. A schematic of the reactor set up is presented in the supplementary information

Furthermore, ammonia production was confirmed using potassium tetraiodomercurate (Nessler's reagent, Sigma Aldrich) for selected reactions. Error propagation analyses have been performed and are reported for each experiment.

3. Results and discussion

3.1. Structural and textural properties of manganese nitride based materials

XRD patterns and SEM images of the various materials investigated are presented in Figures 2-6 and Table 1 summarises the structural and textural properties of the prepared nitrides.

3.1.1. Preparation of Mn_3N_2

The XRD pattern recorded after the reaction of Mn_2O_3 with NaNH₂ at 240°C is presented in Figure 2. All detected reflections matched the tetragonal Mn_3N_2 (PDF number: 01-074-8391). Moreover, the nitrogen content evaluated by elemental analysis was 14.99 % wt which is close to that expected based upon stoichiometry (14.53 wt %). From SEM observations, a significant modification in the morphology was observed upon nitridation (Figure 3). Whilst large micrometric crystals are observed by SEM for Mn_2O_3 , large aggregates of smaller Mn_3N_2 were apparent. It is worth mentioning that all attempts to nitride Mn_2O_3 by ammonolysis were unsuccessful and Mn_2O_3 reduction at high temperature resulted in MnO (Figure S.3).

3.1.2. Preparation of A-Mn-N (A= Fe, Co) materials

Fe-Mn-O and Co-Mn-O oxides were prepared, as precursors for nitridation, by a conventional co-precipitation method followed by calcination at 800°C for 8h. XRD patterns of these oxide precursors are presented in Figure 4. Tetragonal cobalt manganese spinel CoMn₂O₄ (PDF number: 00-055-068) was identified along with Co₂MnO₄ (PDF number: 00-023-1237) as the predominant phases in the Co-Mn-O system. No extra-phases related to simple manganese or cobalt oxides were observed (Fig 4-a). In contrast, only Fe₂O₃ (PDF number: 01-085-0987) and Mn₂O₃ (PDF number: 01-078-0390) were observed in the Fe-Mn-O system and no spinel formation was evidenced by XRD (Fig 4-b).

Upon nitridation, significant textural and structural modifications were observed in both systems. Surprisingly, the nitridation of Co-Mn-O and Fe-Mn-O resulted in X-ray amorphous materials (Figures 5-a and 5-b). Only weak XRD reflections related to Fe₂O₃ (PDF number: 00-002-1165)

were observed in the Fe-Mn-O system which may be related to the presence of un-reacted Fe₂O₃. Nevertheless, the strong fluorescence of iron and cobalt induced by the use of copper radiation may strongly influence the XRD line and background intensities thereby hindering phase identification. The nitrogen content of the nitrides was evaluated by elemental analysis. When compared to Mn_3N_2 , Fe-Mn-N and Co-Mn-N presented lower nitrogen concentration (10.8±0.1 wt % for Fe-Mn-N and 13.4±0.2 wt % for Co-Mn-N.) Also a significant decrease of the surface area was observed upon second metal addition (66 m².g⁻¹ for Mn_3N₂, 36 m².g⁻¹ for Fe-Mn-N and 39 m².g⁻¹ for Co-Mn-N).

3.1.3. Preparation of A-Mn-N (A=Li, K) materials

In a similar manner to above, A-Mn-N (A=Li, K) materials were prepared using the oxide counterparts as precursors for nitridation. XRD patterns recorded for the oxide are presented in Figure 6. For K-Mn-O, all reflections relate to KMnO₄ (PDF number 00-001-0725) while the Li-Mn-O system was identified to comprise a mixture of LiMn₂O₄ (PDF number: 00-018-0736) and of LiO₂ (PDF number: 01-073-7127) However, after the nitridation step only the tetragonal Mn₃N₂ (PDF number: 01-074-8391) was apparent, and no characteristic reflections related to other transition metal nitride or oxide phases were detected (Figure 7). A small shift towards higher angle is observed for the Li-Mn-N system, when compared to Mn₃N₂, indicating a possible change of lattice parameters. Most of the lithium was found to be lost during nitridation reaction. However, post-nitridation analysis confirmed the presence of lithium in the final products (Mn to Li molar ratio of about 1:10). The effect of alkali metal addition was more apparent upon the textural properties. A significant decrease of the surface areas of the A-Mn-N materials was observed upon alkali metal addition and an effect upon the nitrogen content was

also observed (Table 1.) When compared to Mn_3N_2 , the Li-Mn-N system showed lower nitrogen content (12.1±0.2 wt %) while a slightly higher content of nitrogen was measured for K-Mn-N (16.9±0.1 wt %).

3.2. Reactivity of Mn₃N₂ related system for ammonia generation

3.2.1. Reactivity of Mn₃N₂

The reactivity of Mn₃N₂ lattice nitrogen was investigated using ammonia synthesis as a model reaction using a 60 ml min⁻¹ of 3:1 H₂:N₂ (BOC, H₂ 99.998%, N₂ 99.995%). Ammonia production as function of time at 400°C is presented in Figure 8. Over 6 hours of reaction, a very limited amount of ammonia, ca 256 μ mol. NH₃/g of material, was produced which corresponded to the reaction of 3.1% of the available lattice nitrogen to dihydrogen (Table 2). Post-reaction analysis revealed that 76 % of lattice nitrogen was liberated after 6 hours of reaction. However, only 3.1% of the lattice nitrogen was reactive towards H₂ to yield NH₃, suggesting that ca. 73% was lost as N₂. Nevertheless, the loss of the vast majority of the lattice nitrogen of Mn_3N_2 at 400 °C contrasts with the thermochemical stability of Mn₄N and Mn₆N_{2.85} reported elsewhere [20]. Differences in crystalline structure and textural and structural properties prepared by different synthesis methods could affect the nitrogen reactivity. The decrease in the lattice nitrogen during the ammonia synthesis reaction confirms the ability of Mn₃N₂ to act as a nitrogen transfer material, although it is not a true catalyst, but rather a reactant in this context., since as reported later in this manuscript (Figure 12), measurements conducted under 1:3 Ar: H_2 presented very similar results.

3.2.2. Reactivity of A-Mn-N (A= Fe, Co)

To study the effect of transition metal in Mn_3N_2 lattice nitrogen reactivity, A-Mn-N, (A= Fe, Co) systems were prepared and tested for ammonia synthesis (Table 2, Figure 9). Upon iron addition, ammonia synthesis was inhibited and only a very limited amount was produced ca. 138 µmol NH₃/g over 6h. However, post-reaction elemental analysis showed a considerable reduction of nitrogen content to 0.1 wt %. The amount of ammonia generated corresponded to the consumption of 1.8% of available lattice nitrogen which suggests that iron accelerated lattice nitrogen depletion as N₂ rather than the reaction with H₂. Elsewhere in the literature, the presence of Fe has been reported to destabilise the Mn-N bond in Mn₆N_{2.58} and Mn₄N enhancing decomposition and leading to lower NH₃ yields upon reaction with H₂ [20,26]. In the present study, similar result to that obtained for the iron containing system was obtained upon cobalt addition and only limited amount of ammonia was produced after 6h of reaction ca.273 µmol/g.

3.2.3. Reactivity of A-Mn-N (A= K, Li)

The effect of alkali metal on Mn_3N_2 lattice nitrogen reactivity was studied for Li and K containing materials A-Mn-N (Table 2, Figure 10). Upon potassium addition, ammonia synthesis was strongly suppressed and only a very limited amount was produced during the first two hours of reaction. In spite of potassium being reported as an efficient promoter for iron [27] and rhenium [28] based catalysts no enhancement on the reactivity of Mn_3N_2 was observed. In contrast, the nitrogen transfer properties were considerably enhanced when lithium was used as co-metal. ~ 1306±44 µmol NH₃/g is generated during the first 5h of reaction and a total of ~ 1571±53 µmol NH₃/g was generated after 15h. The quantity of ammonia produced at the end of reaction corresponds to the reaction of 18% of the total available lattice nitrogen compared initially to 3.1% in Mn₃N₂. Furthermore, post-reaction CHN analysis confirmed the reduction of N- content in the Li-Mn-N system to 0.5 wt %.

The temperature dependence of nitrogen reactivity was assessed by conducting ammonia synthesis reaction at different temperatures (Figure 11, Table 3). At low temperature, $T = 300^{\circ}C$, the material demonstrated high nitrogen reactivity as evidenced by the significant amount of ammonia produced ~ 1400±48 µmol NH₃/g which corresponded to ~ 16% of the total available lattice nitrogen. Conducting ammonia synthesis reaction at higher temperature, $T = 500^{\circ}C$, resulted in considerable enhancement of the amount of ammonia generated to ~ 2072±70 µmol NH₃/g which corresponded to the consumption of ~ 24% of the total available lattice nitrogen. However, most of the ammonia was generated during the first two hours of reaction and only a small amount of ammonia was produced thereafter.

3.2.4. Nitrogen charge-discharge properties of Li-Mn-N

The regenerability of the Li-Mn-N system was examined by alternating dintridation (Ndischarge) and nitridation (N- charge) cycles under different conditions (Figure 12). The reduction step was conducted using 60 ml min⁻¹ flow of a 1:3 Ar: H₂ at 400°C while the nitridation step was conducted using 60 ml min⁻¹ flow of N₂ at 800°C. Figure 13 shows the reactivity of the Li-Mn-N system over three cycles. During the first reduction cycle, high reactivity was observed and ~ 1738±59 NH₃ µmol/g was generated after 5h of reaction. However, when subject to a regeneration step under a flow of N₂ at 800°C for 5h, Li-Mn-N presented limited reactivity and only a small amount of ammonia 304±10 µmol NH₃/g and 159±5 µmol NH₃/g was generated after the second and the third cycles respectively. Despite

efforts to close the thermochemical ammonia production cycle by regenerating the material using N_2 at high temperature, elemental analysis showed consumption of lattice nitrogen after the denitriding - nitriding cycles. Prolonging the regeneration step to 12h did not affect the regenerability of Li-Mn-N system and no further regain of reactivity was observed during the third cycle of reduction. A decrease of 24% of lithium concentration with respect to the initial concentration of Li in Li-Mn-N system was observed after the denitridation-nitridation cycles.

3.3. Nitrogen bulk transfer properties on manganese related material

The dependence of nitrogen transfer properties upon chemical composition and temperature was evaluated using ammonia synthesis as a model reaction. In view of the reactivity results and post reaction analysis, ammonia synthesis proceeds through a process akin to the Mars - van Krevelen mechanism involving lattice nitrogen reaction. Thus, the amount of ammonia produced during reactivity test can be linked to lattice nitrogen transfer properties of manganese related materials as: A-Mn-N_x+ $3/2\delta H_2 \rightarrow A-Mn-N_{x-\delta}+\delta NH_3$

In Mn_3N_2 , lattice nitrogen reactivity was evidenced by the ammonia synthesis reaction. Unfortunately only a very limited fraction was reactive towards dihydrogen and most of the lattice nitrogen was lost as N_2 . Adding a co-metal to manganese nitride provided a route to alter lattice N- reactivity. However, the addition of cobalt, iron or potassium resulted only in enhancing lattice nitrogen depletion as N_2 . However, adding low levels of lithium improved considerably the reactivity of manganese lattice nitrogen towards hydrogen at low temperature. Since lattice nitrogen reactivity has been evidenced in all the A-Mn-N systems, the higher reactivity of Li-Mn-N possibly could be attributed to dihydrogen activation by lithium. The role

of lithium in enhancing the performance of materials is an area currently undergoing further investigation. In this context, it is interesting to draw intention to a similar positive effect of LiH addition to Mn₂N activity for ammonia synthesis as recently reported by Chen and co-workers [23]. The authors presented a "two-active centre catalyst", where lithium's role was to remove N_{ad} from the surface and activate the hydrogenation step whereas the Mn(N) surface activates N_2 in a continuous manner. LiH-Mn, Mn to LiH molar ratio of about 1:5, was presented as highly active catalyst for ammonia synthesis reaction and showed stability during 10h of reaction. In our case, Li-Mn-N (Mn to Li molar ratio of about 1:10) behaved more as a nitrogen transfer reagent rather than a catalyst with ~ 16% of its lattice nitrogen being reactive towards dihydrogen to yield ammonia at temperatures as low as 300°C. The reactivity of in the Li-Mn-N system was maintained up to complete depletion of lattice nitrogen which was only achieved after 16h of reaction (Figure 13). As ammonia production proceeds in the Li-Mn-N system through a pathway akin to the Mars van Krevelen mechanism, it is possible that the ratedetermining step for NH₃ synthesis during the denitridation cycle is nitrogen transfer from the lattice to the surface which might explain the higher rates reported on Li-Mn-N systems when compared to classical formulations. However, the results of denitridation-nitridation cycles suggest that the limiting step of the overall process is associated with regeneration of the looping materials with N₂. In order to further explore this aspect, the role of dopant in the activation of nitrogen and hydrogen during the different cycles is currently under investigation by means of isotopic exchange reactions.

Another, indirect, aspect of our studies is that they illustrate the necessity for prolonged activation testing and post-reaction N- analysis when applying nitrides to ammonia synthesis. Initial cursory information may suggest that systems are catalytic when, in fact, they may not and

may be functioning as reagents.

Conclusion

In this work, manganese related materials A-Mn-N, A= Fe, Co, K, Li systems, were synthesised by a soft chemistry synthesis technique using NaNH₂ as a source of reactive nitrogen. The impact of chemical composition upon lattice nitrogen reactivity was studied. Although, lattice nitrogen mobility has been evidenced in all the A-Mn-N systems, only Li-Mn-N presented high nitrogen reactivity towards hydrogen which may be attributed to dihydrogen activation by lithium. Reactivity tests and post-reaction analysis confirmed that A-Mn-N systems are better described as reagents than proper catalytic system.

Acknowledgements

We are grateful to M. G. Reddy for very kindly conducting the nitrogen elemental analyses. We are grateful to the Engineering and Physical Sciences Research Council through the provision of funding through grants EP/L02537X/1 and EP/L026317/1.

Reference

[1] S. Enthaler, ChemSusChem 3 (2010) 1024-1029.

[2] D.M. Roundhill, Chem. Rev. 92 (1992) 1-27.

[3] P.B. Cranwell, M. O'Brien, D.L. Browne, P. Koos, A. Polyzos, M. Pena-Lopez, S.V. Ley,Organic & Biomolecular Chemistry 10 (2012) 5774-5779.

[4] V. Amarnath, D.C. Anthony, K. Amarnath, W.M. Valentine, L.A. Wetterau, D.G. Graham, The Journal of Organic Chemistry 56 (1991) 6924-6931.

[5] A. Mittasch, Advances in Catalysis and Related Subjects, Volume II (1950) 81-104.

[6] L. Andrussow, Angewandte Chemie 48 (1935) 593-595.

[7] O. Wilhelm, Improvements in the Manufacture of Nitric Acid and Nitrogen Oxides, 1902.

[8] Y. Tanabe, Y. Nishibayashi, Coordination Chemistry Reviews 257 (2013) 2551-2564.

[9] A.M. Alexander, J.S.J. Hargreaves, C. Mitchell, Top Catal 56 (2013) 1963-1969.

[10] A.M. Alexander, J.S.J. Hargreaves, C. Mitchell, Top Catal 55 (2012) 1046-1053.

[11] S.M. Hunter, D.H. Gregory, J.S.J. Hargreaves, M. Richard, D. Duprez, N. Bion, ACS Catalysis 3 (2013) 1719-1725.

[12] S.V. Ley, L.A. Paquette, Journal of the American Chemical Society 96 (1974) 6670.

[13] G.E. Veitch, K.L. Bridgwood, K. Rands-Trevor, S.V. Ley, Synlett (2008) 2597-2600.

[14] C.D. Zeinalipour-Yazdi, J.S.J. Hargreaves, C.R.A. Catlow, The Journal of Physical Chemistry C 119 (2015) 28368-28376.

[15] D. Zhu, L. Zhang, R.E. Ruther, R.J. Hamers, Nature Materials 12 (2013) 836-841.

[16] J.R. Christianson, D. Zhu, R.J. Hamers, J.R. Schmidt, The Journal of Physical Chemistry B 118 (2014) 195-203.

[17] J. Soria, J.C. Conesa, V. Augugliaro, L. Palmisano, M. Schiavello, A. Sclafani, The Journal of Physical Chemistry 95 (1991) 274-282.

[18] Y. Abghoui, A.L. Garden, J.G. Howalt, T. Vegge, E. Skúlason, ACS Catalysis 6 (2016) 635-646.

[19] S. Laassiri, C.D. Zeinalipour-Yazdi, C.R.A. Catlow, J.S.J. Hargreaves, Catalysis Today 286 (2017) 147-154.

[20] R. Michalsky, A.M. Avram, B.A. Peterson, P.H. Pfromm, A.A. Peterson, Chemical Science 6 (2015) 3965-3974.

[21] M.D. Lyutaya, A.B. Goncharuk, Soviet Powder Metallurgy and Metal Ceramics 16 (1977) 208-212.

[22] R. Yu, X. Chong, Y. Jiang, R. Zhou, W. Yuan, J. Feng, RSC Advances 5 (2015) 1620-1627.

[23] P. Wang, F. Chang, W. Gao, J. Guo, G. Wu, T. He, P. Chen, Nat Chem 9 (2017) 64-70.

[24] A. Miura, T. Takei, N. Kumada, Inorganic Chemistry 52 (2013) 11787-11791.

[25] C.S. Johnson, N. Li, C. Lefief, J.T. Vaughey, M.M. Thackeray, Chemistry of Materials 20 (2008) 6095-6106.

[26] R. Michalsky, P.H. Pfromm, A. Steinfeld, Interface Focus 5 (2015) 2014.0084

[27] G. Ertl, M. Weiss, S.B. Lee, Chemical Physics Letters 60 (1979) 391-394.

[28] C. Liang, Z. Wei, Q. Xin, C. Li, Applied Catalysis A: General 208 (2001) 193-201.





Mn₃N₂- Tetragonal

Mn₄N - Cubic





Mn₂N - Hexagonal

MnN - Tetragonal

Figure 1. Manganese nitride structures adapted from reference [22].



Figure 2. XRD patterns collected after the nitridation of Mn₂O₃.



Figure 3. SEM micrographs of (a) Mn_2O_3 , (b) Mn_3N_2 .



Figure 4. XRD patterns collected after calcination step of (a) Co-Mn-O: ▲ CoMn₂O₄ (PDF number: 00-055-068) ▼ Co₂MnO₄ (PDF number: 00-023-1237), (b) Mn-Fe-O: • Fe₂O₃ (PDF number: 01-085-0987) \circ Mn₂O₃ (PDF number: 01-078-0390).



Figure 5. XRD patterns collected after the nitridation step of: (a) Co-Mn-O, (b) Mn-Fe-O.



Figure 6. XRD patterns collected after the calcination step of: (a) K-Mn-O, (b) Li-Mn-O: (\blacktriangle) LiO₂ PDF number: 01-073-7127, (\bullet) LiMn₂O₄ (PDF number: 00-018-0736)



Figure 7. XRD patterns collected after the nitridation step. (a) Mn_3N_2 , (b) K-Mn-N, (c) Li-Mn-N.





Figure 8. Ammonia yield of Mn₃N₂ with 60 ml Figure 10. Ammonia yield of A-Mn-N with 60 min⁻¹ of 1:3 N₂: H₂ at 400°C. Error propagation within a 95% confidence interval.



ml min⁻¹ of 1:3 N₂: H₂ at 400°C: (•) K-Mn-N, (■) Li-Mn-N. Error propagation within a 95% confidence interval.



Figure 9. Ammonia yield of A-Mn-N with 60 ml min⁻¹ of 1:3 N₂: H₂ at 400°C: (▲) Fe-Mn-N, (*) Co-Mn-N. Error propagation within a 95% confidence interval.

Figure 11. Ammonia yield of Li-Mn-N, with 60 ml min⁻¹ of 1:3 N₂: H₂ as a function of temperature: (\blacksquare) 300°C, (\blacklozenge) 400°C and (\blacktriangle) 500°C. Error propagation within a 95% confidence interval.



Figure 12. Regenerability of Li-Mn-N: (\blacktriangle) first cycle, (\bullet) second cycle and (\blacksquare) third cycle. Reduction step conducted with 60 ml min⁻¹ of 1:3 Ar: H₂ at 400°C. The nitridation step was conducted with 60 ml min⁻¹ flow of N₂ at 800°C. Error propagation within a 95% confidence interval.



Figure 13. Ammonia yield of Li-Mn-N with 60 ml min⁻¹ of 1:3 N₂: H₂ at 400°C for 16h. Error propagation within a 95% confidence interval.

	$\mathbf{S}_{\mathbf{BET}}^{\mathbf{a}}$	[/] Phase composition/ XRD	Chemical composition			
	$m^2 g^{-1}$		N^{b} / wt %	A/Mn ^c / molar ratio		
Mn ₃ N ₂	66	Mn ₃ N ₂ (PDF number: 01-074-8391)	14.9±0.1	-		
Fe-Mn-N	36	Amorphous	10.8±0.1	0.90±0.03		
Co-Mn-N	39	Amorphous	13.4±0.2	0.80 ± 0.02		
K-Mn-N	10	Mn ₃ N ₂ (PDF number: 01-074-8391)	16.9±0.1	n.d.		
Li-Mn-N	11	Mn ₃ N ₂ (PDF number: 01-074-8391)	12.1±0.2	0.10±0.01		
^a , S _{BET} is the specific surface area evaluated using the BET model; ^b , nitrogen analysis undertaken using an Exeter Analytical CE-440 Elemental Analyser, n.d. means not detected.						

Table 1. Physicochemical properties of the prepared materials.

Table 2. Summary of nitrogen reactivity of manganese nitride based materials after reaction with 60 ml min⁻¹ of 1:3 N₂: H₂ at 400°C.

	Nitrogen co	ontent/ wt.%	Total N — content/ μmol/ g of material	N NH ₃ g produced/ µmol	% lattice N lost	
	Pre- reaction	Post- reaction			NH ₃	
Mn_3N_2	14.9 ± 0.1	3.45±0.1	10700±11	256±9	3.1	
Fe-Mn-N	10.9 ± 0.1	0.1 ± 0.1	7780±8	138±5	1.8	
Co-Mn-N	13.4±0.2	1.4 ± 0.1	9565±19	273±9	3.2	
K-Mn-N	16.9±0.1	nil	12063±12	73±3	0.2	
Li-Mn-N	12.1±0.2	0.5 ± 0.1	8644±17	1306±44	15.8	

Table 3. Summary of nitrogen reactivity of lithium manganese nitride related materials after reaction with 60 ml min⁻¹ of $1:3 N_2:H_2$

	Temperature reaction/ °C	Total N content/ µmol/g of material	NH ₃ produced/ µmol after 5h	% lattice N converted to NH ₃
L: Mr. N	300	8644±17	1400±48	16.2
L1-IVIN-IN	400	8644±17	1306±44	15.8
	500	8644±17	2072 ± 70	24.0