

Technical University of Denmark



Electrocatalytic conversion of biomass-derived chemicals in alkaline electrochemical cell

Traulsen, Marie Lund; Joya, Khurram Saleem; Chatzichristodoulou, Christodoulos

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Traulsen, M. L., Joya, K. S., & Chatzichristodoulou, C. (2017). Electrocatalytic conversion of biomass-derived chemicals in alkaline electrochemical cell. Abstract from DEF Annual Meeting 2017, Kgs. Lyngby, Denmark.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



Electrocatalytic conversion of biomass-derived chemicals in alkaline electrochemical cell

**Marie Lund TRAUlsen¹, Khurram Saleem JOYA²,
Christodoulos CHATZICHRISTODOULOU³**

*Department of Energy Conversion and Storage,
Technical University of Denmark, Denmark,
¹matr@dtu.dk, ²khsa@dtu.dk, ³ccha@dtu.dk*

The overall aim in the EU funded TERRA project is to develop a novel type of electrochemical reactor, in which both the anode and cathode reaction is used for simultaneous electrochemical conversion/upgrading of biomass-derived chemicals.

The electrochemical reactor under development is essentially an alkaline electrolysis cell which will operate in the temperature regime 50° C – 200 °C. One of the important tasks within the project is to identify suitable electrode materials and operating conditions for conversion of xylitol into glycols (cathode reaction) and for conversion of HMF into FDCA (anode reaction). In both cases key parameters to be evaluated are the activity, selectivity and durability for the electrode processes.

For the xylitol conversion a series of electrodes has been investigated, including electrodes based on non-noble metal nanoparticles supported on carbon nanotubes, Pt coated Ti-felt and commercial Pt-black infiltrated carbon felt. The investigation has been carried out in the temperature range from 25° C – 200 °C at 40 bar pressure, and the influence of applied potential and pH-value has been evaluated.

At elevated temperatures (150 -200° C) an electrochemically activated conversion of xylitol is taking place, and conversion of close to 100% xylitol is achieved. The electrodes appear stable within the 1-4 hours duration of each test, however the selectivity of the process towards glycol formation is still very low, and has to be improved.