

**TABLE OF CONTENTS**

<b>CHAPTER</b>	<b>TITLE</b>	<b>PAGE</b>
	<b>DECLARATION</b>	ii
	<b>DEDICATION</b>	iii
	<b>ACKNOWLEDGEMENT</b>	iv
	<b>ABSTRACT</b>	v
	<b>ABSTRAK</b>	vi
	<b>TABLE OF CONTENTS</b>	vii
	<b>LIST OF FIGURES</b>	xi
	<b>LIST OF ABBREVIATIONS</b>	xiv
<b>1</b>	<b>INTRODUCTION</b>	1
	1.1 Overview	1
	1.2 Problem Statement	2
	1.2.1 Complex Background Design	2
	1.2.2 Environmental Illumination	3
	1.2.3 Light Reflection	3
	1.2.4 Position Adjustment	4
	1.2.5 Round and Shiny Surfaces	4
	1.3 Objective	5
	1.4 Scope of Work	5
	1.5 Proposal Outline	6

1.6	Summary	6
<b>2</b>	<b>LITERATURE REVIEW</b>	<b>7</b>
2.1	Introduction	7
2.2	Illumination Systems	8
2.2.1	Single Point LED	9
2.2.2	Linear Multiple LED	9
2.2.3	Laser	10
2.2.4	LED Imager	10
2.3	Microcontroller	11
2.3.1	Barcode Scanner with Adjustable Light Source	12
2.3.2	Light Sensitive Automatic Flash control Circuit	13
2.3.3	Smart Camera with Light Controller	14
2.3.4	Synthetic Barcode System	15
2.3.5	Integral Ambient Light and Occupancy Sensor	16
2.3.6	Optical Scanner Head for Processing Barcode Data	17
2.3.7	Portable Barcode Simulator Device and Method	18
2.4	Understanding Lighting Systems Used in Barcode Readers	19
2.4.1	Finding Suitable Automatic Illumination Control Circuit for the Barcode Readers Light Source	19
2.4.2	Techniques to Reduce Glare and Uneven Illumination	22
2.5	Summary	23
<b>3</b>	<b>METHODOLOGY</b>	<b>24</b>
3.1	Introduction	24
3.2	Function of the Lighting System	24
3.3	Flowchart of the Entire System	25

3.3.1	Computing the K Output Value	29
3.3.1.1	Computing the Output Value K Under Different Light Conditions	30
3.4	Software Part	31
3.4.1	Desktop Computer	32
3.4.2	Flowchart for Programming the Microcontroller	32
3.5	Hardware Part	33
3.5.1	Light Source Design	33
3.5.2	Control Circuit	34
3.5.2.1	Microcontroller	35
3.5.2.1.1	Higher Current Load Interface	37
3.5.2.2	Programming the Microcontroller	37
3.5.2.2	The Digital to Analogue Convertor Section	38
3.5.2.2.1	General Biasing Requirements	39
3.5.2.2.2	Output Considerations	40
3.5.2.3	The Power Section	41
<b>4</b>	<b>RESULTS AND DISCUSSIONS</b>	<b>42</b>
4.1	Introduction	42
4.2.1	Laboratory Experiment	43
4.2.1	Experiment No. 1	43
4.2.2	Experiment No. 2	45

4.2.3 Experiment No. 3	47
4.2.4 Experiment No. 4	49
4.2.5 Experiment No. 5	51
4.3 Discussions	53
<b>5 CONCLUSIONS AND RECOMENDATIONS</b>	<b>55</b>
5.1 Conclusions	55
5.2 Recommendations for Future Work	56
<b>REFERENCES</b>	<b>57</b>
<b>APPENDICES (A-C)</b>	<b>60-80</b>

**LIST OF FIGURES**

<b>FIGURE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
1.1(a)	Barcode printed on shiny book cover	2
1.1(b)	Barcode printed on plastic wrap	2
1.2	A barcode in low light.	3
1.3	Specula effect caused by the light reflected from the camera light source	3
1.4	Uneven illuminations on barcode from unusual angle	4
1.5	Barcode printed on a shiny round object	4
2.1	Block diagram of an operable light intensity control	12
2.2	A camera flash circuit	13
2.3	Smart Camera	14
2.4	Block diagram of components of an exemplary synthetic barcode module circuit	15
2.5	Block diagram of electrical circuitry that controls the operation of the sensor	17
2.6(a)	Optical barcode scanner	18
2.6(b)	System to transfer barcode data to host	18

2.7	Block diagram of an electronic bar code simulator (EBCS) device	19
2.8	Barcode scanner with adjustable light source	20
2.9	Automatic light detection circuits	21
2.10	LED light detection circuit	21
2.11	Motor controlled movable light source	22
2.12	Bare bulbs covered by shaded glass	23
2.13	Color coated anti-reflection objects	23
3.1	The block diagram of entire system	25
3.2	Flow chart of entire system	26
3.3	Frame with a pixel	28
3.4(a)	Position of histogram to the left	29
3.4(b)	Position of histogram to the right	29
3.5	Microcontroller programming flowchart	33
3.6	Reflector design details	34
3.7	Schematic diagram of control circuit	35
3.8	Pin layout diagram of PIC16F877A Microcontroller	36
3.9	Microcontroller programmer	38
3.10	Schematic diagram of the interface between DAC0800 and operational amplifier	40
3.11	Schematic diagram of the power circuit	41
4.1	Captured barcode printed on perfume bottle using conventional camera	44
4.2	Captured barcode printed on perfume bottle using developed system	45
4.3	Captured barcode printed on dove therapy plastic tube using conventional camera	46

4.4	Captured barcode printed on dove therapy plastic tube using developed system	47
4.5	Captured barcode printed on Akkord webcam carton using conventional camera	48
4.6	Captured barcode printed on Akkord webcam carton using developed system	49
4.7	Captured barcode printed on Sun Quick juice bottle using conventional camera	50
4.8	Captured barcode printed on Sun Quick juice bottle using developed system	51
4.9	Captured barcode printed on a text book using conventional camera	52
4.10	Captured barcode printed on a text book using developed system	53

## LIST OF ABBREVIATIONS

A/D	-	Analogue to Digital Convertor
CCD	-	Charged Coupled Device.
CD	-	Compact Disk
CDS	-	Cadmium Sulfide
CLK	-	Clock
CMOS	-	Complementary Metal Oxide
COM	-	Communication
CPU	-	Central Processing Unit
3-D	-	Three Dimensional
D/A	-	Digital to Analogue Convertor
EBCS	-	Electronic Barcode Stimulator
FET	-	Field Effect Transistor
FPS	-	Frame Per Second
I/O	-	Input- Output
IR	-	Infrared Red
K	-	Kilo-pixel
LDR	-	Light Dependent Resistor
LED	-	Light Emitting Diode



LVDS	-	Low Voltage Differential Signal
mA	-	Mill ampere
MCU	-	Microcontroller Unit
OP-AMP	-	Operational Amplifier
PC	-	Personal Computer
PDA	-	Personal Digital Assistant
RAM	-	Read Access Memory
ROM	-	Read Only Memory
SI	-	Start Integration
USB	-	Universal Serial Bus
VGA	-	Video Graphics Array

**LIST OF APPENDICES**

<b>APPENDIX.</b>	<b>TITLE</b>	<b>PAGE</b>
A	Schematic Diagram for the Control Circuit	60
B	Data Sheet	61
C	Source Code (C++)	65