

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xi
	LIST OF APPENDICES	xiii
1	INTRODUCTION	
	1.1 Project Background	1
	1.2 Motivation for Research	1
	1.3 Objectives of Project	4
	1.4 Scopes of Project	4
	1.5 Thesis Organization	5
2	LITERATURE REVIEW	
	2.1 Introduction	6
	2.2 Related Works	6
	2.3 Background of Project	9
	2.3.1 Fuzzy Logic	9
	2.3.2 Virtual Laboratory	11
	2.3.3 LABVIEW Software	15

3	METHODOLOGY	
3.1	Introduction	17
3.2	Water Bath	18
3.3	Interface System	20
3.4	NI USB 6008	22
3.5	Thermometer	23
4	SOFTWARE DEVELOPMENT USING LABVIEW	
4.1	Introduction	24
4.2	Development of Fuzzy Logic	24
4.2.1	Fuzzy Set	26
4.2.2	Rulebase	30
4.3	Development of Virtual Environment	35
4.3.1	Publish GUI onto the Web	36
5	RESULTS AND DISCUSSIONS	
5.1	Fuzzy Logic Controller	39
5.2	Virtual Laboratory Environment	41
6	CONCLUSIONS AND FUTURE WORK	
6.1	Conclusions	43
6.2	Future Work	44
	REFERENCES	45
	Appendix A	

LIST OF TABLES

TABLE NO.	TITLE	PAGE
4.1	Linguistic Term and Label	27

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Client-Server Architecture for GUI Module	12
3.1	Flowchart of the Methodology	17
3.2	Schematic Diagram of Water Bath Temperature Control System	19
3.3	Water Bath	19
3.4	Interface Circuit	20
3.5	Schematic Diagram of the Interface Circuit	21
3.6	National Instruments Driver	22
3.7	The Overall Circuit including NI USB 6008	23
3.8	Thermometer	23
4.1	Block Diagram of the Water Bath Temperature Control System	25
4.2	Project Manager Front Panel	26
4.3	Configuration of the Fuzzy Controller	26
4.4	Error Setting	28
4.5	Rate of Error Setting	28
4.6	Consequence Setting	29

4.7	Water Bath Complete Rule Based	30
4.8	Front Panel of the Water Bath Temperature Control System	33
4.9	Block Diagram of the Water Bath Temperature Control System	34
4.10	Web Publishing Tool Setting	35
4.11	VI and Viewing Selection	36
4.12	Web Page Destination Directory	37
4.13	URL Address for Water Bath System	37
5.1	Set Point is 50°C	40
5.2	Set Point are 40°C and 60°C	40
5.3	Set Point are 70°C and 80°C	41
5.4	Front Panel of the Water Bath Control System	43

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	User Guide USB-6008/6009	48