

DIESEL-CNG DUAL FUEL COMBUSTION CHARACTERIZATION USING
VIBRO-ACOUSTIC ANALYSIS AND RESPONSE SURFACE METHODOLOGY

ABD FATHUL HAKIM BIN ZULKIFLI

A thesis submitted in fulfillment of the requirement for the award of the
Doctor of Philosophy of Mechanical Engineering

Faculty of Mechanical and Manufacturing Engineering
Universiti Tun Hussein Onn Malaysia

SEPTEMBER 2019

ACKNOWLEDGEMENT

أَلْحَمْدُ لِلَّهِ to Allah Almighty for His blessing and guidance. To Prophet Muhammad, peace and blessing be upon him.

I would like to express my deepest gratitude and appreciation to my dear and beloved wife Siti Suhana Binti Jamaian, also my lovely kids (Faheem Irsyad, Fayyadh Ifwat, Faathir Ilman, and Farhaa Ilyeen). I am really cherished your tremendous support and prayers that always be the backbone and driving force for me to complete this thesis. Not forgotten to my family members, especially my beloved parents, Zulkifli bin Ab. Latiff and Kasjuniar Abdul Rahman for their endless support and prayers.

My thanks extend to everyone involved in completing this project, especially to my supervisor, Assoc. Prof. Dr Mas Fawzi bin Mohd Ali for his supervision and encouragement throughout my PhD project journey. I also would like to convey my special thanks to my co. supervisor, Dr Shahrul Azmir Bin Osman who has never failed to give me advice and supports to complete my study.

Warmful thanks to Mr Muammar Mukhsin Bin Ismail, Mr Mzahar bin Abd. Jalal, Mr Mustakim Bin Tukiman, Mr Putera Mohamad Adam bin Amat Azman, Dr Norrizal Bin Mustaffa and Dr Rais Hanizam bin Madon for providing guidance and helping me on the equipment and instrumentation setup for experimental work. Special thanks to Universiti Tun Hussein Onn Malaysia for providing funding and facilities such as laboratories, equipment, and library access to accommodate this research work.

ABSTRACT

Engine conversion process from any diesel vehicle to a diesel-CNG dual fuel system requires additional fuel management. The need for an engine monitoring is vital to ensure the dual fuel operation run smoothly without excessive knocking, which may shorten the life of the engine. Knock and air-fuel ratio (AFR) sensors are commonly used for engine monitoring during fuel management setup. However, the engine output characteristics has been overlooked during the monitoring process. This study is aimed to explore a statistical approach by predicting the relationship between fuel management and engine output characteristics of diesel-CNG dual fuel engine using Response Surface Methodology (RSM). Two inputs which are CNG substitution rate and engine speed were used to predict the engine output characteristics in terms of engine performance, exhaust emissions, combustion pattern and combustion stability. Within the investigation, a statistical method was proposed to analyse the vibro-acoustic signal generated by a knock sensor installed at the outer cylinder wall of the engine. The frequency distribution analysis was applied to interpret the high variability of the vibro-acoustic signal. The results were used as the input for combustion stability in RSM analysis. It also provided useful information with regards to the engine stability. The response surface analysis showed that the CNG substitution rate and its properties significantly influenced the engine output characteristics. This study also describes the methodology to determine the accuracy and the significance of the developed prediction models. The prediction models were validated using confirmation test and showed good predictability within 95% confidence interval. Thus, it is concluded that RSM provide models that predict the engine characteristics with significant accuracy, which contributes to the effectiveness of diesel-CNG dual fuel engine conversion process.

ABSTRAK

Proses penukaran enjin dari mana-mana kenderaan diesel kepada sistem dwi bahan bakar diesel-CNG memerlukan pengurusan bahan bakar tambahan. Keperluan pemantauan enjin adalah penting untuk memastikan operasi dwi bahan api berjalan dengan lancar tanpa *knocking* yang berlebihan, yang boleh memendekkan jangka hayat enjin. Sensor bagi *knock* dan udara-bahan api (AFR) biasanya digunakan untuk pemantauan enjin semasa persediaan pengurusan bahan api. Walau bagaimanapun, ciri-ciri output enjin telah diabaikan semasa proses pemantauan. Kajian ini bertujuan untuk meneroka pendekatan statistik dengan meramalkan hubungan antara pengurusan bahan api dan ciri-ciri output enjin diesel-CNG dwi bahan api menggunakan Metodologi Permukaan Respon (RSM). Dua input iaitu kadar penggantian CNG dan kelajuan enjin digunakan untuk meramalkan ciri output enjin dari segi prestasi enjin, pelepasan ekzos, corak pembakaran dan kestabilan pembakaran. Semasa siasatan, kaedah statistik dicadangkan untuk menganalisis isyarat vibro-akustik yang dihasilkan oleh sensor *knock* yang dipasang di luar dinding silinder enjin. Analisis taburan frekuensi digunakan untuk menafsirkan kebolehubahan tinggi isyarat vibro-akustik. Hasilnya digunakan sebagai input untuk kestabilan pembakaran dalam analisis RSM. Ia juga menyediakan maklumat berguna berkaitan dengan kestabilan enjin. Analisis respon permukaan menunjukkan bahawa kadar penggantian CNG dan sifatnya telah mempengaruhi ciri output enjin. Kajian ini juga menerangkan metodologi untuk menentukan ketepatan dan kepentingan model ramalan yang telah dibangunkan. Model ramalan telah disahkan menggunakan ujian pengesahan dan menunjukkan ramalan yang baik dalam lingkungan 95% selang keyakinan. Oleh itu, disimpulkan bahawa RSM menyediakan model ramalan yang mengawasi ciri-ciri enjin dengan ketepatan yang signifikan, yang menyumbang kepada keberkesanan proses pengubahan enjin dwi bahan bakar diesel-CNG.

CONTENTS

ACKNOWLEDGEMENT	iii
ABSTRACT	iv
ABSTRAK	v
CONTENTS	vi
LIST OF TABLES	ix
LIST OF FIGURES	xi
LIST OF SYMBOLS AND ABBREVIATIONS	xv
LIST OF APPENDICES	xx
CHAPTER 1 INTRODUCTION	1
1.1 Background of research	1
1.2 Problem statement	3
1.3 Research questions	4
1.4 Objectives	5
1.5 Scopes of study	5
1.6 Significance of research	6
1.7 Framework of research	6
CHAPTER 2 LITERATURE REVIEW	9
2.1 Introduction	9
2.2 Natural Gas as alternative fuel	9
2.2.1 Applications of CNG in internal combustion engine	11
2.3 CNG demand for transportation sector	12

2.3.1	CNG market in Malaysian's transportation sector	13
2.3.2	CNG in National Automotive Policy (NAP) 2014	16
2.4	Diesel-CNG dual fuel systems tuning	17
2.4.1	Literatures studies on diesel-CNG dual fuel engine using conversion kits	19
2.5	RSM in diesel-CNG dual fuel systems	25
2.6	Vibro-acoustic established methods for engine monitoring	26
2.7	Summary	28
CHAPTER 3	METHODOLOGY	29
3.1	Overview	29
3.2	Design of Experiment	31
3.2.1	Response Surface Methodology (RSM)	31
3.3	Experimental setup	39
3.3.1	Test engine	39
3.3.2	Experiment apparatus	41
3.4	Data Acquisitions (DAQ)	49
3.5	Experimentation of Diesel-CNG Dual Fuel System	52
3.5.1	Fuel properties	52
3.5.2	Diesel fuel injection characteristics	52
3.5.3	Establishment of diesel-CNG dual fuel ratio	54
3.5.4	Steady-state dynamometer testing	57
3.6	Uncertainty Analysis	58
CHAPTER 4	RESULTS AND DISCUSSION	59
4.1	Introduction	59
4.2	Vibro-acoustic analysis based on the statistical approach	59

4.3	Prediction models based on Design of Experiment (DoE) analysis	63
4.3.1	Engine performance	65
4.3.2	Exhaust emissions	73
4.3.3	Combustion Patterns	83
4.3.4	Combustion stability	95
4.4	Model Validation	100
4.5	Summary of the main findings	113
CHAPTER 5	CONCLUSION AND RECOMMENDATION	115
5.1	Conclusion	115
5.2	Contribution to knowledge	116
5.3	Recommendation and Future Work	117
	REFERENCES	118
	APPENDIX A:	
	LIST OF PUBLISHED PAPERS DURING STUDY	128
	APPENDIX B:	
	LIST OF AWARD RELATED TO THIS STUDY	129
	APPENDIX C:	
	APPLICATION FOR STATISTICAL DATA TO JPJ	130
	APPENDIX D:	
	GAS ANALYSER CALIBRATION	132
	VITA	133

LIST OF TABLES

2.1	Comparison of fuel properties of natural gas, diesel and gasoline. Reproduced from [21]	10
2.2	The EEV specification for fuel consumption. Reproduced from [35]	17
2.3	Summary of test engine specification and emission test results. Reproduced from [69]	22
2.4	Summary of literatures studies on diesel-CNG dual fuel system using conversion kits	23
3.1	Input and output variables for the design of experiment	33
3.2	The FDS plot analyses	36
3.3	The specification of Toyota Hilux 2.5L common rail direct injection diesel engine	39
3.4	The specification of the Dynapack 4WD chassis dynamometer	43
3.5	The ALICAT Scientific mass flow meters specification [98]	43
3.6	The specification of Anycar Autochek Gas & Smoke Analyser	45
3.7	The specification of Kistler 6056a pressure transducer	45
3.8	The specification of Kistler 5018a charge amplifier	46
3.9	The specification for piezoelectric knock sensor (vibration sensor)	47
3.10	Properties of test fuels. Reproduced from [105]	52
3.11	The dual fuel ratio for experiment matrix according to design of experiment	55
3.12	Accuracy and uncertainty of measured parameters	58
4.1	Mean values for AI BTDC and AI ATDC from the frequency distribution analysis	63
4.2	ANOVA table for BMEP	66
4.3	ANOVA table for BSEC	67

4.4	ANOVA table for BTE	68
4.5	ANOVA table for HC	78
4.6	ANOVA table for CO	78
4.7	ANOVA table for NO _x	79
4.8	ANOVA table for Ignition Delay (ID)	86
4.9	ANOVA table for Peak Pressure (PP)	87
4.10	ANOVA table for Heat Release Rate (HRR)	87
4.11	ANOVA table for Combustion Duration (CD)	88
4.12	ANOVA table for Acoustic Index BTDC (AI BTDC)	97
4.13	ANOVA table for Acoustic Index ATDC (AI ATDC)	97



LIST OF FIGURES

1.1	CNG fuel system for NGV conversion	2
1.2	Framework of research	8
2.1	Typical combustion phase diagram for diesel engine. Reproduced from [22]	10
2.2	CNG induction methods in the internal combustion engine	11
2.3	Regional growth for NGVs and its refuelling stations. Reproduced from [2]	12
2.4	Fuel market price history in Malaysia. Reproduced from [31]	14
2.5	Statistics of the NGVs registered in Malaysia	15
2.6	The tuning process for DDF systems	19
2.7	Noise sources in internal combustion engine [84]	27
3.1	Research Flowchart	30
3.2	Response Surface Methodology (RSM) process flow	31
3.3	Number of runs required for experimentation	35
3.4	Fractional of design space for response surface design with minimum no of runs	35
3.5	The contour plot (a) and response surface profile (b) for the standard error of the design model	37
3.6	Final number of runs designed for experimentation	38
3.7	Fractional of design space for response surface design with ideal no of runs	38
3.8	Schematic diagram of experimental setup	40
3.9	The installation setup for diesel-CNG dual fuel systems [47]	42
3.10	Diagnostics tool connection diagram	44
3.11	The design and mounting for piezoelectric knock sensor [101]	47
3.12	The installation diagram for piezoelectric knock sensor	47
3.13	Schematic diagram of the MAF sensor working principle	48
3.14	Connection diagram for TDC and clock signal	48

3.15	The compact DAQ NI-9188	49
3.16	BRIC signal processing method	50
3.17	The calibration windows for BRIC signal processing	50
3.18	Fuel injection signal for 1 st injector of test engine at several engine speeds	53
3.19	Fuel injection volume control	56
4.1	Coefficient of Variance (COV) for AI BTDC and AI ATDC at 1500 rpm diesel mode	60
4.2	Legend for the Box-Plot	61
4.3	Acoustic Index at BTDC and ATDC for 1500 rpm during diesel mode	62
4.4	Acoustic index versus CNG substitutions rate for 1500 rpm	62
4.5	Process flow for development of prediction model	64
4.6	Diagnostics plot for BMEP model (a) Normal Plot of Residuals (b) Residuals vs Predicted	66
4.7	Diagnostics plot for BSEC model (a) Normal Plot of Residuals (b) Residuals vs Predicted	67
4.8	Diagnostics plot for BTE model (a) Normal Plot of Residuals (b) Residuals vs Predicted	69
4.9	The contour plot (a) and response surface profile (b) for the BMEP model	70
4.10	The contour plot (a) and response surface profile (b) for the BSEC model	71
4.11	The contour plot (a) and response surface profile (b) for the BTE model	72
4.12	Diagnostics plot for HC emissions model (a) Normal Plot of Residuals (b) Residuals vs Predicted	73
4.13	Box-Cox plot for Power Transformation (a) before transformation (b) after transformation for HC emissions model	74
4.14	The re-diagnostics plot for HC emissions model (a) Normal Plot of Residuals (b) Residuals vs Predicted	75
4.15	Diagnostics plot for CO emissions model (a) Normal Plot of Residuals (b) Residuals vs Predicted	75
4.16	Box-Cox plot for Power Transformation (a) before	

	transformation (b) after transformation for CO model	76
4.17	The re-diagnostics plot for CO emissions model	
	(a) Normal Plot of Residuals (b) Residuals vs Predicted	76
4.18	Diagnostics plot for NO _x emissions model (a) Normal Plot of Residuals (b) Residuals vs Predicted	77
4.19	The contour plot (a) and response surface profile (b) for the HC model	80
4.20	The contour plot (a) and response surface profile (b) for the CO model	81
4.21	The contour plot (a) and response surface profile (b) for the NO _x model	82
4.22	Diagnostics plot for Ignition Delay (ID) model	
	(a) Normal Plot of Residuals (b) Residuals vs Predicted	84
4.23	Diagnostics plot for Peak Pressure (PP) model	
	(a) Normal Plot of Residuals (b) Residuals vs Predicted	85
4.24	Diagnostics plot for Heat Release Rate (HRR) model	
	(a) Normal Plot of Residuals (b) Residuals vs Predicted	85
4.25	Diagnostics plot for Combustion Duration (CD) model	
	(a) Normal Plot of Residuals (b) Residuals vs Predicted	86
4.26	The contour plot (a) and response surface profile (b) for the ID model	89
4.27	The contour plot (a) and response surface profile (b) for the PP model	90
4.28	The contour plot (a) and response surface profile (b) for the HRR model	91
4.29	The contour plot (a) and response surface profile (b) for the CD model	92
4.30	In-cylinder pressure, heat release rate and fuel injection signal for diesel fuel mode	93
4.31	In-cylinder pressure, heat release rate and fuel injection signal for dual fuel mode.	94
4.32	Diagnostics plot for AI BTDC model (a) Normal Plot of Residuals (b) Residuals vs Predicted	96
4.33	Diagnostics plot for AI ATDC model (a) Normal Plot of	

	Residuals (b) Residuals vs Predicted	96
4.34	The contour plot (a) and response surface profile (b) for the AI BTDC model	98
4.35	The contour plot (a) and response surface profile (b) for the AI ATDC model	99
4.36	Predicted versus experiment values for BMEP prediction model	101
4.37	Predicted versus experiment values for BSEC prediction model	102
4.38	Predicted versus experiment values for BTE prediction model	103
4.39	Predicted versus experiment values for HC prediction model	104
4.40	Predicted versus experiment values for CO prediction model	105
4.41	Predicted versus experiment values for NO _x prediction model	106
4.42	Predicted versus experiment values for ID prediction model	107
4.43	Predicted versus experiment values for PP prediction model	108
4.44	Predicted versus experiment values for HRR prediction model	109
4.45	Predicted versus experiment values for CD prediction model	110
4.46	Predicted versus experiment values for AI BTDC prediction model	111
4.47	Predicted versus experiment values for AI ATDC prediction model	112

LIST OF SYMBOLS AND ABBREVIATIONS

AFR	Air Fuel Ratio
AI ATDC	Acoustic Index After Top Dead Centre
AI BTDC	Acoustic Index Before Top Dead Centre
ANOVA	Analysis of Variance
AP	Adequate Precision
BMEP	Brake Mean Effective Pressure
BRIC	Band-pass Rectify Integrate Compare
BSEC	Brake Specific Energy Consumption
BTE	Brake Thermal Efficiency
CAD	Crank Angle Degree
CCD	Central Composite Design
CD	Combustion Duration
cDAQ	compact data acquisition
CI	Confidence Interval
CNG	Compressed Natural Gas
CO	Carbon monoxide
CO ₂	Carbon dioxide
COV	Coefficient of Variance
CPI	Consumer Pricing Index
CWT	Continuous Wavelet Transform
DAQ	Data acquisition
DDF	Diesel Dual Fuel
df	degree of freedom
DF-PCCI	Dual Fuel Premixed Charge Compression Ignition
DoE	Design of Experiment
ECU	Electronic Control Unit
EGR	Exhaust Gas Recirculation
EOC	End of Combustion

EPA	Environmental Protection Agency
ESC	European Stationary Cycle
EUI	Electronic Unit Injector
FDS	Fraction Design Space
FS	Full Scale
FTP	Federal Test Procedure
GHG	Greenhouse Gas
HC	hydrocarbon
HPDI	High Pressure Direct Injection
HOME	Honge Oil Methyl Ester
HRR	Heat Release Rate
Hz	Hertz
ICA	Independent Component Analysis
ID	Ignition Delay
IMEP	Indicated Mean Effective Pressure
IQR	interquartile range
JPJ	Department of Road Transport Malaysia
LNG	Liquefied Natural Gas
LOF	Lack of Fit
MAF	Mass Air Flow
MIDC	Modified Indian Driving Cycle
MS	Malaysia Standard
NGV	Natural Gas Vehicle
NI	National Instrument
NO _x	nitrogen oxide
OBD	On-Board Diagnosis
OEM	Original Equipment Manufacturer
PME	Palm Methyl Ester
PP	peak in-cylinder pressure
PRESS	predicted residual square error sum
Q1	first quartile
Q3	third quartile
RM	Ringgit Malaysia
RNG	Renewable Natural Gas

ROI	Return On Investment
RON	Research Octane Number
rpm	revolution per minute
RSM	Response Surface Methodology
RSS	Root-Sum-Square
SDP	Symmetrised Dot Pattern
SLPM	standard litre per minute
SOC	Start of Combustion
SOI	Start of Injection
Std. Dev.	Standard Deviation
STFT	Short-Time Fourier Transform
SUV	Sport Utility Vehicle
TDC	Top Dead Centre
THC	total hydrocarbon
VGT	Variable Geometry Turbine
vol	volume
WVD	Wigner-Ville Distribution
4WD	four wheel drive
a	area of bore
a_s	velocity of sound
bp	brake power
B	cylinder bore
CV	Calorific Value
cc	cubic centimetre
CO ₂ /km	carbon dioxide per kilometre
$f_{u,s}$	oscillation frequency of in-cylinder gas
ft-lb	foot pound force
g	gravity
g/s	gram per second
J/(kg-K)	Joule per kilogram-Kelvin
J/CAD	Joule per crank angle degree
k	ratio of specific heat
K	Kelvin

kg	kilogram
kg/h	kilogram per hour
kg/m ³	kilogram per metre cubic
kJ/kg/K	kiloJoule per kilogram per Kelvin
ks	kilo seconds
kW	kiloWatts
<i>l</i>	Stroke
L	Litre
L/100 km	Litre per 100 kilometre
<i>m</i>	mass
\dot{m}	mass flow rate
<i>M</i>	physical parameters
m/s	meter per seconds
m ²	meter square
MJ/kg	mega Joule per kilogram
MJ/kWh	mega Joule per kiloWatts hours
mm	millimetres
mm ² /s	millimetre square per second
MOhm	mega unit of resistance
MPa	mega Pascal
ms	milliseconds
mV/g	milliVolt per gravity
<i>n</i>	number of working stroke per minute
<i>n_e</i>	engine speed
Nm	Newton meter
<i>N_r</i>	number of revolution per engine cycle
°C	degree Celsius
<i>P</i>	pressure
Pa	Pascal
pC	pico Coulomb
ppm	part per million
psia	pound per square inch absolute
<i>R</i>	gas constant of working gas

R^2_{ajd}	adjusted R^2
R^2_{pred}	predicted R^2
rel	relative
R_i	measuring range
R_u	random uncertainty
s	number of nodes in the radial oscillation
S_i	uncertainty in M
S_u	Systematic uncertainty
tscf	trillion standard cubic feet
T	temperature
U_{overall}	overall uncertainty
u	number of nodes in the circumferential oscillation
V	Volt
V	volume
X_i	variable
$\rho_{u,s}$	vibration mode factor
γ	specific heat ratio
η_v	volumetric efficiency
θ	crank angle degree
λ	minimum residual sum of squares

LIST OF APPENDICES

A	List of published papers during study	128
B	List of award related to this study	129
C.1	Application letter to JPJ	130
C.2	Response letter to JPJ	131
D.1	Certificate of gas analyser calibration	132



CHAPTER 1

INTRODUCTION

1.1 Background of research

Natural gas is an alternative fuel derived from non-renewable energy source. It has the lowest Greenhouse Gas (GHG) emissions compared to other fossil fuel. According to F. Königsson, natural gas offers 20% reduction in GHG emissions compared to gasoline and diesel because its chemical properties of methane that are larger in hydrogen to carbon ratio [1]. Furthermore, it is inexpensive compared to other fuel and its abundant resource which is sufficient for upcoming decades has appeared as a priority for fossil fuel replacements.

Natural gas can be utilized as Compressed Natural Gas (CNG), Liquefied Natural Gas (LNG) or Renewable Natural Gas (RNG) using retrofitted kits. Retrofitted kits are additional components such as CNG tanks, Electronics Control Unit (ECU), pressure gas regulator, gas injectors and wire harness. These are commonly used for engine conversion into Natural Gas Vehicle (NGV).

Most CNG conversion kits systems for NGV are illustrated in Figure 1.1, which it depends on engine type. For spark ignition engine, it can be converted into either mono-fuel or bi-fuel systems. Meanwhile, for compression ignition engine, either mono-fuel or dual fuel system can be utilized. For mono-fuel systems, the NGV uses 100% CNG, while for bi-fuel systems; the NGV can alternately use 100% CNG or 100% gasoline. In the case of a dual fuel system, $\alpha\%$ of CNG is mixed with $\beta\%$ of diesel fuel in the combustion chamber. The CNG is injected through intake manifold; either using the sequential port injection or by the fumigation method. Then it is mixed with air as a homogeneous charge. The homogeneous charge between air and CNG is ignited as it is initiated by diesel fuel combustion during the compression stroke.




Figure 1.1: CNG fuel system for NGV conversion

According to NGV Global, there is existed about 23 million of NGVs in the world and may exceed 30 million by 2024 [2]. The NGV's market is dominated by passenger cars and its quantity is low compared to gasoline or diesel vehicle. In Europe, the NGV's market is low as 3% [3]. Meanwhile, in Malaysia, the registered NGVs are about 77 thousand compared to 14.68 million for other registered vehicles (cars, public service vehicles, and goods vehicles). This is less than 1% [4, 5]. Despite many efforts have been established in the development of CNG in road transport applications, there is still a barrier need to be addressed in order to enhance the NGV's market [6, 7].

The major obstacle for NGV development is the engine conversion, where it should be the main focus in this research because the availability of the conversion kits is feasible. However, the deployment into the existing vehicles is the key factor [8]. A survey has been conducted to get expert opinions on the NGV's research needed for energy policy development [9]. From the survey, it is noted that the short-term priority for NGV development is on the NGV and refuelling infrastructure. It means that the integration and test of the CNG conversion kits for different vehicle's engine would seek public intention towards the use of NGVs. Besides that, the other barriers for NGV's market penetration are vehicle availability, after-market conversion, refuelling stations, and government policies [10, 11].

In Malaysia, most of NGVs are converted into either mono-fuel or bi-fuel system; that are dominant by public transport service such as taxi. From Department of Road Transport Malaysia (JPJ), most NGVs for logistics vehicles use a mono-fuel system for their diesel engines. However, based on Malaysia's CNG infrastructure facilities, the dual fuel systems is the good option because its offer fuel flexibility where the engine can operates with 100% diesel if the CNG supply is not available [12]. In addition, typical diesel engine comes with common rail fuel injection system where possess great potential for diesel dual fuel (DDF) system due to its flexibility in controlling fuel injection for diesel fuel replacement.

1.2 Problem statement

The conversion kits or retrofitted kits for diesel dual fuel (DDF) systems are additional components installed to run dual fuels in diesel engine. It requires integration process to adopt the DDF components to the diesel engine. Even though no major modification is needed and is mostly add-on components, the configuration setup to operate the dual fuels requires accurate tuning process and it is challenging in order to ensure that the engine has comparable performance and stability. In addition, the exhaust emission aspect should take into account due to stringent emission regulation. For example, in United State, the conversion kits must comply with the Environmental Protection Agency (EPA) requirement to meet the standard emission regulation [13].

Normally, the tuning process for the DDF system involves fuel management setting to reduce the diesel fuel quantity and replace with the CNG fuel. The fuel management setting usually is based on the fuel quantity for both fuels. The CNG substitution rate is dependent on diesel engine installed with dual fuel systems. Therefore, the DDF systems installer uses additional instrumentations such as knock sensor and air-fuel ratio (AFR) sensor during the tuning process for measurement and monitoring purposes. Both inputs from these two sensors are used as the guidance for the DDF systems tuner to verify the dual fuel system operation limitation. This means that the dual fuel engine should have a similar air-fuel ratio compared to diesel mode without any knock event. The efficiency of this tuning method become questionable due to several aspects that might overlook during the tuning process such as actual engine performance, fuel consumption, exhaust emissions and its stability.

Furthermore, the conventional method for measuring engine stability is by observing several consecutive combustion pressures. Generally, the in-cylinder pressure sensor is implemented to measure the combustion pressure where it a suitable instrumentation to provide accurate information. Unfortunately, it is not a practical approach for commercial purpose since it is costly.

The Response Surface Methodology (RSM) has the capability to provide the relation between fuel substitution rate and engine output characteristics through its statistical approach. This approach may help DDF tuner to understand the characteristics of the engine installed with the dual fuel conversion kits. The design of experiment using RSM could provide an experimental technique for predicting the responses of engine performances, exhaust emissions, combustion patterns and combustion stability. In addition, these response characteristics can be presented graphically through its contour plot and response surface profile, which are useful for establishing responses values and operating condition as required. The modelling methodologies are capable to predict the untested conditions with significant accuracy as per reported by [14–16].

The functionality of the commercial knock sensor that provides knock detection indicator can be utilized to provide information regard to engine stability. However, the vibro-acoustic signal from the knock sensor has large variability due to different background noises comes from an engine. A statistical method can be introduced to eliminate the background noises and provides the vibration intensity index. Thus, it can display the distribution of the vibration intensity index that shows the stability of the engine.

1.3 Research questions

The research questions for this study as follows:

- i. What statistical approach can be utilized to overcome the high variability of the acoustic index data for combustion stability data in Response Surface Methodology (RSM) analysis?
- ii. What can be achieved by assessing the responses of designed experiments for predicting the engine's output characteristics, i.e. engine performance, exhaust

emissions, combustion patterns and combustion stability using RSM? In addition, how significant is the prediction models developed using RSM.

- iii. What relationships can be established between fuel management and engine output characteristics for diesel-CNG dual fuel engine using RSM?

1.4 Objectives

The objectives of the research are as follows:

- i. To propose a novel statistical approach for vibro-acoustic signal analysis method via the offline mode to overcome the high variability of the acoustic index data as the input for combustion stability analysis.
- ii. To develop the significant prediction models of engine output characteristics using Response Surface Methodology (RSM) and validate through the confirmation test against the experimental values.
- iii. To predict the relationship between fuel management and engine output characteristics of diesel-CNG dual fuel engine using RSM.

1.5 Scopes of study

The scopes of this research are as follows:

- i. The investigation is based on diesel-CNG dual fuel system conversion kits (brand: GI GASITALY) is installed in Toyota Hilux 2.5L common rail direct injection diesel engine (engine model: 2KD-FTV) with no modification on the stock ECU.
- ii. The study is focused on the fumigated CNG dual fuel system.
- iii. The dual fuel set ratios are targeted at 10%, 20%, 30% and 40% of diesel replacement in term of mass ratio within the operating range of 1500 to 3500 rpm engine speeds.
- iv. The steady-state dynamometer testing is considered for this study by using chassis dynamometer.

REFERENCES

1. F. Königsson, “On Combustion in the CNG - Diesel Dual Fuel Engine,” Royal Institute of Technology, 2014.
2. NGV Global, “Current Natural Gas Vehicle Statistics | NGV Global Knowledgebase,” 2018. [Online]. Available: <http://www.iangv.org/current-ngv-stats/>. [Accessed: 07-Feb-2019].
3. NGVA-Europe, “Statistical Report 2017,” 2017.
4. Malaysia Gas Association, “Malaysia: Natural Gas Industry Annual Review,” 2017.
5. Paultan.org, “Vehicle registrations in Malaysia hit 28.2 million units,” 2017. [Online]. Available: <https://paultan.org/2017/10/03/vehicle-registrations-in-malaysia-hit-28-2-million-units/>. [Accessed: 19-Feb-2019].
6. M. I. Khan, T. Yasmin, and A. Shakoar, “Technical overview of compressed natural gas (CNG) as a transportation fuel,” *Renewable and Sustainable Energy Reviews*, vol. 51, pp. 785–797, 2015.
7. M. Imran, T. Yasmeen, M. Ijaz, M. Farooq, and M. Wakeel, “Research progress in the development of natural gas as fuel for road vehicles : A bibliographic review (1991 – 2016),” *Renewable and Sustainable Energy Reviews*, vol. 66, pp. 702–741, 2016.
8. M. R. Werpy, D. Santini, A. Bumham, and M. Mintz, “Natural Gas Vehicles : Status , Barriers , and Opportunities,” 2010.
9. M. Hosseini, I. Dincer, and A. Ozbilen, “Expert Opinions on Natural Gas Vehicles Research Needs for Energy Policy Development,” *Exergetic, Energetic and Environmental Dimensions*, pp. 731–750, 2018.
10. J. L. Kirk, A. L. Bristow, and A. M. Zanni, “Exploring the market for Compressed Natural Gas light commercial vehicles in the United Kingdom,” *TRANSPORTATION RESEARCH PART D*, vol. 29, pp. 22–31, 2014.
11. Energy Supply Association of Australia, “Developing a market for Natural Gas Vehicles in Australia,” 2014.

12. F. H. Zulkifli, M. M. Ismail, M. Fawzi, and S. A. Osman, "A prospect of compressed natural gas (CNG)-diesel dual fuel system in malaysia," *Advanced Science Letters*, vol. 22, no. 9, 2016.
13. G. Whyatt, "Issues Affecting Adoption of Natural Gas Fuel in Light- and Heavy-Duty Vehicles," 2010.
14. R. S. Hosmath, N. R. Banapurmath, S. V. Khandal, V. N. Gaitonde, Y. H. Basavarajappa, and V. S. Yaliwal, "Effect of compression ratio, CNG flow rate and injection timing on the performance of dual fuel engine operated on honge oil methyl ester (HOME) and compressed natural gas (CNG)," *Renewable Energy*, vol. 93, pp. 579–590, 2016.
15. M. Y. Ismail, "Predicting Engine Performance and Exhaust Emissions of a Spark Ignition Engine Fuelled with 2-Butanol-Gasoline Blends using RSM and ANN Models," Universiti Malaysia Pahang, 2018.
16. I. M. Yusri, A. P. P. A. Majeed, R. Mamat, M. F. Ghazali, O. I. Awad, and W. H. Azmi, "A review on the application of response surface method and artificial neural network in engine performance and exhaust emissions characteristics in alternative fuel," *Renewable and Sustainable Energy Reviews*, vol. 90, pp. 665–686, 2018.
17. G. A. Karim, *Dual-Fuel Diesel Engines*. CRC Press Taylor & Francis Group, 2015.
18. International Gas Union (IGU), "Global gas report," 2018.
19. Malaysia Energy Commission, "ENERGY STATISTICS MALAYSIA HANDBOOK," 2017.
20. M. M. Abdelaal and a. H. Hegab, "Combustion and emission characteristics of a natural gas-fueled diesel engine with EGR," *Energy Conversion and Management*, vol. 64, pp. 301–312, 2012.
21. L. Wei and P. Geng, "A review on natural gas/diesel dual fuel combustion, emissions and performance," *Fuel Processing Technology*, vol. 142, pp. 264–278, 2016.
22. J. B. Heywood, *Internal Combustion Engine Fundamentals*, 1st Editio. Mc Graw Hill, 1988.
23. A. Demirbas, "Natural gas," in *Methane Gas Hydrate*, Springer, 2010, p. 285.
24. M. F. Mohd Ali, "Research on Control of Ignition and THC Formation in CNG Engines by the Application of Gas-jet Direct-ignition Technique," University

of Tokushima, 2012.

25. Volkswagen, “Natural gas engines (TGI) | Volkswagen Newsroom,” 2019. [Online]. Available: <https://www.volkswagen-newsroom.com/en/natural-gas-engines-tgi-3652>. [Accessed: 10-Feb-2019].
26. SEAT, “TGI - Car Terms | SEAT,” 2019. [Online]. Available: <https://www.seat.com/car-terms/t/tgi-technology.html>. [Accessed: 10-Feb-2019].
27. B. S. Brown, C. a. Laforet, S. N. Rogak, and S. R. Munsh, “Comparison of injectors for compression ignition of natural gas with entrained diesel,” *International Journal of Engine Research*, vol. 12, no. 2, pp. 109–122, 2011.
28. PERDANA DIGITAL, “Chief Executives Speech Archive,” 1991. [Online]. Available: <http://www.pmo.gov.my/ucapan/?m=p&p=mahathir&id=730>. [Accessed: 10-Feb-2019].
29. Department of Statistics Malaysia, “Consumer Price Index (CPI) June 2018,” 2018. [Online]. Available: <http://bit.ly/30ioSqi>. [Accessed: 11-Feb-2019].
30. H. M. Zain, N. Ashikin, and M. Yusof, “GST And the Influencing Factors of Prices Hikes In Daily and Consumable Goods after the Implementation of GST,” *Journal Of Science, Technology And Innovation Policy*, vol. 3, no. 2, pp. 13–22, 2017.
31. RinggitPlus.com, “Petrol Price Malaysia Live Updates (RON95, RON97 & Diesel),” 2019. [Online]. Available: <https://ringgitplus.com/en/blog/Petrol-Credit-Cards/Petrol-Price-Malaysia-Live-Updates-RON95-RON97-Diesel.html>. [Accessed: 11-Feb-2019].
32. Jabatan Pengangkutan Jalan (JPJ) Malaysia, “Data Kenderaan Berdaftar Sebagai Kenderaan NGV di Malaysia,” 2018.
33. Amirul Fahmi R. and D. Hands, “The Taxi Service Review: Malaysia context,” *Mediterranean Journal of Social Sciences*, vol. 7, no. 4, pp. 559–563, 2016.
34. A. Ivanco, R. Prucka, M. Hoffman, and Z. Filipi, “Return on investment calculation for a heavy duty vehicle with a dual fuel diesel-natural gas engine,” in *ASME 2016 Internal Combustion Engine Fall Technical Conference, ICEF 2016*, 2016.
35. M. F. Ammelina Dayana, M. A. Mas Fawzi, O. Shahrul Azmir, I. Muammar Mukhsin, and M. S. Mohd Farid, “Potential Consumer Assessment on the Usage of Diesel-CNG Dual Fuel Vehicle in Malaysia,” *Journal of Advanced Research*

- in Fluid Mechanics and Thermal Sciences*, vol. 53, no. 2, pp. 175–184, 2019.
36. Ministry of International Trade and Industry (MITI) Malaysia, “National Automotive Policy (NAP) 2014,” 2014.
 37. H. H, “Dual Fuel Engine,” *Plant Engr*, vol. 14, no. 1, pp. 11–16, 1970.
 38. Landi Renzo, “CNG system on Diesel vehicles | Landi Renzo.” [Online]. Available: <https://landirenzo.com/us/cng-system-diesel-vehicles>. [Accessed: 22-Apr-2019].
 39. DieselGas, “Duel-fuel systems for diesel engines.” [Online]. Available: <https://www.dieselfgas.co.nz/products/>. [Accessed: 21-Apr-2019].
 40. Ecomotive Solution, “What is D-GID? | Technologies to support Ecology - Ecomotive Solutions.” [Online]. Available: <http://www.ecomotive-solutions.com/en/what-is-d-gid/>. [Accessed: 22-Apr-2019].
 41. GI Gasitaly, “Gasitaly F5 DGS Diesel/CNG.” [Online]. Available: <http://www.gasitaly.com/en/product/f5-diesel-dualfuel-kits/gasitaly-f5-dgs-diesel-cng>. [Accessed: 22-Apr-2019].
 42. Prins, “DieselBlend CNG,” 2019. [Online]. Available: http://www.prinsautogas.com/view_attachment/3376/Prins_Dieselblend_Brochure_CNG_-_Regular_Style.pdf. [Accessed: 22-Apr-2019].
 43. American Power Group, “APG Dual Fuel Gliders™.” [Online]. Available: <http://www.americanpowergroupinc.com/apg-dual-fuel-gliders™.html>. [Accessed: 22-Apr-2019].
 44. Blue Energy, “Diesel Dual Fuel Systems: Blue Energy Diesel PRIME.” [Online]. Available: <http://www.blueenergy.com.pl/150/>. [Accessed: 22-Apr-2019].
 45. B. Greg, *Engine Management: Advanced Tuning*. CarTech, 2007.
 46. HKS Co. Ltd., “5 main elements of the engine tuning,” *Tuning*, 1997. [Online]. Available: <https://www.hks-power.co.jp/en/tuning/p3.html>. [Accessed: 21-Apr-2019].
 47. M. M. Ismail, M. Fawzi, F. H. Zulkifli, and S. A. Osman, “CNG-Diesel Dual Fuel Controlling Concept for Common Rail Diesel,” *International Journal of Integrated Engineering*, vol. 10, no. 3, pp. 88–92, 2018.
 48. S. G. Fritz and R. I. Egbunu, “Emissions from heavy-duty trucks converted to compressed natural gas,” *SAE Technical Papers*, 1993.
 49. L. Shenghua, W. Ziyan, and R. Jiang, “Development of compressed natural gas

- / diesel dual-fuel turbocharged compression ignition engine,” *Engineering*, vol. 217, pp. 839–845, 2003.
50. A. Gharehghani, S. M. Mirsalim, and S. A. Jazayeri, “Numerical and Experimental Investigation of Combustion and Knock in a Dual Fuel Gas/Diesel Compression Ignition Engine,” *Journal of Combustion*, vol. 2012, pp. 1–10, 2012.
 51. K. Cheenkachorn, C. Poompipatpong, and C. G. Ho, “Performance and emissions of a heavy-duty diesel engine fuelled with diesel and LNG (liquid natural gas),” *Energy*, vol. 53, pp. 52–57, May 2013.
 52. R. G. Papagiannakis, C. D. Rakopoulos, D. T. Hountalas, and D. C. Rakopoulos, “Emission characteristics of high speed, dual fuel, compression ignition engine operating in a wide range of natural gas/diesel fuel proportions,” *Fuel*, vol. 89, no. 7, pp. 1397–1406, 2010.
 53. J. Cesar, C. Egúsqiza, and S. L. Braga, “Experimental Investigation of a Diesel Cycle Engine Operating on Natural Gas / Diesel Dual-Fuel Mode,” 2013.
 54. J. Liu, F. Yang, H. Wang, M. Ouyang, and S. Hao, “Effects of pilot fuel quantity on the emissions characteristics of a CNG/diesel dual fuel engine with optimized pilot injection timing,” *Applied Energy*, vol. 110, no. x, pp. 201–206, 2013.
 55. A. A. A. Al-Saadi and I. B. Aris, “CNG-diesel dual fuel engine: A review on emissions and alternative fuels,” in *2015 10th Asian Control Conference: Emerging Control Techniques for a Sustainable World, ASCC 2015*, 2015.
 56. Clean Air Power, “Dual-Fuel™ technology,” 2015. [Online]. Available: <http://www.cleanairpower.com/dual-fuel.html>. [Accessed: 14-Feb-2019].
 57. S. S. Thipse, K. P. Kavathekar, S. D. Rairikar, A. A. Tyagi, and N. V Marathe, “Development of environment friendly diesel-CNG dual fuel engine for heavy duty vehicle application in India,” *SAE Technical Papers*, vol. 5, 2013.
 58. S. Thipse *et al.*, “Development of Dual Fuel (Diesel-CNG) Engine for SUV Application in India,” *SAE Int. J. Engines*, vol. 8, no. 1, pp. 341–349, 2015.
 59. K. Wannatong, S. Kongviwattanukul, and T. Tepimonrat, “Development of Hardware in the Loop System Implemented for Engine Control Unit End of Line Test,” *SAE Technical Paper*, no. 2014-01-2584, 2014.
 60. K. Wannatong, N. Akarapanyavit, S. Siengsanorh, and S. Chanchaona, “Combustion and knock characteristics of natural gas diesel dual fuel engine,”

SAE Technical Papers, 2007.

61. K. Wannatong, S. Siengsanorh, and N. Akarapanyavit, "DF-PCCI: Concept Development of New Diesel Dual Fuel Technology for Diesel Common-Rail Light Duty Pickup Truck," in *The 7th International Conference on Automotive Engineering (ICAE-7)*, 2011.
62. W. Chatlatanagulchai, T. Aroonsrisopon, and K. Wannatong, "Robust common-rail pressure control for a diesel-dual-fuel engine using QFT-based controller," *SAE Technical Papers*, 2009.
63. W. Chatlatanagulchai and K. Yaovaja, "Gain-Scheduling Integrator-Augmented Sliding-Mode Control of Common-Rail Pressure in Diesel-Dual-Fuel Engine," *SAE Technical Paper*, p. 18, 2010.
64. W. Chatlatanagulchai and K. Yaovaja, "Air-Fuel Ratio Regulation with Optimum Throttle Opening in Diesel- Dual-Fuel Engine," *SAE Technical Paper*, p. 13, 2010.
65. W. Chatlatanagulchai, S. Rhienprayoon, K. Yaovaja, and K. Wannatong, "Air/fuel ratio control in diesel-dual-fuel engine by varying throttle, EGR valve, and total fuel," *SAE Technical Papers*, 2010.
66. W. Chatlatanagulchai, N. Pongpanich, K. Wannatong, and S. Rhienprayoon, "Quantitative Feedback Control of Air Path in Diesel-Dual-Fuel Engine," *SAE International*, vol. 2010-01-22, 2010.
67. W. Chatlatanagulchai, I. Moonmangmee, S. Rhienprayoon, and K. Wannatong, "Sliding mode control of air path in diesel-dual-fuel engine," in *SAE 2011 World Congress and Exhibition*, 2011.
68. W. Chatlatanagulchai, K. Yaovaja, S. Rhienprayoon, and K. Wannatong, "Fuzzy knock control of diesel-dual-fuel engine," in *SAE 2011 World Congress and Exhibition*, 2011.
69. K. Wannatong, T. Tepimonrat, and S. Kongviwattanakul, "Cylinder Selective Combustion, the New Diesel Dual Fuel Combustion Control Concept for Low Load Operating Condition," *SAE Technical Papers*, 2018.
70. M. C. Besch, J. Israel, A. Thiruvengadam, H. Kappanna, and D. Carder, "Emissions Characterization from Different Technology Heavy-Duty Engines Retrofitted for CNG/Diesel Dual-Fuel Operation," *SAE International Journal of Engines*, vol. 8, no. 3, 2015.
71. A. Cozzolini *et al.*, "Characteristics of exhaust emissions from a heavy-duty

- diesel engine retrofitted to operate in methane/diesel dual-fuel mode,” *SAE Technical Papers*, vol. 6, 2013.
72. R. G. Papagiannakis and D. T. Hountalas, “Combustion and exhaust emission characteristics of a dual fuel compression ignition engine operated with pilot diesel fuel and natural gas,” *Energy Conversion and Management*, vol. 45, no. 18–19, pp. 2971–2987, 2004.
 73. M. E. J. Stettler, W. J. B. Midgley, J. J. Swanson, D. Cebon, and A. M. Boies, “Greenhouse Gas and Noxious Emissions from Dual Fuel Diesel and Natural Gas Heavy Goods Vehicles,” *Environmental Science & Technology*, vol. 50, pp. 2018–2026, 2016.
 74. W. N. Mansor, “Dual Fuel Engine Combustion and Emissions – an Experimental Investigation coupled with computer simulation,” Colorado State University, 2014.
 75. W. N. W. Mansor, J. S. Vaughn, and D. B. Olsen, “Experimental evaluation of diesel and dual fuel combustion in a 6.8 liter compression ignition engine,” in *Western States Section of the Combustion Institute Spring Technical Meeting 2014*, 2014, pp. 307–319.
 76. W. N. W. Mansor *et al.*, “Engine performance, combustion and emissions evaluations of a diesel natural gas dual fuel engine,” *ARPJ Journal of Engineering and Applied Sciences*, vol. 13, no. 23, pp. 9213–9221, 2018.
 77. W. N. W. Mansor, S. Abdullah, D. B. Olsen, and J. S. Vaughn, “Diesel-natural gas engine emissions and performance,” in *AIP Conference Proceedings*, 2018, vol. 2035.
 78. K. Bhavani and S. Murugesan, “Diesel to dual fuel conversion process development,” *International Journal of Engineering and Technology(UAE)*, vol. 7, no. 3, pp. 306–310, 2018.
 79. R. H. Myers, D. C. Montgomery, and C. M. Anderson-cook, *Response Surface Methodology: Process and Product Optimization using designed experiments*, Fourth Edi. 2016.
 80. M. J. Anderson and P. J. Whitcomb, *RSM simplified : optimizing processes using response surface methods for design of experiments*, 2nd Editio. CRC Press Taylor & Francis Group, 2017.
 81. M. A. Bezerra, R. E. Santelli, E. P. Oliveira, L. S. Villar, and L. A. Escalera, “Response surface methodology (RSM) as a tool for optimization in analytical

- chemistry,” *Talanta*, vol. 76, no. 5, pp. 965–977, 2008.
82. phormula, “KS-3 Knock Detection and Engine Tuning Systems,” 2019. [Online]. Available: <https://www.phormula.com/KnockDetection-KS-3.aspx>. [Accessed: 18-Feb-2019].
 83. PLEX Tuning, “PLEX KNOCK MONITOR V2 | Tune Like a Pro. Never Miss Knock Again.,” 2019. [Online]. Available: <https://www.plex-tuning.com/products/plex-knock-monitor/>. [Accessed: 18-Feb-2019].
 84. S. Delvecchio, P. Bonfiglio, and F. Pompoli, “Vibro-acoustic condition monitoring of Internal Combustion Engines: A critical review of existing techniques,” *Mechanical Systems and Signal Processing*, vol. 99, pp. 661–683, 2018.
 85. F. Molinaro and F. Castani , “Signal processing pattern classification techniques to improve knock detection in spark ignition engines,” *Mechanical Systems and Signal Processing*, vol. 9, no. 1, pp. 51–62, Jan. 1995.
 86. W. Li, F. Gu, A. D. Ball, A. Y. T. Leung, and C. E. Phipps, “A Study of The Noise From Diesel Engines Using The Independent Component Analysis,” *Mechanical Systems and Signal Processing*, vol. 15, no. 6, pp. 1165–1184, Nov. 2001.
 87. S. Klinchaeam, P. Nivesrangsan, and M. Lokitsangthong, “Condition Monitoring of a Small Four-stroke Petrol Engine using Vibration Signals,” *KMITL Sci. Tech. J.*, vol. 9, no. 1, pp. 9–17, 2009.
 88. S. B. Devasenapati, V. Sugumaran, and K. I. Ramachandran, “Misfire identification in a four-stroke four-cylinder petrol engine using decision tree,” *Expert Systems with Applications*, vol. 37, no. 3, pp. 2150–2160, Mar. 2010.
 89. S. Delvecchio, G. D’Elia, E. Mucchi, and G. Dalpiaz, “Advanced signal processing tools for the vibratory surveillance of assembly faults in diesel engine cold tests,” *Journal of Vibration and Acoustics, Transactions of the ASME*, vol. 132, no. 2, pp. 210081–2100810, 2010.
 90. S. Delvecchio, G. D’Elia, E. Mucchi, and R. Di Gregorio, “On the monitoring and diagnosis of assembly faults in diesel engine cold tests: A case study,” in *Proceedings of the ASME Design Engineering Technical Conference*, 2009, vol. 1, no. Part A and B, pp. 3–12.
 91. M. J. Mahjoob and A. Zamanian, “Vibration Signature Analysis for Engine Condition Monitoring and Diagnosis,” in *ISMA2006*, 2006.

92. J.-D. Wu and J.-C. Chen, "Continuous wavelet transform technique for fault signal diagnosis of internal combustion engines," *NDT & E International*, vol. 39, no. 4, pp. 304–311, Jun. 2006.
93. Z. Geng, J. Chen, and J. Barry Hull, "Analysis of engine vibration and design of an applicable diagnosing approach," *International Journal of Mechanical Sciences*, vol. 45, no. 8, pp. 1391–1410, Aug. 2003.
94. J. Antoni, J. Daniere, and F. Guillet, "Effective Vibration Analysis of IC Engines Using Cyclostationarity. Part I-A Methodology for Condition Monitoring," *Journal of Sound and Vibration*, vol. 257, no. 5, pp. 815–837, Nov. 2002.
95. J. Antoni, J. Daniere, F. Guillet, and R. B. Randall, "Effective Vibration Analysis of IC Engines Using Cyclostationarity. Part II—New Results on The Reconstruction of The Cylinder Pressures," *Journal of Sound and Vibration*, vol. 257, no. 5, pp. 839–856, Nov. 2002.
96. S. Delvecchio, G. D'Elia, and G. Dalpiaz, "On the use of cyclostationary indicators in IC engine quality control by cold tests," *Mechanical Systems and Signal Processing*, vol. 60, pp. 208–228, 2015.
97. D. C. Montgomery, *Design and Analysis of Experiments*, 8th editio. John Wiley & Sons, Inc., 2013.
98. M. M. Ismail, F. H. Zulkifli, M. Fawzi, and S. A. Osman, "Conversion method of a diesel engine to a CNG-diesel dual fuel engine and its financial savings," *ARPJ Journal of Engineering and Applied Sciences*, vol. 11, no. 8, 2016.
99. Alicat Scientific, "Technical Data for Alicat M-Series Mass Flow Meters," 2017. [Online]. Available: <http://bit.ly/30tgXqC>. [Accessed: 29-Jan-2019].
100. Robert Bosch Gmbh, "Product Details: Bosch KTS 570," 2013. [Online]. Available: <https://fccid.io/ANATEL/02477-14-09026/manual/2A90E3CE-77B6-46F9-B198-4D4B1033353D/PDF>. [Accessed: 30-Jan-2019].
101. Robert Bosch GmbH (Ed.), *Bosch Automotive Electrics and Automotive Electronics: Systems and Components, Networking and Hybrid Drive*, 5th Editio. Springer Vieweg, 2014.
102. National Instrument, "NI cDAQ - 9188 Specification," 2017. [Online]. Available: <http://www.ni.com/pdf/manuals/370086c.pdf>. [Accessed: 31-Jan-2019].
103. National Instrument, "NI 9411 Datasheet," 2015. [Online]. Available:

- http://www.ni.com/pdf/manuals/373506a_02.pdf. [Accessed: 31-Jan-2019].
104. National Instrument, "NI 9222 Datasheet," 2016. [Online]. Available: http://www.ni.com/pdf/manuals/374210a_02.pdf. [Accessed: 31-Jan-2019].
 105. A. Iijima, K. Takeda, Y. Yoshida, Z. Lin, and H. Shoji, "A Study of Interaction between Pressure Waves and Reaction Regions in HCCI Combustion accompanied by Strong Knocking based on High-speed In-cylinder Visualization and Observation," in *26th ICDERS*, 2017, pp. 1–6.
 106. R. Mohsin, Z. A. Majid, A. H. Shihnan, N. S. Nasri, and Z. Sharer, "Effect of biodiesel blends on engine performance and exhaust emission for diesel dual fuel engine," *Energy Conversion and Management*, vol. 88, no. x, pp. 821–828, 2014.
 107. M. M. Ismail, "Effect of Fuel Delivery Ratio of Diesel-CNG Dual Fuel Engine on Performance and Emissions," Universiti Tun Hussein Onn Malaysia, 2016.
 108. Alexander A. Stotsky, *Automotive Engines: Control, Estimation, Statistical Detection*. Springer-Verlag Berlin Heidelberg, 2009.
 109. J. R. Taylor, *An introduction to error analysis the study of uncertainties in physical measurements*, 2nd Editio. University Science Books, 1997.
 110. P. R. Bevington and D. K. Robinson, *Data Reduction and Error Analysis for the Physical Sciences*, 3rd Editio. McGraw-Hill, 2003.
 111. H. W. Coleman and W. G. Steele, *Experimentation, Validation, and Uncertainty Analysis for Engineers*, 4th Editio. John Wiley & Sons, Inc., 2018.
 112. G. W. Oehlert, *A First Course in Design and Analysis of Experiments*. New York: W. H. Freeman, 2010.
 113. K. Ryu, "Effects of pilot injection timing on the combustion and emissions characteristics in a diesel engine using biodiesel-CNG dual fuel," *Applied Energy*, vol. 111, pp. 721–730, 2013.