

Technical University of Denmark



Urban runoff forecasting with ensemble weather predictions

Pedersen, Jonas Wied; Courdent, Vianney Augustin Thomas; Vezzano, Luca; Madsen, Henrik; Mikkelsen, Peter Steen

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Pedersen, J. W., Courdent, V. A. T., Vezzano, L., Madsen, H., & Mikkelsen, P. S. (2017). Urban runoff forecasting with ensemble weather predictions. Abstract from NORDIWA Nordic Wastewater Conference 2017, Aarhus, Denmark.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Title: Urban runoff forecasting with ensemble weather predictions

Authors:

Jonas Wied Pedersen¹, Vianney Courdent^{1,2}; Luca Vezzaro^{1,2}; Henrik Madsen³; Peter Steen Mikkelsen¹

¹DTU Environment

²Krüger A/S, Veolia Water Technologies, Denmark

³DTU Compute

Summary:

This research shows how ensemble weather forecasts can be used to generate urban runoff forecasts up to 53 hours into the future. The results highlight systematic differences between ensemble members that needs to be accounted for when these forecasts are used in practice.

Abstract:

Numerical Weather Predictions (NWP) can help extend the lead time of urban runoff forecasts. The use of these forecasts within integrated stormwater management is, however, still rare. Uncertainty in NWP is generally provided in the form of ensemble forecasts, which sample the uncertainty related to various aspects of the weather model. In this study, weather forecasts from the Danish Meteorological Institute's (DMI) HIRLAM-S05 NWP Ensemble are used. DMI's ensemble consists of 25 individual forecasts that are produced by pairing five different model structures with five ways of generating initial conditions. Ensemble forecasts are generated every six hours with a spatio-temporal resolution of 5x5 km² and 1 hr. The case area is the northern part of the Damhusåen catchment in Copenhagen, Denmark, and data is available from June 2014 to July 2016. The weather forecasts are used to force a conceptual urban runoff model based on Nash cascades, yielding flow forecasts up to 53 hours into the future. The flow forecasts are compared with observed flow at the outlet of the local sewer system. Comparison is only made when the observed flow is above the normal daily dry weather variations, i.e. when stormwater is present.

One figure is attached to this abstract. It shows the Mean Absolute Error (MAE) for each ensemble member as a function of the forecast horizon. Each member's MAE is indicated by a thin line in both the upper and lower part of the figure. The difference between the two parts are the coloring of each line. In the upper part, each member is colored depending on the weather model's structure while the lower part colors each member depending on its approach to setting up initial conditions. The thick lines are the average of each color's error. It is seen that two of the model structures systematically produce larger errors than the others while there is no apparent pattern in the initial condition plot. This suggests that the choice of model structure has a larger effect on forecast skill than the initial conditions. A slight decrease in forecast skill is seen for all ensemble members as the forecast horizon increases. Future research will focus on how the systematic differences in the

ensemble can be accounted for when these types of forecasts are used for integrated stormwater management.

Comments:

This work was funded by a grant from the Innovation Fund Denmark for the project Water Smart Cities under contract no 5157-00009B. We thank HOFOR A/S for flow data and DMI for weather forecasts.

