



# LUND UNIVERSITY

## Fixation detection in noisy eye-movement data

Hessels, Roy S; Niehorster, Diederick C; Kemner, Chantal; Hooge, Ignace T C

2016

*Document Version:*

Publisher's PDF, also known as Version of record

[Link to publication](#)

*Citation for published version (APA):*

Hessels, R. S., Niehorster, D. C., Kemner, C., & Hooge, I. T. C. (2016). *Fixation detection in noisy eye-movement data*. Abstract from The Scandinavian Workshop on Applied Eye Tracking 2016, Turku, Finland.

*Total number of authors:*

4

### General rights

Unless other specific re-use rights are stated the following general rights apply:

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: <https://creativecommons.org/licenses/>

### Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

LUND UNIVERSITY

PO Box 117  
221 00 Lund  
+46 46-222 00 00

### **Fixation detection in noisy eye-movement data**

Roy S. Hessels<sup>1</sup>, Diederick C. Niehorster<sup>2</sup>, Chantal Kemner<sup>1</sup>, & Ignace T.C. Hooge<sup>1</sup>

<sup>1</sup> Utrecht University, <sup>2</sup> Lund University

Eye-tracking research in infants and older children has gained a lot of momentum over the last decades. While eye-tracking research in these participants groups has become easier with the advance of the remote eye tracker, this often comes at a cost of poorer data quality compared to research with well-trained adults (Hessels, Andersson, Hooge, Nyström, & Kemner, 2015; Wass, Forssman, & Leppänen, 2014). Current solutions for automatic detection of fixations in eye-tracking data, both those provided by eye-tracker manufacturers and the research community, are not built for data from infants and older children. As a result, the output of such algorithms are often unreliable when the data are noisy. The purpose of the present work was to address the need for an algorithm capable of labeling fixations across a wide range of noise levels in data where periods of data loss may occur. Here we proposed and evaluated a new algorithm designed specifically for eye-movement data of varying data quality: Identification by 2-Mean Clustering (I2MC). In comparison with seven other state-of-the-art event-detection algorithms, we found that the number of fixations, mean fixation duration and standard deviation of fixation duration by the I2MC algorithm are most robust to increases in noise level and data loss. The I2MC algorithm is applicable to fixation labeling in situations where the data quality may be low, for instance when working with infants, school children, or certain patient groups. The I2MC algorithm may be used when the noise and data loss levels are markedly different between trials and/or subjects; the output should be comparable despite these differences in noise and data loss levels.