Technical University of Denmark



Energy-Aware Synthesis of Fault-Tolerant Schedules for Real-Time Distributed Embedded Systems

Poulsen, Kåre Harbo; Pop, Paul; Izosimov, Viacheslav

Published in: Work-In-Progress Proceedings of 19th Euromicro Conference on Real-Time Systems

Publication date: 2007

Document Version Publisher's PDF, also known as Version of record

Link back to DTU Orbit

Citation (APA):

Poulsen, K. H., Pop, P., & Izosimov, V. (2007). Energy-Aware Synthesis of Fault-Tolerant Schedules for Real-Time Distributed Embedded Systems. In Work-In-Progress Proceedings of 19th Euromicro Conference on Real-Time Systems (pp. 21-24)

DTU Library Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Reliability-Aware Energy Optimisation for Fault-Tolerant Embedded MP-SoCs



Summary

- Design optimisation tool for distributed embedded real-time systems
- Decides mapping, fault-tolerance policy and fault-tolerant schedule
 - Hard real-time,
 - Hard reliability goal,
 - Static schedule for processes and messages,
 - Fault-tolerance for *k* transient/soft faults
- Optimise for minimal energy consumption
- While considering impact of lowering voltages on the probability of faults
- Constraint logic programming (CLP) based implementation

Comparison of FT schemes



Fault-tolerance

- Faults are tolerated by using temporal or spatial redundancy, or a combination of the two
- Fault detection is done using well known techniques such as: timing and bit coding





PE₂ **Re-execution**



Energy vs. Faults

- Recent research¹ shows that the probability of transient/soft faults increases dramatically when decreasing the voltage of a circuit
- Many modern designs uses dynamic voltage scaling (DVS) to minimise energy consumption
- Fault-tolerant systems that use power management techniques may prove to be fault-tolerant but unreliable due to increase in faults
- Relation between faults and voltage is given by¹:

Fault-tolerant scheduling

- More complex scheduling schemes yield more slack for energy management
 - Trade-off transparency for performance
 - Performance, and hence the obtainable energy savings are greatly increased
- More complex schemes demand larger schedule tables to be stored in the processing elements, and more sophisticated online schedulers

Reliable energy management

- System reliability is affected by use of energy management
 - The use of DVS increases the probability of faults, thus damaging the system reliability
- Reliability *must* be considered in the optimisation process
 - Considering reliability in the optimisation process allows for finding the minimum energy schedule that meets the reliability goal
 - Reliability is imposed as a constraint

Reliability can be met at very little energy cost

 Considering the reliability while optimising enables us to find reliable schedules with comparable energy savings



$$\lambda f = \lambda_0 10^{\frac{d 1 - f}{1 - f_{min}}}$$



¹ D. Zhu et al.: "Reliability-Aware Energy Management for Periodic Real-Time Tasks", 2007



IMM / Informatics and Mathematical Modelling

eselab.imm.dtu.dk

