

Technical University of Denmark



## Squeezing Molecularly thin Lubricant Films between curved Corrugated Surfaces with long range Elasticity

Sivebæk, Ion Marius; Samoilov, Vladimir N.; Persson, Bo N. J.

*Published in:*  
14th Nordic Symposium on Tribology - Nordtrib 2010

*Publication date:*  
2010

[Link back to DTU Orbit](#)

*Citation (APA):*  
Sivebæk, I. M., Samoilov, V. N., & Persson, B. N. J. (2010). Squeezing Molecularly thin Lubricant Films between curved Corrugated Surfaces with long range Elasticity. In 14th Nordic Symposium on Tribology - Nordtrib 2010 (pp. 0172)

**DTU Library**  
Technical Information Center of Denmark

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

0172

### **Squeezing Molecularly thin Lubricant Films between curved Corrugated Surfaces with long range Elasticity**

Jon, M Sivebaek<sup>1,2</sup>, Vladimir, N Samoilov<sup>1,4</sup>, Bo, N, J Persson<sup>1</sup>

<sup>1</sup>IFF, Jülich, Germany, <sup>2</sup>Novo Nordisk A/S, Device R&D, Hillerød, Denmark, <sup>3</sup>Mech. Eng., Technical University of Denmark, Lyngby, Denmark, <sup>4</sup>Physics Faculty, Moscow State University, Moscow, Russian Federation

The present work investigates the ability of two nm thick lubrication films to stay in a contact and thereby to prevent excessive wear of the surfaces. At this thickness the film is no longer a fluid but it is the very important intermediate between the lubricated and the dry regimes, the latter one being associated with devastating wear progress.

The properties of alkane lubricants confined between two approaching solids are investigated by a model that accounts for the roughness, curvature and elastic properties of the solid surfaces. We consider linear alkanes of different chain lengths, C<sub>3</sub>H<sub>8</sub>, C<sub>4</sub>H<sub>10</sub>, C<sub>8</sub>H<sub>18</sub>, C<sub>9</sub>H<sub>20</sub>, C<sub>10</sub>H<sub>22</sub>, C<sub>14</sub>H<sub>30</sub> and C<sub>16</sub>H<sub>34</sub>, confined between corrugated gold surfaces. Well defined molecular layers develop in the lubricant film when the width is of the order of a few atomic diameters. An external squeezing pressure induces discontinuous, thermally activated changes in the number of lubricant layers between the corrugation tops. The pressure necessary to squeeze out a single layer of lubricant in the case of corrugated substrate is significantly lower than in the case of flat substrate which is mainly due to the smaller radius of curvature in the corrugated contacts. Single layers are squeezed out at higher pressures for longer alkanes than for shorter ones which indicates that longer alkanes are better lubricants. The longest alkanes are capable of domain formations which result in even higher squeeze out pressures. The short alkanes stay fluid-like during the entire squeeze out process. The corrugation of the substrate plays an important role in lubrication in the investigated systems. Its amplitude and periodicity determine the quantity of lubricant that can be trapped and the number of contact points between the block and the substrate. The latter point is important as lubrication enhancing domain formation of longer alkanes in just one contact point can delay the squeeze out of lubricant in other points which should result in less wear. We obtain good correlation between our theoretical results and wear experiments.