

#### Heuristic Approaches to a Pickup and Delivery Problem with Sequencing Constraints

Petersen, Hanne Løhmann

Publication date: 2006

Link back to DTU Orbit

*Citation (APA):* Petersen, H. L. (2006). Heuristic Approaches to a Pickup and Delivery Problem with Sequencing Constraints. Abstract from CORS / Optimization Days 2006 : Joint Conference, Montreal, Canada, .

#### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



## Heuristic Approaches to a Pickup and Delivery Problem with Sequencing Constraints

# Hanne L. Petersen hlp@ctt.dtu.dk

Optimization Days 2006 | Hanne L. Petersen

Heuristic Solution Approaches

Conclusion and Results



#### Centre for Traffic and Transport Informatics and Matematical Modelling



- 2 Mathematical Model
- Heuristic Solution Approaches
- 4 Conclusion and Results

Introduction Math	
•• ••	

Centre for Traffic and Transport Informatics and Matematical Modelling

Conclusion and Results



### **Problem Definition**

- Pickup and delivery problem from real life
  - pickups and deliveries are performed in separated areas/graphs, ie. all pickups lie before all deliveries
  - each order consists of one item, which has a pickup address and a delivery address
  - all orders served by the same container, no repacking
  - sequencing constraints on loading, the available loading positions form a grid on the floor of the container
  - all items uniform, no stacking

Introduction	
••	

Centre for Traffic and Transport Informatics and Matematical Modelling

Conclusion and Results



## **Problem Definition**

- Pickup and delivery problem from real life
  - pickups and deliveries are performed in separated areas/graphs, ie. all pickups lie before all deliveries
  - each order consists of one item, which has a pickup address and a delivery address
  - all orders served by the same container, no repacking
  - sequencing constraints on loading, the available loading positions form a grid on the floor of the container
  - all items uniform, no stacking
- [DEMO]

Introduction	
00	

Centre for Traffic and Transport Informatics and Matematical Modelling

Conclusion and Results



## **Problem Definition**

- Pickup and delivery problem from real life
  - pickups and deliveries are performed in separated areas/graphs, ie. all pickups lie before all deliveries
  - each order consists of one item, which has a pickup address and a delivery address
  - all orders served by the same container, no repacking
  - sequencing constraints on loading, the available loading positions form a grid on the floor of the container
  - all items uniform, no stacking
- [DEMO]
- With only one available loading row the pickup and delivery routes must strictly obey the LIFO principle.
- With one loading row available per item the two routes are completely independent.

Introduction		
	Centre for Traffic and	Transport DTU

## The Problem II

- The problem has not previously been described in literature
- It is an extension of the regular travelling salesman problem (TSP), with
  - pickups and deliveries
  - multiple loading rows (individually accessible)
- Given: A set of orders, each with a pickup and a delivery address.
- Produce:
  - pickup route
  - delivery route
  - loading plan
- Objective: Minimise travelled distance

Mathematical Model ●00			and Results
	Centre for Traffic and Informatics and Matematical	Transport Modelling	DTU

First variable:  $x_{ij}^{\tau} = 1$  if edge (i, j) is used in graph  $\tau$ , 0 otherwise. Objective:

$$\min \sum_{i,j \in N_0, \tau \in \{\mathsf{P},\mathsf{D}\}} c_{ij}^{\tau} \cdot x_{ij}^{\tau}$$

Flow balance:

$$\sum_{i} x_{ij}^{ au} = 1$$
  $\forall j \in N_0$   
 $\sum_{j} x_{ij}^{ au} = 1$   $\forall i \in N_0$ 

r

	Mathematical Model			
		Centre for Traffic and Traffic and Informatics and Matematical N	Fransport Aodelling	DTU
Prec	edence constra	aints I		

Second variable:  $y_{ij}^{\tau} = 1$  if the address of item *i* is visited prior to that of item *j* in graph  $\tau$ , 0 otherwise.

$$\begin{array}{ll} y_{ij}^{\tau} + y_{ji}^{\tau} = 1 & \forall i, j, \tau, i \neq j \\ y_{ik}^{\tau} + y_{kj}^{\tau} \leq y_{ij}^{\tau} + 1 & \forall i, j, k, \tau \\ x_{ij}^{\tau} \leq y_{ij}^{\tau} & \forall i, j, \tau \end{array}$$

Mathematical Model		
	Centre for Traffic and Informatics and Matematical	DTU

#### Precedence constraints II

Precedences are only relevant when two items in the same row.

Third variable:  $z_{ir} = 1$  if item *i* is placed in row *r*, 0 otherwise.

$$y_{ij}^{\mathsf{P}} + z_{ir} + z_{jr} \le 3 - y_{ij}^{\mathsf{D}}$$
  $\forall i, j, r$ 

Finally keep track of the row assignments:

$$\sum_{r} z_{ir} = 1 \qquad \forall i$$
$$\sum_{i} z_{ir} \leq L \qquad \forall r$$

		Heuristic Solution Approaches •000		
		Centre for Traffic and Informatics and Matematical	Transport Modelling	DTU
Heuri	stics			

The mathematical model has been implemented in GAMS, which can only solve instances with up to 12 orders (typical size in real life is 33 orders for one container).

Heuristics!

- Steepest Descent
- Tabu search
- Simulated Annealing
  - Modified to take running time as parameter instead of the temperature reduction coefficient:

$$T(t) = T_{\text{start}} \cdot rac{T_{ ext{end}}}{T_{ ext{start}}}^{rac{t}{t_{ ext{total}}}}$$

Heuristic Solution Approaches  $0 \bullet 00$ 

Centre for Traffic and Transport Informatics and Matematical Modelling

Conclusion and Results



## **Complication: The LIFO Condition**

- strict LIFO (one row problem) gives a tighter and simpler problem - the two trips must exactly be eachother's opposite:
  - add the two distance matrices
  - solve a regular TSP
- this gives an initial solution


Conclusion and Results





#### **Two Different Neighbourhood Structures**

- Change routing, keep row assignment
  - swap any pair of customers that are adjacent in either route
  - if they are in the same row, also swap in opposite route (loading positions will be swapped)
  - if they are in separate rows, nothing else needs to be changed (loading positions will be unchanged)



Heuristic Solution Approaches  $000 \bullet$ 


Centre for Traffic and Transport Informatics and Matematical Modelling

Conclusion and Results



#### **Two Different Move Structures II**

- Swap rows
  - swap the loading positions of any two items that are in separate rows
  - also swap their positions in both routes



Heuristic Solution Approaches  $000 \bullet$ 


Centre for Traffic and Transport Informatics and Matematical Modelling

Conclusion and Results



#### **Two Different Move Structures II**

- Swap rows
  - swap the loading positions of any two items that are in separate rows
  - also swap their positions in both routes




In the end both moves are necessary to cover the solution space

Heuristic Solution Approaches 0000 Conclusion and Results

DTU







Introduction 00 Mathematical Model


Heuristic Solution Approaches

Conclusion and Results





#### Initial Solution (Savings Algorithm)




Heuristic Solution Approaches 0000 Conclusion and Results





#### **Best Heuristic Solution**



		Conclusion and Results
	Contro for Troffic and	Transport <b>DTII</b>

Informatics and Matematical Modelling



### Summary

- The real-life version of the problem has 3 rows and n = 33 orders.
- GAMS can solve to optimality for up to 12 orders (in 30-45 minutes). (15 orders: 945 v., 8400 c.; 33 orders: 4,500 v., 80,000 c.)
- A feasible solution can be obtained by adding the distance matrices of the graphs and solving TSP (ie. strict LIFO).
- A (weak) lower bound can be obtained by solving a TSP in each graph (ie. relaxing LIFO conditions).

Introduction 00		Conclusion and Re



esults

#### Centre for Traffic and Transport Informatics and Matematical Modelling

### **Results of Heuristics**

- Testing has been done on 10 randomly generated instances with 33 orders.
- Simple steepest descent does not give acceptable results (75% above best known solution).
- Simulated Annealing outperforms Tabu Search.
- Solution not very stable with running times around 10 minutes solutions vary within 3-20% above best known solution.
- Best results from SA (ie. best known) are 10-20% above the "independent TSPs" lower bound

Heuristic Solution Approaches

Conclusion and Results



Centre for Traffic and Transport Informatics and Matematical Modelling

#### Results

Best feas.	LB	LB-ratio	Init.	Initratio
1092	914	1.19	1813	1.66
1066	875	1.22	1747	1.64
1106	935	1.18	1645	1.49
1128	961	1.17	1818	1.61
1097	933	1.18	1700	1.55
1038	898	1.16	1606	1.55
1127	998	1.13	1757	1.56
1162	962	1.21	1816	1.56
1117	976	1.15	1746	1.56
1100	982	1.12	1669	1.52

		Conclusion an	d Results
	Centre for Traffic and T Informatics and Matematical N	ransport lodelling	DTU

#### **Further work**

- Examine the effects of:
  - the number of loading rows (one row and *n* rows are trivial)
  - having several items in one order, ie. sharing pickup and delivery adresses
- Expand the problem:
  - multiple vehicles
  - multiple depots
- Solve to optimality

Heuristic Solution Approaches

Conclusion and Results



Centre for Traffic and Transport Informatics and Matematical Modelling

# Thank you for your attention.

# Questions?