

Technical University of Denmark



Two-Dimensional Modeling of the Electrokinetic Desalination Treatment of a Brick Wall

Abstract of oral presentation

Paz Garcia, Juan Manuel; Johannesson, Björn ; Ottosen, Lisbeth M.; Ribeiro, A.B.; Rodriguez-Maroto, J.M.

Published in:

2011 EREM : Developments in Elektrokinetic Remediation of Soils, Sediments and Construction Materials

Publication date:

2011

Document Version

Early version, also known as pre-print

[Link back to DTU Orbit](#)

Citation (APA):

Paz-Garcia, J. M., Johannesson, B., Ottosen, L. M., Ribeiro, A. B., & Rodriguez-Maroto, J. M. (2011). Two-Dimensional Modeling of the Electrokinetic Desalination Treatment of a Brick Wall: Abstract of oral presentation. In 2011 EREM : Developments in Elektrokinetic Remediation of Soils, Sediments and Construction Materials (pp. 94-95)

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Two-Dimensional Modeling of the Electrokinetic Desalination Treatment of a Brick Wall

J. M. Paz-García^{A*}, B. Johannesson^A, L. M. Ottosen^A, A. B. Ribeiro^B and J.M. Rodriguez-Maroto^C

^A Department of Civil Engineering, Technical University of Denmark, 2800-Kgs. Lyngby, Denmark

^B Department of Environmental Sciences and Engineering, New University of Lisbon, Campus de Caparica, 2829-516 Caparica, Portugal

^C Department of Chemical Engineering, University of Málaga, Campus de Teatinos, 29071 Málaga, Spain

* Corresponding author at: jugra@byg.dtu.dk, Tel: +45 4525 5029, Fax: +45 4588 3282

Introduction

Chlorides, nitrates and sulfates are considered the main responsible of the salt-induced decay in facades and sculptures. Electrokinetic desalination treatments have been showing high efficiency for the recuperation of different construction materials suffering from salt weathering [1]. Buffer substance enhancement methods are typically used in order to avoid damage in the material due to the pH changes, as well as to improve the removal efficiency. In some practical cases, the electrokinetic desalination treatment of a wall requires the electrodes to be placed in the same surface [2]. On these cases, the clean up process proceeds in an inhomogeneous way with respect to the depth of the wall. The region of the wall close the external surface where the electrodes are placed is cleaned faster. Due to changes on the conductivity of the pore solution as a result of the removal process, the desalination proceeds deeper in the domain. At the same time, the gradient in the concentration of the species promotes the transport in the direction of the external surface.

In the present work, a two-dimensional model of electrokinetic desalination process of a brick wall is discussed. In the modeled system, the reactive flow of ionic and non-ionic species is described taking into account the transport phenomena and the chemical and electrochemical interactions affecting the different species in the system as well as the solid matrix. The transport process is modeled by finite elements integration of the strongly coupled Nernst-Planck-Poisson system of equations. A mass balance equation, for each chemical species included in the system, is considered. The flux term of the continuity equation takes into account the contribution of the different transport terms: the diffusion, the electromigration and the electroosmosis. The electrical

potential is calculated from the global charge balance by the use of the Poisson's equation of electrostatics, which completes the equation system [3].

Depending on the concentration and nature of the species in the vicinities of the electrodes, the competition of different electrochemical reactions is considered. In addition to this, a set of feasible chemical equilibrium reactions is defined, and the chemical equilibrium state is assured in any position of the domain during the complete transport process. A line search Newton-Raphson method that iterates on the extents of the reaction is used for this chemical equilibrium model.

Results from simulations of test examples are presented. The brick wall is considered initially contaminated with different combination of salts in the pore solution, and the electrodes placed in the same surface of the wall. Profiles of the target species are obtained, as well as theoretical conductivity and the ionic current in the domain during the desalination process.

Acknowledgements

Authors acknowledge The Danish Agency of Science Technology and Innovation. This research was funded as part of the project "Fundamentals of Electrokinetics in In-homogeneous Matrices".

References:

- [1] L.M. Ottosen, I.V. Christensen, I. Rörid-Dalgård, P.E. Jensen, H.K. Hansen, Utilization of electromigration in civil and environmental engineering - Processes, transport rates and matrix changes, *J. Environ. Sci. Health.* 43 (2008) 795-809.

- [2] L.M. Ottosen, I. Rörig-Dalgaard, A. Villumsen, Electrochemical removal of salts from masonry - Experiences from pilot scale, in: *Salt Weathering on Buildings and Stone Sculptures: Proceedings from the international conference: Copenhagen (2008)* 341-250.

- [3] J.M Paz-García, B. Johannesson, L.M. Ottosen, A.B. Ribeiro, J.M. Rodríguez-Maroto, Modeling of the Ionic Multi-Species Transport Phenomena in Electrokinetic Processes and Comparison with Experimental Results In: *Scientific Advances and Innovative Applications in Electrokinetic Remediation , The 9th Symposium in Electrokinetic Remediation. Kaohsiung, Taiwan (2010)* 69-70.