

Technical University of Denmark



First measurements by the DTU wind energy short range windscanner

Sjöholm, Mikael; Angelou, Nikolas; Hansen, Kasper Hjorth; Mann, Jakob; Mikkelsen, Torben Krogh

Published in:

Proceedings of EWEA 2012 - European Wind Energy Conference & Exhibition

Publication date:

2012

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Sjöholm, M., Angelou, N., Hansen, K. H., Mann, J., & Mikkelsen, T. (2012). First measurements by the DTU wind energy short range windscanner. In Proceedings of EWEA 2012 - European Wind Energy Conference & Exhibition European Wind Energy Association (EWEA).

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

ABSTRACT ID: 359

Theme: RESOURCE ASSESSMENT Topic: Advances in measuring techniques for resource assessment

FIRST MEASUREMENTS BY THE DTU WIND ENERGY SHORT RANGE WINDSCANNER

Mikael Sjöholm(1) (F) (P) Nikolas Angelou(1) Kasper Hjorth Hansen(1) Jakob Mann(1) Torben Mikkelsen(1)

(1) DTU Wind Energy, Roskilde, Denmark

Introduction

Remote sensing Doppler Lidar instruments (Light detection and ranging) have been commercially available for wind resource assessment for quite some time now and they are measuring the radial wind component along their line of sights. The 3D wind vector is extracted from the line of sight wind speeds along several directions on a conical surface combined with the horizontal homogeneity assumption. However, over the large circular area scanned, this assumption is not applicable in complex terrain and around complex structures such as buildings and wind turbines.

Approach

At Risø DTU this is circumvented by the development of an alternative approach where the laser beams of three wind Lidars are directed towards a common movable location which gives the possibility to measure the full 3D wind field. Both a long range WindScanner system based on WindCubes from Leosphere and a short range WindScanner system based on modified ZephIRs from Natural Power are currently developed at Risø DTU.

Main body of abstract

Here, the focus is on the continuous-wave short range ZephIR-based WindScanner that can direct the wind Lidar laser beam by a double prism arrangement in any direction within a cone with a full opening angle of 120 degrees and where the center of the measurement volume is accordingly changed by a dynamic focus mechanism. The WindScanner and its performance are presented and some examples from the initial measurements of the wind within a plane scanned by a single short range WindScanner are reported. The first trials have included scanning in a vertical plane within the wake of a small building as well as within the flow that has passed a steep 12-m high escarpment at the small isolated Bolund peninsula at the Roskilde fjord in Denmark. Previously the flow over Bolund has been measured by classical instrumentation and used for comparison of various flow models since it is a good small scale model site featuring flow phenomena that are typical for complex terrain in which wind turbines often are placed.

Conclusion

The short range WindScanner system advances the possibilities of studying wind and turbulence fields in complex terrain, around wind turbines and buildings remotely without disturbing the flow by meteorological towers which opens up many new research possibilities in the coming years.