

Technical University of Denmark



Vapor–Liquid–Liquid Equilibrium Measurements and Modeling of the Methanethiol + Methane + Water Ternary System at 304, 334, and 364 K

Awan, Javeed; Tsivintzelis, Ioannis; Valtz, Alain; Coquelet, Christophe; Kontogeorgis, Georgios

Published in: Industrial & Engineering Chemistry Research

Link to article, DOI: 10.1021/ie300888d

Publication date: 2012

Document Version Publisher's PDF, also known as Version of record

Link back to DTU Orbit

Citation (APA):

Awan, J., Tsivintzelis, I., Valtz, A., Coquelet, C., & Kontogeorgis, G. (2012). Vapor–Liquid–Liquid Equilibrium Measurements and Modeling of the Methanethiol + Methane + Water Ternary System at 304, 334, and 364 K. Industrial & Engineering Chemistry Research, 51(35), 11561-11564. DOI: 10.1021/ie300888d

DTU Library Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



Vapor-Liquid-Liquid Equilibrium Measurements and Modeling of the Methanethiol + Methane + Water Ternary System at 304, 334, and 364 K

Javeed A. Awan,[†] Ioannis Tsivintzelis,[†] Alain Valtz,[‡] Christophe Coquelet,[‡] and Georgios M. Kontogeorgis*,[†]

[†]Center for Energy Resources Engineering (CERE), Department of Chemical and Biochemical Engineering, Technical University of Denmark, Building 229, DK-2800 Kgs. Lyngby, Denmark

^{*}Mines ParisTech, CEP/TEP-Centre Énergétique et Procédés, 35 Rue Saint Honoré, 77305 Fontainebleau, France

ABSTRACT: New vapor-liquid-liquid equilibrium (VLLE) data for methanethiol (CH_3SH) + methane (CH_4) + water (H_2O) have been obtained at three temperatures (304, 334, and 364 K) and pressures up to 9 MPa. A "static-analytical" method was used to perform all of the measurements. The objective was to provide experimental VLLE data for CH₃SH with other natural gas contents at its crude form for which limited or no data are available in the open literature. Such kinds of data are required for the industrial modeling of sulfur emissions. It is observed from the experimental data that the solubility of CH_4 in the aqueous and organic phases increases with an increase of the total system pressure and decreases with an increase of the temperature. However, the solubility of CH₃SH in the aqueous and organic phases decreases slightly with an increase of the total system pressure and increases significantly with an increase of the temperature. The new VLLE data of this ternary system were compared with predictions of the cubic-plus-association equation of state. The model tends to underpredict the concentration of CH₃SH in all phases, particularly the vapor phase.

1. INTRODUCTION

Methanethiol (methyl mercaptan) is a common component encountered in natural gas, synthesis gas, and various refinery process streams. Its typical concentration in the host gas stream can range from several parts per million to 50% by volume.¹ Treatment processes need to be designed in order to remove not only H₂S and CO₂ but also organic sulfur species like methanethiol and other prohibited compounds. This is necessary because regulations for environmental protection force the petroleum industry to decrease the sulfur content in various petroleum fluids. Furthermore, any thiols/mercaptans (RSH), carbonyl sulfide (COS), and carbon disulfide (CS₂) not absorbed from the sour gas through the amine purification units complicate the process scheme for downstream liquid treatment units.² Knowledge of the phase equilibrium behavior and thermophysical properties of sulfur species mixtures with hydrocarbons/water is important to both process design and product specifications.

This work is a continuation of our previous $work^{2-4}$ on the phase equilibrium measurements of systems containing thiols (mercaptans) with water and hydrocarbons. Such kinds of data are highly important for the design of new separation processes and the upgrade of existing processes. In this work, we provide new vapor-liquid-liquid equilibrium (VLLE) data for methanethiol (CH_3SH) + methane (CH_4) + water (H_2O) at three temperatures (304, 334, and 364 K) and pressures up to 9 MPa. The new VLLE data of these ternary systems were modeled with the cubic-plus-association (CPA) equation of state (EOS) using no adjustable parameters optimized in the ternary system data.

2. EXPERIMENTAL SECTION

Methanethiol (CH₃SH, CAS Registry No. 74-93-1) was obtained from Aldrich and has a purity of 0.99 mole fraction. Methane (CH₄, CAS Registry No. 74-82-8) was obtained from Messer and has a purity of 0.998 mole fraction. Ultrapure water (H₂O) was produced in the laboratory using commercial equipment (Millipore, model Direct-Q5). The electrical conductivity of Direct-Q water (ultrapure H₂O) is $5.495 \times 10^{-6} \text{ S} \cdot \text{m}^{-1}$ at 298.15 K. No further purifications of the chemicals were made. The experimental work was carried at Mines ParisTech, where a "static-analytical" technique-based apparatus consisting of an equilibrium cell equipped with one moveable rapid online sampler injector was used. The equipment was the same as that used by Zehioua et al.,⁵ and the procedure was identical with that of Coquelet et al.⁶ The liquid and vapor samples were analyzed using a gas chromatograph (Varian model CP-3800), equipped with a thermal conductivity detector (TCD) and a flame ionization detector (FID).

In all experiments at first, H₂O was loaded into the equilibrium cell in the absence of air followed by CH₃SH. Then CH₄ was added to reach the desired pressure. The required temperature was obtained by putting the cell into a thermoregulated oil bath. Once equilibrium was achieved; the vapor, aqueous (liquid), and organic (liquid) samples from the equilibrium cell were directly introduced to the gas chromatograph through an isothermally heated transfer line. Two 100 Ω platinum

Received:	April 8, 2012
Revised:	June 26, 2012
Accepted:	August 2, 2012
Published:	August 2, 2012

probes (Pt100) were used for temperature measurements: they were inserted inside thermowells drilled into the body of the equilibrium cell at two different levels and connected to an HP data acquisition unit. They were periodically calibrated against a 25 Ω reference platinum resistance thermometer (Tinsley Precision Instruments, France). The resulting accuracy in the temperature measurements was estimated to be within $u(T, k = 2) = \pm 0.04$ K. Pressures were measured by means of a Druck pressure transducer at 0.1-10 MPa, which was maintained at 353.15 K. The pressure transducer was calibrated against a dead-weight pressure balance (Desgranges & Huot 5202S, CP 0.3-40 MPa, Aubervilliers, France). Accuracies in the pressure measurements have been estimated to be within $u(P, k = 2) = \pm 0.003$ MPa. The gas chromatograph detectors were calibrated using chromatographic syringes with maximum mole number uncertainties of 2% in the TCD and 1.5% in the FID; thus, the maximum uncertainty as mole fraction is $u_{\rm max} = 0.006.$

The gas chromatograph generated peaks of the individual components [CH₄ (FID), CH₃SH (FID), and H₂O (TCD)] at specific retention times, which were recorded using one RS-232 interface. The areas under such peaks correspond to the number of moles of the individual components, which came from the corresponding calibration. Each experimental data point was analyzed more than five times, until we got consistent values. The standard deviation on each experimental datum (σ^{A}) was calculated and is presented along with experimental data in Table 1. The method for calculation of the standard deviation on experimental data (σ^{A}) is reported in our previous article.²

3. MODELING SECTION

The experimental data were modeled using the CPA EOS. The CPA EOS is given in terms of the pressure as a sum of the SRK EOS and an associating contribution in eq 1. The association term in this equation is a simpler but mathematically identical version of the term used in statistical association fluid theory. This form was proposed by Michelsen and Hendriks.⁷ The CPA EOS proposed by Kontogeorgis et al.^{8,9} can be expressed for mixtures in terms of pressure *P* as

$$P = \frac{RT}{V_{\rm m} - b} - \frac{\alpha(T)}{V_{\rm m}(V_{\rm m} + b)} - \frac{1}{2} \frac{RT}{V_{\rm m}} \left(1 + \rho \frac{\partial \ln g}{\partial \rho} \right)$$
$$\times \sum_{i} x_{i} \sum_{A_{i}} (1 - X_{A_{i}})$$
(1)

where $V_{\rm m}$ is the molar volume. The key element of the association term is $X_{\rm A,i}$ which represents the fraction of sites (type A) on molecule *i* not bonded with other active sites, while x_i is the mole fraction of component *i*. $\alpha(T)$ and *b* are the energy and covolume parameters of the SRK term. $X_{\rm A_i}$ is related to the association strength $\Delta_{\rm A,B_j}$ between two sites belonging to two different molecules, e.g., site A on molecule *i* and site B on molecule *j*; more details were presented in previous studies.^{8,9}

The CPA EOS for thiols (mercaptan-containing systems) was described in our previous publications.^{3,4} The 4C association scheme was used for H_2O according to the terminology from Huang and Radosz.¹⁰ Furthermore, CH₃SH was considered to be a non-self-associating fluid but capable of cross associating with H_2O (solvation). For this reason, one negative association site was assumed on every CH₃SH molecule. The cross-association parameters were calculated using the

			vapor pha	se				organic pha	se				aqueous ph	lse	
T/K	P/MPa	yCH ₄	$10^3 \sigma CH_4$	<i>y</i> CH ₃ SH	10 ³ oCH ₃ SH	P/MPa	xCH ₄	$10^3 \sigma CH_4$	<i>x</i> CH ₃ SH	10 ³ oCH ₃ SH	P/MPa	xCH ₄	$10^{3}\sigma CH_{4}$	<i>x</i> CH ₃ SH	10 ³ oCH ₃ SH
304.11	1.210	0.6742	6.2	0.3256	6.2	1.229	0.0114	0.2	0.9886	0.3	1.244	0.0002	0.008	0.0188	0.01
304.11	2.665	0.7421	5.4	0.2577	5.4	2.700	0.0238	0.4	0.9761	0.7	2.722	0.0005	0.01	0.0184	0.01
304.11	5.270	0.8198	4.2	0.1801	4.2	5.328	0.0528	0.9	0.9472	1.4	5.380	0.001	0.02	0.0176	0.03
304.11	6.973	0.8452	3.7	0.1547	3.7	7.065	0.0715	1.2	0.9285	1.9	7.152	0.0013	0.02	0.0169	0.04
304.11	9.033	0.8764	3.1	0.1233	3.1	9.115	0.0955	1.6	0.9044	2.4	9.184	0.0016	0.03	0.0154	0.05
333.65	1.617	0.4683	4.5	0.5315	7.0	1.626	0.0096	0.2	0.9903	0.3	1.631	0.0002	0.00	0.0227	0.01
333.65	2.729	0.6338	4.2	0.3661	6.6	2.746	0.0206	0.4	0.9792	0.6	2.773	0.0004	0.01	0.0221	0.01
333.65	4.836	0.7394	3.5	0.2606	5.5	4.899	0.0413	0.7	0.9586	1.1	4.934	0.0008	0.01	0.021	0.02
333.65	6.938	0.7684	3.2	0.2315	5.0	6.995	0.0645	1.1	0.9355	1.7	7.053	0.0012	0.02	0.0201	0.03
333.65	8.859	0.758	3.3	0.2419	5.2	8.957	0.0842	1.4	0.9157	2.2	9.022	0.0015	0.03	0.0183	0.04
363.68	2.457	0.3501	4.1	0.6496	6.4	2.475	0.0109	0.2	0.9867	0.3	2.380	0.0003	0.01	0.0249	0.01
363.68	5.486	0.5707	4.4	0.4291	6.9	5.546	0.0479	0.8	0.9492	1.3	5.580	0.0007	0.01	0.0237	0.02
363.68	8.871	0.6581	4.1	0.3417	6.4	8.988	0.0798	1.3	0.9135	2.1	9.040	0.0012	0.02	0.0226	0.03
^a y stands f	or mole fra	ction in the	vapor phase,	, and x stand	ls for mole frac	tion in the	organic/aqı	ieous phase.	σ stands for	the standard de	eviation on	each mole f	raction.		

component	$T_{\rm c}/{\rm K}$	$b/L \cdot mol^{-1}$	Γ/K	c_1	$\varepsilon_{\mathrm{A,B}_i}$ /bar·L ⁻¹ ·mol ⁻¹	$eta_{\mathrm{A}_i\mathrm{B}_i}$	% AAD in P^{Sat}	% AAD in $ ho^{ m liq}$
CH ₃ SH ³	469.95	0.0437	2266.2	0.8007			0.69	0.47
CH4 ¹²	190.56	0.0291	959.1	0.4472			0.35	1.97
H_2O^{13}	647.29	0.0145	1017.3	0.6736	166.55	0.0692	0.91	0.98

^{*a*} Average absolute deviation (AAD) is defined as % ADD = $(1/n)\sum_i |(X_i^{cal} + X_i^{exp})/X_i^{exp}| \times 100$, where X stands for P^{Sat} or ρ^{liq} and n is the number of experimental data points, Γ is defined as a_0/Rb where a_0 is the part of energy parameter of the EOS, which is defined using a Soave-type temperature dependency as: $a = a_0 (1 + C_1 [1 - \sqrt{(\text{Tr}]})^2, \text{H}_2\text{O})$ is modeled using the 4C association scheme.

modified CR-1 rule.¹³ The CPA EOS pure-component parameters ($b/L \cdot mol^{-1}$, Γ/K , and c_1) for CH₃SH,³ CH₄,¹² and H₂O¹³ are presented in Table 2. The a_0 parameter is tabulated as $\Gamma = a_0/Rb$. The binary interaction parameters for CH₄– H₂O,¹² CH₄–CH₃SH,⁴ and CH₃SH–H₂O³ are presented in Table 3. The parameters were taken from the literature and applied to predict the VLLE of CH₃SH + CH₄ + H₂O.

Table 3. CPA Binary Interaction Parameters Used in This Work

mixture	temperature range/K	k_{ij}	$\beta_{\rm cross}$
CH4-H2O12	303.1-363.1	0.0098	
CH ₄ -CH ₃ SH ⁴	303.1-363.2	0.079	
CH ₃ SH-H ₂ O ³	303.1-363.3	0.0089	0.0246
^{<i>a</i>} Cross-association ³ using the modified	between CH ₃ SH and I CR-1 rule. ¹³	H ₂ O has beer	1 considered

4. RESULTS AND DISCUSSION

In our previous work,³ we performed CPA calculations for Henry's law constant of methanethiol (MM) in H_2O^{11} as a function of the temperature. It has been observed that, by taking into account the cross-associating effect in the CH₃SH + H₂O system, the CPA results were improved. The CH₃SH + H₂O system has also been studied and discussed in the literature by Gillespie and Wilson.¹¹ The authors observed a drastic change in the solubility of CH₃SH at higher temperature (523-673 K) compared to the lower temperature (313-423 K) data. We did not find any further data in the open literature for the ternary system investigated in this work, so a direct comparison is not possible. It is observed that the solubility of CH4 in the aqueous and organic phases increases with an increase in the total system pressure and decreases with an increase in the temperature. Furthermore, the solubility of CH₃SH in the aqueous and organic phases decreases slightly with an increase of the pressure and increases significantly with an increase of the temperature. It has also been observed that the solubility of CH₃SH is higher than that of CH4 in the aqueous phase in some cases. The solubilities of H₂O in the organic and gas phases were not detected by gas chromatography because they were under the limit of detection. The detection limit of the gas chromatograph detectors in terms of mole numbers are as follows: $CH_3SH = 9.78 \times 10^{-8}$, $H_2O = 3.32$ \times 10⁻⁶, and CH₄ = 4.51 \times 10⁻⁸. However, Gillespie and Wilson¹¹ showed that the solubility of H₂O in the gas phase varies inversely with the system pressure except at temperatures above 422 K. These authors also conclude that the solubility of H₂O in the liquid phase is slightly lower than the solubility in the vapor phase at three-phase saturation conditions.

The CPA EOS predictions for the VLLE of the $CH_3SH + CH_4 + H_2O$ ternary system from 1 to 9 MPa pressure at 304, 334, and 364 K are shown in Figures 1–3, respectively. It is



Figure 1. VLLE of the CH₃SH + CH₄ + H₂O ternary system from 1 to 9 MPa pressure at 304 K: (\triangle) CH₃SH in the organic phase; (\bigcirc) CH₃SH in the vapor phase; (\square) CH₃SH in the aqueous phase. Solid lines: CPA EOS predictions.



Figure 2. VLLE of the CH₃SH + CH₄ + H₂O ternary system from 1 to 9 MPa pressure at 334 K: (\triangle) CH₃SH in the organic phase; (O) CH₃SH in the vapor phase; (\square) CH₃SH in the aqueous phase. Solid lines: CPA EOS predictions.

observed that the deviation between the experimental data and the CPA predictions is sometimes higher than 40%. Especially, the CPA EOS predictions for the vapor-phase composition are rather poor. However, one should keep in mind that the CPA results are pure predictions because no parameters were adjusted to the experimental data. From this point of view, the CPA rather satisfactorily predicts the vapor-liquid and vaporliquid-liquid regions for the CH₃SH + CH₄ + H₂O ternary system at 363.68 K and 8.966 MPa, as plotted in Figure 4, which shows that model can qualitatively predict the complicated three-phase equilibria of this system.



Figure 3. VLLE of the CH₃SH + CH₄ + H₂O ternary system from 1 to 9 MPa pressure at 364 K: (\triangle) CH₃SH in the organic phase; (\bigcirc) CH₃SH in the vapor phase; (\square) CH₃SH in the aqueous phase. Solid lines: CPA EOS predictions.



Figure 4. Phase diagram of the $CH_3SH + CH_4 + H_2O$ ternary system at 363.68 K and 8.966 MPa: (\blacksquare) experimental VLLE data points; (red \blacksquare) CPA EOS predictions. Dashed lines: predicted VLLE with CPA EOS. Solid lines: predicted VLE with CPA EOS. Dotted lines: predicted VLE tie lines with CPA EOS. Bold line: predicted VLE or LLE.

5. CONCLUSION

New VLLE data for $CH_3SH + CH_4 + H_2O$ were performed at three temperatures (303, 334, and 364 K) in a pressure range from 1 to 9 MPa. A "static-analytical" method was used successfully to perform all of the measurements. It is concluded that the gas solubility of CH_3SH is higher than that of CH_4 in the aqueous phase under similar temperature and pressure conditions. The CPA EOS has been applied for the representation of ternary systems containing CH_3SH . These modeling results for the ternary mixture of $CH_4 + CH_3SH + H_2O$ are satisfactory considering that they are predictions without the adjustment of any parameter to the ternary experimental data.

AUTHOR INFORMATION

Corresponding Author

*E-mail: gk@kt.dtu.dk. Phone: +45 45252859. Fax: +45 45882258.

Notes

The authors declare no competing financial interest.

The authors gratefully acknowledge the Danish Council for Independent Research (Technology and Production Sciences) for the Postdoctoral research grant to Dr. J. A. Awan at CERE, DTU Chemical Engineering. We very much appreciate fruitful discussions with Prof. D. Richon (Mines ParisTech, France). The authors thank Statoil and Gassco (Norway), BP (UK, USA), TOTAL (France), and DONG Energy and Mærsk Oil and Gas (Denmark) for supporting the CPA EOS part of this work as part of the CHIGP project (Chemicals in Gas Processing).

REFERENCES

(1) Bymaster, A. Molecular Modeling the Microstructure and Phase Behavior of Bulk and Inhomogeneous Complex Fluids. Ph.D. Thesis, Rice University, Houston, TX, 2009.

(2) Awan, A. J.; Thomsen, K.; Coquelet, C.; Fosbøl, L. P.; Richon, D. Vapor-Liquid Equilibrium Measurements and Modeling of the Propyl Mercaptan + Methane + Water System. *J. Chem. Eng. Data* **2010**, *55*, 842–846.

(3) Awan, J. A.; Tsivintzelis, I.; Breil, M.; Coquelet, C.; Richon, D.; Kontogeorgis, G. M. Phase Equilibria of Mixtures Containing Organic Sulfur Species (OSS) and Water/Hydrocarbons: VLE Measurements and Modeling Using the Cubic-Plus-Association Equation of State. *Ind. Eng. Chem. Res.* **2010**, 49 (210), 12718–12725.

(4) Awan, J. A.; Tsivintzelis, I.; Coquelet, C.; Kontogeorgis, G. M. Phase Equilibria on Three Binary Mixtures; Methyl mercaptan + Methane, Methyl mercaptan + Nitrogen and Methyl mercaptan + Carbon dioxide. J. Chem. Eng. Data **2012**, *57*, 896–901.

(5) Zehioua, R.; Coquelet, C.; Meniai, A. H.; Richon, D. Isothermal vapour–liquid equilibrium data of 1,1,1,2-tetrafluoroethane (R134a) + dimethylformamide (DMF) working fluids for absorption heat transformer. *J. Chem. Eng. Data* **2009**, *55*, 985–988.

(6) Coquelet, C.; Chareton, A.; Richon, D. Vapour-Liquid Equilibrium Measurements and Correlation of the Difluoromethane (R32) + Propane (R290) + 1,1,1,2,3,3,3-Heptafluoropropane (R227ea) Ternary Mixture at Temperatures from 269.85 to 328.35 K. Fluid Phase Equilib. 2004, 218, 209-214.

(7) Michelsen, M. L.; Hendriks, E. M. Physical properties from association models. *Fluid Phase Equilib.* 2001, 180, 165–174.

(8) Kontogeorgis, G. M.; Michelsen, M. L.; Folas, G. K.; Derawi, S.; Solms, N. V.; Stenby, E. H. Ten Years with the CPA (Cubic-Plus-Association) Equation of State. Part-I. Pure Compounds and Self-Associating Systems. *Ind. Eng. Chem. Res.* **2006**, *45*, 4855–4868.

(9) Kontogeorgis, G. M.; Voutsas, E. C.; Yakoumis, I. V.; Tassios, D. P. An Equation of State for Associating *Fluids. Ind. Eng. Chem. Res.* **1996**, *35*, 4310–4318.

(10) Huang, S. H.; Radosz, M. Equation of State for Small, Large, Polydisperse and Associating Molecules. *Ind. Eng. Chem. Res.* **1990**, *29*, 2284–2294.

(11) Gillespie, P. C.; Wilson, G. M. Sulfur Compounds and Water V–L–E and Mutual Solubility MESH–H₂O; ETSH–H₂O; CS₂–H₂O; and COS–H₂O. *GPA Research Report RR-78*; Gas Processors Association: Tulsa, OK, 1984.

(12) Tsivintzelis, I.; Kontogeorgis, G. M.; Michelsen, M. L.; Stenby, E. H. Modeling Phase Equilibria for Acid Gas Mixtures Using the CPA Equation of State. I. Mixtures with H_2S . *AIChE J.* **2010**, *56* (11), 2965–2982.

(13) Kontogeorgis, G. M.; Folas, G. K.; Muro-Suňé, N.; Roca, L, F.; Michelsen, M, L. Solvation phenomena in association theories with applications to oil and gas and chemical industries. *Rev. Inst. Fr. Pet.* **2008**, *63*, 305–319.

(14) Kontogeorgis, G. M.; Yakoumis, I. V.; Meijer, H.; Hendriks, E.; Moorwood, T. Multicomponent phase equilibrium calculations for water-methanol-alkane mixtures. *Fluid Phase Equilib.* **1999**, 201, 158–160.