



Modeling & Simulation of Distribution Grids

Cha, Seung-Tae

Publication date:
2012

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Cha, S-T. (2012). Modeling & Simulation of Distribution Grids [Sound/Visual production (digital)].

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.


Modeling & Simulation of Distribution Grids

- Multi-agent based LFC for islanding operation

Seung Tae Cha (ST)
 Centre for Electric Technology (CET)
 Technical University of Denmark (DTU)

June 21, 2012
 @ Power Event

DTU Electrical Engineering
 Department of Electrical Engineering




Outline

- Introduction
- Real time simulation platform
- Multi-agent based controller
- Description of test system
- Case study simulation results
- Conclusion

Introduction

- Distribution Generation(DG) source is gaining popularity and is ever increasing in importance
- DGs installed in the grid are gaining in complexity
- Specially, **Islanded Distribution System**
- Requires new forms of operation & develop sophisticated control strategies
- EMT simulation is now a common tool for power system engineers
- Real time simulators are more accessible than ever

Frequency control of generators





Source : WeGAT research center, Korea 2011

Partial Blackout (Sept 15, at 3pm, Korea)

- Due to the shortage of frequency reserves
- This could be easily prevented
- As a result, 17 employees were fired (4 Gov, 5 KEPCO, 8 KPX as of Sept 28)

Goal & Idea

- Develop a multi-agent based controller to stabilize the frequency and voltages of an active distribution network in the event of islanding operation




Real Time Simulation Platform

- RTDS is a power system simulator that solves electromagnetic transients in **real time**

What is ***Real Time*** Simulation:

- By using the RTDS Simulator, a system's response over 1 second is computed in ***exactly*** 1 second.
- For a given time step of say 50 microseconds, all calculations required to determine the power system's state are solved in precisely that amount of time. → Sustain real time operation

Real Time Simulation Platform (continue)




Each agent creates its own connection and has an individual channel of control commands which ensures decentralized nature and robustness of the control

Multi Agent based Controller (3 layers)

- Central Control Agent is responsible for controlling & managing the grid.
- Device Agent interact directly with the physical power system components and performs control functions.
 - Generator agent (P, Q set point)
 - Breaker agent (open & close)
- Physical power system components are DGs, loads, lines, etc. These agents have fixed data such as
 - Unit names, min & max power, fuel cost coefficient
 - Current power production & status of the unit

Multi Agent based Controller - Architecture





DG agent calculates its cost function based upon its current state, and sends a bid...cumulates...which DG agent shall provide regulation service and how much power should be delivered !!

Modified IEEE 9-bus Test System

- The modified IEEE 9-bus system comprises a 60kV, 50Hz grid which feeds an 10kV network through a 60/10 kV transformer.
 - 3 DG units (1.5 MW, Bus 1,3,4)
 - 8 T/L
 - 1 TR
 - 4 Loads (6 MW, Bus 5 - 8)
 - **Battery Energy Storage System (BESS)**


Modified IEEE 9-bus Test System (continue)



Modified IEEE 9-bus Test System (continue)

- Intelligent controller : Reacts to respond quickly to the frequency deviation in the event of islanding situation (LFC scheme to control the speed of DGs)

hmMod-Script



Simulated Grid in RTDS

DG 2


DG 3

DG 1

Changes load setting of DGs via the AGC signal based on participation factors

Secondary Regulation

CJLFC (MA)




Send out change in the power output of the BESS

Measurement

Primary Regulation

BESS

Control Reference



Simulation of Islanding Operation

Case I

Step1. **Loss of 1.5 MW** power from the grid due to an outage or intentional islanding

Step2. Created an imbalance in the **islanded** part of the network

Step3. Load agents observe **voltage & frequency drop**

Step4. Load agents contact DF agent for any available regulation service

Step5. DF agents informs the current service availability **and provides its reference** (i.e $P_{Gen2}=0.6415$)


Step6. Load agents request DG #2 agent for provision of service

Step7. DG #2 agent accepts the request and provides the service by increasing its active power set point

Step 8. **Voltage & frequency recover** at the nodes of all loads

Case I

hmMod-Script




Change the set points of Generators


Case 1 – External source disconnected

Simulation Results


Case I




The MA controller was capable of bring back the frequency to 50Hz and restored at about 50 s.




The MA controller was also capable of reducing the voltage deviations and keeping them within the permissible limits.





Case II

hmMod-Script




Load Shedding at Bus 8


Case 2 – External source disconnected

Simulation Results

Case II




A5FREQ




90s

A6FREQ




The controller was capable of bring back the frequency to 50Hz and restored at about 90 s.


A7FREQ




A8FREQ



VLOAD5




VLOAD6





The controller was also capable of reducing the voltage deviations and keeping them within the permissible limits.

VLOAD7







VLOAD8





Wind Speed Variation from 12m/s to 10m/s









Conclusions

- A **multi-agent based controller for islanding operation** of active distribution system has been proposed to help stabilize the frequency & voltage
- The proposed controller can respond to the islanding situation fast and **efficiently stabilize the frequency & voltage with a coordination of BESS under contingency**
- However, there are a number of challenges
- Multi-set of DG units & loads, coordination strategies, and scalability
- SOC control scheme for energy storage

- CONTRIBUTOR : Qiuwei, Arshad, Haoran, Christian, Jacob

Bornholm Power System

- The Bornholm power system comprises a 60kV, 50Hz grid which feeds an 10kV network through a 60/10kV transformer.
 - Peak Load : 63 MW
 - 18 Substations
 - AC submarine cable connection to Sweden
 - 44 Transformers
 - Unit 5 : 25 MW
 - Unit 6 : 37.5 MW CHP
 - Wind, Biogas, Diesels (67 MW)
 - BESS



- To accommodate more wind power and 400 V grid
- Development of Generic Model of Bornholm Power System → Danish Benchmark (similar to IEEE benchmark) for publicly available (ISGT 2012)
- PSO Optimization for BESS controller
- Implementation of IEC Generic Wind Turbine Modelling (Type 1A/B, Type 3)