

Technical University of Denmark



Enhancing the Damping Properties of Viscoelastic Composites by Topology Optimization

Andreasen, Casper Schousboe; Andreassen, Erik; Sigmund, Ole; Jensen, Jakob Søndergaard

Publication date:
2012

[Link back to DTU Orbit](#)

Citation (APA):

Andreasen, C. S., Andreassen, E., Sigmund, O., & Jensen, J. S. (2012). Enhancing the Damping Properties of Viscoelastic Composites by Topology Optimization. Abstract from 8th European Solid Mechanics Conference, Graz, Austria.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Enhancing the Damping Properties of Viscoelastic Composites by Topology Optimization

Casper Schousboe Andreasen[†], Erik Andreassen, Ole Sigmund, Jakob Søndergaard Jensen

Department of Mechanical Engineering, Technical University of Denmark, Nils Koppels Allé, Building 404, Denmark

[†]csan@mek.dtu.dk

ABSTRACT

Vibrations, if undamped, might be annoying or even dangerous. Most often some kind of damping mechanism is applied in order to limit the vibration level. Vibration insulators, for instance of rubber material, have favorable damping characteristics but lack the structural stiffness often needed in engineering structures. Thus, materials or composites with high stiffness and high damping are of great interest to the industry.

The inherent compromise between high stiffness and high damping in viscoelastic materials has been treated theoretically [2, 3] and experimentally [1]. It has been shown that high stiffness and high damping can be realized by Hashin-type composites or Rank-N laminates. However, in order to manufacture such composites it is favorable to obtain single length scale microstructures, i.e. without multiscale structures such that the materials can be manufactured by modern manufacturing techniques. As an example, by the use of e.g. SLM/SLS - Selective Laser Melting/Sintering, an open metallic microstructure can be *printed* and in a subsequent process the porespace can be filled with a high loss compliant material.

Yi and co-workers [6] applied topology optimization to design the 2D microstructural layout of a stiff elastic and a soft viscoelastic material constituent in order to obtain high damping, however, without specific focus on neither the theoretical bounds [2] nor the manufacturability. In this work we extend this work and consider manufacturability by use of various filtering techniques [4, 5]. The inverse homogenization problem is formulated such that the imaginary part of the bulk modulus for the composite is maximized while the real part is constrained from below. This formulation makes it possible to exploit the microstructures related to the upper bound of the imaginary part of the bulk modulus.

Figure 1 shows the bounds on the bulk modulus for a viscoelastic composite using the formulation of [2] along with preliminary structures obtained using topology optimization. It is seen that for low bulk stiffness, the obtained designs approach the bounds for viscoelastic composites.

The theoretical bounds exist for a limited combination of base materials e.g. with equal Poisson's ratio and isotropic composites. In our work we will, numerically, further exploit the parameter space in order to search for composites that offer favorable compromises between loss and stiffness for different loading scenarios. Further, we will extend the study to three dimensions and in future work we plan to investigate the possibility for using the nonlinear response of viscoelastic materials such as rubber to further enhance the damping capabilities.

Acknowledgement. This research is conducted within the Innovation Consortium, F.MAT, funded by a grant from the Danish Agency for Science, Technology and Innovation.




Figure 1: The figure shows the optimized material structures that approach the upper bound. The structures are made from two isotropic materials with equal Poisson's ratio of 0.3. One constituent (black) is a relatively stiff elastic material while the other (white) is a more compliant viscoelastic material having a bulk modulus of $K_1 = 100$ and $K_2 = 0.35 + 0.35i$

References

- [1] Lakes R.S. Brodt, M. Composite materials which exhibit high stiffness and high viscoelastic damping. *Journal of Composite Materials*, 29(14):1823–1833, 1995.
- [2] L. V. Gibiansky and R. Lakes. Bounds on the complex bulk modulus of a 2-phase viscoelastic composite with arbitrary volume fractions of the components. *Mechanics of Materials*, 16(3):317–331, 1993.
- [3] L. V. Gibiansky and G. W. Milton. On the effective viscoelastic moduli of two-phase media. i. rigorous bounds on the complex bulk modulus. *Proceedings of the Royal Society of London. Series A: Mathematical and Physical Sciences*, 440(1908):163–188, 1993.
- [4] O. Sigmund. Morphology-based black and white filters for topology optimization. *Structural and Multidisciplinary Optimization*, 33(4-5):401–424, 2007.
- [5] Fengwen Wang, Boyan Lazarov, and Ole Sigmund. On projection methods, convergence and robust formulations in topology optimization. *Structural and Multidisciplinary Optimization*, 43:767–784, 2011.
- [6] Yeong-Moo Yi, Sang-Hoon Park, and Sung-Kie Youn. Design of microstructures of viscoelastic composites for optimal damping characteristics. *International Journal of Solids and Structures*, 37(35):4791–4810, 2000.