**Technical University of Denmark** 



### Application of model uncertainty analysis on the modelling of the drying behaviour of single pharmaceutical granules

Mortier, S.T.F.C.; Van Hoey, S.; Cierkens, K.; De Beer, T.; Gernaey, Krist V.; Nopens, L.

Publication date: 2012

Document Version Publisher's PDF, also known as Version of record

#### Link back to DTU Orbit

Citation (APA): Mortier, S. T. F. C., Van Hoey, S., Cierkens, K., De Beer, T., Gernaey, K., & Nopens, L. (2012). Application of Mortier, S. T. F. C., Van Hoey, S., Cierkens, K., De Beer, T., Gernaey, K., & Nopens, L. (2012). Application of model uncertainty analysis on the modelling of the drying behaviour of single pharmaceutical granules. Abstract from 5th Pan-European QbD & PAT Science Conference, Gent, Belgium.

## DTU Library Technical Information Center of Denmark

#### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- · You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Application of model uncertainty analysis on the modelling of the drying behaviour of single pharmaceutical granules

Mortier S.T.F.C.<sup>1,2,\*</sup>, Van Hoey S.<sup>1</sup>, Cierkens K.<sup>1</sup>, De Beer T.<sup>2</sup>, Gernaey K.V.<sup>3</sup> and Nopens I.<sup>1</sup>

<sup>1</sup> BIOMATH, Department of Mathematical Modelling, Statistics and Bioinformatics, Faculty of Bioscience Engineering, Ghent University, Coupure Links 653, 9000 Ghent, Belgium

<sup>2</sup> Laboratory of Pharmaceutical Process Analytical Technology, Department of Pharmaceutical Analysis, Faculty of Pharmaceutical

Sciences, Ghent University, Harelbekestraat 72, 9000 Ghent, Belgium

\* Corresponding author (severine.mortier@ugent.be)

A shift from batch processing towards continuous processing is of interest in the pharmaceutical industry. However, this transition requires detailed knowledge of all consecutive continuous unit operations in a continuous manufacturing line to design adequate control strategies. This can be facilitated by developing mechanistic models of the multiphase systems under study. Since modelling efforts only started recently in this field, uncertainties about the model predictions are generally neglected. However, model predictions have an inherent uncertainty originating from uncertainty in input data, model parameters, model structure, boundary conditions and software. In this presentation, the model prediction uncertainty originating from parameter uncertainty will be illustrated for a model describing the continuous drying of pharmaceutical wet granules in a six-segmented fluidized bed drying unit, which is part of the full continuous from powder to tablet manufacturing line (Consigma,...). A validated model describing the drying behaviour of a single pharmaceutical granule in two consequent phases is used (Mortier et al., 2011).

First, an uncertainty analysis is performed based on the parameters that are directly linked to model assumptions and boundary conditions i.e. all particles are assumed to be spherical (Rp), have a certain porosity ( $\epsilon$ ) and have a certain gas flow rate passing their surface equal to an average gas flow rate (Vgas). The Generalised Likelihood Uncertainty Estimation (GLUE) (Beven, 2006) method is used to propagate uncertainty to the model output. Calculated model prediction uncertainties are shown in Figure 1. As expected, assumed prior parameter distributions have limited influence on uncertainty boundaries and confidence boundaries may slightly depend on the selected fit criterion and its threshold value. As a second step, the same analysis is performed on the most sensitive parameters since they have the largest influence on the model predictions. Finally, all mentioned uncertain parameters are taken into account and confidence boundaries are evaluated. These analyses give a realistic view on the prediction power of the models and can be very important when using models in scenario analysis, control and optimisation.



Beven, K., 2006. A manifesto for the equifinality thesis. Journal of Hydrology 320: 18-36.

<sup>&</sup>lt;sup>3</sup> Center for Process Engineering and Technology, Department of Chemical and Biochemical Engineering, Technical University of Denmark, Building 229, 2800 Kgs. Lyngby, Denmark

Mortier, S.T.F.C., De Beer, T., Gernaey, J. Vercruysse, M. Fonteyne, K.V., Remon, J.P., Vervaet, C., Nopens, I., 2011. Mechanistic modelling the drying behaviour of single pharmaceutical granules. European Journal of Pharmaceutics and Biopharmaceutics (In Press).

EuPAT session: Process modeling for in-depth understanding and control