

Technical University of Denmark



A Bayesian geostatistical approach for evaluating the uncertainty of contaminant mass discharges from point sources

Troldborg, Mads; Nowak, Wolfgang; Binning, Philip John; Bjerg, Poul Løgstrup

Publication date:
2012

[Link back to DTU Orbit](#)

Citation (APA):

Troldborg, M., Nowak, W., Binning, P. J., & Bjerg, P. L. (2012). A Bayesian geostatistical approach for evaluating the uncertainty of contaminant mass discharges from point sources. Abstract from 2012 AGU Fall Meeting, San Francisco, United States.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

A Bayesian geostatistical approach for evaluating the uncertainty of contaminant mass discharges from point sources

Mads Trolborg*¹, Wolfgang Nowak², Philip J. Binning³ and Poul L. Bjerg³

¹*The James Hutton Institute, Craigiebuckler, Aberdeen, AB15 8QH, United Kingdom.*

²*Institute of Hydraulic Engineering (LH2, Stochastic modelling of hydrosystems), Universität Stuttgart, Pfaffenwaldring 61, 70569 Stuttgart, Germany.*

³*Department of Environmental Engineering, Technical University of Denmark (DTU), Miljøvej, Building 113, 2800 Kgs. Lyngby, Denmark*

*mads.trolborg@hutton.ac.uk

Abstract

Estimates of mass discharge (mass/time) are increasingly being used when assessing risks of groundwater contamination and designing remedial systems at contaminated sites. Mass discharge estimates are, however, prone to rather large uncertainties as they integrate uncertain spatial distributions of both concentration and groundwater flow. For risk assessments or any other decisions that are being based on mass discharge estimates, it is essential to address these uncertainties.

We present a novel Bayesian geostatistical approach for quantifying the uncertainty of the mass discharge across a multilevel control plane. The method decouples the flow and transport simulation and has the advantage of avoiding the heavy computational burden of three-dimensional numerical flow and transport simulation coupled with geostatistical inversion. It may therefore be of practical relevance to practitioners compared to existing methods that are either too simple or computationally demanding.

The method is based on conditional geostatistical simulation and accounts for i) heterogeneity of both the flow field and the concentration distribution through Bayesian geostatistics, ii) measurement uncertainty, and iii) uncertain source zone and transport parameters. The method generates multiple equally likely realisations of the spatial flow and concentration distribution, which all honour the measured data at the control plane. The flow realisations are generated by co-simulating the hydraulic conductivity and the hydraulic gradient across the control plane and are consistent with measurements of both hydraulic conductivity and head at the site. An analytical macro-dispersive transport solution is employed to simulate the mean concentration distribution across the control plane, and a geostatistical model of the Box-Cox transformed concentration data is used to simulate observed deviations from this mean solution. By combining the flow and concentration realizations, a mass discharge probability distribution is obtained. Tests show that the decoupled approach is both efficient and able to provide accurate uncertainty estimates.

The method is demonstrated on a Danish field site contaminated with chlorinated ethenes. For this site, we show that including a physically meaningful concentration trend and the co-simulation of hydraulic conductivity and hydraulic gradient across the transect helps constrain the mass discharge uncertainty. The number of sampling points required for accurate mass discharge estimation and the relative influence of different data types on mass discharge uncertainty is discussed.

Key words mass discharge; groundwater contamination; risk assessment; uncertainty; geostatistics; Bayesian statistics