

Technical University of Denmark



## Topology optimization of antennas and resonators

Aage, Niels; Sigmund, Ole

*Publication date:*  
2012

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*  
Aage, N., & Sigmund, O. (2012). Topology optimization of antennas and resonators. Paper presented at 9th World Congress on Structural and Multidisciplinary Optimization, Shizuoka, Japan.

## DTU Library

Technical Information Center of Denmark

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

## Topology optimization of antennas and resonators

Niels Aage<sup>1</sup>, Ole Sigmund<sup>1</sup>

<sup>1</sup> Technical University of Denmark, Department of Solid Mechanics, DK-2800 Lyngby, Denmark, naa@mek.dtu.dk

### Abstract

The research presented here consists of a novel extension to the topology optimization method, that allows for systematic design of 3D metallic/dielectric devices for microwave applications. The work is a natural continuation of the 2D design formulation presented in [1] which again is motivated by the 3D antenna design from [2] and the dielectric antenna designs presented in [3] and [4]. However, it was found that modifications to the 2D design formulation from [1] were needed, both due to the presence of a plentitude of local minima in the 3D setting, but also due to issues with the design parameterization for certain antenna optimization problems. In those cases it was not possible to find a monotonous interpolation and hence we resort to a heuristic discrete scheme based on filtering and gradient evaluation for discrete variable values.

The motivation for the work originates from the ever increasing usage of small hand-held, or autonomous, electrical devices such as hearing aids, medical implants and communication devices. These devices all require antennas for communication as well as a power supply, usually a battery. Since more and more functionality is incorporated into these devices, standard antenna designs are becoming less and less usable and the requirements to the batteries are increasing. The power supply issue took a new turn in 2007, where a MIT group lead by Prof. M. Soljacic demonstrated that one could obtain efficient mid-range wireless energy transfer (WiTricity) using magnetically resonant coupled copper coils. Common for the design of antennas and devices for WiTricity are that they consist of an elaborate spatial distribution of a conductor, e.g. copper, in a dielectric background, e.g. air. This makes the design of such devices an obvious candidate for the topology optimization method.

The proposed design scheme is implemented in a fully parallel C++ FE/topology optimization code, and is demonstrated on the design of 3D resonators for energy harvesting from radio frequency signals as well as the design of electrically small antenna systems.

[1] Aage, N., Mortensen, N. A., Sigmund, O, "Topology optimization of metallic devices for microwave applications", Int. J. Numer. Meth. Engng., 2010; **83**(2):228–248.

[2] Erentok A, Sigmund O. Three-dimensional topology optimized electrically small conformal antenna. *IEEE AP-S International Symposium on Antennas and Propagation and USNC/URSI National Radio Science Meeting*, San Diego, CA, U.S.A., 5–12 July 2008.

[3] Kiziltas G, Kikuchi N, Volakis JL, Halloran J. Topology optimization of dielectric substrates for filters and antennas using SIMP. *Archives of Computational Methods in Engineering* 2004; **11**(4):355–388.

[4] Nomura, T., Sato, K., Taguchi, K., Kashiwa, T., Nishiwaki, S., Structural topology optimization for the design of broadband dielectric resonator antennas using the finite difference time domain technique. Int. J. Numer. Meth. Engng., 2007; **71**(11):1261–1296.