

Technical University of Denmark



Fabrication and Characterization of Proton Conducting Phosphate Electrolytes for Intermediate Temperature Fuel Cell Assembling

Jensen, Annemette Hindhede; Li, Qingfeng; Anfimova, Tatiana; Christensen, Erik; Barner, Jens H. Von; Bjerrum, Niels J.

Publication date:
2012

[Link back to DTU Orbit](#)

Citation (APA):

Jensen, A. H., Li, Q., Anfimova, T., Christensen, E., Barner, J. H. V., & Bjerrum, N. J. (2012). Fabrication and Characterization of Proton Conducting Phosphate Electrolytes for Intermediate Temperature Fuel Cell Assembling. Abstract from Nordic Conference on Ceramic and Glass Technology, Roskilde, Denmark.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Fabrication and Characterization of Proton Conducting Phosphate Electrolytes for Intermediate Temperature Fuel Cell Assembling

Nordic conference on ceramic and glass technology, 6th – 7th December 2012

Annemette H. Jensen, Q. Li, T. Anfimova, E. Christensen, J. H. von Barner, N. J. Bjerrum

DTU Energy Conversion
Technical University of Denmark, Building 207,
DK 2800 Lyngby, Denmark

Outline

The worldwide development of fuel cells and electrolyzers has so far almost exclusively addressed either the low temperature window (20 - 200 °C) or the high temperature window (600 - 1000 °C). The intermediate temperature window enables the possibility of combining advantages from low and high temperature technologies. Fast electrode kinetics and material stability are key parameters. However, in the intermediate temperature interval there are no proton conductors working satisfactorily. The finding of such electrolytes is an ultimate goal of solid electrolyte research. [1]

Certain proton conducting materials are plastic in nature e.g. CsH₂PO₄, whereas others are not e.g. NdPO₄. By combining the materials in a ceramic composite with at least one other component, it is possible that suitable mechanical properties can be reached.

In former work, proton conduction has been demonstrated for ceramic NdPO₄-CsH₂PO₄ composites using EIS. [2][3]

Based on the novel ceramic composite a hydrogen cell and hydrogen-air fuel cells has been constructed and operated. Under these conditions proton conduction was confirmed by EMF and thermal stability in fuel cell conditions was confirmed by OCV.

Acknowledgement

Funding for this work is obtained from the Danish National Research Foundation (the Danish-Chinese Center for Intermediate Temperature Proton Conducting systems (PROCON)).

[1] T. Norby. NATURE| VOL410|19APRIL2001 s. 877-87

[2] A. H. Jensen, 3rd CARISMA International Conference on Medium and High Temperature PEM Fuel Cells, Copenhagen, 3 – 5 September 2012, 60 – Poster session

[3] T. Anfimova, 3rd CARISMA International Conference on Medium and High Temperature PEM Fuel Cells, Copenhagen, 3 – 5 September 2012, 65 – Poster session