

1 **SPRAY IRRIGATION OF LANDFILL LEACHATE: ESTIMATING**
2 **POTENTIAL EXPOSURES TO WORKERS AND BYSTANDERS USING A**
3 **MODIFIED AIR BOX MODEL AND GENERALISED SOURCE TERM**

4
5 Duncan Gray^a, Simon J.T. Pollard^{a*}, Lynn Spence^b, Richard Smith^c and Jan R. Gronow^c

6 ^a*Integrated Waste Management Centre, Cranfield University, Cranfield, MK43 0AL, UK*

7 ^b*Spence Environmental Engineering, 239 Main Street, Pleasanton, CA 94566, USA*

8 ^c*Environment Agency, Science Group – Waste and Remediation, Block 1, Government Buildings, Burghill Road,*
9 *Westbury-on-Trym, Bristol, BS10 6BF, UK*

10
11 **Abstract**

12 Generalised source term data from UK leachates and a probabilistic exposure model (BPRISC₄)
13 were used to evaluate key routes of exposure from chemicals of concern during the spraying
14 irrigation of landfill leachate. Risk estimates secured using a modified air box model are reported
15 for a hypothetical worker exposed to selected chemicals within a generalised conceptual exposure
16 model of spray irrigation. Consistent with pesticide spray exposure studies, the key risk driver is
17 dermal exposure to the more toxic components of leachate. Changes in spray droplet diameter
18 (0.02-0.2 cm) and to spray flow rate (50-1000 l/min) have little influence on dermal exposure,
19 although the lesser routes of aerosol ingestion and inhalation are markedly affected. The risk
20 estimates modelled using this conservative worst case exposure scenario are not of sufficient
21 magnitude to warrant major concerns about chemical risks to workers or bystanders from this
22 practice in the general sense. However, the modelling made use of generic concentration data for
23 only a limited number of potential landfill leachate contaminants, such that individual practices
24 may require assessment on the basis of their own merits.

25
26 Keywords: spray irrigation, landfill leachate, exposure, aerosols, dermal, risk, assessment

27
28 **INTRODUCTION**

29
30 The irrigation of landfill leachate by spray or pipe flow systems onto grassland, woodland or peat
31 slopes has been widely practised in the UK, particularly in areas (Scotland, Cornwall) where: (i)

* Corresponding author. Tel: +44 1234 754 101; Fax +44 1234 751 671; E-mail s.pollard@cranfield.ac.uk

1 high rainfall leads to the production of large volumes of dilute leachate; (ii) there are appropriate
2 areas of land for irrigation; or (iii) where isolation from sewer watercourses makes off-site
3 disposal difficult or expensive. The practice has been regarded as suitable for dilute, high volume
4 leachate and for the polishing of pre-treated leachate. To be successful, it relies on a combination
5 of physicochemical and biological processes (plant uptake, evapotranspiration, oxidation,
6 nitrification, denitrification, absorption and adsorption) for treating leachate volume and pollutant
7 (chemical oxygen demand (COD), biochemical oxygen demand (BOD), inorganic nitrogen) load
8 (Tyrrel *et al.*, 2002). In Cornwall, for example (Ankers and Ruegg, 1993), leachate
9 concentrations of up to 1500 mg BOD₅ /l and 300 mg NH₄⁺-N/l, have been spray irrigated to
10 woodland at appropriate loadings that show no detrimental effects on the irrigated vegetation; the
11 loadings having been established on the basis of extended operational experience (Cornwall
12 County Council, 1994). Irrigation equipment used historically includes slotted pipes, rain guns,
13 sprinklers and spray nozzles. The practice was common in the UK during the late 1970s and early
14 1980s, though fine spray irrigation has decreased in recent years. Currently, most operations are
15 conducted using larger spray guns to redistribute leachate within the landfill site (Figure 1).
16 Application rates per unit area vary substantially (Table 1) but are typically in the order of *ca.* 50
17 (m³/ha)/d (Knox, 2003; *personal communication*). Irrigation volumes applied vary widely and
18 seasonally (Table 1) and the practice is regulated through limits on volume and nitrogen load to
19 the receiving land through regulatory conditions on waste management licences.

20 Spray irrigation results in the generation of aerosols, the volatilisation of contaminants
21 and may result in the subsequent exposure of human receptors (workers, bystanders) to hazardous
22 components in leachate through inhalation, ingestion or dermal exposure routes. Operators of
23 waste facilities have statutory obligations with respect to protecting workers and public health.
24 The general approach for assessing exposures to bystanders from chemical sprays has been to
25 assume that, since bystanders may be exposed less frequently than workers, worker exposure,
26 providing it is found not to be significant, is protective of public health (ACP, 2002).

27 This study concerns the preliminary screening of potential exposures in hypothetical site
28 workers to specific leachate constituents during the spray irrigation of landfill leachate, with
29 broader public health considerations in mind. We seek to understand the potential significance (in
30 terms of the relative order of magnitude) of exposures that might arise from this practice and the
31 relative contributions to total exposure from a range of exposure routes and hazardous
32 components present in typical UK landfill leachate. In this context, the study might contribute to

1 the risk screening requirements for landfill sites recently by the regulator (Environment Agency
2 (2004). Our approach has been to modify and apply a shower model combined with an outdoor
3 air box model (Foster and Chrostowski, 1986; Walden and Spence, 1997) to represent an
4 exposure space, or volume, on site, and to use generalised data from UK leachates as the source
5 term for estimating exposures to hypothetical and maximally exposed workers. The risk estimates
6 and hazard quotients generated cannot be regarded as definitive quantitative predictions of health
7 risk. Their value is in illustrating the dominant exposure routes and likely chemicals of concern
8 and thus in highlighting where further study might best be focused. Following an initial screen, a
9 quantitative examination of the implications of varying certain key parameters in the analysis was
10 undertaken. Results are interpreted in the context of the literature on dermal and inhalation
11 exposures to chemicals in outdoor sprays.

12

13 **Modelling exposures from spray irrigation**

14 The estimation of human exposure to chemicals in sprays has its origins in the quantitative
15 models used to estimate exposures to volatile organic compounds (VOCs) in shower stalls and in
16 the development of regulatory models for the control of exposures to pesticide spray (van
17 Hemmen, 1993; Hamey, 2001; USEPA, 2001; European Commission, 2002). The modelling of
18 inhalation exposures to contaminants from water used during showering is reported by several
19 workers (Andelman, 1985; McKone, 1987, 1992; Little 1992a, 1992b). One model, the Integrated
20 Household Exposure Model (IHEM; Foster and Chrostowski, 1986) examines potential
21 household exposures to VOCs through the ingestion of drinking water, inhalation of volatiles
22 while showering, inhalation of water while bathing and through dermal absorption while bathing.
23 An assessment of the IHEM (Carver *et al.*, 1991), notes it as the most conservative of a range of
24 models, predicting shower air concentrations approximately double those of the least
25 conservative model. The IHEM is based on the two-film, gas-liquid mass transfer theory. The
26 rate of volatilisation across the surface of a hypothetical droplet is estimated and the volatile
27 chemical concentration in the air is predicted using the concept of dilution within a box. The
28 model assumes that a volatile organic chemical evaporating into the air of the shower stall (the
29 'box') is completely mixed and there is no build up of the volatile organic chemical at the air-
30 water interface. It does not take time-dependent distributions or *in vivo* toxicological
31 considerations following exposure into account.

1 Shower models have been adapted to simulate the volatilisation of contaminants during
 2 spray irrigation. Walden and Spence (1997) applied the IHEM to a US groundwater irrigation
 3 scenario in which potential exposures to BTEX (benzene, toluene, ethylbenzene, xylenes)
 4 compounds were a concern. Residential use of contaminated groundwater for watering lawns or
 5 gardens (including vegetables) was considered and exposures, including the dermal contact of
 6 children playing under the sprinkler with spray, the ingestion of groundwater by the child, and
 7 the vapour inhalation by the adult or child under, or downwind of the receptor, were modelled.
 8 The model estimates vapour emissions from spray and the aqueous concentrations of
 9 contaminants in grounding spray. Air phase concentrations are estimated assuming complete
 10 mixing of air in the box and dilution within the box volume. Volatilisation is limited by mass
 11 transfer rates.

12 Briefly, the overall mass transfer coefficient is calculated as (see Glossary, for symbols):

$$13 \quad K_L = [1/k_1 + RT/Hk_g]^{-1} \quad (1)$$

14 Gas and liquid phase mass transfer coefficients for contaminants can be estimated from measured
 15 values for carbon dioxide (CO₂) and water (H₂O) and the following correlations:

$$16 \quad k_{g(\text{VOC})} = k_{g(\text{H}_2\text{O})} [18/\text{MW}_{\text{VOC}}]^{0.5} \quad (2)$$

$$17 \quad k_{l(\text{VOC})} = k_{l(\text{CO}_2)} [44/\text{MW}_{\text{VOC}}]^{0.5} \quad (3)$$

18 The overall mass transfer coefficient is adjusted for the shower temperature and the viscosity of
 19 water at the lower temperature:

$$20 \quad K'_{L(T_s)} = K_L [T_l \mu_s / T_s \mu_l]^{-0.5} \quad (4)$$

21 Volatilisation is assumed to be a first order process:

$$22 \quad C_{\text{sh}} = C_o e^{-K'_L t/600d} \quad (5)$$

23 The total amount of contaminant that volatilises is given by:

$$24 \quad M_{\text{sh}} = f_v \cdot Q \cdot \text{time}_{\text{sh}} \cdot C_o \quad (6)$$

25 Finally, the concentration of the shower air can be estimated from:

$$26 \quad C_{\text{sh}} = M_{\text{sh}}/V_{\text{sh}} \quad (7)$$

27 Walden and Spence (1997) coded the model into the peer-reviewed BPRISC₄ (British
 28 Petroleum Risk Integrated Software Cleanup) software program (version 4, BP, 2001). Modelling
 29 a spray irrigation scenario, the concentration of volatilised chemicals in the air is calculated using
 30 an outdoor box approach, where the 'shower' volume (V_{sh}), the volume of air in which exposure
 31 occurs, is represented by a hypothetical box. The dimensions of the box are defined by the
 32 product of the wind speed and exposure time, the width of the spray source and the height of the

1 receptor. The rate of mass volatilisation is calculated and the air in the box is assumed to be
2 ventilated - differing from the shower scenario, where the air is stagnant and a total volatilised
3 mass is calculated. The model assumes that the air in the box is fully mixed, the concentration in
4 the box is constant and the receptor is inside the box. The model only considers on-site exposures
5 and does not consider receptors at distance from the source. The on-site exposure will be more
6 conservative than any exposures downwind of the source.

8 **METHODOLOGY**

10 **Rationale**

11 Caution must be exercised in conducting and interpreting quantitative risk studies (HSE, 2003).
12 Conceptual models of exposure and the subsequent characterisation of risks rely on numerous
13 assumptions, many of which have gross uncertainty. The value of such analyses is in providing
14 insights into system behaviour, rather than definitive point estimates of risk, for the purpose of
15 informing an appraisal of the options for managing risk (Paustenbach, 2002a). To this end, the
16 aim of this study was to understand the relative importance of a range of exposure routes and
17 trace components in a generalised leachate for worker and bystander exposure during spray
18 irrigation.

20 **Source term data**

21 Leachate compositional data were abstracted from Robinson (1995), Knox *et al.*, (2000) and
22 Robinson and Knox, (2001) (Table 2). These studies reported analytical data on approximately
23 4000 leachate samples for 72 landfill sites throughout the UK (Robinson, 1995). Knox *et al.*,
24 (2000), further reported on 57 organic substances and 8 metals listed in the UK Pollution
25 Inventory (PI), in raw and treated leachates from UK landfills. Following extension of the PI in
26 2002 to include a further 32 substances, these researchers sampled raw leachate and treated
27 effluent from 24 leachate treatment plants. Thirty six substances were tested for and of these 17
28 were present in more than 5% of samples (Robinson and Knox, 2001). Our assessment was
29 limited to 17 chemicals (Table 2), selected (i) on the basis that they were identified in >5% of the
30 leachates sampled; and (ii) on account of their accepted toxicological relevance and the
31 availability of toxicological data. With respect to chemical classes and multivalent species, for
32 ease, total polynuclear aromatic hydrocarbons (Σ PAH) were represented by benzo[*a*]pyrene

1 alone, as a conservative surrogate. Similarly, hexavalent chromium (Cr^{VI}) represented the total
2 chromium content of the leachate. Analytical data expressed PCBs in Aroclor 1260 equivalents
3 and the toxicological profile for this substance was used to represent the mixture of PCB
4 compounds. Where dose-response assessment data were not available for each exposure route,
5 route-to-route extrapolations were invoked; oral carcinogenic slope factors and oral reference
6 doses (RfDs) being used for dermal and inhaled exposures for organic compounds. Route
7 extrapolations were not made for inorganics due to reported differences in absorption efficiencies
8 for the two routes of exposure. This is acceptable within BPRISC₄ (BP, 2001) and is supported,
9 for example, by regulatory guidance in the US EPA's Region 9 Preliminary Remediation Goals
10 (EPA, 2003).

11 12 **Operational assumptions for spray irrigation**

13 There is considerable scope for variation in flow rates for the irrigation of leachate with the type
14 of irrigation system used and loading rate of the soil, as well as with the age, type and location of
15 the landfill site (Ankers and Ruegg, 1993; Alker *et al.*, 2002). Estimated values for flow rate vary
16 widely from *ca.* 11 l/min (Alker *et al.*, 2002) to >800 l/min (Webb, 2003; *personal*
17 *communication*). A nominal flow rate of 100 l/min was selected as a reasonable assumption. A
18 review of spray droplet distribution data from Kohl (1974), Edling (1985), Soloman *et al.*,
19 (1985), Li *et al.*, (1994) and Kincaid *et al.*, (1996) and the rationale given by Walden and Spence
20 (1997) resulted in the selection of a value of 0.2 cm for the droplet diameter. The droplet
21 residence time represents the length of time that a particular droplet is available to contribute
22 emissions of volatile contaminants to the outdoor box. A conservative assumption of droplet
23 residence time is 10 s, to account for volatilisation occurring from water travelling through the air
24 to the point where it is puddled or standing before it soaks into the soil, after which volatilisation
25 is assumed not to occur.

26 Localised environmental conditions influence exposure. For the probabilistic analysis,
27 triangular distribution data for average wind speed were approximated from the UK annual mean
28 wind speed (BWEA, 2003), values for mean, minimum and maximum being 5, 0 and 9 m/s,
29 respectively. Finally, because volatilisation increases with temperature and spray irrigation of
30 leachate tends to be carried out during the summer, a leachate temperature of 20°C was used.

1 **Receptor characteristics**

2 Receptor assumptions are presented in Table 3. A hypothetical maximally exposed receptor is an
3 adult worker occupationally exposed to leachate spray. In this study, receptor assumptions were
4 based, where appropriate, on the Department for the Environment, Food and Rural Affairs'
5 (Defra's) Contaminated Land Exposure Assessment (CLEA) model (Defra, 2002). In CLEA, the
6 critical receptor is a female aged 15 to 69 years. BPRISC₄ default values of fraction of total skin
7 surface area exposed (10%; hands and forearms) were selected, where the CLEA value is for
8 exposed hands only. The duration of exposure by the potential receptor is highly site-specific, but
9 should reflect a reasonable estimate of the time spent by the receptor in the outdoor box. For
10 consideration of an adult worker on a landfill site during spray irrigation, a conservative estimate
11 of time spent in the outdoor air box is 4 hours, while the maximum would be 8 hours. The
12 number of exposure events per year is based on irrigation during the eight warmest months, for a
13 5 day working week *i.e.* 175 days or events/year. BPRISC₄ default estimates of typical exposure
14 duration for workers is 8.3 years, with a maximum of 50 years (US Bureau of Labor Statistics,
15 1992). These assumptions were regarded as suitable for the purposes of this screening study.

17 **Modifications to the outdoor air box**

18 The inhalation of aerosol in spray is a route of potential concern. BPRISC₄ does not code for
19 exposures due to inhalation and ingestion of aerosols (*i.e.* very fine water droplets) and the model
20 requires modification. Exposure to contaminants that may be dissolved or suspended in the
21 leachate, and then inhaled and inwardly ingested as aerosols was assessed in the same fashion as
22 the ingestion of irrigated groundwater in the BPRISC₄ model. Whilst this approach does not
23 accurately account for aerosols taken directly into the lung airways, it does allow for exposures
24 from larger aerosols trapped in the upper respiratory tract and ingested. A conservative
25 assumption of the percentage of irrigated leachate that would aerosolise was chosen as 1%^{v/v}
26 (Sorber *et al.*, 1976; Camann *et al.*, 1978, 1988). For a 4-hr exposure and a flow rate of 100
27 l/min, this gives an estimate of 240 l. The volume of the outdoor air box was estimated to account
28 for the total volume of leachate irrigated. This required selecting a value for the width of the
29 outdoor air box to reflect the diameter of the spray area. Examination of data for irrigation
30 equipment, suggested considerable variation between wetted spray radii of different irrigation
31 systems. Using literature data, conservative estimates of spray diameter (10 m), wind speed (2
32 m/s), exposure time (4 hr) and receptor height (2 m), provide a value for the volume of the

1 outdoor air box (576,000 m³). Thus the concentration of aerosolised leachate in the air box may
 2 be estimated (0.42 ml/m³), assuming instantaneous dispersion and no settling of the aerosol over
 3 the exposure time.

4
 5 **Exposure assessment and risk characterisation**

6 Given an active respiration rate for an adult female receptor of 1.2 m³/hr, the rate of inhalation of
 7 aerosol can then be estimated at 0.52 ml/hr. For a 4-hr exposure time and flow rates of 50 and
 8 1000 l/min, the rates of inhalation of aerosol are 0.26 and 5.2 ml/hr respectively. Although the
 9 model is conservative in that it assumes that aerosols are dispersed and do not settle during
 10 exposure, it cannot account for the position of the receptor relative to the source within the
 11 outdoor air box, *i.e.*, the closer the receptor the greater the volume of aerosol the receptor is likely
 12 to inhale.

13 A generalised leachate was subjected to probabilistic analysis in BPRISC₄ using mean,
 14 minimum and maximum leachate compositional data from UK leachates (Table 2). Probability
 15 distributions of risk were generated on 10 000 iterations of the model using parameter
 16 distributions identified in Table 3. BPRISC₄ adopts a US approach to risk estimation and risk
 17 characterisation for long term exposures. Chronic average daily doses (CADD; glossary for
 18 abbreviations) for non-carcinogens and lifetime average daily doses (LADD) for carcinogens are
 19 estimated using (Walden & Spence, 1997; BP, 2001):

20 *For inhalation*

21
$$\text{LADD} = C_{\text{air}} \cdot \text{InhR} \cdot \text{AAF}_{\text{inhal}} \cdot \text{LRF} \cdot \text{ET} \cdot \text{EF} \cdot \text{ED} / (365 \cdot \text{LT} \cdot \text{BW}) \quad (8)$$

22
$$\text{CADD} = C_{\text{air}} \cdot \text{InhR} \cdot \text{AAF}_{\text{inhal}} \cdot \text{LRF} \cdot \text{ET} \cdot \text{EF} / (365 \cdot \text{LT} \cdot \text{BW}) \quad (9)$$

23 *For dermal contact*

24
$$\text{LADD} = 10^{-3} C_w \cdot \text{SA} \cdot \text{FS} \cdot \text{AAF}_{\text{dermal}} \cdot \text{ET} \cdot \text{PC} \cdot \text{EF} \cdot \text{ED} / (365 \cdot \text{LT} \cdot \text{BW}) \quad (10)$$

25
$$\text{CADD} = 10^{-3} C_w \cdot \text{SA} \cdot \text{FS} \cdot \text{AAF}_{\text{dermal}} \cdot \text{ET} \cdot \text{PC} \cdot \text{EF} / (365 \cdot \text{LT} \cdot \text{BW}) \quad (11)$$

26 *For ingestion*

27
$$\text{LADD} = 10^{-3} C_w \cdot \text{IR}_{\text{iw}} \cdot \text{ET} \cdot \text{AAF} \cdot \text{EF} \cdot \text{ED} / (365 \cdot \text{LT} \cdot \text{BW}) \quad (12)$$

28
$$\text{CADD} = 10^{-3} C_w \cdot \text{IR}_{\text{iw}} \cdot \text{ET} \cdot \text{AAF} \cdot \text{EF} / (365 \cdot \text{BW}) \quad (13)$$

29
 30 For carcinogens, risks are estimated as individual excess lifetime cancer risks (IELCR):

31
$$\text{IELCR} = \text{SF} \cdot \text{LADD} \quad (14)$$

1 Potential non-carcinogenic effects are evaluated using the hazard quotient (HQ) and, where
2 relevant, the hazard index (HI):

$$3 \quad \text{HQ} = \text{CADD}/\text{RfD} \quad (15)$$

$$4 \quad \text{HI} = \Sigma\text{HQ}_1 + \text{HQ}_2 + \text{HQ}_3 \dots \text{HQ}_n \quad (16)$$

5 The (US) carcinogenic slope factor and hazard quotient approach to risk characterisation above is
6 not adopted in the UK. Occupational and dietary exposures are assessed by reference to
7 occupational exposure limits (OELs), including maximum exposure limits (MELs) for
8 carcinogens, and tolerable daily intakes (TDIs); and are referenced to air concentrations and dose,
9 not risk (Illing, 2001). For pesticide sprays, an acceptable operator exposure level (AOEL – a
10 dose) is used (ACP, 2002). Environmental exposures are conventionally characterised by
11 reference to the drinking water and air quality guidelines (Defra, 2001), that act as risk-based
12 quality standards, expressed as concentrations, in the exposure medium of concern. The above
13 toxicological criteria are referenced to individual statutes and do not easily fit the range of
14 exposures considered in this study. For screening purposes therefore, risks were assessed using
15 the US approach and dose-response data obtained from the USEPA integrated risk information
16 system (IRIS; USEPA, 2003), a database of human health effects that may result from exposure
17 to various substances found in the environment. The updated RISC₄ (BP, 2001) software is cross-
18 referenced to IRIS.

19 20 **RESULTS AND DISCUSSION**

21 **Risk estimates and apportionment**

23 Risk estimates for the spray irrigation of generalised leachate, with a nominal flow rate of 100
24 l/min and droplet diameter of 0.2 cm, are summarised in Tables 4 to 7. Taking an IECLR
25 (expressed as a lifetime risk, not an annual) of 1E-04 (1 in ten thousand; LaGrega *et al.*, 2001) as
26 an upper bound guideline for exposure to carcinogens from leachate and, for screening purposes,
27 a HQ value of 1E+00 (*i.e.* 1) as an indicator level for non-threshold contaminants, we can screen
28 for exposure routes and principal chemicals of concern within the subset of 17 candidates
29 substances (Tables 4 to 7). Acknowledging the uncertainties and model artefacts inherent to such
30 an exercise and discussed below, an examination of the risk estimates modelled using this
31 conservative worst case exposure scenario suggests that they are not of a sufficient order of

1 magnitude to warrant major concerns about the chemical risks to workers or bystanders from this
2 practice in a general sense.

3 In terms of contribution to exposure and reviewing the 95th %ile values in Tables 4 to 5,
4 dermal contact with spray and benzo[*a*]pyrene emerge as key contributors to the potential
5 carcinogenic risk. Were we to adopt a toxicological equivalency factor (TEF) approach to
6 apportioning the toxicity of ΣPAH between individual PAH the contribution would be lowered
7 significantly. For illustrative purposes, if the risk component attributable to benzo[*a*]pyrene is set
8 aside, the potential carcinogenic risk is reduced substantially with the key contributions to dermal
9 exposure from Aroclor 1260, arsenic and dichloromethane (Figure 2) at the 95th %ile level. The
10 HI data by route and by chemical from the Monte Carlo analysis are summarised in Table 6 and
11 7, respectively. In terms of overall hazard, the major contributing routes are dermal contact and
12 the inhalation of volatile components from spray irrigated leachate. None of the indices are
13 expressed at a level of significance (*i.e.* HQ > 1). From Table 7, leachate components with the
14 highest contribution to hazard quotient are Aroclor 1260, arsenic, Cr^{VI}, lindane, mercury,
15 dichloromethane, naphthalene, toluene and xylenes. Again, because of the toxicity / permeability
16 coefficient of Aroclor 1260 used for all PCBs in the leachate and because the significant route of
17 exposure is by dermal contact, its contribution to the overall hazard is artificially increased.

19 **Sensitivity analysis**

20 Three simulations were executed varying certain of the input parameters: (i) decreasing the
21 droplet diameter to 0.02 cm, since volatilisation increases with a decrease in droplet size (Edling,
22 1985); (ii) increasing the flow rate to 1000 l/min; and (iii) decreasing the flow rate to 50 l/min, to
23 reflect the variance in operational practice. An analysis of the carcinogenic risk estimates for each
24 route is shown in Table 8 and for the hazard quotients, in Table 9. Again, dermal contact with
25 irrigated leachate spray drives the exposure under these scenarios that assume that 10% of the
26 receptor's skin surface area is wetted for 4 hr/d.

27 Adjusting operational variables such as flow rate, droplet size, droplet residence time and
28 the dimensions of the outdoor air box, appears to exhibit little effect on the level of dermal
29 exposure. This may appear counterintuitive. One normally expects, from Fick's law of diffusion,
30 dermal absorption to be directly proportional to the applied concentration and the amount of
31 chemical applied (entering the box; Paustenbach, 2002*b*). However, in the spray scenario, dermal
32 exposure is not sensitive to flowrate and droplet size because it assumes that the skin is

1 completely wet already and that there is enough water exchange (from the water already in
2 contact with the skin) so that chemicals are not further depleted as they become absorbed. Under
3 these assumptions, the only pathway-specific exposure parameters that dermal exposure to
4 sprayed water pathway is dependent on are skin surface area in contact with water and the time
5 spent in the water. The chemical-specific dermal permeability coefficients are also time
6 dependent. Note this is quite different than the mechanism used for dermal absorption from
7 chemicals in soil. By means of illustration, dermal contact was excluded as a route from the
8 analysis and the effects of operational variables on the other two routes compared with a
9 'baseline' flow rate of 100 l/min (Figure 4). These data indicate that over a reasonable range of
10 input values, flow rate is an important input variable when estimating exposures via inhalation
11 and ingestion as one would intuitively expect. All values for IECLR via ingestion of leachate
12 aerosol or inhalation are proportionately less for a flow rate of 50 l/min compared with a flow
13 rate of 1000 l/min, or reduced droplet size (and a flow rate of 100 l/min). Data for the inhalation
14 route are closer for a droplet size of 0.02 cm compared with a flow rate of 1000 l/min, and greater
15 in comparison to the values for the baseline flow rate of 100 l/min and droplet size of 0.2 cm,
16 although within the same order of magnitude. The analysis suggests that droplet diameter also
17 plays a significant role in the extent of volatilisation and subsequent exposure for the inhalation
18 of volatile components. Minimum, mean and 95th %ile values for IECLR are greater for the
19 ingestion of leachate aerosol than corresponding values for the inhalation of volatile
20 contaminants, suggesting that the ingestion route is of greater significance in this scenario.
21 Examination of data for the minimum, mean and 95th %ile values of HQ (Figure 5) indicate a
22 reversal of this order. Nevertheless, these effects are masked by the apparent dominance of the
23 dermal to the total exposure.

24

25 **Model artefacts**

26 As discussed earlier, the width of the outdoor air box is assumed to be constant at 10 m. This is a
27 conservative assumption based on examination of data for 360° rotating sprinklers, which are
28 subject to very large variations between irrigation systems. The width of the outdoor air box is
29 also treated as if the flow rate was from a single static sprinkler head, rather than from several
30 sprinkler heads spaced along a distribution pipe allowing spray overlap, or from mobile spray
31 irrigation systems. This considerably reduces the size of the outdoor air box and therefore
32 increases the concentration of volatilised contaminants within the box. Thus our assumptions

1 about the air box are regarded as conservative. Further, the BPRISC model assumes that the
2 spray (and/or volatile chemicals) is limited to the height of the receptor. All contaminants are
3 assumed to stay below that height and are assumed to pass by the receptor. Therefore, a
4 conservative assumption for height of the box is 2 m for an adult; this would be reduced for
5 consideration of a child receptor. Use of the surrogate benzo[*a*]pyrene for ΣPAH and Aroclor
6 1260 for ΣPCB accounts for further artefacts in terms of the magnitude of the risk estimates in
7 this study. This said, the pattern of exposure is consistent with other spray studies within the
8 pesticide spray and exposure literature.

9 10 **Analogous studies from pesticide spray – bystander risk assessments**

11 In this study, the dermal contact route is a function of concentration, the dermal permeability
12 coefficient, the fraction of skin exposed and the exposure time, and was shown to be
13 insufficiently sensitive to other variables such as wind speed or flow rate. To confirm,
14 simulations were conducted for each of the following variables in turn: wind speed, water
15 temperature, droplet time, droplet diameter, flow rate and spray width and we found no
16 appreciable difference for 95% ile risk estimates and only slight differences for the maximum
17 values in two cases (when droplet time changed to 100 seconds; and where flow rate was
18 increased to 10 000 l/min).

19 It is useful to consider our findings in light of research on worker and bystander exposure
20 to pesticides, where the dermal and inhalation routes of uptake can also be important (Hamey,
21 2001; European Commission, 2002; ACP, 2002). Ross *et al.*, (2001) have argued that pesticide
22 toxicology studies have much to offer occupational risk assessments, in particular, with respect to
23 our understanding of dermal exposure. Considering the validity of our modification of Walden
24 and Spence (1997) to account for aerosol inhalation exposure, ACP (2002) reported two
25 experimental studies undertaken by the former Ministry of Agriculture Fisheries and Food (Lloyd
26 and Bell, 1983; Lloyd *et al.*, 1987) on pesticide exposures to bystanders (persons incidentally
27 located at or adjacent to the site of pesticide application who take no action to control exposure)
28 downwind (8 m) of the spray drift. Harmless tracers were used. From studies of arable crop spray
29 in high wind speeds (Lloyd and Bell, 1983; Lloyd *et al.*, 1987) inhalation exposures of *ca.* 0.02
30 ml/m³ (max. values 0.1 ml/m³) and 0.002 ml/m³ were estimated. At a distance of 5 m from
31 conventional pesticide spray equipment, the typical levels of pesticide spray drift deposited on
32 the ground are reportedly *ca.* 1% of the applied dose (ACP, 2002). Using this assumption with

1 respect to dermal exposure, Ganzelmeier *et al.* (1995) estimated bystander exposure to pesticide
2 spray 5 m from the point of application (at 200 l/ha) to be < 0.4 ml/person. These analogous
3 studies reinforce our view that an aerosol exposure estimate of 0.42 ml/m³ is a reasonable worst
4 case estimate.

6 **CONCLUSIONS**

7
8 The spray irrigation of landfill leachate is regarded by many operators as an attractive option for
9 meeting discharge consent limits when considered alongside the costs of tankering leachate off-
10 site for specialist treatment. Spray irrigation releases volatiles from the leachate volume and
11 disperses leachate in the form of a fine mist that can be inhaled, ingested or deposited on the skin
12 of site workers. To date, no estimate of these exposures to site workers or bystanders has been
13 conducted. A risk screening exercise in this study used an accepted air box model, with
14 modifications. Chemical exposures to a hypothetical and maximally exposed worker during the
15 simulated spray irrigation of landfill leachate were screened and the IHEM developed to simulate
16 the ingestion of leachate aerosol.

- 17
18 (i) Routes of exposure were ranked in the following order according to their contribution to
19 carcinogenic risk: dermal contact >> ingestion of aerosol > inhalation of volatiles; and,
20 hazard index: dermal contact >> inhalation of volatiles > ingestion of aerosol. Whilst the
21 quantification of site-specific risk estimates from the spray irrigation of leachate may
22 require additional study and was not the purpose of this work, it is prudent for workers to
23 wear suitable personal protective clothing where they are likely to be in close proximity to
24 sprayed leachate, or remain beyond the spray radius.
- 25
26 (ii) Increasing flow rate to 1000 l/min, and to a lesser extent reducing droplet diameter to 0.02
27 cm from the 'baseline' parameters of 100 l/min flow rate and 0.2 cm droplet size, resulted
28 in increased contribution to both risk and hazard due to inhalation exposure, but had little
29 effect on dermal exposures. Procedures to reduce irrigation flow rate and/or high
30 populations of fine droplets, such as lower operating pressures, larger nozzles, low or
31 downward pointing spray trajectories may serve to reduce potential exposures, by

1 minimising volatilisation and spray mist.

2
3 (iii) The quantitative risk estimates modelled using this conservative worst case exposure
4 scenario are not of sufficient magnitude to warrant major concerns about chemical risks to
5 workers or bystanders from this practice in the general sense. This would also require
6 occupational exposure limits and environmental assessment levels for these substances to
7 be exceeded in the occupational setting. However, it should also be noted that the
8 modelling made use of generic concentration data for only a limited number of potential
9 landfill leachate contaminants, such that individual practices may require assessment on
10 the basis of their own merits.

11
12 (iv) This study adopted a generalised conservative modelling approach. Processes and model
13 features for site-specific application and that, were they better characterised within the
14 model with site data, might lessen the conservative nature of the approach include: (a) the
15 dispersion and aerosol deposition within the outdoor box; (b) a more representative
16 analysis of exposure times; (c) inclusion of various spraying regimes *e.g.* under coppice
17 canopies.

18 19 **ACKNOWLEDGEMENTS**

20 This work was funded by the Environment Agency of England and Wales to whom we are
21 grateful for permission to publish. We acknowledge the assistance of Sean Tyrrel, Keith
22 Weatherhead, Frank Taylor and Sam Tohill, Martin Lowe (Cranfield University); Keith Knox
23 (Knox Associates, UK); Sue Webb (CES Group); and Terry Walden (BP International). The
24 opinions and interpretations expressed herein are those of the authors alone.

1 **GLOSSARY OF TERMS**

2

3 **Equation 1**

4 K_L = overall mass transfer coefficient (cm/hr)

5 H = Henry's Law constant for contaminant ($\text{atm}\cdot\text{m}^3/\text{mol}$)

6 R = gas constant (assumed to be 8.2×10^{-5}) ($\text{atm}\cdot\text{m}^3/\text{mol}\cdot\text{K}$)

7 T = absolute temperature (293 K)

8 k_g = gas phase mass transfer coefficient (cm/hr)

9 k_l = liquid phase mass transfer coefficient (cm/hr)

10

11 **Equations 2 and 3**

12 $k_{g(\text{H}_2\text{O})}$ = gas phase mass transfer coefficient for water (cm/hr) = 3000 cm/hr

13 $k_{l(\text{CO}_2)}$ = liquid phase mass transfer coefficient for carbon dioxide (cm/hr) = 20 cm/hr

14 18 = molecular weight of H_2O

15 44 = molecular weight of CO_2

16 MW_{VOC} = molecular weight of contaminant

17

18 **Equation 4**

19 $K'_{L(T_S)}$ = adjusted overall mass transfer coefficient (cm/hr)

20 T_1 = calibration water temperature of K_L (K)

21 T_S = shower water temperature (K)

22 μ_1 = water viscosity at T_1 (g/m.s)

23 μ_S = water viscosity at T_S (g/m.s)

24

25 **Equation 5**

26 C_{sh} = concentration of contaminant in shower droplet after time t (mg/l)

27 C_o = concentration of contaminant in shower water (mg/l)

28 d = shower droplet diameter (cm)

29 t = shower droplet drop time (s)

30

31 **Equation 6**

32 M_{sh} = mass of contaminant volatilised (mg)

1 $f_v =$ the fraction of contaminant volatilised ($1 - e^{-K_L t/600d}$) (mg/mg)

2 $Q =$ the volumetric flow rate of water (l/min)

3 $time_{sh} =$ the duration for which the shower water is flowing (min)

4 $C_o =$ the concentration of contaminant in the shower water (mg/l)

5

6 **Equation 7**

7 $C_{sh} =$ air concentration in the shower (mg/m³)

8 $V_{sh} =$ volume of air in the shower (m³).

9

10 **Equations 8-13**

11 $C_{air} =$ concentration of contaminant of concern in air (mg/m³)

12 $C_w =$ concentration of contaminant of concern in leachate (mg/l)

13 $InhR =$ inhalation rate (m³/hr)

14 $SA =$ total skin surface area (cm²)

15 $FS =$ fraction of total skin surface area exposed to irrigation water (cm²/cm²)

16 $IR_{iw} =$ water ingestion rate (ml/hr)

17 $AAF_{inhal} =$ contaminant specific absorption adjustment factor for inhalation route
18 (mg/mg); assumed to be 1

19 $AAF_{dermal} =$ contaminant specific absorption adjustment factor for dermal route (mg/mg)

20 $LRF =$ lung retention factor (dimensionless); assumed to be 1

21 $AAF =$ chemical-specific oral-water absorption adjustment factor (mg/mg)

22 $ET =$ exposure time/activity duration (hr/day)

23 $PC =$ Chemical specific skin permeability coefficient (cm/hr)

24 $EF =$ exposure frequency for occupation (days/year)

25 $ED =$ exposure duration (years)

26 $365 =$ days/year

27 $LT =$ lifetime (years)

28 $BW =$ body weight (kg)

29

30 **Equations 14-15**

31 $IELCR =$ individual excess lifetime cancer risk for a specified chemical and exposure route (for
32 annual risk this is divided by the exposure duration)

1 SF = slope factor (chemical carcinogenic toxicity) for a specified chemical and exposure route
2 (mg/kg-day)⁻¹

3 HQ = hazard quotient for a specific chemical and exposure route

4 RfD = reference dose for a specific chemical and exposure route (mg/kg-day)

5 HI = hazard index

6

7 REFERENCES

8

9 Advisory Committee on Pesticides (ACP) (UK) (2002) *Bystander risk assessment, Papers for the*
10 *Open Meeting of 10th July, 2002*, Item 4, 9pp. at

11 http://www.pesticides.gov.uk/committees/acp/Open_Meetings/Open_ACP_2002/Bystander3
12 [.pdf](#) <<accessed 11-11-03>>

13 Alker, G. R., Godley, A. R., Hallett, J. E. (2002) *Landfill leachate management using short*
14 *rotation coppice*, Final technical report CO5126, WRc Swindon.

15 Andelman, J.B. (1985) Inhalation exposure in the home to volatile organic contaminants of
16 drinking Water. *Sci. Tot. Environ.* **47**, 443-460.

17 Ankers, W. B., Ruegg, J. (1993) *Research into leachate treatment by woodland and grassplot*
18 *irrigation*. PECD 7/10/135. Waste Regulation Authority, Cornwall County Council, UK

19 British Petroleum (BP) (2001). *Risk integrated software for cleanups RISC₄*, L. Spence and T.
20 Walden (eds.) User's Manual, British Petroleum, London, 439pp.

21 British Wind Energy Association (BWEA) (2003) *UK wind speed database*,
22 <http://www.bwea.com/noabl/> <<accessed 21 July, 2003>>

23 Camann, D.E., Sorber, S.A., Sagik, B.P., Glennon, J.P., Johnson, D.E. (1978) A model for
24 predicting pathogen concentrations in wastewater aerosols. In: *Risk assessment and health*
25 *effects of land application of municipal wastewater and sludges*, University of Texas at San
26 Antonio, Texas, US, pp 240-267

27 Camann, D.E., Moore, B.E., Harding, H.J., Sorber, C.A. (1988) Microorganism levels in air near
28 spray irrigation of municipal wastewater: the Lubbock infection surveillance study. *J. Water*
29 *Pollut. Control Fed.* **60**, 1960-1970.

30 Carver, J.H., Seigneur, C.S., Block, R.M., Miller, T.M. (1991) Comparison of exposure models
31 for volatile organics in tap water. In: *Proceedings of Hazmacon*, Santa Clara, California, US

- 1 Cornwall County Council (1994) *A manual of good practice for leachate treatment by irrigation*
2 *to land – summary report*, Cornwall County Council Waste Regulation Authority for the
3 Department of the Environment, 54pp.
- 4 Department for Environment, Food and Rural Affairs (Defra) (UK) (2001). *Air quality strategy:*
5 *particles, benzene, carbon monoxide and polycyclic aromatic hydrocarbons; Section 4:*
6 *polycyclic aromatic hydrocarbons.*
7 <http://www.defra.gov.uk/environment/consult/airqual01/11.htm>
- 8 Department for Environment, Food and Rural Affairs (Defra) and the Environment Agency
9 (2002) *Contaminants in soil: collation of toxicological data and intake values for humans.*
10 Environment Agency, Bristol,
11 <http://www.defra.gov.uk/environment/landliability/pdf/clr9.pdf>
- 12 Edling, R.J. (1985) Kinetic energy, evaporation and wind drift of droplets from low pressure
13 irrigation nozzles. *Trans Amer. Soc. Agric. Eng.* **28**, 1543-1550.
- 14 Environment Agency (2004) *Guidance on assessment of risks from landfill sites*, External
15 consultation v1.0, May 2004, Environment Agency, Bristol, 73pp.
- 16 European Commission (2002). *Guidance document on dermal absorption*. EC Health and
17 Consumer Protection Directorate-General, Sanco/222/2000 rev.6, dated 27th November
18 2002, 14pp.
- 19 Foster, S.A., Chrostowski, P.C (1986) Integrated household exposure model for use of tap water
20 contaminated with volatile organic chemicals. *Presented at the 79th Annual Meeting of the*
21 *Air Pollution Control Association*, Minneapolis, Minnesota, pp 1-25.
- 22 Ganzelmeier, H., Rautmann, D., Spangenberg, R., Streloke, M., Herrmann, M., Wenzelbuger, H-
23 J. and Walter, H-F. (1995) *Studies on the spray drift of plant protection products. Results of*
24 *a test programme carried out through the Federal Republic of Germany.* Mitteilungen aus
25 de Biologischen Bundesansalt für Land- und Forstwirtschaft, Berlin-Dahlem, Heft 305.
- 26 Giardino, N.J., Esmen, N.A., Andelman, J.B. (1992) Modelling volatilisation of trichloroethylene
27 from a domestic shower spray: the role of drop-size distribution. *Environ Sci Technol*, **26**,
28 1602-1606.
- 29 Hamey, P.Y. (2001) An example to illustrate the potential use of probabilistic modelling to
30 estimate operator exposure to pesticides. *Ann Occup. Hyg.* 45(1001) S55-S64.
- 31 HSE (2003) *Good practice and pitfalls in risk assessment*, HSE Books, Sudbury, 54pp.

- 1 Kincaid, D.C., Solomon, K.H., Oliphant, J.C. (1996) Drop size distributions for irrigation
2 sprinklers. *Trans Amer. Soc. Agric. Eng.* **39**, 839-845.
- 3 Kohl, R. A. (1974) Drop size distribution from medium-sized agricultural sprinklers. *Trans*
4 *Amer. Soc. Agric. Eng.* **17**, 690-693.
- 5 Kohl, R. A., DeBoer, D.W. (1984) Drop size distributions for a low pressure spray type
6 agricultural sprinkler. *Trans Amer. Soc. Agric. Eng.* **27**, 1836-1840.
- 7 Knox, K., Robinson, H.D., van Santen, A., Tempany, P.R. (2000). The occurrence of trace
8 organic components in landfill leachates and their removal during on-site treatment. *IWM*
9 *Sci. Tech. Rev.* **11**, 5-10.
- 10 LaGrega, M.D., Buckingham, P.L. and Evans, J.C. (2001) *Hazardous waste management*, 2nd
11 edition, McGraw-Hill International Edition, pp.300-301
- 12 Li, J., Kawano, H., Yu, K. (1994) Droplet size distributions from different shaped sprinkler
13 nozzles. *Trans Amer. Soc. Agric. Eng.* **37**, 1871-1878.
- 14 Little, J.C. (1992a) Applying the two-resistance theory to contaminant volatilisation in showers.
15 *Environ. Sci. Technol.* **26**, 1341-1349.
- 16 Little, J.C. (1992b) Correspondence: Comment on Human exposure to volatile organic
17 compounds in household tap water: the indoor inhalation pathway. *Environ. Sci. Technol.*
18 **26**, 836-837.
- 19 Lloyd G.A. and Bell, G.J. (1983) *Hydraulic nozzles: a comparative study*. Ministry of
20 Agriculture Fisheries and Food, London, UK
- 21 Lloyd G.A., Bell, G.J., Samuels, S.W., Cross, J.V., and Berries, A.M. (1987) *Orchard sprayers:*
22 *comparative operator exposure and spray drift study*. Ministry of Agriculture Fisheries and
23 Food, London, UK
- 24 Illing, P. (2001) *Toxicity and risk: context, principles and practice*. Taylor and Francis, London,
25 154pp.
- 26 McKone, T.E. (1987) Human Exposure to volatile organic compounds in household tap water:
27 the indoor inhalation pathway. *Environ. Sci. Technol.* **21**, 1194-1201.
- 28 McKone, T.E. (1992) Correspondence: Comment on Human exposure to volatile organic
29 compounds in household tap water: the indoor inhalation pathway. *Environ. Sci. Technol.*,
30 837-838.

- 1 Paustenbach, D.J. (2002a) Primer on human and environmental risk assessment. In: *Human and*
2 *ecological risk assessment: theory and practice* (D.J Pautenbach, ed.), John Wiley & Sons,
3 New York, NY, 45-46
- 4 Paustenbach, D.J. (2002b) Exposure assessment. In: *Human and ecological risk assessment:*
5 *theory and practice* (D.J Pautenbach, ed.), John Wiley & Sons, New York, NY, 215-216
- 6 Robinson, H.D. (1995) *A review of the composition of leachates from domestic wastes in landfill*
7 *sites*. R&D Technical Report CWM072/95, Environment Agency, Bristol, UK
- 8 Robinson, H.D, Knox, K. (2001) *Updating the landfill leachate Pollution Inventory reporting*
9 *tool*. R&D Technical Report No PI-496/TR(2), Environment Agency, Bristol, UK
- 10 Ross, J.H., Driver, J.H., Cochran, R.C., Thongsinthusak, T. and Krieger, R.I. (2001) Could
11 pesticide toxicology studies be more relevant to occupational risk assessment?. *Ann Occ.*
12 *Hyg.* **54**(1001): S5-S17
- 13 Solomon, K.H., Kincaid, D.C., Bezdek, J.C. (1985) Drop size distributions for irrigation spray
14 nozzles. *Trans Amer. Soc. Agric. Eng.* **28**, 1966-1974.
- 15 Sorber, C.A., Bausum, H.T., Schaub, S.A., Small, M.J. (1976) A study of bacterial aerosols at a
16 wastewater irrigation site. *J. Water Pollut. Control Fed.* **48**, 2367-2379.
- 17 Tyrrel, S.F., Leeds-Harrison, P.B., and Harrison, K.S. (2002) Removal of ammoniacal nitrogen
18 from landfill leachate by irrigation onto vegetated treatment planes. *Wat. Res.* **36**, 291-299.
- 19 US Bureau of Labor Statistics (1992) <http://www.bls.gov/>
- 20 USEPA (2001). *Risk assessment guidance for Superfund. Volume 1: Human health evaluation*
21 *manual. Part E, supplementary guidance for dermal risk assessment (interim). Review draft*
22 *for public comment*. EPA/540/R/99/05, Office of solid waste and emergency response
23 9285.7-02EP, USEPA. 2001. Washington, DC
- 24 USEPA (2003). *Region 9: Superfund. Preliminary remediation goals*,
25 <http://www.epa.gov/region09/waste/sfund/prg/index.htm>
- 26 USEPA (2003). Integrated risk information system. Current update, 2003. available at
27 <http://www.epa.gov/iris/subst/index.html> <<accessed 11/11/03>>
- 28 Walden, J.T., Spence, L.R. (1997) Risk-based BTEX screening criteria for a groundwater
29 irrigation scenario. *Hum. Ecol. Risk Assess.* **3**, 699-722.

1 **Table 1.** Illustrative spray irrigation conditions for UK landfill sites in Cornwall, UK

2

Site	Pump rates (m ³ /hr)	Spray regime (vols. in 2002)	Nitrogen load (kg/ha)	Leachate quality	Conditions
A	80 (wood); 50 (fields)	150 055 m ³ 32 500 m ³ (Nov.); 389 m ³ (Sept.)	50 (grassland) 70 (wood)	35-45 mg/l NH ₄ ⁺ -N 5-16 mg/l NO ₃ ⁻ -N	Old leachate; Hypro TM spray nozzle 10 mm
B	80 (wood); 50 (fields)	23 600 m ³ 7 600 m ³ (Nov.); 725 m ³ (Sept.)	700 (wood); 500 (grassland)	9 mg/l NH ₄ ⁺ -N 20 mg/l NO ₃ ⁻ -N	Weak leachate only; Hypro TM spray nozzle 10 mm
C	80 (wood); 50 (fields)	6 060m ³ 859 m ³ (Nov.); 229 m ³ (Sept.)	700 (wood); 500 (grassland)	220 mg/l NH ₄ ⁺ -N 7 mg/l NO ₃ ⁻ -N	Hypro TM spray nozzle 10 mm

3

4
5 **Table 2.** Leachate compositional data (after Robinson, 1995; Knox *et al.*, 2000; and, Robinson
6 and Knox, 2001).

7

Chemical	Frequency of occurrence in leachate samples (%)	Assumed distribution	Mean (mg/l)	Min (mg/l)	Max (mg/l)
aniline	17	Triangular	1.46E-03	1.00E-03	7.00E-03
Aroclor 1260	20	Triangular	8.00E-05	2.00E-05	3.40E-04
arsenic	94	Triangular	1.60E-02	1.0E-03	1.60E-01
benzo[a]pyrene	29	Triangular	5.60E-03	5.25E-03	1.22E-02
cadmium	20	Triangular	2.00E-02	1.00E-02	3.00E-02
chromium (VI)	33	Triangular	9.20E-02	5.00E-02	1.24E+00
dieldrin	7	Triangular	1.30E-04	7.00E-05	2.00E-04
ethylbenzene	15	Triangular	1.90E-02	1.00E-02	5.90E-02
hexachlorobenzene	17	Triangular	9.00E-05	4.00E-05	2.20E-04
lead	8	Triangular	6.00E-02	5.00E-02	4.10E-01
lindane	23	Triangular	3.37E-03	2.00E-05	2.03E-02
mercury	30	Triangular	3.00E-04	1.00E-04	1.00E-03
dichloromethane ¹	13	Triangular	4.28E-02	1.00E-03	5.04E-01
naphthalene	70	Triangular	3.04E-03	1.00E-04	4.20E-02
toluene	54	Triangular	8.70E-02	1.00E-02	1.29E+00
1,2,3-trichlorobenzene	17	Triangular	5.80E-04	8.00E-05	1.29E-03
xylenes	35	Triangular	5.90E-02	3.00E-02	2.08E-01

8 ¹ methylene chloride

1 **Table 3.** Summary of baseline input parameters for BPRISC₄.

Input Parameter	Distribution	Mean	Std Dev	Min	Max
Receptor characteristics					
body weight (kg) ^a	Normal	68.5	13.9	46.4	68.5
lifetime (y)	Constant	70	-	-	-
ingestion rate (ml/hr)	Constant	5.2E-01	-	-	-
inhalation rate outdoors (m ³ /hr) ^c	Triangular	1.23	-	4.11	1.63
lung retention factor (unitless)	Constant	1	-	-	-
total skin surface area (cm ²)	Constant	1.76E+04	-	-	-
fraction skin exposed to water (unitless)	Constant	1.1E-01	-	-	-
height of breathing zone (m)	Constant	2	-	-	-
Exposure characteristics					
time in sprinkler (hr/day)	Constant	4	-	-	-
exp. freq irrigation (events/year)	Constant	175	-	-	-
exposure duration leachate (years) ^d	Lognormal	8.3	8.7	0	50
Spray operational parameters					
width of sprinkler spray (m)	Constant	10	-	-	-
sprinkler flow rate (l/min)	Constant	100	-	-	-
droplet diameter sprinkler (cm)	Constant	0.2	-	-	-
droplet droptime for sprinkler (s)	Constant	10	-	-	-
Environmental parameters					
temperature of irrigation water (°C)	Constant	20	-	-	-
average windspeed (m/s) ^b	Triangular	5	-	0	9

^abody weight maximum and minimum values taken as 5th and 50th percentile values for critical adult female receptor aged 16-59 (Defra, 2002)

^baverage wind speed approximated from BWEA (2003)

^cinhalation rate determined: mean of active respiration rate; minimum of passive respiration rate; and, maximum as 95th percentile of active respiration rate for critical adult female receptor aged 16-59 (CLEA, 2003)

^dexposure duration; default values from BPRISC, based upon Bureau of Labor Statistics (1992).

2
3
4

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15



16 **Fig. 1.** Representative spray irrigation of landfill leachate using spray guns
17 and illustrating typical spray radii