

Elsevier Editorial System(tm) for Automation
in Construction
Manuscript Draft

Manuscript Number: AUTCON-D-16-00352R2

Title: The Building Information Modelling Trajectory in Facilities
Management: A Review

Article Type: Review Article

Keywords: Building information modelling; data interoperability;
facilities management; asset operations and maintenance

Corresponding Author: Miss Erika Anneli Pärn, BSc Architectural
Technology, PGCert,

Corresponding Author's Institution: Birmingham City University

First Author: Erika Anneli Pärn, BSc Architectural Technology, PGCert,

Order of Authors: Erika Anneli Pärn, BSc Architectural Technology,
PGCert,; David J Edwards, BSc, PhD; Michael C Sing, BSc, PhD

HIGHLIGHTS

- For new buildings, research into BIM-FM integration is rare.
- A review of developments and opportunities for BIM-FM integration is presented.
- Challenges posed include interoperability, performance enhancement and training.
- Future work seeks to produce commercial products and record contemporary practice.

1 **The Building Information Modelling Trajectory in Facilities Management:**
2 **A Review**

3
4 Pärn, E.A.¹, Edwards, D.J.² and Michael, C.P. Sing³
5

6
7 ¹Faculty of Technology Environment and Engineering, Birmingham City University
8 City Centre Campus, Millennium Point, Birmingham B4 7XG, United Kingdom
9 **Email:** Erika.Pärn@bcu.ac.uk (Corresponding Author)
10

11
12 ²Faculty of Technology Environment and Engineering, Birmingham City University
13 City Centre Campus, Millennium Point, Birmingham B4 7XG, United Kingdom
14 **Email:** David.Edwards@bcu.ac.uk
15

16
17 ³Department of Building and Real Estate
18 7/F, Block Z, The Hong Kong Polytechnic University
19 **Email:** mcpsing@outlook.com
20

21 **ABSTRACT**

22 There is a paucity of literature that examines building information modelling (BIM) for asset
23 management within the architecture, engineering, construction and owner-operated (AECO)
24 sector. This paper therefore presents a thorough review of published literature on the latest
25 research and standards development that impact upon BIM and its application in facilities
26 management (FM) during the operations and maintenance (O&M) phase of building usage. The
27 purpose is to generate new ideas and provide polemic clarity geared to intellectually challenge
28 readers from across a range of academic and industrial disciplines. The findings reveal that
29 significant challenges facing the FM sector include the need for: greater consideration of long-
30 term strategic aspirations; amelioration of data integration/ interoperability issues; augmented
31 knowledge management; enhanced performance measurement; and enriched training and
32 competence development for facilities managers to better deal with the amorphous range of
33 services covered by FM. Future work is also proposed in several key areas and includes: case
34 studies to observe and report upon current practice and development; and supplementary research
35 related to concepts of knowledge capture in relation to FM and the growing use of BIM for asset
36 management.
37

38 **KEYWORDS**

39 Building information modelling, data interoperability, facilities management, asset operations and
40 maintenance

41 1.0 INTRODUCTION

42 The proliferation of advanced computerisation throughout industry has revolutionised the way that
43 buildings are designed, constructed, operated and maintained [1]. Today, computerisation is firmly
44 embedded within a building's lifecycle from earliest concept through to occupation and operation, a
45 transition made possible via disruptive technologies such as Building Information Modelling (BIM)
46 which have displaced traditional approaches and created virtual communities of practice (CoP) [2]. A
47 virtual CoP represents an extensive 'multiple stakeholder' collaboration platform that is generated
48 during design and construction through a single integrated BIM [1]. The dynamic, open access,
49 digital environment afforded by BIM enables storage, sharing and integration of information for
50 buildings' operations and management (O&M) (*ibid*). BIM can embed key product and asset data
51 within a three-dimensional computer model to effectively and efficiently manage building
52 information [3]. Consequently, BIM deployment becomes extremely invaluable to organisations that
53 seek to reap inherent value and efficiency gains from the technology [4, 5].

54
55 However, capturing a building's intricate and expanding portfolio of data requirements for facilities
56 management (FM) is complex and requires facilities managers with tenacious strategic and tactical
57 skills [6,7]. These skills encompass diverse roles and duties may include the strategic planning and
58 management of: plant operations; computer systems analysis; building assets; interior operations; and
59 day-to-day tactical operations of assets and staff [8]. The problems related to optimising O&M are
60 further exacerbated by the vast complexity and volume of data and information generated during a
61 building's whole life cycle [9]. Automating this amorphous range of roles and duties, and
62 engendering intelligent decision support, are feasible with the aid of BIM-FM integration [10,11,12].
63 However, within the UK, practitioners¹ reside within a transition period of adopting BIM and the
64 extant literature simultaneously discloses limitations in: related procedures [13]; established
65 standards [12]; and computerised FM system integration [11]. Many practitioners have sought
66 bespoke pathways to adopting new technologies in a climate of exponential technological
67 advancement but few have sought guidance from more technologically advanced sectors as aerospace
68 and automotive manufacturing [14]. Inconsistencies in technology adaptation are complicated by a
69 paucity of standardisation within FM procedures and processes. At present, the literature contains
70 limited evidence of applied studies of hybrid BIM-FM environment development and the tangible
71 benefits to be accrued from such [12,9].

72

¹ Practitioners in the context of this paper includes all parties involved in construction project development including: client's estates department; construction manager; architect; mechanical electrical plumbing designer; structural engineer; sub-contractor; and consultant.

73 To provide polemic clarity of the emergent hybrid BIM-FM environment, this research aims to: i)
74 conduct a critical synthesis of extant literature and identify key challenges around BIM-FM
75 integration; and ii) investigate state of-the-art tools used for BIM-FM knowledge capture. In realising
76 these aims, the objectives are to argue the case for greater BIM-FM integration and stimulate wider
77 debate and software development amongst academics and practitioners from a broader range of
78 industrial sectors (including aerospace and automotive manufacturing). Knowledge transfer from
79 these more technologically advanced industries will be beneficial to the AECO sector.

80

81 **2.0 FACILITIES MANAGEMENT: DEFINITIONS, INFLUENCES AND CHALLENGES**

82 FM represents an integrated approach to maintaining, improving and adapting an organisation's
83 buildings to promote a fertile environment that supports the organisation's primary objectives
84 [15,16]. Literature is replete with FM definitions, for example, Alexander [17] defines FM as: "*the*
85 *process by which an organization delivers and sustains support services in a quality environment to*
86 *meet strategic needs.*" McGregor and Then [18] further proffer that FM is: "*a hybrid management*
87 *discipline, which combines the management expertise of people, property and process(es).(p.1)*",
88 whilst Nutt [19] defines FM as: "*a supporting tool to obtain sustainable and operational strategy for*
89 *an organisation over time through management of infrastructure resources and services.(p.462)*".
90 Chotipanich [20] elucidates the benefits derived from FM, highlighting improvements in managing
91 facility resources, support services and working environment.

92

93 These delineations illustrate that the definition of FM has evolved over time and this can be attributed
94 to several influential, interventional factors which impact upon the configuration of FM regime
95 adopted. These factors can be conveniently allocated to three thematic groupings: i) *business*
96 *environment* – including organisational structure [16,21]; business objectives [22]; and company
97 culture and contextual issues [23]; ii) *buildings and facilities characteristics* – for example, facility
98 type [23]; location; and size (*ibid.*); and iii) *external interventions/ factors* – such as business needs
99 and processes [18]; asset maintenance priorities [24, 22]; legislation [21]; and interrelationships with
100 other contractors [16]. In synthesising and evaluating the literature, Chotipanich [20] suggests
101 categorising these factors as *internal factors* (i.e. characteristics of the organisation, facility features
102 and business sectors) or *external factors* (i.e. social, economic, legislative and regulative, local
103 culture and context and market context for FM) [25]. Appraising this eclectic mix of definitions and
104 factors illustrates that internal factors have received wider attention vis-à-vis external factors, even
105 though the latter are quintessentially important to organisational resilience and business stability [15].

106

107 Information is critical for supporting efficient and effective building maintenance and day-to-day
108 operations [15,24,26]. However, the FM sector continues to grapple with information management,
109 predominantly due to the peculiarity of information and its fragmentation [1, 7]. These two causal
110 factors are attributed as being the leading causes for knowledge loss within the architecture,
111 engineering, construction, owner-operated (AECO) sector [27]. Computerisation alleviates asset
112 information capture and retrieval, but knowledge capture and automated data analysis is limited
113 within computer aided facilities management (CAFM) systems [15,11]. Commonly established
114 CAFM tools are: computer aided design (CAD) (*ibid.*); integrated workplace management systems
115 (IWMS) [28]; enterprise asset management (EAM) [29]; and computerized maintenance management
116 systems (CMMS) [30]. Although these disparate tools have inherently different capabilities and
117 functions, a vital prerequisite to implementing an appropriate CAFM system is that an organisation
118 perceives data as its most invaluable asset [31]. A recent survey result is juxtaposed against this
119 position and reveals that 43% of UK employees do not understand the value of business data [32].

120

121 The performance of FM must be measurable via knowledge management (KM) [33]. However,
122 agreement over a common definition of KM remains a vexatious issue in FM [34,35,36]. For
123 example, Bosch *et al.* [37] suggest that KM encapsulates a process of managing corporate knowledge
124 to facilitate competitive advantage and organisational success, whilst Bhatt [38] emphasises KM
125 characteristics and traits such as learning, collaboration, experimentation and implementation of
126 powerful information systems. Commonly used FM performance measurement tools include: post-
127 occupancy evaluation [38]; British Institute for Facilities Management (BIFM) measurement protocol
128 [40]; key performance indicators (KPIs) [23]; and the balanced scorecard (BSC) [41] – refer to Table
129 1. Many of these tools are antiquated, often subjective and frequently client driven – consequently,
130 they may fail to accurately portray issues facing the facilities management team (FMT) [33].

131

132 *<Insert Table 1 FM performance measurement tools>*

133

134 **2.1 BIM-FM INTEGRATION**

135 The UK Government define BIM as: “*a collaborative way of working, underpinned by digital*
136 *technologies which unlock more efficient methods of designing, creating and maintaining assets*”
137 [63], whilst Succar [3] defines BIM as: “*a set of interacting policies, processes and technologies*
138 *producing a methodology to manage the essential building design and project data in digital format*
139 *throughout the building’s life-cycle.*” The capacity to harness valuable data and information
140 throughout a building’s life cycle is integral within these ubiquitous definitions (*ibid.*). BIM has

141 orchestrated a paradigm shift in the way that information is managed, exchanged and transformed to
142 stimulate greater collaboration between stakeholders via a single integrated model during the design
143 and construction phases [1]. This integrated approach to BIM ensures a smooth flow of information
144 between all stakeholders and is specified and articulated through Levels of Development or Design
145 [1,64] The Level of Design (LOD) is classified to range from LOD 100 (covering a conceptual ‘low
146 definition’ design) to LOD 500 (for an as-built ‘high definition’ model). In practice, models that
147 provide LOD500 are rare.

148

149 BIM and FM integration can be classified as 6D modelling (refer to Table 2) [65], where nD
150 modelling is defined as the addition of supplementary information to three-dimensional model(s) for
151 analysis and simulation purposes. BIM-FM integration is increasingly utilised for the building’s
152 O&M and provides several benefits which include: augmented manual processes of information
153 handover; improved accuracy of FM data (e.g. manufacturer specifications); and increased efficiency
154 of work order execution to access data and locate interventions [66]. Watson [67] recommends that
155 every constructed facility requires a bespoke BIM model, analogous to an owner’s manual, with
156 mandates for model updates that correspond to periodic repair or refurbishment works. In practice,
157 6D BIM data becomes the FMT’s responsibility but this can create problems in other areas
158 [11,12,68]. For example, Teicholz [26] reports a litany of issues including: inconsistent naming
159 conventions; a myriad of bespoke FMT information requirements; inadequate data categorization in
160 BIM and CAFM systems; poor information synchronization; and lack of methodology to capture
161 existing facilities and assets. During O&M, more than 80% of an FMT’s time is consumed finding
162 relevant information that is often disregarded by designers during pre-construction work [11]. Such
163 information is important when handing-over an accurate as-built model to building owners for the
164 purpose of asset management. The Institution of Civil Engineers [69] states that the provision of a
165 reliable, BIM-sourced suite of information can eliminate these issues. A lack of tacit knowledge and
166 technical expertise within the FMT represents a major obstacle to the ICE’s (*ibid*) assertion.

167

168

<Insert Table 2 Dimension of BIM>

169

170 McArthur [71] contends that identifying information required to inform operational decisions is
171 critical to configuring data retrieval techniques at the post-construction stages - yet this task, and
172 linking such to the as-built model for O&M usage, remains problematic [72]. Meadati *et al.* [73]
173 observe that inconsistencies between demand and availability of particular information in an as-built
174 model incur unnecessary expenditures. Thus, linking data and configuring retrievable information

175 within the as-built model for the project's post-construction operational phase must be considered
176 during the design and development of BIM data.

177

178 BIM offers the FMT opportunities to manipulate and utilise information contained within 3D objects
179 [74]. However, Lavy *et al.* [75] find that during the design phase, participants in a BIM project focus
180 predominantly upon clash detections and ignore future-proofing maintenance accessibility. The
181 authors (*ibid*) highlight potential in BIM for designers to explore the background geometry and
182 parametric database and incorporate functions to assist the FMT anticipate and solve maintenance
183 accessibility issues. Similarly, Meadati *et al.* [73] and Motawa and Almarshad [30] propose
184 additional tools to improve BIM performance at the O&M stage by more effectively engaging
185 stakeholders. Longstreet [76] further adds that the value of implementing BIM increases
186 exponentially as a project lifecycle unfolds. This is because BIM value in FM stems from
187 improvements to: current manual processes of information handover; accuracy of FM data;
188 accessibility of FM data; and efficiency increases in work order execution [12]. Consequently, FMT
189 involvement during the BIM development process is essential because the building delivery team can
190 be alerted of any issues related to O&M. Interestingly, Bosch *et al.* [37] contradict this position and
191 conclude that the current added value of BIM in the O&M stage is marginal due to a lack of
192 alignment between the supply of, and demand for, FM related information and the context-dependent
193 role of information. Although this view (*ibid*) is contrary to those stated within the broader academic
194 discourse, it does resonate with Kassem *et al.* [12] who concede that BIM-FM integration represents
195 a major challenge.

196

197 **2.2 INDUSTRY STANDARDISATION AND INTEROPERABILITY**

198 The FM industry standards acknowledge the importance of an organisation's strategic management
199 of its property assets. ISO 55000 (ISO, 2014) for example, is regarded as the principal international
200 document for establishing conformity in asset management, where asset management is defined as
201 the: "*coordinated activity of an organisation to realise value from assets.*" Other emergent standards
202 (which cover building asset maintenance and management) include: PAS 55:2008 published by BSI;
203 ISO 55001 and ISO 55002. Notably, the greatest influx of standardisation occurred between 2010-
204 2014 such as ISO 16739: 2013 (covering industry foundation classes (IFCs)); PAS 1192:1,-5,
205 (covering data format specification), ISO:29481;1, (covering BIM information manual). Importantly,
206 these standards profoundly stress the standardisation of data exchange formats for improved semantic
207 data interoperability. Figure 1 presents an abridged timeline overview of prominent UK and
208 international standards governing FM, alongside the key developments in FM and BIM
209 documentation in the UK. These standards provide coverage of: data management; naming

210 conventions; common data environment; IFCs data management and interoperability; as well as
211 construction information transfer. Construction Operations Building Information Exchange (COBie)
212 standards (published since 2007 in the US and later adopted as British Standard in 2014) help to
213 improve the handover of asset related data via the BIM model to the facility managers and/ or
214 building owners [1,77]. This improvement is achieved by standardisation of data management in
215 COBie for improved interoperability between BIM and CAFM systems [37].

216

217 < Insert Figure 1 Development of BIM and FM standards >

218

219 **2.3 DATA INTEGRATION**

220 Data integration is embedded within the broader concept of interoperability between systems,
221 services or programs [78] and is commonly defined as: “*the combination of data from different*
222 *sources with unified access to the data for its users*” [79]. Inadequate data integration is a constant
223 issue amongst building information modellers because of differences in syntax, schema or semantics.
224 Multiple levels of data interoperability exist. However, out of the six levels of conceptual
225 interoperability, ‘semantic interoperability’ is the one most applied to BIM data integration with
226 other systems. Semantic heterogeneity of data results from different meanings or interpretations of
227 data that may arise from various contexts (*ibid*). Hence, data integration and interoperability are
228 inextricably linked when discussing BIM and other systems that need to integrate with it.

229

230 Data interoperability issues related to integration of BIM data with existing FM systems may be
231 partly resolved through the use of ISO 16739 certification (ISO, 16739).
232 The IFCs specification within ISO 16739 is an open and neutral data file format for data sharing and
233 exchange within construction and FM, affording greater integration between BIM software vendors.
234 IFCs is the only object orientated 3D “*vendor-neutral BIM data format for the semantic information*
235 *of building objects*” [77]. IFCs models have been used as the file format for transferring BIM model
236 data into CAFM tools due to the lack of interoperability between existing CAFM tools and the
237 growing number of commercially available BIM packages [11]. Emerging literature on data
238 integration between BIM and FM shows that software interoperability remains a significant and
239 persistent obstacle [11,80, 81].

240

241 **3.0 BIM AS A FACILITATOR FOR FM EFFICIENCY**

242 Environmental impact and stricter environmental regulations have required the AECO sector to
243 manage resources more efficiently [82]. This includes a building’s O&M costs which far exceed
244 capital expenditures (CapEx) incurred during design and construction [21]. According to Mirjana and

245 Milan [83], the cost of O&M occupies more than 80% in the lifecycle of the building. The global
246 economic crisis has further exacerbated the need for organisations to cut business overheads in
247 response to tighter budgets [82]. Within this climate of financial austerity, BIM has been heralded as
248 a facilitator for improvements in FM efficiency by enhancing the integration of FM related
249 information [82,11,84]. These improvements are accrued during: the generation and management of a
250 facility's digital specification and characteristics data; and cooperation between all parties involved
251 in both building design and operation [20]. Consequently, BIM can overcome some of the
252 complexity and fragmentation experienced within the FM sector [84].

253

254 The effective management of asset maintenance is heavily reliant upon continuous and reliable
255 information on asset inventory, condition and performance [85]. Such non-geometrical information
256 can be gathered and integrated with existing geometrical data retrievable in the BIM environment.
257 This affords ease of access for information retrieval and enhanced visual recognition when locating
258 facility assets [4]. Such measures provide substantial enhancements to traditional methods of
259 managing assets during the O&M phase; case studies of BIM applied to FM have demonstrated
260 palpable long-term benefits for O&M [86, 87]. An early case study observed a 98% reduction in time
261 and resourcing for producing and managing an FM database through BIM [88]. Similarly, the Sydney
262 Opera House case study demonstrates increased efficacy in data consistency, data mining and
263 operating from a single source of information for the FMT [1]. Evidence also reveals how BIM has
264 orchestrated efficient data retrieval and storage, and reduced time and resource spent on finding
265 relevant equipment and building materials information [1,87]. Ding *et al.* [89] further reinforces these
266 findings and reveals that BIM enabled FM witnessed a 98% reduction in time used to update FM
267 databases.

268

269 Implementing BIM in FM also allows asset owners to formulate intelligent decisions on facility
270 related activities, and consequently optimize the outcome [75]. Because BIM facilitates collaboration
271 and information integration during the O&M phases, it is beneficial for processing large sets of
272 complex information typically associated with maintaining building assets [4]. The aggregation of
273 various FM information perspectives requires a high-level integration generated by different
274 stakeholders using multiple sources such as maintenance records, work orders, causes and knock-on
275 effects of failures [90]. It also describes how information flows through three different analysis
276 nodes, namely: legal; technical; and administrative aspects. Each node produces outputs that are
277 influential to others in order to correctly process and interpret data. However, when examining FM
278 holistically and how extensive its information perspectives and disciplines are, it can be argued that
279 three nodes cannot provide universal coverage of all sources of information flow. Given the inherent

280 complexity of facilities and FM maintenance procedures, BIM process adaptation offers exciting
281 opportunities for encapsulating such data for asset maintenance. Future research is needed to further
282 substantiate the potential benefits afforded by BIM-FM integration using real life case-studies [11].
283

284 **3.1 OBSTACLES IN BIM-FM INTEGRATION**

285 As-built BIM models require data updates when maintenance work is conducted to ensure that the
286 most recent asset history data is readily available for the FMT [24]. This movement towards BIM
287 reuse for FM imposes new processes and tasks for the FMT, and represents a challenge for BIM-FM
288 integration (*ibid*). For example, BIM and CAFM integration has been heavily criticized for limited
289 data interoperability, namely the aptitude for transferring appropriate FM semantic data [13], whilst
290 Bosch *et al.* [37] find the benefits of BIM for operations are marginal. Incongruence between the
291 supply of, and demand for, information has also proved to be the key obstacle of BIM-FM
292 integration. Although BIM enables greater data integration, such data is not necessarily presented in
293 a pertinent semantic format for FM [91]. FMT involvement in the design and construction phase
294 could improve interoperability of semantic data and hence the delivery of O&M [75]. COBie has
295 similarly been criticised for its inability to ensure comprehensive semantic data for FM and provide
296 guidance for the design team on sourcing additional operational semantic data for FM [13]. Table 3
297 presents a critical synthesis and evaluation of the benefits derived from BIM-FM integration and the
298 corresponding obstacles reported in the literature.
299

300 <Insert Table 3 Overview of the commonly outlined benefits and corresponding obstacles in the
301 BIM-FM integration>
302

303 Decision making for the O&M of assets directly influences the annual expenditure of buildings [8].
304 However, accurate decision-making is unnecessarily convoluted given disintegration of multiple
305 databases and data formats used [21]. Often decisions derive from various information sources (i.e.
306 historical data, design drawings, inspection records and sensor data) which frequently reside in
307 separate text-based spreadsheets [99]. Decisions based upon their large, textual based, data sets are
308 unintuitive, time consuming and prone to human error (*ibid.*). Moreover, FM is inextricably linked to
309 business operations within a building which vary building-to-building, hence the need for a tailored
310 service [100,18]. The challenge is for BIM to provide strategic decision making for improved
311 maintenance performance - often measured in terms of cost, time, health and safety, functionality and
312 maintainability [101]. Successfully integrated CAFM and BIM systems provide an invaluable source
313 of knowledge capture for existing facilities [102]. Figure 2 demonstrates how functions of existing
314 maintenance processes have been integrated via BIM and CMMS, BIM and CAFM and in BIM

315 Expert systems; it also illustrates that decision support and diagnosis is yet to be achieved using BIM
316 systems or with BIM and CAFM systems.

317

318 <Insert Figure 2 O&M functions mapped with CAFM, CMMS, BIM tools>

319

320 Knowledge capture becomes beneficial for predictive and preventative maintenance where asset
321 information and operation data is accumulated and turned into insights about FM [109,72]. A dearth
322 of studies demonstrate initial concepts of knowledge capture in relation to FM and the growing use of
323 BIM for asset management. Table 4 summarises these studies to provide a foundation for knowledge
324 based predictive maintenance management with BIM. Hassanain *et al.* [110] were the first to propose
325 an IFCs based data model for an integrated maintenance management system. Later, Hassanain *et al.*
326 [109] proposed an object-oriented method for supporting the information exchange between different
327 domains in an FM project which allows the computer applications used by all project participants to
328 share and exchange the project information. For example, using the concept of virtual reality, Chen
329 and Wang [99] developed a 3D visual approach for maintenance management which provides the
330 FMT with component and maintenance information.

331

332 <Insert Table 4 State of the art knowledge based decision tools in FM >

333

334 Lin and Su [64] developed a BIM-based facility maintenance management system for the FMT in the
335 O&M phase – this allows the FMT to access and review 3D BIM models for updating maintenance
336 records in a digital format. The study proved that the structured information handover is fundamental
337 to implementing BIM for FM. Motamedi *et al.* [72] also applied information generated from BIM to
338 detect failure patterns of building components. As IFCs (and model view definitions (MVD) integral
339 within these) are published and maintained by the *buildingSMART* alliance, it is currently supported
340 by circa 150 software applications worldwide and used throughout industry [117]. The
341 interoperability of the IFCs format allows designers, contractors and the FMT to utilize different
342 software through the entire building lifecycle and improve the building’s maintainability. Motawa
343 and Almarshad [30] developed knowledge-based Building Information Modeling (K-BIM) that has
344 been highly advocated in the field of facility management. Unlike the traditional application of BIM,
345 the K-BIM proposed to capture the failure-cause-effect pattern of the component failure and then link
346 to the corresponding elements of the BIM.

347

348 Whilst an influx of innovative, state-of-the-art tools demonstrate knowledge capture, limited
349 evidence exists to substantiate the presence of a systematic feedback loop from the FMT (reporting

350 upon actual- vis-a-vis predicted-building performance) to other relevant stakeholders engaged earlier
351 in the development (e.g. design team members, contractors and other parties within the supply chain).
352 BIM is heralded as a new facilitator for collaboration, however the key beneficiaries of building
353 performance knowledge should not be limited to the FMT in the post occupancy phase. In order to
354 facilitate a CoP that could augment the performance of future building developments, such
355 knowledge is most valuable when fed back to participating stakeholders during the design and
356 construction phases. Optimising the effectiveness of knowledge generated will require existing and
357 future generations of personnel to be fully trained and competent in computer software systems,
358 applications and developments. Figure 3 presents a diagrammatic representation of the potential for a
359 knowledge based feedback loop from BIM and FM data integration. This development could
360 improve interoperability in several key areas. First, data pertaining to a building's operational
361 performance during the O&M phase allows clients to develop optimum strategic maintenance plans.
362 Second, comparison between actual and predicted building performance will allow both designers
363 and contractors to improve the performance of future building developments [13].

364

365 <Insert Figure 3 Potential for the knowledge based feedback loop from BIM and FM integration>

366

367 **4.0 CONCLUSIONS**

368 The extant literature is replete with widespread endorsement for BIM, which is seen to expedite the
369 enhancement in building data management throughout the building's life-cycle. The increased
370 demand for data management due to computerisation within the AECO industry has engendered a
371 shift in existing processes towards more model based collaboration that has impacted upon the way in
372 which buildings are operated and maintained. BIM and computerised FM tools used to manage and
373 operate building asset data are ubiquitous whilst FMT requirements are often unique and bespoke.
374 While some academics expound the virtues of COBie, anecdotal evidence suggests that this one shoe
375 fits all approach is not well received by practitioners – indeed, the general consensus appears to
376 suggest that there is little value in collecting data for the sake of such. Nevertheless, the inherent
377 complexity of FM maintenance procedures presents exciting opportunities for encapsulating rich
378 semantic data within BIM at the earlier stages of the building life cycle (design and construction).
379 This early integration of both geometric and semantic data would prove invaluable to the FMT during
380 building occupancy, particularly with respect to monitoring building performance. In turn, a more
381 accurate measurement of building performance in-use provides a virtual circle and invaluable
382 knowledge based feedback opportunity for designers and contractors to improve the development of
383 future projects commissioned.

384

385 However, efficient utilisation and integration of complex FM semantic data in BIM poses three
386 significant challenges. First, computerisation technology is developing at an exponential pace and
387 hence, training personnel to keep abreast of the latest knowledge and developments can be
388 problematic for industry. Higher education institutes (and other education providers) must collaborate
389 more closely with practitioners to fully embrace the concept of a life-long learner in order to avoid
390 tacit knowledge redundancy within the workforce. Second, there is a lack of alignment in the supply
391 and demand of FM semantic data from project clients, which can also indicate an inadequate
392 understanding in what semantic data is usable or required during the building's life cycle. Realising a
393 solution to this issue will be multifaceted but is likely to include a combination of aspects relating to
394 greater knowledge management, better education during building conception, supported by a robust
395 form of procurement. Third, data within BIM for FM is not fully exploited for the decision support
396 knowledge inherent within it. Therefore the opportunity to enhance a building's performance using
397 rich semantic data is lost. This issue is further exacerbated by gaps in software interoperability when
398 transitioning between as-built BIM and a CAFM system. Subsequently, the broad range of geometric
399 and semantic data embedded in BIM model, points to the potential to augment data analysis and
400 generate accurate knowledge capture and decision making. Opportunities are myriad but include the
401 greater use of plug-ins to meet bespoke client requirements and machine learning algorithms to assist
402 with the collation and interpretation of voluminous data accrued throughout the building's life cycle.

403

404 Future research is however needed to: i) further develop the concepts of, and applied methodological
405 approaches for, knowledge capture in relation to FM and the growing use of BIM for asset
406 management. Such work should aspire to produce tangible commercial products founded upon robust
407 testing by scientific validation; ii) substantiate the potential benefits afforded by BIM-FM integration
408 using real life case-studies as a means of broadening the industrial engagement, collaboration and
409 future participation. To date, case studies of practice-based initiatives are scant or provide
410 rudimentary insight into the myriad of opportunities available to clients and the building's FMT; and
411 iii) conduct comparative analysis between BIM applications within the AECO sector and more
412 technologically advanced industries such as aerospace and automotive. Such analysis may propagate
413 the transference of readily available solutions to challenges reported upon in this paper. Automation
414 within the BIM-FM integration process will revolutionise how buildings are conceived, developed,
415 built and utilised – the challenges and opportunities identified here require innovative solutions to
416 transform industry practice and should be augmented with far greater industry-academic
417 collaboration and education.

418

419 Table 1 FM performance measurement tools

Performance Measurement Tools	Definitions and Attributes	Authors
Post-occupancy evaluation	The evaluation of a building's performance in use by auditing client satisfaction. Implemented at the concluding stage of the design process, this can identify potential system inefficiencies and improve design and procurement for future projects.	[39, 42,43,44,45]
Business excellence model (BEM)	Represents a conceptual framework to measure business performance, using processes based upon cause and effect. More widely accepted and more effective than other types of performance measurement tool.	[33,46,47,48]
Capability maturity model (CMM)	A process maturity framework of five maturity levels (the structural components that comprise the CMM Software), based upon a software development evaluation methodology which has been introduced to other disciplines.	[33,49,50]
Balanced scorecard (BSC)	A semi-standard structured report used by managers to monitor staff activities and any consequences arising from these actions It may include additional perspectives such as service, physical, financial, community, environmental and utilisation. The most popular method of measurement in the FM field.	[33,41,51,52,53,54]
BIFM measurement protocol	Measures the effectiveness of facility management operation in terms of cost and attempts to measure value for money. Aims to resolve the problems resulting from the amorphous range of services covered by FM and represents a first step in the development of standardised facilities management performance measurement.	[13,51,55]
Hierarchical system of performance indicators	Key performance indicators (KPIs) that have intrinsic mutual relationships/ dependencies with other KPIs that are linked through a hierarchal structure.	[56]
Benchmarking and cost of operation	Benchmarking reflects the ethos of promoting continuous improvement, determined from both within and outside the organisation. It is the associated tool used to achieve critical success factors such as operational service efficiency	[57]
Key performance indicators (KPIs)	A performance measure of the success of an organisation or activity in which it engages; performance indicators are seen to deliver a service and are used to select providers of FM; KPIs seek to benchmark industry performance with a view to improving it; results show that there is a relationship between types of maintenance strategy implemented and end user satisfaction. Widely used performance measurement tool in FM.	[23,58,59,60,61]
Input versus output based performance measurement	Seeks to develop standardized performance metrics.	[51,62]
Service balanced scorecard (SBS)	A method for measuring facility performance that encompasses financial and non-financial indicators.	[52]

420 Table 2 Dimensions of BIM

Dimension of Development	Descriptions	Stakeholder Impact
3D	Consists of two and three dimensional model data to represent the building design. 3D BIM can also be defined as: “ <i>geometric presentation, parametric descriptions and legal regulations associated with the construction of a building</i> ” [70]	Design team, supplier
4D (3D + time)	Links scheduling/time related information to the 3D model’s objects in order to sequence the construction process over time. [65]	Contractor, sub-contractor
5D (3D + cost)	Adds cost related information to the 3D model’s elements. This enables early cost estimation and quantity take offs directly from a single 3D file (<i>ibid.</i>).	Quantity surveyor
6D (3D + FM)	Integrates FM and building lifecycle information. 6D is related to asset information useful for facility management processes, but after 5D no general consensus on the dimensions has been reached in the literature (<i>ibid.</i>).	Facility manager, building owner
nD (3D + ...nD)	Other possible dimensions associated with the BIM model.	Can relate to any specified stakeholder.

421


Table 3 Critical overview of commonly outlined benefits associated with BIM and FM integration

Benefit	Results	Authors	Limitations
Increased utility and speed for data retrieval from a centralised BIM model.	Information is more easily shared, can be value-added, and reused.	[26,37,75,92,93,94,98]	Designers do not always know what data is relevant to the FMT, slowing down the process of COBie data drops. Although BIM enables for more data to be added this does not necessarily mean it will be usable during the FM stages. Data is not necessarily presented in a usable format, survey results illustrate that manual input can take up to two years into CMMS after the handover stages.
Enhanced collaboration through BIM processes and modelling.	Built asset proposals can be rigorously analysed across disciplines and organisations. Simulations can be quickly executed and performance benchmarked, enabling improved and innovative solutions	[26,75,94,95,96,98]	Collaboration between building owners and the FMT at the design stages is very limited. Little evidence shows FM related constraints being analysed in BIM. For example, Lavy <i>et al.</i> [75] find that maintenance accessibility tends to be ignored in the design stages although collaboration is facilitated through BIM. Collaboration that is afforded with the design team stakeholders for the design of the building will not necessarily improve upon how that building is to be maintained in the latter stages.
Improved embedded building data in a centralised model.	Requirements, design, construction, and operational information can be used in FM resulting in better management of assets.	[26,73,75,94,95,96]	There are still many limitations with BIM integration into existing CAFM systems; this integration is necessary as not all FM related information is suitable for hosting in a BIM environment. There is also a lack of standardized tools and processes and determining the specific data required remains a key challenge for both the design team members and the building owner.
Visualisation of assets.	The value of 3D visualization eliminates misinterpretation. Navigation of information becomes more fluent in a 3D environment.	[37,94,95]	Locating and navigating in a complex BIM becomes difficult if GIS information or barcoding is not linked with the BIM model.
Longer equipment asset life.	Through better knowledge of existing assets and CAFM integration preparation and planning enables longer asset life.	[26,94,95,97]	The learning process needs to be facilitated during building operations for better knowledge on asset performance. Lindkvist [95] highlighted the necessity of balance between exploration and exploitation of learning in order to shape BIM for maintenance.
More effective space/ move planning.	In depth knowledge on the assets that are fixed or movable means better space movement can be planned and executed.	[26,73,94]	If RFID tags are not used this can limit the accuracy of model data as it is so heavily reliant on precise and up to date information being added by the management team.


423 Table 4 State of the art knowledge based decision tools in FM

Use/Functionality	Methods	Authors	Limitations
3D visual approach for maintenance management	Utilises an external database and OpenGL technology. Virtual facility provides administrators with component and maintenance/ management information	[99]	Requires a substantial amount of manual data input in order to retrieve usable information. No knowledge capture evident.
Roof maintenance management	Proposed IFCs-based data model for integrated maintenance management for roofing systems.	[110]	Lacking integration of network based data, e.g. weather conditions that may impact upon maintenance.
Visualizer	An interactive and graphical, decision-support tool for service life prediction for asset managers.	[111]	Limited in showing how learning can occur for an organisation.
Object-oriented method of asset maintenance management.	Supports information exchange among different domains.	[109]	Does not reveal knowledge capture capacity, merely sets the stage for it.
Decision support for maintenance evaluation and suggestion	A problem-oriented method of diagnosis of human diseases known as Building Medical Record (BMR) adopted for maintenance engineers, and contractors to access information for evaluations and maintenance suggestions.	[112]	No use of BIM data evident
Framework for facilities knowledge mapping	The study reveals the main benefits of knowledge mapping for FM: improvements in decision making process, problem identification and solving by providing quick access to critical information, knowledge gaps and island of expertise.	[113]	This framework does not mention how BIM data could be utilised in knowledge mapping.
Diagnosis of the facility when making decisions	Extension of BMR called Building Diagnosis Navigation System to support on-site managers during the diagnosis of the facility when making decisions about treatment options.	[114]	No use of BIM data evident
Navigational algorithm in BIM for asset management	For effective utility maintenance management of facilities equipped with passive Radio Frequency Identification (RFID).	[115]	Requires RFID tags, and ignores facilities that may simply be using BIM model data linked into existing CAFM or CMMS system.
FM visual analytics system (FMVAS) for failure detection	Knowledge capture for root cause failure detection in FM.	[94,72]	Limited in showing knowledge capture as a method.
Knowledge based FM using BIM (K-BIM)	As constructed information of the facility has the capability for effective and efficient FM and thereby, enhances the competitive advantage of a FM organisation.	[116]	Demonstrates limited learning capacity with K-BIM system (i.e. diagnosis of potential issues).
Case-based reasoning and BIM systems for asset management	An integrated system to capture, retrieve and manage information/ knowledge for the key asset management operation of building maintenance (BM). This aims to establish the concept of Building Knowledge Modelling (BKM).	[30]	Further research needed to show how this platform can be integrated with various CAFM systems.

424 Figure 1 Development of BIM and FM standards





426 Figure 2 O&M functions mapped with CAFM, CMMS, and BIM tools.



427

428

429 Figure 3 Diagrammatic representation of the potential for knowledge based feedback loop from BIM and FM data integration



431 **REFERENCES**

- 432 [1] Eastman, C., Eastman, C.M., Teicholz, P., Sacks, R. and Liston, K. (2011) BIM
 433 Handbook: A Guide to Building Information Modeling for Owners, Managers,
 434 Designers, Engineers and Contractors, John Wiley & Sons, Hoboken. ISBN: 978-0-
 435 470-54137-1
- 436 [2] Dubé, L., Bourhis, A. and Jacob, R. (2005) The Impact of Structuring Characteristics
 437 on the Launching of Virtual Communities of Practice, Journal of Organizational
 438 Change Management, Vol. 18, No. 2, pp. 145-166.
 439 DOI: <http://dx.doi.org/10.1108/09534810510589570>
- 440 [3] Succar, B. (2008) Building Information Modelling Framework: A Research and
 441 Delivery Foundation for Industry Stakeholders, Automation in Construction, Vol. 18,
 442 No.3, pp. 357-375. DOI: <http://dx.doi.org/10.1016/j.autcon.2008.10.003>
- 443 [4] Love, P.E., Matthews, J., Simpson, I., Hill, A. and Olatunji, O.A. (2014) A Benefits
 444 Realization Management Building Information Modeling Framework for Asset
 445 Owners, Automation in Construction, Vol. 37, pp. 1-10. DOI:
 446 <http://dx.doi.org/10.1016/j.autcon.2013.09.007>
- 447 [5] Love, P.E., Simpson, I., Hill, A. and Standing, C. (2013) From Justification to
 448 Evaluation: Building Information Modeling for Asset Owners, Automation in
 449 Construction, Vol. 35, pp. 208-216. DOI:
 450 <http://dx.doi.org/10.1016/j.autcon.2013.05.008>
- 451 [6] Antje Junghans, D., Steenhuizen, D., Flores-Colen, I., Reitsma, A. and Branco Ló, P.
 452 (2014) The Road to Facility Management, Facilities, Vol. 32, No.1/2, pp. 46-57. DOI:
 453 [10.1108/f-09-2012-0072](http://dx.doi.org/10.1108/f-09-2012-0072).
- 454 [7] Codinhoto, R., Kiviniemi, A., Kemmer, S. and da Rocha, C.G. (2013) BIM-FM
 455 Implementation: An Exploratory Investigation, International Journal of 3-D
 456 Information Modeling (IJ3DIM), Vol. 2, No. 2, pp. 1-15. DOI:
 457 <http://dx.doi.org/10.4018/ij3dim.2013040101>
- 458 [8] Demkin, J.A. (2006) The Architect's Handbook of Professional Practice, John Wiley
 459 & Sons, Hoboken, New Jersey. ISBN-13: 978-1118308820
- 460 [9] Mohandes, S., Abdul Hamid, A. and Sadeghi, H. (2014) Exploiting Building
 461 Information Modeling Throughout the Whole Lifecycle of Construction Projects,
 462 Journal of Basic and Applied Scientific Research, Vol. 4, No. 9, pp. 16-27. Available
 463 on-line at:
 464 [http://www.textroad.com/pdf/JBASR/J.%20Basic.%20Appl.%20Sci.%20Res.,%204\(9\)](http://www.textroad.com/pdf/JBASR/J.%20Basic.%20Appl.%20Sci.%20Res.,%204(9)16-27,%202014.pdf)
 465 [16-27,%202014.pdf](http://www.textroad.com/pdf/JBASR/J.%20Basic.%20Appl.%20Sci.%20Res.,%204(9)16-27,%202014.pdf) (Accessed: November, 2016).
- 466 [10] Azhar, S. (2011) Building Information Modeling (BIM): Trends, Benefits, Risks, and
 467 Challenges for the AEC Industry, Leadership and Management in Engineering, Vol.
 468 11, No. 3, pp. 241-252. DOI: [http://dx.doi.org/10.1061/\(ASCE\)LM.1943-](http://dx.doi.org/10.1061/(ASCE)LM.1943-5630.0000127)
 469 [5630.0000127](http://dx.doi.org/10.1061/(ASCE)LM.1943-5630.0000127)
- 470 [11] Becerik-Gerber, B., Jazizadeh, F., Li, N. and Calis, G. (2011) Application Areas and
 471 Data Requirements for BIM-enabled Facilities Management, Journal of Construction
 472 Engineering and Management, Vol. 138, No. 3, pp. 431-442. DOI:
 473 [http://dx.doi.org/10.1061/\(ASCE\)CO.1943-7862.0000433](http://dx.doi.org/10.1061/(ASCE)CO.1943-7862.0000433)
- 474 [12] Kassem, M., Kelly, G., Dawood, N., Serginson, M. and Lockley, S. (2015) BIM in
 475 Facilities Management Applications: A Case Study of a Large University Complex,
 476 Built Environment Project and Asset Management, Vol. 5, No. 3, pp. 261-277. DOI:
 477 <http://dx.doi.org/10.1108/BEPAM-02-2014-0011>
- 478 [13] British Institute of Facilities Management, (2013) Benchmarking: Effective
 479 Performance Management for FM, British Institute of Facilities Management, UK.

- 480 Available on-line at: [file:///C:/Users/pc%20user/Downloads/3benchmarking-effective-](file:///C:/Users/pc%20user/Downloads/3benchmarking-effective-performance-management-for-fm-fmlf.pdf)
481 [performance-management-for-fm-fmlf.pdf](file:///C:/Users/pc%20user/Downloads/3benchmarking-effective-performance-management-for-fm-fmlf.pdf) (Accessed: November, 2016).
- 482 [14] Khosrowshahi, F. and Arayici, Y. (2012) Roadmap for Implementation of BIM in the
483 UK Construction Industry, Engineering, Construction and Architectural Management
484 Vol. 19 No. 6, pp. 610-635. DOI: <http://dx.doi.org/10.1108/09699981211277531>
- 485 [15] Atkin, B. and Brooks, A. (2009) Total Facilities Management, 3rd ed., Wiley and
486 Blackwell, Hong Kong. ISBN-13: 978-1118655382
- 487 [16] Barrett, P. and Baldry, D. (2009) Facilities Management: Towards Best Practice,
488 Blackwell Science, Oxford. ISBN-13: 978-0632050437
- 489 [17] Alexander, K. (2013) Facilities Management: Theory and Practice, Routledge, New
490 York. ISBN-13: 978-0419205807
- 491 [18] McGregor W. and Then, D.S.S. (1999) Facilities Management and the Business of
492 Space, Arnold, London. ISBN-13: 978-0415503129
- 493 [19] Nutt, B. (2004) Infrastructure Resources: Forging Alignments Between Supply and
494 Demand, Facilities, Vol. 22, No. 13/14, pp. 335-343. DOI:
495 <http://dx.doi.org/10.1108/02632770410563031>
- 496 [20] Chotipanich, S. (2004) Positioning Facility Management, Facilities, Vol. 22, No.
497 13/14, pp. 364-372. DOI: <http://dx.doi.org/10.1108/02632770410563086>
- 498 [21] Cotts, D., Roper, K., and Payant, R. (2010) Facilities Management Handbook, 3rd ed.,
499 Amacom, USA. ASIN: B00OVMPMJM
- 500 [22] Lee, J.H., Lee, M.S., Lee, S.H., Oh, S.G., Kim, B.H., Nam, S.H. and Jang, J.S. (2013)
501 Development of Computerized Facility Maintenance Management System Based on
502 Reliability Centered Maintenance and Automated Data Gathering, International
503 Journal of Control and Automation, SERSC, Vol. 6, No. 1, pp. 1-12. Available on-line
504 at: http://www.sersc.org/journals/IJCA/vol6_no1/1.pdf (Accessed: November, 2016).
- 505 [23] Hinks, J. and McNay, P. (1999) The Creation of a Management-by-Variance Tool for
506 Facilities Management Performance Assessment, Facilities, Vol. 17, No. 1/2, pp. 31-
507 53. DOI: <http://dx.doi.org/10.1108/02632779910248893>
- 508 [24] Gu N., Singh V., London K., Brankovic L. and Taylor C. (2008) Adopting Building
509 Information Modeling (BIM) as Collaboration Platform in the Design Industry,
510 CAADRIA 2008: Beyond Computer-Aided Design: Proc. of the 13th Conference on
511 Computer Aided Architectural Design Research in Asia, The Association for
512 Computer Aided Architectural Design Research in Asia (CAADRIA).
- 513 [25] Olatunji, O.A. and Akanmu, A. (2015) BIM-FM and Consequential Loss: How
514 Consequential Can Design Models be? Built Environment Project and Asset
515 Management, Vol. 5, No. 3, pp. 304-317. DOI: [http://dx.doi.org/10.1108/BEPAM-03-](http://dx.doi.org/10.1108/BEPAM-03-2014-0021)
516 [2014-0021](http://dx.doi.org/10.1108/BEPAM-03-2014-0021)
- 517 [26] Teicholz, P. (2013) BIM for Facility Managers, John Wiley & Sons, New Jersey.
518 ISBN-13: 978-1118382813
- 519 [27] Kamara, J., Augenbroe, G., Anumba, C. and Carrillo, P. (2002) Knowledge
520 Management in the Architecture, Engineering and Construction Industry,
521 Construction Innovation, Vol.2, No.1, pp.53-67. DOI:
522 <http://dx.doi.org/10.1108/14714170210814685>
- 523 [28] IBM Corporation (2013) Implementation Guide for Integrated Workplace
524 Management Software, IBM Corporation, US.
- 525 [29] Lin, S., Gao, J. and Koronios, A. (2006) Key Data Quality Issues for Enterprise Asset
526 Management in Engineering Organisations, International Journal of Electronic
527 Business Management (IJEEM), Vol. 4, No. 1, pp. 96-110. Available on-line at:
528 [http://ijeem.ie.nthu.edu.tw/IJEEM_Web/IJEEM_static/Paper-V4_N1/A10-](http://ijeem.ie.nthu.edu.tw/IJEEM_Web/IJEEM_static/Paper-V4_N1/A10-E684_3.pdf)
529 [E684_3.pdf](http://ijeem.ie.nthu.edu.tw/IJEEM_Web/IJEEM_static/Paper-V4_N1/A10-E684_3.pdf) (Accessed: November, 2016)

- 530 [30] Motawa, I. and Almarshad, A. (2015) Case-based Reasoning and BIM Systems for
531 Asset Management, Built Environment Project and Asset Management, Vol.5, No.3,
532 pp. 233-247. DOI: <http://dx.doi.org/10.1108/BEPAM-02-2014-0006>
- 533 [31] Handzic, M. and Durmic, N. (2015) Knowledge Management, Intellectual Capital and
534 Project Management: Connecting the Dots, Electronic Journal of Knowledge
535 Management, Vol. 13, No. 1, pp. 51-61. Available on-line at:
536 <file:///C:/Users/pc%20user/Downloads/ejkm-volume13-issue1-article656.pdf>
537 (Accessed: November 2016).
- 538 [32] Warwick, A. (2015) Study Shows UK Workers Fail to Understand Data Value,
539 Putting Firms at Risk, Vol. 2015, 27 June. Available on-line at:
540 [http://www.computerweekly.com/news/4500250569/Study-shows-UK-workers-fail-](http://www.computerweekly.com/news/4500250569/Study-shows-UK-workers-fail-to-understand-data-value-putting-firms-at-risk)
541 [to-understand-data-value-putting-firms-at-risk](http://www.computerweekly.com/news/4500250569/Study-shows-UK-workers-fail-to-understand-data-value-putting-firms-at-risk) (Accessed: November, 2016).
- 542 [33] Meng, X. and Minogue, M. (2011) Performance Measurement Models in Facility
543 Management: A Comparative Study, Facilities, Vol.29, No. 11/12, pp. 472-484.
544 <http://dx.doi.org/10.1108/02632771111157141>
- 545 [34] Bollinger, A.S. and Smith, R.D. (2001) Managing Organizational Knowledge as a
546 Strategic Asset, Journal of Knowledge Management, Vol.5, No.1, pp. 8-18. DOI:
547 <http://dx.doi.org/10.1108/13673270110384365>
- 548 [35] Marakas, G.M. (1999) Decision Support System in the Twenty First Century, Prentice
549 Hall, Englewood Cliffs. ISBN-13: 978-0137441860
- 550 [36] Uit Beijerse, R.P. (2000) Knowledge Management in Small and Medium-sized
551 Companies: Knowledge Management for Entrepreneurs, Journal of knowledge
552 management, Vol. 4, No. 2, pp. 162-179. DOI:
553 <http://dx.doi.org/10.1108/13673270010372297>
- 554 [37] Bosch, A., Volker, L. and Koutamanis, A. (2015) BIM in the Operations Stage:
555 Bottlenecks and Implications for Owners, Built Environment Project and Asset
556 Management, Vol. 5, No. 3, pp. 331-343. DOI: [http://dx.doi.org/10.1108/BEPAM-03-](http://dx.doi.org/10.1108/BEPAM-03-2014-0017)
557 [2014-0017](http://dx.doi.org/10.1108/BEPAM-03-2014-0017)
- 558 [38] Bhatt G.D. (2001) Knowledge Management in Organizations: Examining the
559 Interaction Between Technologies, Techniques, and People, Journal of Knowledge
560 Management, Vol. 5, No. 1, pp. 68-75. DOI:
561 <http://dx.doi.org/10.1108/13673270110384419>
- 562 [39] Preiser, W.F.E. (1998) Post-occupancy Evaluation, Van Nostrand Reinhold, New
563 York. ISBN-13: 978-1138888326
- 564 [40] British Institute of Facilities Management, (1997) Facilities Management
565 Measurement Protocol, Saffron Walden, Essex.
- 566 [41] Kaplan, R.S. and Norton, D.P. (1992) The Balanced Scorecard: Measures that Drive
567 Performance, Harvard Business Review, Vol. 70, No. 1, p. 71. Available on-line at:
568 <https://hbr.org/2005/07/the-balanced-scorecard-measures-that-drive-performance>
569 (Accessed: November, 2016).
- 570 [42] Cooper, I. (2001) Post-occupancy Evaluation-where Are You?, Building Research &
571 Information, Vol. 29, No. 2, pp. 158-163. DOI:
572 <http://dx.doi.org/10.1080/09613210010016820>
- 573 [43] Egan, J. (1998) Britain, Rethinking Construction: The Report of the Construction
574 Task Force to the Deputy Prime Minister, John Prescott on the Scope for Improving
575 the Quality and Efficiency of UK Construction, Department of the Environment,
576 Transport and the Regions London, London. Available on-line at:
577 [http://constructingexcellence.org.uk/wp-](http://constructingexcellence.org.uk/wp-content/uploads/2014/10/rethinking_construction_report.pdf)
578 [content/uploads/2014/10/rethinking_construction_report.pdf](http://constructingexcellence.org.uk/wp-content/uploads/2014/10/rethinking_construction_report.pdf) (Accessed: November,
579 2016).

- 580 [44] Jaunzens, D., Cohen, R., Watson, M., Maunsell, F. and Picton, E. (2002) Post
581 Occupancy Evaluation – A Simple Method for the Early Stages of Occupancy Usable
582 Buildings. Building Research Establishment (BRE). Available online at:
583 <http://www.google.com.mx/url?sa=t&ret=j&q=&esrc=s&source=web&cd=2&cad=rja&uact=8&ved=0CCQQFjAB&url=http%3A%2F%2Fwww.usablebuildings.co.uk%2Ffp%2FOutputFiles%2FPdfFiles%2FFR4p1POEFYCIBSEpaperOct02.pdf&ei=uEssVISJIYa5yQTUxYcAg&usg=AFQjCNFbc08ccBOxr5gFoTzd42kSnUDfJQ&sig2=UOEuD92kG88ek245v2AX8g&bvm=bv.76477589> (Accessed: November, 2016).
- 588 [45] Zimmerman, A. and Martin, M. (2010) Post-occupancy Evaluation: Benefits and
589 Barriers, *Building Research & Information*, Vol. 29, No. 2, pp. 168-174. DOI:
590 <http://dx.doi.org/10.1080/09613210010016857>
- 591 [46] Bassioni, H.A., Price, A.D. and Hassan, T.M. (2005) Building A Conceptual
592 Framework for Measuring Business Performance in Construction: An Empirical
593 Evaluation, *Construction Management and Economics*, Vol. 23, No. 5, pp. 495-507.
594 DOI: <http://dx.doi.org/10.1080/0144619042000301401>
- 595 [47] European Foundation for Quality Management (1999) Assessing for Excellence: A
596 Practical Guide for Self-Assessment, EFQM. Available on-line at:
597 http://www.flow.de/en/pdf/1203change_e.pdf (Accessed: November, 2016).
- 598 [48] Wongrassamee, S., Simmons, J. and Gardiner, P. (2003) Performance Measurement
599 Tools: The Balanced Scorecard and the EFQM Excellence Model, *Measuring
600 Business Excellence*, Vol. 7, No. 1, pp. 14-29. DOI:
601 <http://dx.doi.org/10.1108/13683040310466690>
- 602 [49] Chrissis, M.B., Konrad, M., Shrum, S. (2003) CMMI Guidelines for Process
603 Integration and Product Improvement, Addison-Wesley Longman Publishing Co., Inc.,
604 Boston. ISBN-13: 978-0321154965
- 605 [50] Paulk, M., Curtis, B., Chrissis M., B. and Weber, C., V. (1993) Capability Maturity
606 Model for Software, *Encyclopedia of Software Engineering*, Technical Report, pp. 3-
607 10. Available on-line at: <https://www.sei.cmu.edu/reports/93tr024.pdf> (Accessed:
608 November, 2016).
- 609 [51] Amaratunga, D., Haigh, R., Sarshar, M. and Baldry, D. (2002) Assessment of
610 Facilities Management Process Capability: A NHS Facilities Case Study,
611 *International Journal of Health Care Quality Assurance*, Vol. 15, No.6, pp.277-288.
612 DOI: <http://dx.doi.org/10.1108/09526860210442047>
- 613 [52] Brackertz, N. and Kenley, R. (2002) A Service Delivery Approach to Measuring
614 Facility Performance in Local Government, *Facilities*, Vol. 20, No. 3/4, pp. 127-135.
615 DOI: <http://dx.doi.org/10.1108/02632770210423885>
- 616 [53] Felice De Toni, A., Fornasier, A., Montagner, M. and Nonino, F. (2007) A
617 Performance Measurement System for Facility Management: The Case Study of a
618 Medical Service Authority, *International Journal of Productivity and Performance
619 Management*, Vol. 56, No. 5/6, pp. 417-435. DOI:
620 <http://dx.doi.org/10.1108/17410400710757123>
- 621 [54] Lohman, C., Fortuin, L. and Wouters, M. (2004) Designing a Performance
622 Measurement System: A Case Study, *European Journal of Operational Research*, Vol.
623 156, No. 2, pp. 267-286. DOI: [http://dx.doi.org/10.1016/S0377-2217\(02\)00918-9](http://dx.doi.org/10.1016/S0377-2217(02)00918-9)
- 624 [55] Varcoe, B.J. (1996) Facilities Performance Measurement, *Facilities*, Vol.14, No.10/11,
625 pp. 46-51. DOI: <http://dx.doi.org/10.1108/02632779610129168>
- 626 [56] Belcher, R.G. (1997) Corporate Objectives, Facilities, Measurement and Use: A
627 University Model, Proc. of the RICS Cobra Conference, Portsmouth, UK.

- 628 [57] Featherstone, P. and Baldry, D. (2000) The Value Of The Facilities Management
629 Function In The UK NHS Community Health- Care Sector, *Facilities*, Vol. 18, No.
630 7/8, pp. 302 – 311. DOI: <http://dx.doi.org/10.1108/02632770010340690>
- 631 [58] McDougall, G., Kelly, J., R., Hinks, J. and Bititci, U., S. (2002) A Review of the
632 Leading Performance Measurement Tools for Assessing Buildings, *Journal of*
633 *Facilities Management*, Vol. 1, No. 2, pp. 142–153. DOI:
634 <http://dx.doi.org/10.1108/14725960310807881>
- 635 [59] Loosemore, M. and Hsin, Y. (2001) Customer-focused Benchmarking for Facilities
636 Management, *Facilities*, Vol. 19, No. 13/14, pp. 464-476. DOI:
637 <http://dx.doi.org/10.1108/EUM0000000006204>
- 638 [60] Marsh, L. and Flanagan, R. (2000) Measuring the Costs and Benefits of Information
639 Technology in Construction, *Engineering Construction and Architectural*
640 *Management*, Vol. 7, No. 4, pp. 423-435. DOI: <http://dx.doi.org/10.1108/eb021164>
- 641 [61] Shohet, I.M., Lavy-Leibovich, S. and Bar-On, D. (2003) Integrated Maintenance
642 Monitoring of Hospital Buildings, *Construction Management & Economics*, Vol. 21,
643 No. 2, pp. 219-228. DOI: <http://dx.doi.org/10.1080/0144619032000079734>
- 644 [62] Heavisides, B. and Price, I. (2001) Input Versus Output-based Performance
645 Measurement in the NHS-the Current Situation, *Facilities*, Vol. 19, No. 10, pp. 344-
646 356. DOI: <http://dx.doi.org/10.1108/EUM0000000005533>
- 647 [63] HM Government (2012) Final Report to Government by the Procurement/Lean Client
648 Task Group, Government Construction Strategy, London. Available at:
649 [https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/61157/](https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/61157/Procurement-and-Lean-Client-Group-Final-Report-v2.pdf)
650 [Procurement-and-Lean-Client-Group-Final-Report-v2.pdf](https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/61157/Procurement-and-Lean-Client-Group-Final-Report-v2.pdf) (Accessed: November,
651 2016).
- 652 [64] Lin, Y.C. and Su, Y.C. (2013) Developing Mobile-and BIM-based Integrated Visual
653 Facility Maintenance Management System, *The Scientific World Journal*. DOI:
654 <http://dx.doi.org/10.1155/2013/124249>
- 655 [65] Aouad, G., Cooper, R., Fu, C., Lee, A., Ponting, A., Tah, J. and Wu, S. (2005) nD
656 Modelling – A Driver or Enabler for Construction Improvement, *RICS Research*
657 *Paper Series*, Vol.5, No.6. Available on-line at: <http://usir.salford.ac.uk/id/eprint/621>
658 (Accessed: November, 2016).
- 659 [66] Kelly G., Serginson, M., Lockley, S., Dawood, N., Kassem, M., (2013) BIM for
660 Facility Management: A Review and a Case Study Investigating the Value and
661 Challenges, *Proc. of the 13th international Conference on Construction Applications*
662 *of Virtual Reality*, London, pp. 30-31.
- 663 [67] Watson, A. (2011) Digital Buildings – Challenges and opportunities, *Advanced*
664 *Engineering Informatics*, Vol. 25, No. 4, pp. 573-581. DOI:
665 <http://dx.doi.org/10.1016/j.aei.2011.07.003>.
- 666 [68] Volk, R., Stengel, J. and Schultmann, F. (2014) Building Information Modeling (BIM)
667 for Existing Buildings — Literature Review and Future Needs, *Automation in*
668 *Construction*, Vol. 38, pp. 109-127. DOI:
669 <http://dx.doi.org/10.1016/j.autcon.2013.10.023>
- 670 [69] The Institution of Civil Engineers, (2015) Leveraging the Relationship Between BIM
671 and Asset Management, Available on-line at:
672 [https://www.ice.org.uk/getattachment/disciplines-and-resources/best-](https://www.ice.org.uk/getattachment/disciplines-and-resources/best-practice/relationship-between-bim-and-asset-management/BIM_Modelling-and-Asset-Management_Position-Paper.pdf.aspx)
673 [practice/relationship-between-bim-and-asset-management/BIM_Modelling-and-](https://www.ice.org.uk/getattachment/disciplines-and-resources/best-practice/relationship-between-bim-and-asset-management/BIM_Modelling-and-Asset-Management_Position-Paper.pdf.aspx)
674 [Asset-Management_Position-Paper.pdf.aspx](https://www.ice.org.uk/getattachment/disciplines-and-resources/best-practice/relationship-between-bim-and-asset-management/BIM_Modelling-and-Asset-Management_Position-Paper.pdf.aspx) (Accessed: November, 2016).
- 675 [70] Jiao, Y., Wang, Y., Zhang, S., Li, Y., Yang, B. and Yuan, L. (2013) A Cloud
676 Approach to Unified Lifecycle Data Management in Architecture, Engineering,
677 Construction and Facilities Management: Integrating BIMs and SNS, *Advanced*

- 678 Engineering Informatics, Vol. 27, No. 2, pp. 173-188. DOI:
679 <http://dx.doi.org/10.1016/j.aei.2012.11.006>
- 680 [71] McArthur, J. (2015) A Building Information Management (BIM) Framework and
681 Supporting Case Study for Existing Building Operations, Maintenance and
682 Sustainability, *Procedia Engineering*, Vol. 118, pp. 1104-1111. DOI:
683 [10.1016/j.proeng.2015.08.450](http://dx.doi.org/10.1016/j.proeng.2015.08.450)
- 684 [72] Motamedi, A., Setayeshgar, S., Soltani, M. and Hammad, A. (2013) Extending BIM
685 to Incorporate Information of RFID Tags Attached to Building Assets, 4th
686 Construction Specialty Conference, May 29 - June 1, 2013, Montréal, Québec, pp.1-9.
- 687 [73] Meadati, P., Irizarry, J. and Akhnoukh, A.K. (2010) BIM and RFID Integration: a
688 Pilot Study, *Advancing and Integrating Construction Education, Research and
689 Practice Second International Conference on Construction in Developing Countries
690 (ICCIDC-II)* August 3-5, 2010, Cairo, Egypt, pp. 570-578.
- 691 [74] HM Government (2013) Building Information Modeling industrial Strategy:
692 Government and industry in partnership, *Government Construction Strategy*, London.
693 Available at:
694 [https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/34710/
695 12-1327-building-information-modelling.pdf](https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/34710/12-1327-building-information-modelling.pdf) (Accessed: November, 2016).
- 696 [75] Lavy, S., Liu, R. and Issa, R.R.A (2014) Design for Maintenance Accessibility using
697 BIM Tools, *Facilities*, Vol. 32, No.3/4, pp.153-159. DOI: [http://dx.doi.org/10.1108/F-
698 09-2011-0078](http://dx.doi.org/10.1108/F-09-2011-0078)
- 699 [76] Longstreet, B., (2010) Finding the Right Solution to Create an As-built BIM of
700 Portland International Airport's Baggage Handling Facility, *Professional Surveyor
701 Magazine*, Oct 2010.
- 702 [77] Volker, T. (2011) Industry Foundation Classes (IFCs): BIM Interoperability Through
703 a Vendor-independent File Format, *A Bentley White Paper*, September 2011.
704 Available at: [http://consultaec.com.au/white-paper-ifc-bim-interoperability-through-a-
705 vendor-independent-file-format/](http://consultaec.com.au/white-paper-ifc-bim-interoperability-through-a-vendor-independent-file-format/) (Accessed: November, 2016).
- 706 [78] Bishr, Y. (1998) Overcoming the Semantic and Other Barriers to GIS Interoperability,
707 *International Journal of Geographical Information Science*, Vol. 12, No. 4, pp. 299-
708 314. DOI: <http://dx.doi.org/10.1080/136588198241806>
- 709 [79] Cruz, I.F. and Xiao, H. (2009) Ontology Driven Data Integration in Heterogeneous
710 Networks, *Complex Systems in Knowledge-based Environments: Theory, Models
711 and Applications*, Springer, Heidelberg, pp. 75-98. ASIN: B00LKDLDYI
- 712 [80] Codinhoto, R., Kiviniemi, A., Kemmer, S., Essiet, U.M., Donato, V. and Tonso, L.G.
713 (2013) BIM-FM Manchester Town Hall Complex, *Research Report 2*, Manchester
714 City Council, University of Salford.
- 715 [81] Ghosh, A. and Chasey, A. (2013) Structuring Data Needs for Effective Integration of
716 Building Information Modeling (BIM) with Healthcare Facilities Management, *ISEC
717 2013 - 7th International Structural Engineering and Construction Conference: New
718 Developments in Structural Engineering and Construction*, pp. 1471-1476. DOI:
719 [10.3850/978-981-07-5354-2-FAM-5-324](http://dx.doi.org/10.3850/978-981-07-5354-2-FAM-5-324)
- 720 [82] Akbarnezhad, A., Ong, K.C.G. and Chandra, L.R. (2014) Economic and
721 Environmental Assessment of Deconstruction Strategies using Building Information
722 Modeling, *Automation in Construction*, Vol. 37, pp. 131-144. DOI:
723 <http://dx.doi.org/10.1016/j.autcon.2013.10.017>
- 724 [83] Mirjana D. and Milan, R. (2013) Facility Management: A Paradigm for Expanding the
725 Scope of Architectural Practice, *International Journal of Architectural Research:
726 ArchNet-IJAR*, Vol. 1, No. 3, pp. 127-139. Available on-line at:
727 <file:///C:/Users/pc%20user/Downloads/43-141-1-PB.pdf> (Accessed: November, 2016).

- 728 [84] Sabol, L. (2008) Challenges in Cost Estimating with Building Information Modeling,
729 IFMA World Workplace. Available on-line at:
730 http://www.dcstrategies.net/files/2_sabol_cost_estimating.pdf (Accessed: November,
731 2016).
- 732 [85] Alvarez-Romero, S.O. (2014) Use of Building Information Modeling Technology in
733 the Integration of the Handover Process and Facilities Management, Worcester
734 Polytechnic Institute, Dissertation.
- 735 [86] The State of Wisconsin (2011) Digital Facility Management Information Handover:
736 Current DSF Practices Industry-wide Movement Future Directions, A Research,
737 Findings and Recommendations Report, Vol. Jul 15. Available at:
738 [ftp://doafpt1380.wi.gov/master_spec/Digital%20FM%20Handover/FM%20Findings
739 &RecRpt.pdf](ftp://doafpt1380.wi.gov/master_spec/Digital%20FM%20Handover/FM%20Findings&RecRpt.pdf) (Accessed: November, 2016).
- 740 [87] UNITEC's Integrated Information System, BIM As An Information Sharing Resource
741 For Facilities Management And Operations, UNITEC, Available on-line at:
742 [https://www.building.govt.nz/assets/Uploads/projects-and-consents/building-
743 information-modelling/nz-bim-case-study-5-unitec.pdf](https://www.building.govt.nz/assets/Uploads/projects-and-consents/building-information-modelling/nz-bim-case-study-5-unitec.pdf) (Accessed: November, 2016).
- 744 [88] Dempsey, J. (2009) A Coast Guard Pilot to Make Better Facility Decisions, Journal of
745 Building Information Modeling, Vol. Fall 26, p26. Available at:
746 https://www.wbdg.org/pdfs/jbim_fall09.pdf (Accessed: November, 2016).
- 747 [89] Ding, L., Drogemuller, R., Akhurst, P., Hough, R., Bull, S. and Linning, C. (2009)
748 Towards Sustainable Facilities Management, Technology, Design and Process
749 Innovation in the Built Environment, Spon Press, London, pp. 373-392.
- 750 [90] Cesarotti, V., Benedetti, M., Dibisceglia, F., Di Fausto, D., Introna, V., La Bella, G.,
751 Martinelli, N., Ricci, M., Spada, C. and Varani, M. (2014) BIM-based Approach to
752 Building Operating Management: A Strategic Lever to Achieve Efficiency, Risk-
753 shifting, Innovation and Sustainability, Proc. Conference: XVIII International
754 Research Society for Public Management (IRSPM) Conference, At Ottawa, Canada.
- 755 [91] Shen, W., Hao, Q., Mak, H., Neelamkavil, J., Xie, H., Dickinson, J., Thomas, R.,
756 Pardasani, A. and Xue, H., (2010) Systems Integration and Collaboration in
757 Architecture, Engineering, Construction, and Facilities Management: A Review,
758 Advanced Engineering Informatics, Vol. 24, No. 2, pp. 196-207. DOI:
759 <http://dx.doi.org/10.1016/j.aei.2009.09.001>
- 760 [92] El-Mekawy, M. and Östman, A. (2010) Semantic Mapping: An Ontology Engineering
761 Method for Integrating Building Models in IFC and CityGML, 3rd ISDE Digital
762 Earth Summit, 12-14 June, Nessebar, Bulgaria.
- 763 [93] Korpela, J. and Miettinen R. (2013) BIM in Facility Management and Maintenance —
764 The Case of Kaisa Library of Helsinki University, Proc. of 29th Annual ARCOM
765 Conference, Reading, UK, pp. 2-4.
- 766 [94] Motamedi, A., Hammad, A. and Asen, Y. (2014) Knowledge-assisted BIM-based
767 Visual Analytics for Failure Root Cause Detection in Facilities Management,
768 Automation in Construction, Vol. 43, pp. 73-83. DOI:
769 <http://dx.doi.org/10.1016/j.autcon.2014.03.012>
- 770 [95] Lindkvist, C. (2015) Contextualizing Learning Approaches Which Shape BIM for
771 Maintenance, Built Environment Project and Asset Management, Vol. 5, No. 3, pp.
772 318-330. DOI: <http://dx.doi.org/10.1108/BEPAM-03-2014-0018>
- 773 [96] Love, P.E., Matthews, J. and Lockley, S. (2015) BIM for Built Asset Management,
774 Built Environment Project and Asset Management, Vol. 5, No. 3, DOI:
775 <http://dx.doi.org/10.1108/BEPAM-12-2014-0062>
- 776 [97] Alwan, Z. and Gledson, B.J. (2015) Towards Green Building Performance Evaluation
777 Using Asset Information Modelling, Built Environment Project and Asset

- 778 Management, Vol. 5, No. 3, pp. 290-303. DOI: [http://dx.doi.org/10.1108/BEPAM-03-](http://dx.doi.org/10.1108/BEPAM-03-2014-0020)
779 [2014-0020](http://dx.doi.org/10.1108/BEPAM-03-2014-0020)
- 780 [98] Parsanezhad, P., and Dimyadi, J. (2014) Effective Facility Management and
781 Operations via a BIM-based Integrated Information System. CIB Facilities
782 Management (CFM) 2014 Conference, Copenhagen, Denmark, pp .8
- 783 [99] Chen, H.M. and Wang, Y.H. (2009) A 3-dimensional Visualized Approach for
784 Maintenance and Management of Facilities, Proc. of ISARC09, pp. 468-475.
- 785 [100] Kincaid, D. (1994) Integrated Facility Management, Facilities, Vol. 12, No. 8, pp. 20-
786 23. DOI: <http://dx.doi.org/10.1108/02632779410062353>
- 787 [101] Talebi, S. (2014) Exploring Advantages and Challenges of Adaptation and
788 Implementation of BIM in Project Life Cycle, 2nd BIM International Conference,
789 BIM Forum Portugal, Lisbon.
- 790 [102] Keraminiyage, K., Amaratunga, R. and Haigh, R. (2004) A Literature Review of
791 Knowledge Management, Facilities Management and Link Between those Two
792 Disciplines, Research Institute for the Built and Human Environment, University of
793 Salford, London.
- 794 [103] Miettinen, R. and Paavola, S. (2014) Beyond the BIM utopia: Approaches to
795 the Development and Implementation of Building Information Modeling,
796 Automation in Construction, Vol. 43, pp. 84-91. DOI:
797 <http://dx.doi.org/10.1016/j.autcon.2014.03.009>
- 798 [104] Sackey, E., Tuuli, M., and Dainty, A. (2014) Sociotechnical Systems Approach to
799 BIM Implementation in a Multidisciplinary Construction Context, Journal of
800 Management in Engineering, Vol. 31, No. 1, A4014005. DOI:
801 [http://dx.doi.org/10.1061/\(ASCE\)ME.1943-5479.0000303](http://dx.doi.org/10.1061/(ASCE)ME.1943-5479.0000303)
- 802 [105] Singh, V., Gu, N. and Wang, X. (2011) A Theoretical Framework of a BIM-based
803 Multidisciplinary Collaboration Platform, Automation in Construction, Vol. 20, No. 2,
804 pp. 134-144. DOI: <http://dx.doi.org/10.1016/j.autcon.2010.09.011>
- 805 [106] Liu, R. and Issa, R. (2012) Automatically Updating Maintenance Information from a
806 BIM Database, International Conference on Computing in Civil Engineering, June
807 2012, pp. 373-380. DOI: 10.1061/9780784412343.0047
- 808 [107] Gnanarednam, M. and Jayasena, S., H. (2013) Ability of BIM to Satisfy CAFM
809 Requirements, Proceedings of the Second World Construction Symposium 2013:
810 Socio-Economic Sustainability in Construction 14 – 15 June, Colombo, Sri Lanka, pp.
811 12-20.
- 812 [108] Rich, S., and Davis, K. H. (2010) Geographic Information Systems (GIS) for Facility
813 Management, Whitepaper, IFMA Foundation, pp. 12-17. Available at:
814 [https://foundation.ifma.org/docs/default-source/Whitepapers/foundation-geographic-](https://foundation.ifma.org/docs/default-source/Whitepapers/foundation-geographic-information-systems-(gis)-technology.pdf?sfvrsn=2)
815 [information-systems-\(gis\)-technology.pdf?sfvrsn=2](https://foundation.ifma.org/docs/default-source/Whitepapers/foundation-geographic-information-systems-(gis)-technology.pdf?sfvrsn=2) (Accessed: November, 2016).
- 816 [109] Hassanain, M.A., Froese, T. and Vanier, D. (2003) Implementation of a Distributed,
817 Model-based Integrated Asset Management System, Journal of Information
818 Technology in Construction, Vol. 8, pp. 119-134. Available on-line at
819 <http://www.itcon.org/2003/10> (Accessed: November, 2016).
- 820 [110] Hassanain, M.A., Froese, T.M. and Vanier, D.J. (2001) Development of a
821 Maintenance Management Model Based on IAI Standards, Artificial Intelligence in
822 Engineering, Vol. 15, No. 2, pp. 177-193. DOI: [http://dx.doi.org/10.1016/S0954-](http://dx.doi.org/10.1016/S0954-1810(01)00015-2)
823 [1810\(01\)00015-2](http://dx.doi.org/10.1016/S0954-1810(01)00015-2)
- 824 [111] Kyle, B.R., Vanier, D.J., Kosovac, B., Froese, T.M. and Lounis, Z. (2002) Visualizer:
825 An Interactive, Graphical, Decision-support Tool for Service Life Prediction for Asset
826 Managers, Proc. 9th International Conference on Durability of Building Materials
827 and Components, Brisbane, pp. 17-20.

- 828 [112] Chang, C.Y., Huang, S.M. and Guo, S.J. (2007) Medical Records for Building Health
829 Management, Journal of Architectural Engineering, Vol. 13, No. 3, pp. 162-171. DOI:
830 [http://dx.doi.org/10.1061/\(ASCE\)1076-0431\(2007\)13:3\(162\)](http://dx.doi.org/10.1061/(ASCE)1076-0431(2007)13:3(162))
- 831 [113] Yasin, F. and Egbu, C. (2010) Exploitation of Knowledge Mapping Benefits in the
832 Facilities Performance Evaluation Process: A Conceptual Framework, Proc. of the
833 26th Annual ARCOM Conference, Association of Researchers in Construction
834 Management, Leeds, UK, pp. 799-808.
- 835 [114] Chang, C.Y. and Tsai, M.D. (2013) Knowledge-based Navigation System for
836 Building Health Diagnosis, Advanced Engineering Informatics, Vol. 27, No. 2, pp.
837 246-260. DOI: [10.1016/j.aei.2012.12.003](http://dx.doi.org/10.1016/j.aei.2012.12.003)
- 838 [115] Costin, A., Shaak, A. and Teizer, J. (2013) Development of a Navigational Algorithm
839 in BIM for Effective Utility Maintenance Management of Facilities Equipped with
840 Passive RFID, ASCE Computing In Civil Engineering, Los Angeles, CA, pp. 653-660.
- 841 [116] Charlesraj, V.P.C. (2014) Knowledge-based Building Information Modeling (K-BIM)
842 for Facilities Management, The 31st International Symposium on Automation and
843 Robotics in Construction and Mining (ISARC 2014), pp. 1-6.
- 844 [117] Wetzels, E.M. and Thabet, W.Y. (2015) The Use of a BIM-based Framework to
845 Support Safe Facility Management Processes, Automation in Construction, Vol. 60,
846 pp. 12-24. DOI: <http://dx.doi.org/10.1016/j.autcon.2015.09.004>
- 847
- 848