

STORING SUNFLOWER SEEDS AND QUALITY LOSSES DURING STORAGE*

Can Burak SISMAN, Lokman DELIBAS

Trakya Univ. Tekirdag Agricultural Faculty, Farm Structure and Irrigation Dept.59030 Tekirdag, Turkey
Tel: +90 282 2931442, Fax: +90 282 2931454, e-mail: cbsisman@tu.tzf.edu.tr

Manuscript received: May 25, 2004; Reviewed: December 16, 2004; Accepted for publication: December 17, 2004

ABSTRACT

In this research, sunflower storage buildings in the Thrace region were examined. Influences of storage condition on product losses were investigated. According to the results of experiments in selected stores, the worst storage conditions and the most quality losses were determined in the concrete store, on the other hand the most suitable conditions and the least losses were determined in model store.

KEY WORDS: storage, sunflower, storage buildings, storage conditions, aeration

*This study was supported by Thrace Univ. Scientific Research Fund

DETAILED ABSTRACT

The aim of storage is to preserve properties of products and their freshness. If suitable storage conditions aren't supplied according to product variety, quality and quantity losses increase. Decreasing this losses is possible with providing suitable storage condition and storage management.

In this study, sunflower storage buildings in the Thrace region were examined. Influences of storage condition on product losses were investigated. The study was conducted in one of the Trace Union's reinforced concrete store, temporary store and a model store having aeration system built specifically for this research in Tekirdag Agricultural Faculty's area. Temperature and relative humidity of the sunflower mass as storage conditions in the stores and moisture content due to its effect on quality parameters, oil content and free fatty acids contents as quality parameters were monitored during the storage. According to the results of experiments in selected stores, the worst storage conditions and the most quality losses were determined in the concrete store, on the other hand the most suitable conditions and the least losses were determined in model store.

INTRODUCTION

Food which is to be both vegetable and animal origin undergoes some changes because of its structures when kept for long time. Therefore, storage or keeping food and food's raw materials without spoiling is vital. The aim of storage is to preserve properties of products and their freshness until marketing or consuming. Storage is done to maintain harvesting quality of products not to improve it [1].

The losses of farm crops because of spoilage, sprouting, warming, insect and mold damages cost millions dollars per year during harvesting, carrying and storing. These losses and spoilage during storage can only be reduced by suitable storage and storage management and this leads to contribute to country economy [2].

Turkey is 9th largest sunflower producer in the world with the average of 843 000 ton the 578 000 ha farm area. However this production covers 50 % of sunflower requirement of Turkey and the remaining part is important 60 % of sunflower production in Turkey (500 000 t) is produced in Thrace region [3]. On the other hand, because of restricted storage possibility in this region and using temporary stores widespreadly leads to quality losses of approximately 10 million US \$ per year [4].

The objective of this study is to investigate the present state of different sunflower storage buildings in Thrace Region, to identify the reason effective for the losses

during the storages and to suggest suitable storage conditions and features of sunflower storage buildings for the Region to minimize the losses.

MATERIAL

The study was carried out in one of the Thrace Union's, which is the state oil production company in Tekirdag, reinforced concrete store (flat store), Yağcı Village temporary store and a model store built specifically for this research in the Agricultural Faculty's area. Sunflower seeds were collected from these stores every month regularly during the three months storage period started from September 2001 and all analysis were done on these samples.

Tekirdag concrete store had total 1526 t capacity with 16 m in width, 48 m in length, 6.4 m in side wall height and 10.4 m in ridge pole height. It was built South-North direction and in the shape of joined (three-pal). Sunflower seeds harvested in 2001 with 7 % moisture content and 3 % foreign material were placed in this store.

Temporary sunflower store in Yağcı village had 1642 t capacity and was settled up in East-West direction. This store was 180 m length, 10 m width and 3.6 m height. During its construction, first soil was compressed, drainage ditches were opened at side of the store and a nylon canvas was spread over the soil. 1.3 m height store walls were formed by stacking sacks full of sunflower one on the top of the other. Sunflowers were heaped between the walls and covered with canvas and then it was tied firmly. Sunflower seeds harvested in 2001 having 6 % moisture content and 3 % foreign material were placed in this store.

A model store having an aeration system and 2 m³ capacity was built and the quality losses in this store were compared to the losses occurred in the existing stores in the region. The floor of the model store was concrete, walls were bricks and plaster. The aeration in the store was done using two ducts on the floor having 1.5x0.1 m cross sectional area as suggested by Hellevang [5] and Proctor [6]. Air flow rate was supplied with a fan having 0.3 m³/min per 2 m³ crop and having 0.2 m diameter as proposed by Hall [2], Hellevang [5], Cloud & Morey [7], Bloome et al. [8], Hofman & Hellevang [9], and Harner et al. [10]. The size of the open area in the roof was 0.75 m² (cross sectional area) as recommended by Hellevang [5], Proctor [6] and Bloome et al. [8]. 830 kg sunflower having 6 % moisture content and 3 % foreign material was placed in this store.

METHODS

Mass temperature and relative humidity as storage conditions and moisture content due to its effect on quality criteria, oil content and free fatty acidity as sunflower quality criteria were determined on the sample collected from each stores during the storage. 3x4x3 factorial experimental design as randomized plot design was applied [11]. Factors in this design were the three stores, four locations and the three months storage period.

Measurements of mass temperature and humidity in the stores were recorded using digital humidity/temperaturemeter instrument weekly as triple replicated at four different points of each stores as recommended by Harrier [12], Thompson & Shelton [13], Noyes et al. [14] and Harner & Hellevang [15]. Temperature and humidity measurements were done at two different points in the center and side of store and also at two different depths, at 25 % and 75 % of the mass depth.

Weather temperature and relative humidity were measured by a termohydrograph and these records regulated when to operate the aeration system in the model store. Aeration was operated as soon as the air temperature was 5°C cooler than that of the mass and was continued until the temperatures became equal. Aeration system was also shut when the relative humidity exceeded 75 % and during the rainy period [5, 7, 12 and 15].

Sunflower samples were taken every month regularly in the stores to determine the quality losses occurred in the stores during storage period. The samples were taken in tree replications from the center and side of the stores and at two different depths, 25 % and 75 % of the mass depths according to Turkish Standarts no 163 related to Taking Sample from Oil Seed (Turkish Standard Institute, 1980) [16]. Partitioned hand probe was used for taking samples.

Analyzes of moisture content, oil content and free fatty acidity in the laboratory were done on the samples. Moisture contents were determined on basis of dry weight. To determined the oil contents Soxhlet method (IUPAC method no: 1.122) was used [17]. Free fatty acidity was determined using titratable acidity in IUPAC method no: 2.201 [17].

The results obtained were evaluated using SPSS and MSTAT computer programs for Variance analysis and Duncan tests.

RESULT AND DISCUSSIONS

Storage Conditions

Changes in the average temperatures and humidities during the storage period were presented in Fig 3.1,

3.2 and 3.3 for concrete, temporary and model stores, respectively.

As seen in Fig 3.1, in general, mass temperature varied with the weather temperature. However, as expected, a quick response to weather temperature was observed in the sides and upper part of the mass in order to meet the heat losses from these parts [6, 9, 18, and 19].

A continuous increase in the humidity of mass in this store from about 82 % to 92 % was recorded (Fig 3.1). This was attributed to the increase in the mass temperature causing to rise in the crop respiration and therefore more damp was released in to the mass [20]. The increase in the humidity more got to side of store and upper part of mass. The reason for the rise in the humidity in these parts is because of the moisture migration that is resulted from temperature differences in the store [1, 19, 20, and 21].

As shown Fig 3.2, generally, temperature of the crops that was put into the place at high temperature in the temporary store reduced. In this period, mass temperature increased as parallel to increasing weather temperature from time to time. In these months, especially temperature of sides and upper part of mass was more affected from weather temperature changes as explained by Hellevang [5], Harner et al. [10], Thompson & Shelton [13] and Hellevang [19] and it reduced.

In generally, mass humidity in temporary store rose steadily and reached 94 % except an abrupt change in the end of September. While the humidity rose in middle of the store, it reduced in the side of the store. This is because of high mass temperature and respiration. An abrupt change in the end of September may be explained by heavy rains during that period. In the second month the storage, a relatively more rise in the humidity of the side and upper part of the store resulted from the moisture migration that was created by the temperature differences in the store as explained by Jones & Shelton [1], Cloud & Morey [7], Harner et al. [10], Thompson & Shelton [13], Hellevang [19] and Hellevang [21].

Temperature of the crops in the model store (Fig. 3.3) decreased gradually from about 32 °C to 14 °C towards the end of the storage. Because of aeration (total 193h), temperature differences occurred between the zones in the store were not significant. Therefore moisture migration in the store in great extent was prevented [1, 5, 7, 10, 19 and 21]. When aeration was stopped, mass temperature rose, but it was decreased again with operating of aeration.

Mass humidity in the model store was reduced to 69 % by aeration which is minimum value observed during the storage. After than, mass humidity rised until 81 % for not operating the aeration due to rainy.

In this part, temperature and humidity values were evaluated statistically separately, in order to determine differences between stores (Table 3.1, Table 3.2 and Table 3.3).

As seen in Table 3.1, the most suitable storage conditions with 25.28 °C temperature and 73.78 % humidity was obtained in the model store and the most unfavorable conditions with 36.02 °C temperature and 86.77 % humidity was obtained in concrete store.

These differences between stores clearly show the effect of aeration done in the model store. The temporary store is better than concrete store for short period of storages, because temporary store was quickly affected from decreasing weather temperature during the storage as expressed by Harner et al. [10], Brooker et al. [18] and Hellevang [22].

When the temperature of the zones within the stores were compared (Table 3.2), variations between upper middle part and other zones of the mass for the model store, between side and middle zone for the temporary store and among all zones for the concrete store were observed. In the same way, when the zones of the mass were compared in terms of humidity, while there were not any differences between zones for the model store, statistically significant differences between side and middle zone of the temporary store and between lower middle zones and other zones in the concrete store were determined. According to these results, it may be concluded that moisture migration due to the temperature and humidity variations in the mass, could be prevented in the model store while it was not possible in the temporary and the concrete stores.

When the stores were compared in terms of storage period, a continuous decrease in the mass temperatures of the model and temporary store during the storage period was seen because of lower weather temperature. However in the concrete store the temperature increased during the first month and then increased until the end of the storage. Warming up in the concrete store in the first month is resulted from lack of aerating and crop respiration. While mass humidity decreased in the model store because of aerating in the first month, it raised for temporary and concrete stores.

Sunflower Quality Criteria

Moisture Content

Moisture content is one of the most important criteria effective on the losses during storage. Therefore, moisture contents of sunflower samples taken regularly from the stores were determined and changes in the moisture contents with time during the storage were presented in

Fig 3.4.

With the decreasing weather temperature from October, while the moisture content in the lower part of the mass decreased, it increased about 9.7 % in the upper part of the mass in response to the moisture migration created by the temperature variations in the mass. Moisture content of the crop in the store exceeded 8 % which was recommended level by Hofman & Hellevang [9], Harrier [12], Brooker et al. [18], Hellevang [19] and Patterson [20].

Moisture contents in the temporary store continuously increased throughout the storage period. This increase was more in the upper part of the mass when compared with the bottom. Moisture content in the second month of the storage continued to increase and it especially raised more in the sides of the store. The highest moisture content during storage was determined as 9.2 % in this zone. This was because of moisture migration. Moisture content in this store exceeded 8 % suggested for safely storage by Hofman & Hellevang [9], Harrier [12], Brooker et al. [18], Hellevang [19] and Patterson [20].

Unlike other stores, moisture contents of sunflowers in the model store decreased because the relative humidity of the fresh air entering into the store by ventilation was below 75 %. Moreover, the moisture accumulation due to the respiration was removed by ventilation.

The result of Duncan tests on moisture contents in the stores were given in Table 3.4. According to Duncan test (Table 3.4), while moisture content in the model store decreased by 0.075 %, it increased in the other stores and the highest increase was recorded in the temporary store by 0.902 %. Decreasing moisture content in the model store resulted from aeration.

When the zones in the stores were compared, it was seen that the highest decrease in the moisture content was observed in the model store in upper side of the mass and in side of store; on the other hand the highest increase in the concrete and temporary stores was in upper side of the mass.

End of the storage, moisture contents of model store decreased 0.16 % and while it increased in concrete and temporary stores. Especially in the temporary stores, moisture content increased by 2.04 % because it was influenced much by the outside air condition of these stores [10, 22]).

Oil Content

Changes of oil contents, which is the most important feature of sunflowers, was determined by analyzes that was regularly done on the samples taken from stores and changes in the oil contents with time were presented in Fig 3.5.

Oil contents in the concrete store were continuously decreased during the storage. The oil content of 43.5 % at the beginning decreased approximately 0.5 %. This loss in the first month was higher in the middle part of the store. This is because of high temperature and moisture content of the crops in these zones. In the second month of the storage, oil contents decreased 0.7 % and 2.8 % in middle of the store and in side of the store, respectively. This decrease was due to 9.7 % moisture content in side of store suddenly.

Oil contents in temporary store were continuously decreased during the storage and in the first month, this decrease was 0.3 %. In the second month, oil content in the sides of the store and in the bottom of the mass reduced more. A considerable decrease in these zones was resulted from the high moisture content in the sides and high temperature in the bottom zones.

According to Fig 3.5, oil content in the model store continuously decreased during the storage, but relatively less losses occurred in this store when compared with the others due to temperature and humidity which is lower than 8 %, suggested for a safe storage [5, 6, 12, 18 and 19].

Duncan tests done to compare oil contents changes during the storage were given in Table 3.5, respectively. According to the Duncan test (Table 3.5), model store gave the best result with 0.271 % decrease in the oil content and the worst result was obtained for concrete store with 0.889 % decrease. The highest oil loss in the concrete store was caused by mass temperature and humidity in this store higher than other stores.

When the zones in stores were investigated, there were differences between the middle upper side zones of the mass and other zones in the model store and between all zones in the temporary and concrete stores. Because of being the same amount of oil losses between the zones in the model store statistically, it can be concluded that temperature and humidity distributions was homogeneous. A significant amount of oil losses in bottom zones of the temporary store was determined. Higher temperature in bottom zones of temporary store caused more lost in the oil content. In the concrete store, oil losses in the sides of the store were found to be more than that of the other zones because of higher temperature and moisture content within these zones.

Oil contents in all stores decreased during the storage. In the end of the storage, while the concrete store gave worst result with 2.167 % oil losses, the model store gave best result with 0.52 % losses.

Free Fatty Acidity

Free fatty acidity which affects losses occurred during the

refinement was determined by analysis that was regularly done on the sample taken from the stores and changes in the free fatty acidity with time were presented in Fig 3.6.

Free fatty acidity of sunflowers in the stores continuously increased during the storage. In the concrete stores, free fatty acidity in sides of store and undersides of the mass were higher than in the middle of the store and in the upper side of the mass. High temperature and humidity in undersides of the mass caused to increase in the free fatty acidity. Nas et al. [23] explained that increase in the temperature and humidity caused to spoil of oil and increasing of free fatty acidity.

In the temporary store, free fatty acidity increased more in the upper part of the mass. Increased moisture content owing to the moisture migration in upper part of the mass caused to increasing in the free fatty acidity in this zone. Acidity in the upper parts of mass increased by 0.55 %.

The increase in the free fatty acidity in the model store was less than in the other stores. The increase in the acidity in the upper part of the mass near the walls was more than in the other zones. High temperature in this zone during the first month of the storage caused this increase in the acidity.

Duncan tests to determine the differences between the stores was given in Table 3.6. Among the stores, least acidity change appeared in model store with 0.062 % and this was followed by the temporary store with 0.075 % and the concrete store with 0.215 %. Relatively higher temperature and humidity in the concrete store caused to more increase when compared with the other stores in the acidity.

When the acidity differences among the zones in the stores were considered (Table 3.6), it can be seen that the acidity change in the upper part of the mass near the walls of model store differed from the other zones and for temporary store, change in the sides of the store deviated from the middle and for the concrete store, changes in whole zones varied from each other. The results imply that while the homogeneous storage conditions in the model store were created, worst storage condition prevails in the concrete store.

The least free fatty acidity in the stores during the storage was determined at beginning of the storage and acidity continuously increased in all stores. In the end of the storage, the free fatty acidity increased and reached 0.13 % for the model store, 0.15 % for the temporary store and 0.41 % for the concrete store. Acidity increases in the concrete store was three times more than the other stores.




Figure 3.1. Changes in the temperature and humidity in the concrete store during the storages




Figure 3.2. Changes in the temperatures and humidities in the temporary store during the storages




Figure 3.3. Changes in the temperature and humidity with time in the model store

STORING SUNFLOWER SEEDS AND QUALITY LOSSES DURING STORAGE




Figure 3.4. Change in moisture content of sunflower samples.




Figure 3.5. Change in oil content of sunflower samples.




Figure 3.6. Changing of free fatty acidity of sunflower samples

Table 3.1. Duncan test results related to storage conditions in the stores

Store	Store	Avarage	Standard Error	Duncan* 0.01
Temparature	Model	25.280	0.098	A
	Temporary	29.269	0.098	B
	Concrete	36.023	0.098	C
Mass Humidity	Model	73.784	0.184	A
	Temporary	81.226	0.184	B
	Concrete	86.774	0.184	C

* Significant at 0.01 confidence level

Table 3.2. Duncan test results related to storage conditions in the stores

Store *Zone	Store	Zone	Avarage	Standard Error	Duncan* 0.01
Sıcaklık	Model	Midle 0.25	25.603	0.196	B
		Midle 0.75	25.223	0.196	AB
		Side 0.25	24.790	0.196	A
		Side 0.75	25.503	0.196	AB
	Temporary	Midle 0.25	30.520	0.196	D
		Midle 0.75	30.630	0.196	D
		Side 0.25	28.166	0.196	C
		Side 0.75	27.760	0.196	C
	Concrete	Midle 0.25	34.537	0.196	E
		Midle 0.75	36.807	0.196	G
		Side 0.25	35.473	0.196	F
		Side 0.75	37.273	0.196	G
Mass Humidity	Model	Midle 0.25	74.120	0.369	A
		Midle 0.75	74.133	0.369	A
		Side 0.25	73.577	0.369	A
		Side 0.75	73.307	0.369	A
	Temporary	Midle 0.25	81.218	0.369	BC
		Midle 0.75	82.073	0.369	C
		Side 0.25	80.233	0.369	B
		Side 0.75	81.380	0.369	BC
	Concrete	Midle 0.25	86.037	0.369	D
		Midle 0.75	88.600	0.369	E
		Side 0.25	85.563	0.369	D
		Side 0.75	86.897	0.369	D

* Significant at 0.01 confidence level

STORING SUNFLOWER SEEDS AND QUALITY LOSSES DURING STORAGE

Table 3.3. Duncan test results related to storage conditions in the stores

Store*Period	Store	Period	Avarage	Standard Error	Duncan* 0.01
Temperature	Model	September	32.213	0.170	D
		October	26.140	0.170	C
		November	17.488	0.170	A
	Temporary	September	35.625	0.170	F
		October	31.820	0.170	D
		November	20.362	0.170	B
	Concrete	September	35.113	0.170	EF
		October	38.165	0.170	G
		November	34.790	0.170	E
Mass Humidity	Model	September	75.738	0.319	C
		October	70.482	0.319	A
		November	75.133	0.319	BC
	Temporary	September	74.125	0.319	B
		October	79.843	0.319	D
		November	89.710	0.319	G
	Concrete	September	82.550	0.319	E
		October	85.540	0.319	F
		November	92.232	0.319	H

* Significant at 0.01 confidence level

Table 3.4. Duncan test results of changing moisture content in the stores

Store	Store		Avarage	Standard Error	Duncan* 0.01
Moisture Content Changing Store *Zone	Model		-0.075	0.005	A
	Temporary		0.902	0.005	C
	Concrete		0.563	0.005	B
Moisture Content Changing Store*Period	Model	Zone			
		Middle 0.25	-0.086	0.011	C
		Middle 0.75	-0.167	0.011	B
		Side 0.25	-0.223	0.011	A
		Side 0.75	0.173	0.011	D
		Middle 0.25	1.140	0.011	I
	Temporary	Middle 0.75	0.730	0.011	H
		Side 0.25	1.177	0.011	I
		Side 0.75	0.563	0.011	G
	Concrete	Middle 0.25	0.460	0.011	F
		Middle 0.75	0.187	0.011	D
		Side 0.25	1.357	0.011	J
	Side 0.75	0.247	0.011	E	
Moisture Content Changing Store*Period	Model	September	0	0.009	C
		October	-0.062	0.009	B
		November	-0.165	0.009	A
	Temporary	September	0	0.009	C
		October	0.660	0.009	D
		November	2.047	0.009	F
	Concrete	September	0	0.009	C
		October	0.647	0.009	D
		November	1.040	0.009	E

* Significant at 0.01 confidence level

Table 3.5. Duncan test results relating to changing oil content in the stores

Store	Store		Avarage	Standard Eror	Duncan* 0.01
Oil Content	Model		-0.271	0.007	A
Changing	Temporary		-0.387	0.007	B
	Concrete		-0.889	0.007	C
Store *Zone	Store	Zone			
		Middle 0.25	-0.350	0.013	B
	Model	Middle 0.75	-0.217	0.013	A
		Side 0.25	-0.250	0.013	A
		Side 0.75	-0.267	0.013	A
		Middle 0.25	-0.217	0.013	A
Oil Content	Temporary	Middle 0.75	-0.483	0.013	D
Changing		Side 0.25	-0.400	0.013	C
		Side 0.75	-0.450	0.013	D
		Middle 0.25	-0.567	0.013	E
	Concrete	Middle 0.75	-0.667	0.013	F
		Side 0.25	-1.133	0.013	G
		Side 0.75	-1.189	0.013	H
Store*Period	Store	Period			
	Model	September	0	0.011	A
		October	-0.287	0.011	B
		November	-0.525	0.011	D
		September	0	0.011	A
Moisture	Temporary	October	-0.375	0.011	C
Content		November	-0.787	0.011	E
Changing		September	0	0.011	A
	Concrete	October	-0.500	0.011	D
		November	-2.167	0.011	F

* Significant at 0.01 confidence level

Table 3.6. Duncan test results relating to changing free fatty acidity in the stores

Store	Store		Avarage	Standard Eror	Duncan* 0.01
Acidity	Model		0.062	0.003	A
Changing	Temporary		0.075	0.003	B
	Concrete		0.215	0.003	C
Store *Zone	Store	Zone			
		Middle 0.25	0.043	0.006	A
	Model	Middle 0.75	0.056	0.006	AB
		Side 0.25	0.093	0.006	D
		Side 0.75	0.056	0.006	AB
		Middle 0.25	0.066	0.006	ABC
Acidity	Temporary	Middle 0.75	0.066	0.006	ABC
Changing		Side 0.25	0.080	0.006	BCD
		Side 0.75	0.086	0.006	CD
		Middle 0.25	0.147	0.006	E
	Concrete	Middle 0.75	0.180	0.006	F
		Side 0.25	0.253	0.006	G
		Side 0.75	0.280	0.006	H
Store*Period	Store	Period			
	Model	September	0	0.006	A
		October	0.057	0.006	B
		November	0.130	0.006	C
		September	0	0.006	A
Acidity	Temporary	October	0.075	0.006	B
Changing		November	0.150	0.006	C
		September	0	0.006	A
	Concrete	October	0.228	0.006	D
		November	0.417	0.006	E

* Significant at 0.01 confidence level

CONCLUSION

In this study conducted in the Thrace Region, influences of storage conditions on the quality losses occurred during storage of different storage buildings used for sunflower was investigated. According to the results of experiments in the selected stores, the worst storage conditions and the highest quality losses were determined in the concrete store, on the other hand the most suitable conditions and the least losses were determined in the model store.

Creating suitable storage conditions to reduced losses in the concrete store which was recommended for sunflower storage in the previous study by Gaytancıoğlu [4] is not possible for the present situation. The biggest problem in this store may be prevented by increasing temperature and humidity in the store due to lack of aeration and increase in structural spoilages in the crop and losses created by insects.

Although results of temporary store was better than concrete store, in the temporary store, recommended suitable storage conditions is difficult to achieve and to maintain sunflowers quality features [12, 19, 22 and 24]. Temperature differences and moisture migration in the store were not prevented because the store was quickly affected by the outside conditions and rain entering into the store during rainy periods.

Storage conditions in the model store were kept under the 17 °C temperature and 75 % relative humidity which were proposed for safe storage during autumn [1, 7, 13, 19 and 21]. Maintaining suitable storage conditions decreased the sunflower quality losses and losses in the controlled store was less than in the other stores.

Points that should be taken into consideration for sunflower storage were given as below:

Temporary storage widely used in The Thrace region because of low construction and operating costs can be used for durations less than five months in Autumn when the weather temperature decreases continuously. However these stores must be unloaded before Spring while weather temperature increases. These stores should not be used in the districts having much rain.

Present concrete stores in this region must be improved and first of all aeration system must be constructed. Aeration system which will be established in the concrete stores is founded easily with fans located on short side wall in the store and perforated ducts settled on floor. Fan capacity, air velocity, cross sectional area of ducts and duct arrangement, size of open area in the roof, how much and when will be done aeration are important.

Cross sectional area of ducts and capacity of selected fans are determined depending on

store capacity and airflow rate must be supplied minimum 0.08 m³/min and maximum 0.8 m³/min for each cubic meter crop [7, 8, 9, 19 and 22]. Cross sectional area of ducts and perforated surface area should carry to this airflow rate. Air velocity in the ducts must be 0.2-10 m/s. Fans must place on walls to dominating wind direction for pressure fans and place on walls to across dominating wind direction for sucking fans.

Especially aeration system should be operated in autumn and spring months and mass temperature must be kept at 17-18 °C during this month and 0-5 °C in winter [12, 19, 22, and 24]. Aeration system in the winter should be run periodically for a day or two during good weather when the outside temperature is near the temperature of the crops. Aerating of sunflower storage for Thrace region is adequate 200-210 h for autumn, 140-150 h for spring.

Time of aeration must be determined according to the temperature measurement in the store. When regional or completely warming occurs in the store, aeration system must be operate and mass must be cooled. Temperature measurement in the store must be done as weekly in spring and monthly in winter for different zones and depths. When relative humidity of outside air is higher than 75 %, aeration must be closed and especially fans and chimneys must be covered on rainy days.

Maximum moisture content for storage of sunflowers is less than 9 % for storage period shorter than six months and 8 % for storage period longer than six months [2, 9, 12, 15, 18, 19, 20 and 22].

REFERENCES

- [1] Jones D; Shelton P (1994). Management to Maintain Stored Grain Quality. Nebraska State Univ. Cooperative Extension Service, Institute of Agriculture and Natural Resources, G 94-1199-A, USA.
- [2] Hall C W (1980). Drying and Storage of Agricultural Crops. The AVI Publishing Company Inc. ISBN 0-87055-364-X, USA.
- [3] Anonymous (2002). Tarımsal Yapı (Üretim, Fiyat, Değer) 2000. T.C. Başbakanlık Devlet İstatistik Enstitüsü, Yayın No: 2547, Ankara.
- [4] Gaytancıoğlu O (1999). Ayçiçeğinde Uygulanan Tarım Politikaları ve Depolamadan Doğan Ürün Kayıplarının Ekonomik Analizi. Yayınlanmamış.
- [5] Hellevang K J (1990). Crop Storage Management. NDSU. Extension Service, ND 58105-AE-791, North Dakota, USA.
- [6] Proctor D L (1994). Grain Storage Techniques Evolution and Trends in Developing Countries. FAO Agricultural Service Bulletin No 109, ISBN 92-5-

103456-7,Roma.

[7] Cloud H A; Morey R V (1991), Management of Stored Grain with Aeration, University of

Minnesota. Collage of Agricultural Food and Enviromental Science, FO 1327-GO, USA.

[8] Bloome P; Brusewitz G; Harp S (1995). Aeration and Cooling of Stored Grain. Oklahoma State Univ. Cooperative Extension Service, Division of Agricultural Science and Natural Resource, F-1101, Oklahoma.

[9] Hofman V L; Hellewang K J (1997). Harvesting Drying and Storage of Sunflower. Sunflower Technology and Production, American Society of Agronomy, Soil Science Society of American, Agronomy Monograph No 35, Madison, USA.

[10] Harner J P; Herrman T J; Reed C (1998). Temporary Grain Storage Considerations. Kansas State Univ. Agricultural Experiment Station and Cooperative Extension Service, MF 2362, Kansas.

[11] Soysal M İ (2000). Biometrinin Prensipieri. T.Ü. Tekirdağ Ziraat Fak. Yayın No: 74, Tekirdağ.

[12] Harrier J P (1987). Drying and Storing Sunflowers. Kansas State Univ. Cooperative Extension Service, Ag. Facts 158, Kansas.

[13] Thompson T L; Shelton D P (1993). Aeration of Stored Grain. Nort Dakota State Univ. Extension Service, G84-692, USA.

[14] Noyes R T; Clary B L; Cuperus G W (1998). Maintaining Quality of Stored Grain by Aeration. Oklahoma State Univ. Extension Service Division of Agricultural Science and Natural Resources, USA.

[15] Harner J P; Hellevang K (1999). High Plains

Sunflower Production Handbook. Kansas State Univ. Agricultural Experiment Station and Extension Service, MF 2384.

[16] Ekmeklier H Y; Geçit H H (1986). Tarla Ürünleri Standardizasyonu ve Depolanması Uygulama Klavuzu. Ankara Üniv. Ziraat Fakültesi Yayınları No: 989, Ankara.

[17] Anonymous (1987). International Union for Pure and Applied Chemistry, Standard Methods of Analysis for the Analysis of Oil. Fats and Derivatives, 7th. End., Blacwell, Jevent Publishers, Oxford.

[18] Brooker D B; Arkema F B; Hall C W (1992). Drying and Storage of Grains and Oilseeds. An AVİ Book, Published by Van Nostrand Reinhold, ISBN 0-442-20515-5, New York

[19] Hellevang K J (2000). Storing Wet Sunflower. Irrigator's Workshops, Bismarck Radisson Inn. 4 Decenber 2000.

[20] Patterson H B W (1989). Handiling and Storage of Oilseed, Oils, Fats and Meal. Elsevier Applied Science, 294 p., NewYork.

[21] Hellevang K J (1995), Grain Moisture Content Effects and Management. NDSU. Extension Service AE-905, North Dakota.

[22] Hellevang K J (1998). Temporary Storage of Sunflower Seed. The Sunflower Magazine, Septenber, National Sunflower Association.

[23] Nas S; Gökalp H Y; Ünsal M (1998). Bitkisel Yağ Teknolojisi. Pamukkale Üniv. Mühendislik Fak. Ders Kitapları Yayın No 005, 329s, Denizli.

[24] Anonymous (1995). Drying and Storage Sunflower Production. NDSU Extension Service, Agricultural Experiment Station, EB 25, USA.