

Copyright is owned by the Author of the thesis. Permission is given for a copy to be downloaded by an individual for the purpose of research and private study only. The thesis may not be reproduced elsewhere without the permission of the Author.

THE EFFECT OF LAND DISPOSAL OF DAIRY FACTORY
WASTES ON SOIL PROPERTIES

A thesis presented in partial fulfilment of
the requirements for the degree of
Master of Agricultural Science in Soil Science
Massey University

Keith William McAuliffe

1978

ABSTRACT

Many New Zealand dairy factories dispose of their wastewater by spray irrigating onto pasture. Little is known, however, about the effects of this disposal on soil properties. Research was undertaken at three pasture disposal sites in order to determine whether certain soil property changes may have occurred as a result of the wastewater treatment. Of particular interest were those properties related to water movement.

Laboratory studies using 'undisturbed' soil cores indicated that dairy factory wastewater can impede soil water movement. A single application of simulated whey effluent resulted in approximately a 50% decrease in saturated hydraulic conductivity (K) within two days. This reduction was observed to be caused by a combination of both physical and biological blockage processes. With repetitive doses of effluent a K decrease of over 99% was induced in some cores. Several cores, particularly those containing earthworms, showed signs of recovery, and in some cores the final hydraulic conductivity value was greater than the initial value.

Analyses of soil samples from the disposal and control sites at Te Rehunga and Tokomaru suggest that fifteen years of wastewater irrigation have resulted in marked changes in soil physical, chemical and biological properties. Total carbon and nitrogen levels were found to be significantly higher at the disposal site; for the Te Rehunga site, the differences in the organic matter level down to 600mm represented an increase of 250 000 kg ha⁻¹.

Water balances for the Te Rehunga and Longburn sites indicate that, in the absence of wastewater, pasture is likely to be water stressed on average for approximately forty days per year. The water balance also shows that deep percolation will be greatly increased by the wastewater application. The period of maximum deep percolation loss is likely to be September to October at both the Te Rehunga and Longburn disposal sites.

The major site management problems encountered at the disposal sites examined occurred as a result of poor soil drainage, pasture burning and pasture pulling. An infiltration problem was observed at the Longburn site and the recently established disposal site at Tokomaru, with two major causes of the low infiltration rate appearing to be blockage from the effluent and pugging; these observations illustrate the need for controlling the effluent application rate, the suspended solids level in the wastewater, and the stock grazing pattern, in order to minimise site drainage problems. A drainage problem over the winter-spring period at Te Rehunga was due to a high groundwater table. Pasture burning was observed at all three disposal sites. The pasture pulling problem at Te Rehunga is the only cited example of such a problem occurring at a dairy factory disposal site.

Observations made at the established Te Rehunga and Tokomaru disposal sites show that long term spray irrigation of dairy factory wastewater can occur without inducing undesirable soil property changes. It appears as though considerable benefit can be gained from the wastewater irrigation, particularly in reducing the incidence of water stress in the pasture and decreasing the requirement for fertilizer.

ACKNOWLEDGEMENTS

I wish to express my thanks to my supervisors, Dr Dave Scotter, Dr Neil Macgregor and Kevin Earl for their guidance and friendship during all stages of my work. I would also like to thank the Dairy Research Institute for financial assistance throughout my work. Thanks also to Mr Lindsay Jamieson for assistance and advice with the illustrations.

To my wife Amanda, thanks for the encouragement given throughout my masterate.

For the typing I wish to thank Judy McKegg.

TABLE OF CONTENTS

	Page
ABSTRACT	(i)
ACKNOWLEDGEMENTS	(iii)
TABLE OF CONTENTS	(iv)
LIST OF FIGURES	(x)
LIST OF TABLES	(xiv)

CHAPTER ONE

INTRODUCTION	1
------------------------	---

CHAPTER TWO

SITE DESCRIPTIONS	6
2.1 The Te Rehunga Disposal Site	6
2.2 The Longburn Disposal Site	6
2.3 The Tokomaru Disposal Site	6
2.4 The Tokomaru Silt Loam	7
2.5 The Manawatu Silt Loam	7

CHAPTER THREE

METHODS OF SOIL ANALYSIS	8
3.1 Determination of Soil Physical Properties	8
3.1.1 Bulk density	8
3.1.2 Particle density	8
3.1.3 Water retention properties of the soil	8
3.1.4 Laboratory measurement of hydraulic conductivity	9
3.1.5 Field measurement of infiltration	11
3.1.6 Dye tracing of soil macropores	11
3.2 Determination of Soil Chemical Properties	11
3.2.1 Organic carbon	11
3.2.2 Total nitrogen	12
3.2.3 Ammonium and nitrate	12
3.2.4 Mineralisable nitrogen	12

	Page
3.2.5 Plant-available phosphorus	13
3.2.6 Soil pH	13
3.3 Determination of Soil Biological and Microbiological Properties	13
3.3.1 Soil microbial respiration	13
3.3.2 Earthworm numbers	16
3.4 Determination of Effluent Properties	16
3.4.1 Total and suspended solids	16
3.4.2 Electrical conductivity	16
3.4.3 Carbohydrate	16
3.4.4 Simulation of whey effluent	17
CHAPTER FOUR	
SOIL WATER BALANCE STUDIES	18
4.1 Introduction	18
4.2 Procedure for the Construction of the Basic Soil Water Balance	19
4.3 Results and Discussion	21
CHAPTER FIVE	
THE EFFECTS OF DAIRY FACTORY EFFLUENT ON SOIL HYDRAULIC CONDUCTIVITY	26
5.1 Introduction	26
5.1.1 Reduction in soil saturated hydraulic conductivity following effluent application	26
5.1.2 A review of observations made on pore clogging and of the mechanisms involved	27
5.1.3 The relevance of previous work to clogging from dairy factory effluent	30
5.1.4 Increases in soil hydraulic conductivity	33

	page
5.2 Aims of Permeability Studies	34
5.3 Experimental Design	34
5.4 Results and Discussion	35
5.4.1 "Undisturbed" soil core reaction to repetitive applications of simulated whey effluent	36
5.4.2 Changes in saturated hydraulic conductivity following a single application of simulated whey effluent to "undisturbed cores".	44
5.4.3 Isolating the biological blockage mechanism	49
5.4.4 Isolating the physical blockage mechanism	53
5.4.5 The extent of blockage as a function of effluent quality	56
5.4.6 A study of the increase in saturated hydraulic conductivity of "undisturbed" cores	60
5.4.7 Use of the "Double Staining Technique" to study blockage and recovery of channels in "undisturbed" cores	61
5.4.8 Information obtained from field studies	65
5.4.9 Relevance of the "undisturbed" core studies to the field situation	67
5.5 Summary of Results	68

CHAPTER SIX

LONG TERM CHANGES IN SOIL PROPERTIES RESULTING FROM THE APPLICATION OF DAIRY FACTORY EFFLUENT	70
6.1 Introduction	70
6.1.1 Scope of the study	70
6.1.2 Plant nutrient effects	70
6.1.3 Effects on groundwater quality	72

	page
6.1.4 Gaseous losses to the atmosphere	73
6.1.5 The nutrient balance	74
6.1.6 Soil pH	76
6.1.7 Soil physical property changes	76
6.1.8 Soil biological property changes	76
6.1.9 Conclusion	78
6.2 Experimental Design	79
6.3 Results and Discussion	79
6.3.1 Bulk density	80
6.3.2 Depth of the surface horizon	81
6.3.3 Soil pH	82
6.3.4 Soil nitrate and ammonium	83
6.3.5 Plant-available phosphate	85
6.3.6 Potentially mineralisable nitrogen	86
6.3.7 Total nitrogen	87
6.3.8 Organic matter	89
6.3.9 Earthworm numbers	91
6.3.10 Soil respiration	93
6.4 Summary of Results	96

CHAPTER SEVEN

MANAGEMENT PROBLEMS AT DAIRY FACTORY DISPOSAL SITES	98
7.1 Introduction	98
7.2 Soil Drainage	98
7.2.1 Te Rehunga - A high groundwater table drainage problem	98
7.2.2 Longburn - An infiltration problem	99
7.2.3 Integration of stock management with the disposal system	104

	page
7.3 Pasture Burning	106
7.4 Pasture Pulling	107
7.5 Stock Health	111
7.6 Summary	112

	page
APPENDIX I	
PROFILE DESCRIPTIONS	113
APPENDIX II	
BASIC DATA AND CALCULATIONS RELATING TO THE WATER BALANCE	
STUDIES	115
A2.1 Rainfall	115
A2.2 Evapotranspiration	115
A2.3 Effluent Application	115
A2.4 Soil Information.	117
APPENDIX III	
DERIVATION OF THE RESPIROMETER EQUATION	122
APPENDIX IV	
ADDITIONAL RESPIROMETRY STUDIES AND CARBOHYDRATE ANALYSIS DATA . .	123
A4.1 Respirometry Studies	123
A4.2 Carbohydrate Analysis	125
APPENDIX V	
ANALYSIS OF EFFLUENT SAMPLES	128
BIBLIOGRAPHY	129

FIG. 3.1	The apparatus used to study saturated hydraulic conductivity in the laboratory	10
3.2	The respirometry apparatus	14
4.1	Average seasonal runoff for the Te Rehunga site in the presence and absence of the irrigation component .	22
4.2	Average season runoff for the Longburn site in the presence and absence of the irrigation component . . .	22
4.3	The average number of days per month on which the Te Rehunga site is likely to be water-stressed (at the -15 bar and -1 bar level) in the absence of irrigation	23
4.4	The average number of days per month on which the Longburn site is likely to be water-stressed (at the -15 bar level) in the absence of irrigation	23
5.1	Changes of K with time following repetitive applications of simulated effluent to two Tokomaru silt loam (0-100mm) cores, with a water only treatment core for comparison	38
5.2	Changes of K with time following repetitive applications of simulated effluent to two Tokomaru silt loam (0-100mm) cores, with a water only treatment core for comparison	38
5.3	Changes of K with time following repetitive applications of simulated effluent to a Tokomaru silt loam (100-200mm) core, with a water only treatment core for comparison	39
5.4	Changes of K with time following repetitive applications of simulated effluent to two Tokomaru silt loam (100-200mm) cores, with two water only treatment cores for comparison	39
5.5	Changes of K with time following repetitive applications of simulated effluent to two Kopua silt loams (0-100mm) cores, with a water only treatment core for comparison	40
5.6	Changes of K with time following repetitive applications of simulated effluent to two Kopua silt loams (0-100mm) cores, with two water only treatment cores for comparison	40
5.7	Changes of K with time following repetitive applications of simulated effluent to two Kopua silt loam (100-200mm) cores, with a water only treatment core for comparison	41
5.8	Changes of K with time following repetitive applications of simulated effluent to a Kopua silt loam (100-200mm) core, with a water only treatment core for comparison	41

FIGURE 5.9	Changes of K with time following repetitive applications of simulated effluent to two Manawatu silt loam (0-100mm) cores, with a water only treatment core for comparison	42
5.10	Changes of K with time following repetitive applications of simulated effluent to a Manawatu silt loam (0-100mm) core, with a water only treatment core for comparison	42
5.11	Changes of K with time following a single application of simulated effluent to a Tokomaru silt loam (100-200mm) core, with a water only treatment core for comparison	45
5.12	Changes of K with time following a single application of simulated effluent to two Tokomaru silt loam (100-200mm) cores, with a water only treatment core for comparison	45
5.13	Changes of K with time following a single application of simulated effluent to three Tokomaru silt loam (0-100mm) cores	46
5.14	Changes of K with time following a single application of simulated effluent to two Kopua silt loam (0-100mm) cores, with a water only treatment core for comparison	46
5.15	Changes of K with time following two applications of simulated effluent (on days '0' and '14') to three Tokomaru silt loam (100-200mm) cores, with a water only treatment core for comparison	47
5.16	Changes of K with time following repetitive applications of simulated effluent and effluent plus inhibitor treatments to Tokomaru silt loam (0-100mm) cores	50
5.17	Changes of K with time following repetitive applications of simulated effluent plus inhibitor treatments to Tokomaru silt loam (0-100mm) cores	50
5.18	Changes of K with time following repetitive applications of simulated effluent and effluent plus inhibitor treatments to Tokomaru silt loam (100-200mm) cores	51
5.19	Changes of K with time following repetitive applications of simulated effluent and effluent plus inhibitor treatments to Tokomaru silt loam (100-200mm) cores	51
5.20	Changes of K with time following repetitive applications of simulated effluent and effluent plus inhibitor treatments to Manawatu silt loam (0-100mm) cores	52

FIGURE 5.21	Changes of K with time following repetitive applications of simulated effluent and effluent plus inhibitor treatments to Manawatu silt loam (0-100mm) cores . . .	52
5.22	Changes in K during ponding and over the two day period following application of simulated effluent to Tokomaru silt loam (0-100mm) cores, with a water only treatment core for comparison	54
5.23	Changes in K during ponding and over the two day period following application of simulated effluent to Tokomaru silt loam (100-200mm) cores, with a water only treatment core for comparison	54
5.24	Changes in K during the ponding period and over the two day period following application of simulated effluent to two Karapoti brown sandy loam (0-100mm) cores, with a water only treatment core for comparison	55
5.25	Changes in K during the ponding period and over the two day period following application of simulated effluent to two Karapoti silt loam (0-100mm) cores, with a water only treatment core for comparison . . .	55
5.26	Changes of K with time following a single application of high suspended solids effluent to two Tokomaru silt loam (0-100mm) cores, with a water only treatment core	57
5.27	Changes of K with time following application of high suspended solids effluent to a Tokomaru silt loam (0-100mm) core, with a water only treatment core for comparison	57
5.28	Changes of K with time following application of high suspended solids effluent to four Tokomaru silt loam (100-200mm) cores, with a water only treatment core for comparison	58
5.29	Changes in K during ponding and over the two day period following an application of high suspended solids effluent to three Tokomaru silt loam (0-100mm) cores, with a water only treatment core for comparison. . . .	59
5.30	Changes in K during ponding and over the two day period following an application of high suspended solids effluent to three Karapoti silt loam (0-100mm) cores, with a water only treatment core for comparison . . .	59
5.31	A section through a Tokomaru silt loam (100-200mm) core following staining with Methylene Blue	62
5.32	A section through a Tokomaru silt loam (0-100mm) core following staining with Rhodamine-B	62
5.33	Successive sections through a Tokomaru silt loam (0-100mm) core following "double staining"	63

FIGURE 5.34	A section through a Manawatu silt loam (0-100mm) core following "double staining"	63
5.35	An enlarged section of a Manawatu silt loam (0-100mm) core following "double staining"	64
6.1	Changes in soil oxygen consumption with time following effluent or water applications to soil samples from the Te Rehunga disposal site	95
6.2	Changes in soil oxygen consumption with time following effluent or water applications to soil samples from the Te Rehunga control site	95
7.1	A ponded depression area at the Longburn disposal site	101
7.2	Effluent solids material coating the soil surface following spray irrigation	101
7.3	Changes of K with time in soil cores from the depression and elevated area of the Longburn disposal site with core surfaces removed on days 4 and 8	103
7.4	Pasture burning at the Tokomaru disposal site.	108
7.5	Pasture pulling at the Te Rehunga disposal site	110
A2.1	Seasonal dairy production in New Zealand (averaged over the ten year period 1965-1975)	118
A2.2	Bulk density of the Te Rehunga disposal site profile	119
A2.3	Water retentivity characteristics of the Te Rehunga disposal site profile	119
A2.4	Bulk density of the Longburn disposal site profile	120
A2.5	Water retentivity characteristics of the Longburn disposal site profile	120
A4.1	Changes in soil oxygen consumption with time following the application of simulated effluent, effluent plus inhibitor and water treatments to soil samples from the Te Rehunga control site	124
A4.2	Changes in soil oxygen consumption with time following either the sectioning or sieving of soil cores collected from the depression area of the Longburn disposal site	124
A4.3	Changes in soil oxygen consumption with time following application of simulated effluent or water at time '0' to surface layer soil from the Tokomaru disposal site	126
A4.4	Changes in soil oxygen consumption with time following an application of simulated effluent or water at time '0' to surface layer soil from the Longburn disposal site	126

LIST OF TABLES

TABLE 5.1	Comparison of the changes in K between a two- or four-day spelling interval following application of simulated effluent to Tokomaru silt loam (100-200mm) cores	49
5.2	Forty-five minute infiltration rates recorded prior to and two days after spray irrigation at the Longburn disposal site	65
5.3	Mid-season and end of season infiltration rates for the Te Rehunga disposal and control sites	66
5.4	Pre-season and mid-season infiltration rates at the recently established Tokomaru disposal site	67
6.1	Bulk density of the surface 100mm of soil from two disposal sites and their corresponding control sites.	80
6.2	The depth of the Ap horizon at the Te Rehunga disposal and control sites	81
6.3	Soil pH values for the Te Rehunga disposal and control sites	82
6.4	Nitrate and ammonium levels at the Te Rehunga disposal and control sites	84
6.5	Nitrate and ammonium levels at the Tokomaru disposal and control sites	84
6.6	Nitrate and ammonium levels at the Longburn disposal and control sites	85
6.7	"Plant-available" phosphate levels for the disposal and control sites at Te Rehunga and Tokomaru	85
6.8	Potentially mineralisable nitrogen values for the disposal and control sites at Te Rehunga, Tokomaru and Longburn	86
6.9	Total nitrogen levels at the Te Rehunga disposal and control sites	87
6.10	Total nitrogen levels at the Tokomaru disposal and control sites	88
6.11	Organic matter levels at the Te Rehunga disposal and control sites	90
6.12	Organic matter levels at the Tokomaru disposal and control sites	90
6.13	Earthworm numbers in the surface 100mm of soil at the Te Rehunga, Tokomaru and Longburn disposal and control sites	92

TABLE 6.14	Oxygen consumption rates in soil samples taken from the Te Rehunga disposal and control sites at seven and fourteen days after waste application	93
7.1	Infiltration rates at a rotationally grazed disposal site (Field 1) and at a set stocked disposal site (Field 2)	105
A1.1	Profile description of the Kopua silt loam	113
A1.2	Profile description of the Karapoti brown sandy loam at the Longburn disposal site	113
A1.3	Profile description of the Kairanga fine sandy loam at the Tokomaru disposal site	114
A1.7	Profile description of the Manawatu silt loam	114
A2.1	Mean monthly rainfall data (in mm) for Te Rehunga, Tokomaru and Palmerston North over the period 1941-1970	116
A2.2	Average potential evapotranspiration values for pasture at Palmerston North (mm month^{-1})	117
A2.3	Calculation of the "available water holding capacity" and readily available water	118
A2.4	An example of the working procedure involved in the construction of a daily water balance (from the Te Rehunga water balance)	121
A2.5	Maximum daily rainfall figures (in mm) for Te Rehunga (over the 10 year period 1967-1977) and for Palmerston North (over the 42 year period 1928-1970)	121
A4.1	The percentage of applied carbohydrate collected in the leachate following addition of a 35 mm dose of simulated effluent to "undisturbed" soil cores	127
A5.1	Composition analysis of effluent samples from Longburn dairy factory	128