Copyright is owned by the Author of the thesis. Permission is given for a copy to be downloaded by an individual for the purpose of research and private study only. The thesis may not be reproduced elsewhere without the permission of the Author.

# Development and Mathematical Analysis of a Modular CNG Valve

A thesis presented in partial fulfilment of the requirements for the degree of

Master of Engineering

Mechatronics

at

Massey University,

Albany, New Zealand.

Gordon Warren

2006

### Masters Abstract

# Development and Mathematical Analysis of a Modular CNG valve

With the rising cost of oil and uncertainty of supply, there has never been a greater opportunity to offer an alternative fuel into the automotive market than at this present time. Compressed natural gas (CNG) and liquid petroleum gas (LPG) are popular alternatives, producing less green house gasses after the combustion process that add to the raising global warming concern. With high performance fuel injected state of the art engines used in the majority of the late model vehicles, the problem when running on CNG or LPG is poor control of the air/fuel ratio throughout the engine's speed and load range using the conventional zero pressure regulator and mixer combination gas conversion equipment used previously for carburetted engines. This problem is completely eliminated with gas injection system.

The Harrison CNG Electronic Gas injection System control valve is a linear proportional valve. Testing on the valve has found that the response is linear under all operating conditions; however the valve exhibits occasional instances of hysteresis. Due to this unfortunate characteristic further analysis is required, in the form of a mathematical analysis, to determine the exact causes of this problem. Another point of concern is the complexity of the valve, due to the many moving parts, this results in high production costs and increased reliability concerns.

This masters project will include the mathematical analysis of the current Harrison CNG Electronic Gas injection system, further testing and refinement. The objective is to produce a modular system that can be retrofitted to any make of vehicle. Research will be directed in the development of mathematical equations to analyse valve operation for improvement of operation, to increase performance the valve will be redesigned to reduce complexity and ready it for production. The valve will be tested on a variety of vehicles from a 2 litre sedan to a 5.8 litre diesel engine that has been converted to operate on CNG, to prove the versatility of the valve and its ability to tailor the engine torque curve to that required for the vehicles unique operating requirements.

### Acknowledgments

I would like to take this opportunity to thanks those that have helped me throughout the project. I would firstly like to thanks my parents, Ian and Lin, and also my brother, Graeme for their continuous support and encouragement. Secondly I would like to thank John Harrison the original inventor of the valve for opportunity to he awarded me when he approached Massey University for further development on the valve. Never in my wildest dreams did I think that I would travel to China to do diesel engine conversions at the beginning of the project. I would like to thank Jou and Lin Lee-Shian Ma for sponsoring the development of the valve and for the trips to China to prove the versatility of the valve and also for their tremendous patience during the development process.

To the Massey University staff of the engineering department, Dr Johan Potgieter, Dr Olaf Diegel, Eddy Rogers and Raymond Hoffman, I would like to express my gratitude for all their time spent in both the workshop making small intricate components and also the time spent listening to my complaints of why the valve isn't working during the development.

I would also like to thank my friends, Conan, Brendan, Travis, Johno, for the fun times spent to give the brain a chance to relax and for reckless behaviour over weekends. To all the other postgraduate students I would like to say thanks for the encouragement and also for the chance to exchange strange and wonderful ideas for future projects and also for the good laughs.

Lastly but by no means least to my girlfriend, Shu Chin, for all her endless encouragement and never-ending confidence in me, I would like to tribute this poem:

## She Takes Me...

by William Thomas Kinsey

She takes me many places that I have never been: all I do is look at her it's then she takes me in.

Into a new and different world one I've heard mention of; a world of grace and beauty a world of endless love.

A world of peace and kindness (the way the world should be), with her I see it every day she is that 'world' to me.

While with her life's a fantasy,
a dream world I would say;
yes, she makes my dreams come true
and she does it every day.

Her world of love is awesome,
it fills the poets pen.
All I do is look at her
and then... she takes me in.

## Table of Contents

Masters Abstract
Acknowledgments 2
Table of Contents
List of figures
List of tables
Chapter 1: Introduction
Chapter 2: Literature Review
2.1 Overview of CNG
2.1.1 Origin of Natural Gas Accumulations
2.1.2 Supply and Demand
2.1.3 Combustion properties of natural gas
2.1.4 Fuel composition
2.1.5 Effects of fuel composition on engines and vehicles
2.2 Natural Gas history in New Zealand
2.3 Other alternative fuels
2.3.1 Alcohols (methanol and ethanol)
2.3.2 M85 and E85
2.3.3 DME
2.3.4 LPG
2.3.5 Vegetable oils
2.3.6 Hydrogen
2.4 Exhaust emissions and testing procedures
2.4.1 Test methods
2.4.2 Passenger cars and light duty vehicles
2.4.2.1 CARB
2.4.2.2 EPA
2.4.2.3 EU
2.4.2.4 Japanese Legislation
2.4.3 Heavy duty vehicles
2.4.3.1 U.S legislation
2.4.3.2 EU legislation
2.4.3.4 Japanese Legislation
2.4.4 Unregulated Emissions
2.5 OBD (On-Board Diagnostics)

2.6 Exhaust gas after treatment	55
2.7 Fuel systems	60
2.8 Stoichiometric and lean burn operation of gas engines	63
2.8.1 Engine operation overview	63
2.8.2 Stoichiometric engines	70
2.8.3 Lean-burn engines	71
2.9 Inductive discharge versus capacitive discharge ignition	73
2.9.1 Ignition overview	73
2.9.2 Inductive ignition	75
2.9.3 Capacitive discharge ignition	77
2.10 Advantages and disadvantages of natural gas	78
Chapter 3: Mechanical operation and development of valve	81
3.1. Valve Introduction	81
3.1.1. Valve operation	81
3.1.2. Fluid dynamics of valve	86
3.1.3. Numerical analysis of valve	88
3.2. Integration of Valve into an existing petrol vehicle platform	103
3.2.1. Vehicle platform and conversion requirements	103
3.2.2. Valve location	105
3.2.3. Natural gas injection device	106
3.3. Diesel conversion system	107
3.3.1 Diesel conversion requirements	107
3.3.2. Placement of valve	110
3.3.3. Intercooler	111
3.3.4. Timing discs	113
Chapter 4: Electronic control systems	116
4.1. Bench testing system	116
4.2. Subaru electronic control strategy	119
4.2.1. Commonly used ignition systems in light duty vehicles	120
4.2.2. Ignition modifier	124
4.2.3. Injector emulator	126
4.3. Diesel engine conversion	127
4.3.1. ECU Control system	128
4.3.2 Ignition system	131
Chapter 5: Testing and Validation	135
5.1. Bench Tests	135
5.2. Retrofit Test	138

5.3. Diesel engine testing	144
5.4. Comparison of diesel and CNG performance	145
5.5. Changes for diesel conversion	150
Chapter 6: Future developments	
Chapter 7: Conclusion	158
References	161
Appendix A	164
Appendix B	168
Appendix C	179

# List of figures

Figure 2.1: Methane molecule [2]14
Figure 2.2: Proven world natural gas supply [4]
Figure 2.3: World natural gas supply [5]
Figure 2.4: World natural gas consumption [5]
Figure 2.5: Exhaust emissions with respect to lambda [6]
Figure 2.6: World regions implementing emission regulations [14]
Figure 2.7: USA test cycles for passenger and light commercial vehicles [14]
Figure 2.8: EPA emission limit compared to that of CARB [14]
Figure 2.9: EU emission limits for gasoline passenger cars and light commercial vehicles [14]
44
Figure 2.10: EU/ECE test cycle for passenger cars and light commercial vehicles [14]45
Figure 2.11: Japanese test cycles for passenger cars [14]
Figure 2.12: U.S HD transient test [14]
Figure 2.13: ESC test cycle [14]
Figure 2.14: ETS cycle test [14]
Figure 2.15: Bosch Motronic ME7 engine management system with OBD [2]
Figure 2.16: The effect of a TWC with respect to air/fuel ratio [2]
Figure 2.17: Passive and active SCR converter
Figure 2.18: Model example of NO <sub>x</sub> storage and regeneration [17]
Figure 2.19: First generation CNG fuel system [18]
Figure 2.20: Second generation CNG fuel system [18]
Figure 2.21: Third generation CNG fuel system [18]
Figure 2.22: Effect of ON on auto-ignition temperature [19]
Figure 2.23: Timing effect on combustion [19]
Figure 2.24: Effect of lambda on natural gas engine performance [19]
Figure 2.25:Trade off of NO <sub>x</sub> emissions and engine efficiency [2]
Figure 2.27: Spark plug voltage characteristic [21]
Figure 2.28: Inductive discharge ignition schematic [22]
Figure 2.29: Capacitive discharge ignition schematic [23]
Figure 3.1: Second stage regulator and feedback assembly
Figure 3.2: Main metering control valves
Figure 3.3: Injector and Reference chamber
Figure 3.4: Accelerator Pump
Figure 3.6: Floworks analysis of valve design

Figure 3.7: Second stage regulator valve model	91
Figure 3.8: Second stage feedback regulator model	92
Figure 3.9: Main control valve model	93
Figure 3.10: Fine needle valve model	94
Figure 3.11: Discharge coefficient versus lift for needle valve	95
Figure 3.12: Flow chart for Harrison valve	96
Figure 3.13: First stage regulator and filler point	104
Figure 3.14: Harrison Valve installation on Subaru	105
Figure 3.15: CNG mixer	106
Figure 3.16: CNG and Diesel pistons	108
Figure 3.17: Spark plug location in cylinder head	109
Figure 3.18: Intake plenum for Isuzu engine	110
Figure 3.19: Flow path of intake plenum	111
Figure 3.20: Intercooler mounted on engine	112
Figure 3.21: SolidWorks model of timing assembly	114
Figure 3.22: Timing discs on Isuzu engine	115
Figure 4.1: LM1949 Peak and hold current control output	117
Figure 4.2: Injector simulation System	118
Figure 4.3: Ignition map [14]	119
Figure 4.4: Ignition timing effect on combustion pressure [14]	120
Figure 4.5: Electronic Distributor Ignition [24].	121
Figure 4.6: Transistorised ignition, single fire [24]	122
Figure 4.7: Transistorised ignition, dual spark [24].	123
Figure 4.8: Electronic ignition with integrated ignitor [24].	123
Figure 4.9: Ignition modifier	124
Figure 4.10: Injector emulator	126
Figure 4.11: PCLink software	130
Figure 4.12: CD200 Terminal program	133
Figure 4.13: CD200 placement on test engine	134
Figure 5.1: Valve test bench excluding gas cylinder and rotameters	137
Figure 5.2: Valve flow requirements	137
Figure 5.3: Petrol and CNG power output at wide open throttle	139
Figure 5.4: 50% load run comparison	140
Figure 5.5: Power output from dynamometer testing through load range	141
Figure 5.6: CO% emissions for petrol and CNG at WOT	142
Figure 5.7: HC ppm emissions at WOT for petrol and CNG	142
Figure 5.8: CO2% emissions at WOT for petrol and CNG	143

Figure 5.9: O2% emissions at WOT for petrol and CNG	143
Figure 5.10: Diesel engine output at WOT	145
Figure 5.11: Torque and fuel consumption for CNG and diesel at 1600 RPM	146
Figure 5.12: CNG versus Diesel power and torque	147
Figure 5.13: Diesel and CNG comparison at WOT	148
Figure 5.14: New Timing disk assembly with flexible coupling and bearings	15
Figure 5.15: Integrated intercooler and plenum	152
Figure 6.1: Valve prototype	156

## List of tables

Table 2.1: Natural gas composition [1]	14
Table 2.2: World proven natural gas supply [4]	17
Table 2.3: NZS 5442 natural gas composition limits [7]	26
Table 2.4: LEV II emissions standards for passenger cars and light commercial	vehicles [15]
	41
Table 2.5: EU emission limits [15]	45
Table 2.6: Natural gas storage tank equivalence to that of petrol [11]	60
Table 2.7: Effective mean pressure of modern engines [17]	69
Table 3.1: Intercooler efficiency	113
Table 5.1: Turbo pressure with respect to RPM	148
Table 5.2: Emissions for 1600RPM varying load run	149

### Chapter 1: Introduction

CNG is seen as the most promising alternative fuel at present, containing between 80% and 95% methane and some other heavier hydrocarbons. Methane has a simple structure and therefore better emissions after combustion; it also has a very high anti-knock value which allows one to increase the thermal efficiency of the engine. Recent surveys have found that the world resources of natural gas are estimated to be 6358.575 trillion cubic feet. At today's current level of consumption this is estimated to last for the next 70 years [3].

Due to methane having a high octane a rating of approximately 120 and also the extended flammability limits of 5-15%, natural gas is well suited to lean burn operation. A lean burn engine operates with an excess air, stoichiometric operation has an air/fuel ratio of 17.2:1 (lambda 1) for methane, if an engine operates with a lean burn condition then the air/fuel ratio is then greater than 17.2:1. The advantages of lean burn are that it decreases fuel consumption and reduces exhaust emissions. Current generator sets operate at lambda 2 (A/F = 34.4:1), but these engines have specially designed combustion chambers having a precombustion chamber that ignites a richer mixture and then the main combustion chamber that contains a very lean mixture. Lean burn operation is not only limited to natural gas, diesel engines operate with excess air due to emissions laws, if diesel engines were to operate with stoichiometric air/fuel mixtures, high particulate emissions (black smoke) are produced which is restricted by current emissions laws. Gasoline engines may also be operated at lean burn using technology known as GDI (Gasoline Direct Injection), this creates a stratified charge within the combustion chamber resulting in a richer mixture present at the spark plug to initiate combustion and a lean mixture throughout the rest of the combustion chamber. Natural gas will result in better emissions than both gasoline and diesel due to its simple structure. Studies have shown that NO<sub>x</sub> reductions of 50-80% and particulate matter reductions of 80-90% are possible when heavy-duty vehicles are converted to operate on natural gas instead of diesel.

One of the major disadvantages of natural gas is its low energy density, therefore requiring large heavy storage cylinders. This can be overcome by liquefying natural gas, however natural gas only liquefies at -162°C thereby requiring cryogenic freezing which increases complexity of the system and also the cost. Other technologies have been introduced that use a porous absorbent material that is introduced into the cylinder that increases the energy density of the vessel. This technology uses low pressures of 3.5-5MPa to store 2/3 of the total

energy density present in a standard CNG cylinder filled at 20MPa, this allows the saving in cylinder cost, allows the storage devise to have a irregular shape and be made of a lighter material.

Natural gas has had an interesting history in New Zealand that saw New Zealand as a world leader in CNG technology in 1970-1985 after which the infrastructure unfortunately fell apart and today there is very little use or infrastructure present. However Europe and the United States have now seen a resurgence in natural gas technology with international OEM vehicle manufacturers introducing specially designed vehicles to operate with both natural gas and gasoline. With the stringent emissions laws currently in effect and the push by governments to reduce overall green house gases the opportunity for natural gas to become a dominant fuel is almost a reality.

The purpose of this master study was to examine and perfect a CNG (Compressed Natural Gas) fuel metering system. The metering system uses the vehicle's onboard electronic control unit (ECU) used to meter petrol into the OEM (Original Equipment Manufacturer) engine to create a reference signal that is then used to meter the required fuel for a given engine operating condition. This metering system is a mechanical system that has been in development independently for the last few years and was brought to Massey University for further development. The scope of the project included a mathematical analysis of the apparatus to determine the mostly likely cause of action, followed by further testing on a motor vehicle. This thesis will detail the advantages and disadvantages of natural gas and also look at the other alternative fuels that are presently available; it will also discuss some of the testing done to prove the versatility of the metering apparatus and some of the mathematical analysis done. There will be a brief description of the valve operation and a discussion on the results from testing, highlighting achievements and likely shortcomings that future development may eliminate.

The metering apparatus was designed to be a modular system that may be employed on a large variety of vehicles with very little modification to the OEM equipment so that the vehicle may then operate on CNG. The range of engines that can be operated using this apparatus range from a small 1 litre engine to a large 5.7 litre diesel engine that had been converted to operate on diesel. When converting a SI (spark ignition) engine to operate on CNG very little has to be modified to allow for this alternative fuel, the basic components required are:

- CNG cylinder
- Injector emulator
- · Ignition advance unit
- CNG metering system
- Mixer unit

The components are easily installed and require no adjustments or calibration by the end users. The advantages of the system are that the vehicle performance is maintained with the alternative fuel operation due to precise metering of natural gas and that the vehicle operator experiences little if no evidence of vehicle operation on natural gas.

Chapter two will introduce natural gas, the history of natural gas in New Zealand, introduce other alternative fuels, testing procedures for emissions standards, exhaust after-treatment, onboard diagnostics, and the advantages and disadvantages of various control systems for engine operation. Chapter three will concentrate on the mechanical development of the valve, firstly describing the operation of the valve and then describe the development to improve the valve. Chapter four will concentrate on the electronic requirement for vehicle conversion to natural gas. Chapter five describes the testing and results of the vehicle conversions. Chapter six will detail future developments of the valve to ready it for production.