

**Proceedings in
Scientific Conference**


SCIECONF 2013

10. – 14. June 2013



ScieConf
SCIENTIFIC CONFERENCE 2013

Published by: EDIS - Publishing Institution of the University of Žilina

 Univerzitná 1
01026 Žilina
Slovak Republic

Editors: Ing. Michal Mokryš; Ing. Štefan Badura, Ph.D.; Ing. Anton Lieskovský, Ph.D.

ISBN: 978-80-554-0726-5

ISSN: 1339-3561

Pages: 529

Printed in: 200 copies

Publication year: 2013

Other: All published papers undergone single blind peer review.

 **Warning:**

All rights reserved. Reproduction or publication of this material, even partial, is allowed only with the editor's permission. Unauthorized duplication is a violation of applicable laws.

CONSTRUCTION COST ESTIMATES FOR RESIDENCES IN SPAIN: practical application of the Pcr.5n model	398
<i>Pedro Pina Ruiz, Federico García Erviti, Gema Ramirez Pacheco</i>	
Optimization of energy consumption for the drying process with pre-heating of the material	406
<i>Volodymyr Potapov, Yakushenko Evgen, Stoyan Evgen</i>	
The theoretical model of calculation of the power during viscous mediums mixing	412
<i>Volodymyr Potapov, Mayak Olga</i>	
Methodological principles of energy efficiency upgrading of microwave treatment of food semi-products	415
<i>Volodymyr Potapov, Svetlana. Mykhaylova, Victoria Arkhipova</i>	
Curing At High Temperature On Mechanical Of Geopolymer Adding Carbon Fiber.....	420
<i>Linh Trinh Thi, Dora Kroisova, Petr Louda</i>	
Modelling and Simulation Techniques for Assessment of Urban Form Sustainability.....	426
<i>Jurgis Zagorskas, Inga Veteikytė</i>	
SECTION 20. Informatics	431
Data Integration with Evolving Ontologies.....	432
<i>Michal Smiraus</i>	
Distributed Greedy Approach to Solving Travelling Salesman Problem.....	436
<i>Pawel Woloszyn</i>	
SECTION 21. Information Technology.....	440
The impact of virtual space on the evolution of the direct environment of an enterprise in the context of the customer	441
<i>Ewa Forystek-Zabojszcz, Jolanta Staszewska</i>	
Approach for an Object-Based Data View for Mobile PDM Users Supported Through a Timeline	447
<i>Michael Hopf, Jivka Ovtcharova</i>	
Web-Based Monitoring and Evaluation	455
<i>Olga Cherednichenko, Olha Yanholenko, Olena Iakovleva</i>	
Plate recognition algorithm for ITV spanish system by mathematical morphology	459
<i>Javier Ortiz, Alberto Gómez</i>	
E-learning system in vocational reahabilitation	462
<i>Airina Savickaitė</i>	
Modeling of random Markov processes in view of time factor.....	465
<i>Dulat N. Shukayev, Nazgul O. Yergaliyeva, Zhanar B. Lamasheva</i>	
Power unit based on supercapacitors and solar cell module.....	468
<i>Peter Ševčík, Oldřich Kovář</i>	
The evolution of web browser architecture	472
<i>Tedo Vrbanec, Nenad Kirić, Matija Varga</i>	
SECTION 22. Transport and Logistics	481
Gini Coefficient, Dissimilarity Index and Lorenz Curve for the Spanish Port System by type of goods	482
<i>Nicoletta González-Cancelas, Francisco Soler-Flores, M. Carmen Palomino-Monzón, J.Luis Almazán-Gárate</i>	
An Econometric Model for the Analysis and Forecast of Rail Passenger Demand	488
<i>Vassilios K. Stefanis, George N. Botzoris</i>	
Delphi-SWOT as a strategic tool of planning for the Port of Manta.....	494
<i>Mariela Macías Párraga, Nicoletta González-Cancelas, Francisco Soler-Flores</i>	
Pitfalls of controlling in corporate logistics	501
<i>Peter Majerčák, Eva Majerčáková</i>	
Setting of weighting factors influencing the determination of the location of Dry Ports using a DELPHI methodology.....	505
<i>Samir Awad Núñez, Nicoletta González Cancelas, Alberto Camarero Orive</i>	

CONSTRUCTION COST ESTIMATES FOR RESIDENCES IN SPAIN: practical application of the Pcr.5n model

Pedro Pina Ruiz

- Faculty of Architecture and Building Engineering
at the University Catholic Saint Anthony of Murcia [UCAM]
, Murcia, Spain
- info@pedropinaarquitecto.com

Federico García Erviti

- Faculty of Architecture
at the Polytechnic University of Madrid
[ETSA UPM], Madrid, Spain

Gema Ramirez Pacheco

- Faculty of Architecture
at the Polytechnic University of Madrid
[ETSA UPM], Madrid, Spain

Abstract. The construction cost estimation systems in Spain are undeveloped and, hence, infrequently used by technicians and professionals in the building sector. However, estimation of an approximate real cost prior to the execution of the work is compulsory under current legal regulations (Technical Building Code). Therefore, the development of research projects on construction cost estimation models such as the one described and demonstrated in this talk is extremely interesting.

The objectives of the present research are to establish a construction cost estimation system for the residential building sphere in Spain, and to demonstrate the practical application of a quick and precise model for estimating the construction costs by contract.

This model is referred to as Pcr.5n (Cost estimation with 5 levels of process design) it makes it possible to formulate a cost estimate that is implemented in the stages prior to the conceptualization of the architectural project, namely during the process of carrying out preliminary studies, drafting and the basic project.

At each level of calculation, the model adjusts the estimate in accordance with how the definition of the project advances (successive approximations at finite intervals). The final objective and hypothesis of the model is the achievement of at least 90% accuracy with regard to the final cost estimation of the work.

The cost calculation for material execution is structured using functional three-dimensional cubic parameters for the planned space, and constructive two-dimensional metric parameters for the surface that envelopes around the facade and the building's footprint on the plot of land. These functional and constructive parameters are considered in each stage of the calculation process along with other thematic/specific parameters having to do with the management, design and execution of the exact building project, the cost of which has been estimated for the planned works, according to contract.

Keywords: Building, cost, estimation, housing, model, project.

I. HISTORIC PRECEDENTS

In the introduction to his "Ten Books on Architecture", Vitruvius Polion (Vitruvio, 1787), makes reference to an old law stipulating that the architect is obliged to calculate the "true estimate" of a project's final cost. Once the budget had been accepted and approved, all of the architect's properties were mortgaged by the government administration behind the project in question, until its ultimate financial settlement.

If the work was settled with a cost increase that did not exceed "*more than a quarter part*" of the approved budget, it was paid for using public funds, and the architect was not "*...subject to any penalty*". But if the project's final cost exceeded the original estimate by more than a quarter part, this excess was defrayed with the architect's own mortgaged property. When the originally approved financial forecasts had been met, the architect's property was released from the mortgage and he received fees in recognition of this fact.

This demonstrates that in 1 BC, there was already awareness about methods of final cost estimation for building projects, with penalties in effect for architects that strayed from financial provisions by more than 25% over the initial cost estimate for the construction project.

II. PLANNED OBJECTIVES AND FORMULATED HYPOTHESES

The research has two basic goals. On the one hand, to describe the current situation in Spain with regard to construction cost estimation techniques for residences, and on the other, to explain the concept of the Pcr.5n cost estimation model for architectural projects using preliminary studies of the project to be executed.

The goal is to obtain a useful working tool for students, technicians and professionals in the building sector that enables the calculation of the actual cost of the planned work, and to demonstrate with a simple practical application a reasonable and feasible technical calculation that is easy to use.

The objective focuses on achieving a reasonable level of precision in the estimation of final construction costs for a project, insuring that the deviations remain below the 10% permitted by the EU with regard to the project's initially approved budget. This deviation can also be considered the maximum in terms of what is reasonable from a perspective of financial security and the initial viability of the development, both on a public and private level. Thus, by applying the developed model, the objective is to obtain deviations of less than 10% of the actual cost of the finished work. These deviations will be measured at the following intervals, arranged from lowest to highest in terms of the project's level of definition: at level 1, initial development valuation (+/- 25%, a quarter part according to Vitruvius' *Ten Books*); at level 2, corresponding to preliminary studies (+/- 20%, maximum margin of error allowed by Law 3/2011 on Contracts for the Spanish Public Sector); at level 3, drafting (+/- 15% of the admissible maximum margin of error); and at levels 4 and 5, corresponding to the basic project, deviations of less than 10%. This is the legally allowed percentage for the financial acceptance of the work through an increment in the project's final mediation, with respect to the initial mediation state of the executed project.

Therefore, the calculation stages or levels contemplated in the Pcr.5m model, prior to the execution stage of the project are:

1. Initial development: Construction costs calculation based on initial sale price
2. Preliminary studies: Estimation of construction costs based on total cubic meters
3. Drafting: Estimation of construction costs based on the external envelope, the interior volume and the footprint on the ground
4. Basic Project: Estimation of construction costs based on square meters built, with wheighted average parameters of management, project and development
5. Basic development: Costs construction calculation based on basic sale price

Figure 1 shows the trend in percentage of deviation of costs estimates from the initial stages nr. 1 (10% deviation) to the Basic development nr. 5 (5% deviation)




Figure 1. Estimated calculation process by level

Source: the authors

The purpose of these objectives is to provide a positive response to four hypotheses, formulated as follows:

1. The first hypothesis is based on the fact that estimated cost calculations for residential architectural projects result in maximum deviations of 10% over the project's final cost, which is to say, half of the maximum margin of error permitted by Law 3/2011, Law of Contracts for the Public Sector, in which articles 311 and 312 stipulate that the maximum deviation is 20%, in order to ensure that the planning technician is not subject to penalties over the actual construction cost.

2. The second hypothesis asks that, in addition to being accurate, the model in development must be fast, with easy practical application. This supports the objective of introducing it into everyday construction cost estimates in the building sector of our country, through the approximate calculation based on two-dimensional (m2) and three-dimensional parameters (M3), which is a common approach in countries such Germany (BKI, 2012), United States (Cox & William, 1996) and Australia (Cheung, 2005).

3. The third hypothesis intends that the model go beyond the methodology that is usually found in cost estimation methods, which are based on an estimation of costs per square meter. To this end, the proposed cost estimation model is structured around building systems and functional spaces, costs that are gradually defined and estimated during the design process (successive approximations at finite intervals).

4. The fourth hypothesis is that history supports this model, both in its conceptual origins and in its methodological development: Vitruvius (beauty + utility + solidity) versus the Pcr Model: (exterior envelope + interior space + foundation footprint).

III. STATE OF THE MATTER: COST ESTIMATION IN SPAIN

In Spain there have been very few treatises published on construction cost estimation. Only two (Paricio, 1971) and (Carvajal, 1992) have explored this issue in-depth. Additionally, there are only two commercial construction cost estimation programs available in the Spanish market, Presto (Soft) and Arquimedes (Cype).

However, the current Technical Building Laws stipulate that the basic project include at least one approximate budget by chapter (Anejo I.2.V). This budgetary estimation should be calculated using cost estimation models, since this planning stage does not include detailed documents or highly developed plans that correspond to the executed project. Therefore, the need exists for the specification and development of construction cost estimation models.

IV. RESEARCH METHODOLOGY

The methodology used to obtain the intended results for the development of the Pcr.5n model and to respond to the established hypotheses, has been structured into the three following stages:

1st Stage: INTRODUCTION

During this initial phase, the origin and justification of the research is set out, based on the requirements stipulated by current legislation on construction cost estimation and its

possible penalties when deviations occur in the actual costs of the work in question.

The proposed objectives and formulated hypothesis are specified and designed, as well as the advisability and advantages of the developed cost estimation model.

2nd Stage: ANALYSIS. EVALUATION

This second phase involves the development of the internal calculations made using traditional analytical methodology on projects and real building costs (Pina, 1989, 1991 and 2004), thereby obtaining the minimal functional unit costs (half-bath, bedroom, kitchen, washroom, living room), the costs of the building systems for the exterior envelopes (roof and facades), and the cost of the building's footprint on the plot of land (preparation of the land, foundation, basements). Also, an estimate is made of the percentages by which management, planning and construction parameters increase the calculated cost of the planned work, beyond the contractor's general costs and profits.

As a result of the research have been obtained with statistics costs performed by the software SPSS (Statistical Package of the Social Sciences) (Figure 2).




Figure 2. Analytical cost/surface area calculations in use (SPSS)

Source: the authors

Finally, the internal, theoretical results of the model are analyzed through information that is structured using tables which make it possible to contrast and validate these results against the external calculations and evaluations of the actual final construction costs.

Subsequently, the external analysis and evaluation of the Pcr.5n model (Estimation of reference costs using 5 calculation levels) is carried out, and the theoretical model is applied to 240 completed building projects, whose real and final construction

costs are known. This contrasting and evaluation process makes it possible to reconcile the results and definitively validate compliance with the four original hypotheses:

- (1) Errors / deviations less than 10% over the final construction cost.
- (2) A model that is fast with an easy practical application.
- (3) Spatial / volumetric calculations (from 2D to 3D).
- (4) (Beauty + utility + solidity) versus (exterior envelope + interior space + foundation footprint).

Finally, this stage involves the synthesizing of the theoretical and practical conclusions.

In summary, the methodology developed for the current research project has centered on the theoretical and practical development of the synthetic calculation procedure, in order to achieve compliance with the four hypotheses detailed in items (1), (2), (3) and (4), above.

And lastly, the Pcr.5n model incorporates and integrates the commonly applied methods in our country that are based on specifications for constructed surface areas by floor, the cubic method for constructed volume, and the "Storey" box method that takes into account floors and facades and their corresponding heights (Cheung, 2005). This results in an integrated model with fewer errors and deviations than those results obtained using the independent application of the aforementioned methods.

Figure 3 graphically displays the five levels of calculation developed by the Pcr.5n model.




Figure 3. – General cost estimation model.

Figure 4 shows one of the 240 factsheets type of the projects database. The zoomed area includes the detailed data of the project. The down part and the upper right includes the two-dimensional and three-dimensional graphics references.


<p>Situación: Fuenlabrada (Madrid) Denominación: Vv.colectiva Calle Miguel de Cervantes 3 Tipología: B1/ Cb- Colectiva bloque Arquitecto: Antonio Ruiz Barbarín Promotor: Sociedad Cooperativa Artículo 47 Fecha proyecto/inicio/fin obra: 1995/1996/1998 Duración estimada de obra: 2.1 años m2 construidos: 11.389m2 /Coste de contrata: 351€/m2c M3 edificados: 31.890m3 /Coste contrata: 125€/ M3e Altura: 7 Plantas + 1 Sótano Total coste construcción por contrata final de obra: 3.995.252€ Exterior: Fábrica de ladrillo visto Fuente: Costes+Datos de Edificación-SOFT, Archivo_VIC280033</p> <p>USO/TIPOLOGÍA: RESIDENCIAL/COLECTIVA BLOQUE TOTAL M3 PROYECTADOS: [28.700 / 35.075].....M3p DENOMINACIÓN DEL PROYECTO: SITUACIÓN DE LA OBRA: AÑO PREVISTO FINAL DE OBRA: (Fg) Factor geográfico= Fg(.....): Fg(Madrid)=..... : =..... (Fa) Factor actualización = Fa(.....): Fa(1998)=..... : =..... (Cc.2) Coste construcción= (Fg)(Fa) x Cc (Coste contrata final)= = (.....)x(.....)x3.995.252€= € : 31.890M3= = [.....€/M3 actualizados] x [.....M3 proyectados]= Cc.2 = [.....€/M3 actualizados] x [.....M3 proyectados] =€</p> <p>Predimensionado coste construcción por contrata final de obra: (Cc.2) =€(iva no incluido)=Aq/Rs/Cb/ 042 /.....</p>  <p>TEBRI DOCTORALIZO, DESARROLLO DE UN MODELO DE PREDIMENSIONADO DE COSTES DE CONSTRUCCIÓN EN EL PROYECTO ARQUITECTÓNICO ESCUELA TÉCNICA SUPERIOR DE ARQUITECTURA Y DISEÑO UNIVERSIDAD POLITÉCNICA DE MADRID AUTOR PEDRO PINA RUIZ - ARQUITECTO</p> <p>B1/Cb 042</p>	<p>Situación: Fuenlabrada (Madrid) Denominación: Vv.colectiva Calle Miguel de Cervantes 3 Tipología: B1/ Cb- Colectiva bloque Arquitecto: Antonio Ruiz Barbarín Promotor: Sociedad Cooperativa Artículo 47 Constructor: Bouygues Construcciones España S.A. Fecha proyecto/inicio/fin obra: 1995/1996/1998 Duración estimada de obra: 2.1 años m2 construidos: 11.389m2 /Coste de contrata: 351€/m2c M3 edificados: 31.890m3 /Coste contrata: 125€/ M3e Altura: 7 Plantas + 1 Sótano Total coste construcción por contrata final de obra: 3.995.252€ Exterior: Fábrica de ladrillo visto Fuente: Costes+Datos de Edificación-SOFT, Archivo_VIC280033</p> <p>USO/TIPOLOGÍA: RESIDENCIAL/COLECTIVA BLOQUE TOTAL M3 PROYECTADOS: [28.700 / 35.075].....M3p DENOMINACIÓN DEL PROYECTO: SITUACIÓN DE LA OBRA: AÑO PREVISTO FINAL DE OBRA: (Fg) Factor geográfico= Fg(.....): Fg(Madrid)=..... : =..... (Fa) Factor actualización = Fa(.....): Fa(1998)=..... : =..... (Cc.2) Coste construcción= (Fg)(Fa) x Cc (Coste contrata final)= = (.....)x(.....)x3.995.252€= € : 31.890M3= = [.....€/M3 actualizados] x [.....M3 proyectados]= Cc.2 = [.....€/M3 actualizados] x [.....M3 proyectados] =€</p> <p>Predimensionado coste construcción por contrata final de obra: (Cc.2) =€(iva no incluido)=Aq/Rs/Cb/ 042 /.....</p>
--	--

Figure 4. type of data sheet found in the Pcr.5n model database.

Source: the authors.

Figure 5 shows the apartment building of 159 units whose costs construction and percentage deviations are estimated.




Figure 5. **Figure 5:** Perspective, floor plans and sections of 159 residences, retail spaces, parking garages and storage units

Source: Mariano y Luz de la Villa-Arquitectos- Murcia - Spain

V. DATA ANALYSIS, DISCUSSION AND SUMMARY OF RESULTS

For an example of the practical application of the specified model, we chose a project consisting of 159 residences, retail spaces, parking garages and storage units in Murcia (Spain).

The project consists of four blocks of community housing with a square floor plan, that are each 8 stories high with 2 basement garages.

Table 1, contains a selection of 12 projects excerpted from the Pcr.5n model database, which were selected using criteria related to the volume of the construction and its overall typology.

The sample size is sufficiently representative for the cost estimation of a similar project (BKI, 2012).

TABLE I. SELECTED PROJECTS FROM THE OF THE Pcr.5N MODEL DATABASE (COLLECTIVE HOUSING/B1Cb: 159 RESIDENCES)

Code number	Designation	Location	Year construction finalized	Contracted cost	m2	M3	Cost €/m2	Cost €/M3
B1/Cb/027	56 Subsidized housing	Madrid	1993	1.952.154	7.305	21.501	267	91
B1/Cb/031	Collective housing	Malaga	1998	2.339.259	8.242	22.686	284	103
B1/Cb/034	53 Subsidized housing	Madrid	2003	3.409.352	8.497	26.004	401	131
B1/Cb/035	85 Subsidized housing	Murcia	1987	1.878.808	9.000	27.000	209	70
B1/Cb/041	128 Residences ✓	Madrid	2003	3.847.334	10.492	31.476	367	122 ✓
B1/Cb/042	Collective housing ✓	Madrid	1998	3.995.252	11.389	31.890	351	125 ✓
B1/Cb/054	96 Subsidized housing ✓	S.Sebastian	2001	5.080.000	13.116	44.980	387	113 ✓
B1/Cb/060	155 Residences ✓	Madrid	1995	5.629.053	18.847	55.081	299	102 ✓
B1/Cb/062	45+48 Residences	Madrid	2000	4.640.414	15.308	58.407	303	79
B1/Cb/063	Building with 174 Residences ✓	Seville	2002	7.283.420	21.479	62.431	339	117 ✓
B1/Cb/064	168 Subsidized housing ✓	Vitoria	2002	7.420.037	23.086	67.345	321	99 ✓
B1/Cb/067	156 Residences for young people	Madrid	2007	12.187.375	28.237	75.500	432	161

Source: the authors

Table 2 depicts a selection of six projects that are comparable to the project being evaluated, with specific design-type criteria and similar in features and quality to the group of planned projects. This criteria (graphically displayed on figure 6) is supported by the Spanish Order/805/2003 ECO, regarding the rules for valuing real estate assets and which defines the fees for certain financial purposes. We obtain certain average unitary costs of 548€/m2 and **189 €/m3** (2013) weighting the cost per square meter (€/m2c) and cubic meter (€/M3e) to a restatement factor (Fa) and to a geographical factor (Fg).

TABLE II. CONTROL/COMPARABLE SIMILARITIES TO THE PLANNED PROJECT (COLLECTIVE HOUSING/B1/CB: 159 RESIDENCES)

Code number	Designation	Location	Cost €/m2c	Cost €/M3e	Fa 2013/.....	Fg Murcia/.....	Cost 2013 €/m2	Cost 2013 €/M3	
B1/Cb/041	128 Residences ✓	Madrid	367	122	172/115	100/112	488	162 ✓	
B1/Cb/042	Collective housing ✓	Madrid	351	125	172/86	100/112	625	222 ✓	
B1/Cb/054	96 Subsidized housing	S.Sebastian	387	113	172/104	100/110	580	169	
B1/Cb/060	155 Residences	Madrid	299	102	172/75	100/112	610	208	
B1/Cb/063	Building with 174 Residences ✓	Seville	339	117	172/108	100/101	532	184 ✓	
B1/Cb/064	168 Subsidized housing	Vitoria	321	99	172/108	100/110	465	144	
B1/Cb/XXX	159 Residences (2013)	Murcia					548	189

Source: the authors

Table 3 contains specific calculations for the planned building of 159 residences, retail spaces, parking garages and storage units, along with the five calculation levels of the Pcr.5n model, numerically developing the formulas and concepts summarized in Figure 4, as described below:

Stage 1. At this first level of the initial development, construction costs are calculated by multiplying the homogenized surface area by the selling price per square metre of the finished building divided by the coefficient (Ksg), whose value is a function of the cost of the land and the costs and benefits of the construction company.

Stage 2. At this second initial study level, the construction costs are calculated by multiplying the mean unitary cost per cubic metre of projects of similar characteristics by the cubic metres projected.

Stage 3. In this third level of the draft project, the construction costs are estimated by the product of the georeferenced material cost of construction (Cg), comprising the roof, façade, interior volume and “footprint” of the building (all increased by the thematic parameter (Pt) which takes into consideration general costs and the benefits of the construction company.

Stage 4. At this fourth level of the basic project estimation, basic plans and specifications are already available, and the predimensioning of the construction cost can be broken down into three chapters: (I) roof and façade, (II) interior functional uses and (III) foundations and basements. The result of the above calculation is then weighted by the parameters management, project and execution (Pg + Pp + Pe), which provides the closed estimate of the projected work.

Stage 5. At this level, the calculation is based on the selling value minus the cost of the land, promotion costs and benefits of the construction company, giving the construction costs of the project as “remainder”.

The results represent construction costs with a deviation range of [4.79% - 9.52%] over the actual costs. This error is less than the 10% maximum that was originally proposed as the objective and hypothesis of this study.

Table 3 reveals that the further one advances through the model's calculation levels, the better the approximation of the estimated value to the real and final cost of the planned construction. In short, Level 1 (market evaluation of the initial project) provides a greater deviation than Level 5 (market evaluation of the basic project) [+ 6.93 compared with + 4.79 %]. Level 2 (Construction costs in previous study phase) gives a higher deviation than the subsequent phases of calculating construction costs, Level 3 (pre-project) and Level 4 (basic project) [+ 9.52 % compared with + 6.55 % and + 5.46 %, respectively] .

TABLE III. COST ESTIMATES PLANNED BUILDING (B1/Cb/XXX:159 RESIDENCES) AND CALCULATION OF DEVIATION % OVER REAL COST

Calculation level	REAL FINAL COST (2013) OF BUILDING B1/Cb/XXX=159 Residences (Murcia/Spain: 13.609.803€) CALCULATIONS FOR ESTIMATING CONSTRUCTION COSTS BY CONTRACT (without taxes)	% error deviation
	<p>Stage 1: Valuation of initial development (Vpi): [Cc= Vm/Ksg]</p> <p>Total constructed surface area = 24.310m² Homogenized surface area of "entire residence" = (433 m².Ex1,214)+ (13.861 m²Vx1,000)+ (1.098 m².Lx0,435) + (8.214 m².Gx0,565)+(704 m².Tx0,649)= <u>Sh=19.974 m²h.V</u></p> <p>Cc.1 = $\frac{Cc.0}{Sh} \times Vm = \frac{Vm}{Ksg} \times m2h.V = 2.550€/m2c : 3,50 \times 19.974 = \mathbf{14.552.486 €}$</p>	+6,93%
	<p>Stage 2: Preliminary cost studies (Cep): [M3xFgxFa]</p> <p>Total projected volume= 78.865M³e; €/M³e (2013)= 189 €/M³ updated (Table 2)</p> <p>Cc.2 = $\frac{€/M3 real}{M3e projected} \times M3e projected = 189€/M3 real \times 78.865 M3 projected = \mathbf{14.905.485 €}$</p>	+9,52%
	<p>Stage 3: Drafting cost (Cap): [(Ex + In + Em)%Pt]</p> <p>Cg = Cost material execution x F location</p> <p>Cc.3 = $\frac{(Cg) Cost M.E. location}{Pt} + \frac{23\% Pt specific parameter}{Pt} = [(1.976m2Q \times 172€/m2Q) + (10.852m2Fx152€/m2F) + (8 UdA \times 36.600€/UdA) + (1.461M3E \times 134€/M3E) + (45.741M3V \times 134€/M3V) + (4.941M3L \times 58€/M3L) + (2.112M3T \times 87€/M3T) + (24.642M3G \times 76€/M3G) + (8.661m2H \times 119€/m2H)] \times x[Fg = Murcia = 1,000] + [23% over (Cg)] = \mathbf{Cc.3} = \mathbf{14.733.913€}$</p>	+6,55%
	<p>Stage 4: Cost basic project (Cpb): [(I+II+III)x(Pg+Pp+Pe)] (NTE/CTE)</p> <p>Cc.4 = $\frac{(Cg) Cost M.E. location}{Pt} + \frac{(€Pt) specific parameter}{Pt} = [(I) Exterior + (II) Interior + (III) Built-in] \times [Pg + Pp + Pe]$</p> <p>(I) Exterior = $[(1.976 m2Q \times 172 €/m2Q) + (8.580 m2 Fm \times 110€/m2 Fm) + (2.262m2 Fh \times 365 €/m2Fh)] = \mathbf{2.109.302€ EXTERIOR}$</p> <p>(II) Interior = $[(8 UdA \times 27.200€/UdA) + (443m2 \times E \times 420 €/m2E) + (620m2 B1 \times 1.495 €/m2B1) + (803m2 B2 \times 1.346 €/m2B2) + (1.515m2Cx 592€/m2C) + (1.604m2V \times 506€/m2V) + (461m2L \times 413€/m2L) + (2.120m2D1 \times 357 €/m2D1) + (2.450m2D2 \times 319€/m2D2) + (4.287m2S \times 295 €/m2S) + (1.098m2L \times 159€/m2L) = \mathbf{7.287.932€ INTERIOR}$</p> <p>(III) Built-in = $(8UdA \times 9.100 UdA) + (8.214m2S \times 328€/m2S) + (8.661m2H \times 119m2H) = \mathbf{2.976.251 € BUILT-IN}$</p> <p>$€ Pt = Pg+Pp+Pe = 6% + 4% + 6% = 16% sobre (I) + (II) + (III).$ Cc.4 = $[(I) + (II) + (III)] \times Fg \times 1,16 (€Pt) = (2.109.302€ + 7.287.932€ + 2.976.251€) \times 1,000 \times 1,16 = \mathbf{14.353.243 €}$</p>	+5,46%
	<p>Stage 5: Valuation basic development (Vpb): Vm= Sr (ue) + Cc(ui) + Gp + Bp; [Cc(ui) = Vm - Sr(ue) - Gp - Bp]</p> <p>Cc.5 = $\frac{Vm - Sr(ue) - Gp - Bp}{m2h.V} = [Vm - Sr(ue) - Gp - Bp] \times m2h.V = \mathbf{2.550€/m2c - (35% sobre/2.550) - (37% sobre/2.550)} \times 19.974m2h.V = \mathbf{Cc.5} = [2.550€/m2c - 893€/m2c - 943 €/m2c] \times [19.974m2h.V] = \mathbf{14.261.436 €}$</p>	+4,79%

Source: the authors

VI. CONCLUSION

The construction cost estimation systems used in Spain are very underdeveloped, thanks to their general disuse by technicians and professionals from the construction sector. At the same time, the Spanish regulatory framework establishes the need to specify a cost for the project during the design stage (Technical Building Code).

Therefore, the value of this research lies in the importance of specifying cost-approximation models that can be used as useful tools for construction work and the development of building projects.

The model is conceptually based on the three pillars of architecture as described by Vitruvius in his "Ten Books on Architecture": beauty (exterior envelope) + utility (interior functional space) + solidity (footprint on the land).

Our conclusion with regard to the practical application of the Pcr.5n model is that it has fulfilled both its original objectives and formulated hypotheses, achieving a level of precision in estimating costs that is better than 90%. Specifically, the resulting deviations are less than 10%, and range from 4.8% to 9.5% in the analyzed control group.

Additionally, the practical application of this model is fast and simple throughout its five levels of implementation.

This model incorporates the innovative features of volumetric calculation and the box method, neither of which is habitually used in Spain, but whose application is common throughout as another countries like Germany, United States and Australia. The incorporation of these tools is of particular interest given that they result in a significant reduction in margins of error.

REFERENCES

- [1] Asworth, A. (2004) Cost studies of buildings. Pearson Education Limited, 4th ed.
- [2] BKI (2012) Baukosten Gebäude. Baukosteninformationszentrum. Stuttgart.
- [3] Carvajal, E. (1992) El predimensionado de Coste en Arquitectura. Consejería de Obras Públicas y Transportes de Andalucía
- [4] Cheung, F. (2005) - Development and Testing of a Method for Forecasting Prices of Multi-Storey Buildings during the Early Design Stage: the Storey Enclosure Method Revisited. PhD Thesis. Queensland University of Technology (Australia)
- [5] Cox, J. & William, F. (1996) Square Foot Estimating Methods. R.S. Means Company, Inc.
- [6] Ferry, D.J., Brandon, P.S. & Ferry, J.D. (2006) Cost planning of buildings. Blackwell Publishing. 7th ed.
- [7] Flanagan, R & Tate, B. (1997) Cost control in planning design. Blackwell Science.
- [8] Jaggard, D. & Smith, Jim. (2007) Building cost planning for the design team. Elsevier Science, 2nd. Ed.
- [9] Kirkham, R. (2008) Cost planning of buildings. Blackwell Publishing.
- [10] Langston, C. A. (2005) Life-Cost approach to building evaluation. Elsevier.
- [11] Olusegun, E. , Olusola. S. and Opawole, A. (2011) Comparative accuracy of area, storey enclosure and cubic methods in preparing preliminary estimate in Nigeria. Macmillan Publishers
- [12] Paricio, I. (1971) Predimensionado de costos en la vivienda. Colegio Oficial de Arquitectos de Cataluña y Baleares
- [13] Pina, P. (1989). Banco de costos en obras de Arquitectura y Urbanismo. 1989/90: obra nueva, restauración, rehabilitación y urbanismo. (Publicación declarada de interés profesional por el Consejo Superior de los Colegios de Arquitectos de España) Coamu, Murcia
- [14] Pina, P. (1991). Banco de costos en obras de Arquitectura y Urbanismo 1991/92: obra nueva, restauración, rehabilitación y urbanismo. Coamu, Murcia
- [15] Pina, P. (2004) Base de precios/costos de construcción de la Región de Murcia: Edificación y urbanización. Coamu, Coaatmu, Frecom y Ucam, Murcia
- [16] Vitruvio, M. (1787) Los diez libros de Arquitectura – Joseph Ortiz – Imprenta Real de Madrid