

Closure to “A cantilever approach to estimate bending stiffness of buildings affected by tunnelling” by Twana K. Haji, Alec M. Marshall, and Walid Tizani

Twana Kamal Haji^{a,*}, Alec M. Marshall^a, Walid Tizani^a

^a*Department of Civil Engineering, Faculty of Engineering, University of Nottingham, Nottingham, United Kingdom.*

1 The discussion of Franza and DeJong (2018) raises some interesting points.
2 The discussion covers three main areas, namely [1] the proposed method for
3 estimating building bending stiffness, [2] the assumed boundary condition for
4 the building base columns, and [3] the utilisation of the proposed method.
5 Below are some additional comments organised according to these points.
6 [1] Franza and DeJong (2018) highlighted that the point-load analogy (i.e.
7 bending stiffness = force/deflection) used in [Haji et al. \(2018\)](#) to develop
8 equations for estimating the bending stiffness of a building includes the
9 effect of shear and bending deformations, and referred to this as the ‘total
10 stiffness’. It was suggested that the contribution of shear and bending should
11 be distinguished for the evaluation of building bending stiffness, which is
12 sensible. We simply note that the intention of the proposed method was not
13 to follow a strict analytical scheme; it is intended as a simplified approach
14 to estimate building bending stiffness that attains a good level of accuracy
15 (by virtue of its development with rigorous numerical analyses) and is able

*Corresponding author

Email address: twana.k.haji@gmail.com (Twana Kamal Haji)

16 to capture features that are not incorporated in existing analytical methods
17 (e.g. constraint of building due to length in unaffected zone).

18 Franza and DeJong (2018) also commented on the comparison of total
19 bending stiffness, K_b , with values provided using the method of [Franzius et al.](#)
20 (2006), where flexural rigidity (EI) does not account for shear-type flexibility.
21 We agree that, due to the underlying differences in the approaches, a strict
22 comparison between the methods is not possible, however we felt that an
23 attempt to put results within the context of existing methods was worthwhile.
24 The original paper discusses some differences between the proposed method
25 and those provided by [Franzius et al. \(2006\)](#) and [Potts and Addenbrooke](#)
26 (1997), including boundary conditions and length of building affected by
27 tunnelling; addition of ‘total’ versus ‘bending only’ stiffness to the list of
28 differences between the methods is a useful contribution.

29 [2] Franza and DeJong (2018) noted that the physical basis of the assumed
30 fixed boundary conditions in the original paper should be clarified. We
31 completely agree that the role of the foundation scheme is an important
32 parameter in determining the response of the building. The assumed fixed
33 boundary condition at the base of columns may not be realistic for some
34 foundation types, such as single footings or combined (strip) footings running
35 parallel to the tunnel axis, since horizontal displacements and rotations can
36 have an impact on the building behaviour. For this reason, the methodology
37 is most applicable to reasonably large, reinforced concrete framed buildings
38 which are likely to have combined or raft foundations rather than single
39 shallow footings. In such foundation cases, reinforced concrete base columns
40 would behave reasonably rigidly, in a way that is close to a fixed support. We

41 would also note that a fixed boundary is a popular option in the structural
42 analysis and design of reinforced concrete buildings in static cases when
43 columns are subjected to large axial forces and small bending moments (due
44 to lateral loads), where large foundations are provided (Duggal, 2009).

45 [3] Franza and DeJong (2018) presented two main points related to the
46 utilisation of the proposed methodology. First, it was noted that the length
47 of the building influenced by tunnelling is fixed and does not depend on
48 soil-structure interaction. The developed equations will of course lead to more
49 realistic results when the building length affected by tunnelling is predicted
50 accurately, however the focus of the proposed method was not to concentrate
51 on this aspect. In addition, results from the proposed method show that
52 building stiffness does not vary considerably if two or more building panels
53 are affected (refer to Figure 15a of the original paper), which will be the case
54 for most practical scenarios).

55 Second, Franza and DeJong (2018) commented on the applicability of the
56 proposed method within the currently accepted modification factor frame-
57 works (e.g. works proposed by Franzius et al. (2006) and Giardina et al.
58 (2015)). These frameworks mainly depend on the flexural rigidity (EI), while
59 the method proposed by Haji et al. (2018) considers important additional
60 parameters that influence the bending stiffness of a building. As previously
61 discussed, this makes comparison of results from the proposed methodology
62 against those from existing methods difficult. We feel that development of
63 building damage assessment methods that incorporate some of the important
64 features addressed by Haji et al. (2018) are needed but agree with Franza
65 and DeJong (2018) in that this is an area that requires further work.

- 66 Duggal, S., 2009. Design of steel structures, 3rd Edition. Tata McGraw-Hill
67 Education.
- 68 Franzius, J. N., Potts, D. M., Burland, J. B., 2006. The response of surface
69 structures to tunnel construction. Proceedings of the Institution of Civil
70 Engineers-Geotechnical Engineering 159 (1), 3–17.
- 71 Giardina, G., DeJong, M. J., Mair, R. J., 2015. Interaction between surface
72 structures and tunnelling in sand: Centrifuge and computational modelling.
73 Tunnelling and Underground Space Technology 50, 465–478.
- 74 Haji, T. K., Marshall, A. M., Tizani, W., 2018. A cantilever approach to
75 estimate bending stiffness of buildings affected by tunnelling. Tunnelling
76 and Underground Space Technology 71, 47–61.
- 77 Potts, D., Addenbrooke, T., 1997. A structure's influence on tunnelling-
78 induced ground movements. Proceedings of the ICE-Geotechnical Engineer-
79 ing 125 (2), 109–125.