

University of New Mexico
UNM Digital Repository

Electrical & Computer Engineering Faculty
Publications

Engineering Publications

6-4-2006

Experimental investigation of active feedback control of turbulent transport in a magnetized laboratory plasma

Chaouki T. Abdallah

M. Gilmore

S. Xie

S. Will

P. Ram

See next page for additional authors

Follow this and additional works at: https://digitalrepository.unm.edu/ece_fsp

Recommended Citation

Abdallah, Chaouki T.; M. Gilmore; S. Xie; S. Will; P. Ram; A.G. Lynn; C. Watts; A.S. Ware; and L. Pangioni. "Experimental investigation of active feedback control of turbulent transport in a magnetized laboratory plasma." *The 33rd IEEE International Conference on Plasma Science* (2006): 237. doi:10.1109/PLASMA.2006.1707109.

This Article is brought to you for free and open access by the Engineering Publications at UNM Digital Repository. It has been accepted for inclusion in Electrical & Computer Engineering Faculty Publications by an authorized administrator of UNM Digital Repository. For more information, please contact disc@unm.edu.

Authors

Chaouki T. Abdallah, M. Gilmore, S. Xie, S. Will, P. Ram, A.G. Lynn, C. Watts, A.S. Ware, and L. Pangioni

**EXPERIMENTAL INVESTIGATION OF ACTIVE
FEEDBACK CONTROL OF TURBULENT
TRANSPORT IN A MAGNETIZED LABORATORY
PLASMA***

M. Gilmore, S. Xie, S. Will, P. Ram, A.G. Lynn, C. Watts,
and C.T. Abdallah

*University of New Mexico, MSC01 1100, 1 University of
New Mexico
Albuquerque NM 87131-0001 USA*

A.S. Ware

*University of Montana, 32 Campus Dr #1080
Missoula, MT 59812, USA*

L. Pangioni

Universita' di Roma, Tor Vergata, Rome, Italy

Many toroidal fusion devices now routinely generate edge and/or core transport barriers, where heat and particle transport are reduced far below Bohm diffusion levels. However, minimal particle transport is not necessarily desirable, since it can lead to core impurity accumulation, or alpha particle buildup. Ideally, active, stable control over the transport, rather than simple minimization, could be obtained. To this effect, research is now underway to investigate active control of particle transport. Turbulence and transport dynamics are, of course, strongly nonlinear, and apparently not deterministic. However, modern nonlinear control methods now exist, such as chaotic control and fuzzy control, which do not rely on a model of the system dynamics to affect stable control. Experiments are being conducted in the new HELCAT (HELicon-CATHode) linear device at UNM. HELCAT is a 4 m long device, with $B < 0.22$ T, and cathode-produced densities, $n \sim 1-5 \times 10^{12}$ cm⁻³. Sheared ExB flows, generated via biased concentric rings, will be utilized to modify the transport. Fluctuations and flux will be monitored with probe arrays. Additionally, a 1D transport code is being utilized to model the system in order to investigate possible control methods numerically. Initial experimental and modeling results will be presented.

* Work supported by the U.S. D.o.E. under grant no.
DE-FG02-04ER54791