



UNIVERSITI PUTRA MALAYSIA

ROBOTIC SYSTEM FOR HAZARDOUS CHEMICAL EXPERIMENT

JENNY TEH CHENG CHOO

FK 2002 56

ROBOTIC SYSTEM FOR HAZARDOUS CHEMICAL EXPERIMENT

By

JENNY TEH CHENG CHOO

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirement for the Degree of Master of Science**

July 2002



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirements for the degree of Master of Science

ROBOTIC SYSTEM FOR HAZARDOUS CHEMICAL EXPERIMENT

By

JENNY TEH CHENG CHOO

July 2002

Chairman: Dr. Ishak Bin Aris

Faculty: Electrical and Electronic Engineering

Normally the experiments conducted in laboratories are done manually. This may lead to unpredictable accidents. It can cause damage to both experiment apparatus and its user. Results obtained from the experiment conducted manually are not accurate especially if the same experiment has to be repeated for many times. This technique needs to be improved.

The main objective of this project is to provide a robotic system that is capable of handling hazardous chemical processing and experiments at laboratories. It can be reprogrammed to perform various tasks with flexible degrees of freedom. This



system is called Robolab. This project starts from the development of a simple concept of XYZ movements and gripper, into a final form of a Cartesian robot.

The main structure of the Robolab can be divided into software and hardware parts. The software is responsible to drive the robotic arms in order to move to a precise position and at the same time control the inputs and outputs devices of the system. The program consists of various functions such as home routine, stop routine, process routine, jog/manual routine and on-error routine. Meanwhile, the hardware of the Robolab system can be divided into electrical and mechanical modules.

The electrical module consists of a power distribution system, a SmartStep/3 control board and a personal computer. The mechanical consists of an end effector, a pneumatic system, a Z-axis module, a Y-axis module, an X-axis module, a pipette module, a vibrator module, a conveyor belt system, a system base and jigs and fixtures module.

A personal computer is needed to download program into the EPROM of the motion controller through the connection of RS232 host link system. The motion controller acts as the main processor of the robotic system. The actuators are used to drive the mechanical robotic arm. This robot also has a built-in fault detection system. It will inform its main controller if any particular faults occur to the system.

The SmartStep/3 controller is chosen for this project to control the robot. CTERM, a terminal emulator is specially configured for the controller to use on PC. MINT's flexible and powerful command set is used as a solution to motion control applications.

From the experimental results, it is proven that the proposed robotic arm was successfully designed, constructed and controlled.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untk ijazah Master Sains

SISTEM ROBOTIK UNTUK UJIKAJI BAHAN KIMIA MERBAHAYA

Oleh

JENNY TEH CHENG CHOO

Julai 2002

Pengerusi: Dr. Ishak Bin Aris

Fakulti: Kejuruteraan Elektrik dan Elektronik

Lazimnya, eksperimen-eksperimen di dalam makmal-makmal dilakukan secara manual. Ini mungkin membawa kepada kemalangan yang tidak dapat dijangka. Ia, boleh menyebabkan kerosakan pada bahan eksperimen dan mengancam keselamatan pengguna. Selain itu, keputusan-keputusan yang diperolehi daripada eksperimen yang dijalankan secara manual adalah kurang tepat khususnya apabila eksperimen yang sama perlu banyak diulang. Jadi, teknik ini perlu diperbaiki.

Tujuan utama yang mendorong kepada pembinaan projek ini adalah untuk merekacipta suatu sistem yang mampu mengendalikan pemprosesan dan pengujian bahan kimia yang berbahaya di makmal-makmal. Ianya boleh diaturcarakan untuk

melakukan pelbagai jenis tugas dengan darjah kebebasan yang fleksibel. Sistem ini dikenali sebagai Robolab. Projek ini bermula dari pembangunan satu konsep mudah pergerakan XYZ, sehinggalah ke suatu bentuk robot jenis Kartesian.

Proses penghasilan projek ini melibatkan pembangunan bahagian perisian dan bahagian perkakasan. Bahagian perisian bertanggungjawab untuk mengawal kedudukan lengan robot dengan tepat dan pada masa yang sama dapat mengawal peranti-peranti masukan serta keluaran sistem ini dengan bijak. Program yang ditulis mengandungi pelbagai fungsi seperti rutin asalan, rutin reset, rutin proses, rutin manual dan juga rutin semasa ralat. Sementara itu, perkakasan untuk sistem Robolab boleh dibahagikan kepada modul elektrik dan modul mekanikal.

Modul elektrik merangkumi sistem pengagihan kuasa, pengawal SmartStep/3 dan komputer. Bahagian mekanikal meliputi pencengkam, sistem pneumatik, modul paksi Z, modul paksi Y, modul paksi X, modul pipet, modul penggerak, sistem konveyor, tapak dan modul 'jigs and fixtures'.

Sebuah komputer diperlukan untuk memasukkan program yang ditulis ke dalam EPROM pada pengawal melalui rangkaian RS232. Pengawal gerakan ini bertindak seperti pemproses; utama kepada sistem robotik ini. Penggerak digunakan untuk memacu segala pergerakan yang diarahkan. Sistem ini juga mempunyai pengesan ralat dalaman, dimana sistem kawalan utama akan bertindak sekiranya berlaku ralat di dalam sistem keseluruhan.

Sistem kawalan SmartStep/3 telah dipilih dalam projek ini untuk mengawal robot. CTERM, suatu 'terminal emulator', dikonfigurasi supaya sistem kawalan dapat digunakan dengan komputer. MINT ialah suatu bahasa tahap tinggi yang mampu memberikan penyelesaian kepada penggunaan yang luas di dalam industri kawalan pergerakan.

Daripada keputusan ujikaji yang dijalankan, ternyata bahawa sistem robot ini berjaya direkabentuk, dibina dan dikawal.

ACKNOWLEDGEMENTS

First and foremost, I would like to thank Dr. Ishak Aris for supervising me in this project and for being my mentor in many aspects of this project. Through his patience and endless guidance, I managed to understand the fundamentals of many concepts, which includes hardware and software.

I would like to express my gratitude and sincere thanks to Professor Madya Ir. Dr. Norman Mariun and Dr. Sinan Mahmud, as project co-supervisors and for passing their knowledge to me. It has been part of my personal goal to get involved in a project that enables me to design and develop an automation system, a chance I never had previously. Many thanks are conveyed to the staff of Faculty of Engineering, especially to En. Tajul Ariffin and En. Suleiman, who have provided me the equipment and suggestions to carry out the project.

I would also like to thank my friends and contacts in industry. Jonathan Teoh from ELCOM Automation Company, Y.S. Chee and J.H. Ong from Computer Services and Automation Company, who have shared their views regarding trends in automation with me in hundreds of discussions. They have discussed their field of expertise, allowing me to expand my horizons and keep on top of new developments.

Last but not least, I would like to thank my family and all my friends who have worked together with me, giving me moral support and ideas to complete this project.




I certify that an Examination Committee met on 18th July 2002 to conduct the final examination of Jenny Teh Cheng Choo on her Master of Science thesis entitled "Robotic System for Hazardous Chemical Experiment" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

SAMSUL BAHARI, Ph.D.
Faculty of Engineering,
Universiti Putra Malaysia
(Chairman)

ISHAK BIN ARIS, Ph.D.
Faculty of Engineering,
Universiti Putra Malaysia
(Member)

SINAN MAHMUD, Ph.D.
Faculty of Engineering,
Universiti Putra Malaysia
(Member)

NORMAN MARIUN, Ph.D.
Associate Professor
Faculty of Engineering,
Universiti Putra Malaysia
(Member)


SHAMSHER MOHAMAD RAMADILI, Ph.D.
Professor/Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date : 13 SEP 2002

This Thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfillment of the requirement for the degree of Master of Science. The members of the Supervisory Committee are as follows:

ISHAK BIN ARIS, Ph.D.
Faculty of Engineering,
Universiti Putra Malaysia
(Chairman)

SINAN MAHMUD, Ph.D.
Faculty of Engineering,
Universiti Putra Malaysia
(Member)

NORMAN MARIUN, Ph.D.
Associate Professor
Faculty of Engineering,
Universiti Putra Malaysia
(Member)

AINI IDERIS, Ph.D.
Professor/ Dean,
School of Graduate Studies,
Universiti Putra Malaysia

Date:



I hereby declare that the thesis is based on my original work except for quotations and citations, which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.



JENNY TEH CHENG CHOO

Date: 28/9/2002

TABLE OF CONTENTS

	Page
ABSTRACT	ii
ABSTRAK	v
ACKNOWLEDGEMENTS	viii
APPROVAL SHEETS	ix
DECLARATION FORM	xi
TABLE OF CONTENTS	xii
LIST OF TABLES	xvi
LIST OF FIGURES	xvii
LIST OF ABBREVIATIONS	xxii
LIST OF SYMBOLS	xxiv

CHAPTER

1	INTRODUCTION	
1.1	Why Robotic System for Hazardous Chemical is Important	1.1
1.2	Aims and Objectives	1.2
1.3	Overview of the Project	1.3
1.4	Features and Limitations of the Robolab	1.7
1.5	Layout of the Thesis	1.9
2	LITERATURE REVIEW	
2.1	The Study of Robot	2.1
	2.1.1 Automation and Robots	2.2
	2.1.2 Definition of Robot	2.4
2.2	Robot Classification	2.5
	2.2.1 Drive Technologies	2.5
	2.2.2 Work-Envelope Geometries	2.6
	2.2.3 Motion Control Methods	2.11
2.3	Applications	2.12
2.4	Robot Specifications	2.14
	2.4.1 Number of Axes	2.15
	2.4.2 Capacity and Speed	2.16
	2.4.3 Reach and Stroke	2.17
	2.4.4 Tool Orientation	2.19
	2.4.5 Repeatability, Precision, and Accuracy	2.22
	2.4.6 Operating Environment	2.28
2.5	Types of Controllers and Software Used in Industries	2.29
	2.5.1 Programmable Logic Controller (PLC)	2.29
	2.5.1.1 Definition of PLC	2.29
	2.5.1.2 Advantages of PLC	2.29
	2.5.1.3 Disadvantages of PLC	2.30
	2.5.2 Advance Control Language (ACL)	2.31
	2.5.2.1 Overview of ACL	2.31
	2.5.2.2 Coordinate Systems	2.32



2.5.3	Microcontroller System	2.33
2.5.4	The Smart Step Controller (3-Axis Controller)	2.33
	2.5.4.1 Introduction	2.34
	2.5.4.2 Controller's Features	2.34
2.5.5	The Terminal Emulator Program (cTERM)	2.35
2.5.6	Motion Interpreter (MINT) Language	2.35
	2.5.6.1 Introduction	2.35
	2.5.6.2 MINT Version	2.36
2.6	Pneumatic System	2.36
2.7	Summary of Literature Review	2.37

3 METHODOLOGY

3.1	System Design Approach	3.1
	3.1.1 Identifying the Problem Category	3.1
	3.1.2 Flowchart of the System	3.4
	3.1.3 Input and Output Assignment of the System	3.6
	3.1.4 Test, Evaluation and Troubleshooting	3.9
3.2	Mechanical Stage Design and Construction	3.9
	3.2.1 X-axis Module	3.10
	3.2.1.1 Leadscrew	3.11
	3.2.1.2 Flexible Shaft Coupling	3.12
	3.2.1.3 Approximation	3.13
	3.2.2 Y-axis Module	3.22
	3.2.2.1 Recirculating Ball Screw	3.25
	3.2.2.2 Approximation	3.25
	3.2.3 Z-axis and End Effector Modules	3.31
	3.2.4 Pipette Module	3.33
	3.2.5 Vibrator, Jigs and Fixtures Modules	3.35
	3.2.6 Conveyor Belt and System Base	3.36
	3.2.7 Electro-Pneumatic System	3.38
	3.2.7.1 Consideration of Air Pressure	3.38
	3.2.7.2 The Design of Pneumatic System Layout	3.40
3.3	Electrical Module	3.46
	3.3.1 Stepper Motor	3.46
	3.3.1.1 Basic Principle of a Stepper Motor	3.47
	3.3.1.2 Commutation	3.47
	3.3.2 Development of Electrical Wiring	3.48
	3.3.2.1 Small Signal Wiring	3.49
	3.3.2.2 Power Wiring	3.60
	3.3.2.3 Power Distribution System	3.64
3.4	Software Testing and Development	3.67
	3.4.1 Development of the Configuration File	3.67
	3.4.2 Development of the Program File	3.68
	3.4.2.1 Process Routine	3.69
	3.4.2.2 Jog/Manual Routine	3.77
	3.4.2.3 On-Error Routine	3.78
	3.4.2.4 Home and Stop Routines	3.79
3.5	System Integration	3.80

4	RESULTS AND DISCUSSION	
4.1	Pipette System	4.1
	4.1.1 Test Conducted to the Pipette Module	4.4
	4.1.1.1 Adjustment of the Level Sensor	4.4
	4.1.1.2 Control of the Software	4.6
4.2	Gripper System	4.7
4.3	X-axis Module	4.10
	4.3.1 Motion Simulation	4.10
	4.3.2 Repeated Positioning Accuracy	4.12
	4.3.3 Linear Speed Performance	4.13
4.4	Y-axis Module	4.14
	4.4.1 Motion Simulation	4.14
	4.4.2 Repeated Positioning Accuracy	4.16
	4.4.3 Linear Speed Performance	4.18
4.5	Conveyor Module	4.19
4.6	Safety Features	4.21
	4.6.1 Electrical Protection	4.21
	4.6.2 Mechanical Protection	4.21
	4.6.3 Software Protection	4.21
	4.6.4 User Safety Boundary	4.22
4.7	Electrical Module	4.23
	4.7.1 Optical Sensor	4.23
	4.7.2 Electro-Pneumatic System	4.25
	4.7.3 Stepper Motor Speed Limitation	4.27
4.8	Software Module	4.28
	4.8.1 Handling of Errors	4.28
	4.8.2 Data Recording	4.28
	4.8.3 Optimisation of Code	4.30
	4.8.3.1 Code Size	4.30
	4.8.3.2 Execution Speed	4.31
	4.8.4 Upload/Download a File	4.33
	4.8.5 MINT Execution Speed	4.34
4.9	System Integration	4.36
4.10	Ability of the Robolab	4.39
	4.10.1 Advantages	4.39
	4.10.2 Disadvantages	4.40
5	CONCLUSION	
5.1	Conclusion	5.1
5.2	Recommendations	5.3
	REFERENCES	R.1

APPENDICES

Appendix A: Mechanical Drawings	A.1
Appendix B: Program	B.1
Appendix C: Electrical Wiring	C.1
Appendix D: Mechanical Components	D.1
Appendix E: Electrical Components	E.1
Appendix F: Pneumatic System	F.1
VITA	V.1



LIST OF TABLES

Table	Page
1.1 Limitations of the Robolab	1.8
2.1 Types of Robot Joints	2.6
2.2 Robot Work Envelopes Based on Major Axes	2.7
2.3 Types of Robot Motion Control	2.11
2.4 U. S. Robot Market (1986)	2.12
2.5 Distribution of World Robot Population (1984)	2.14
2.6 Robot Characteristics	2.15
2.7 Axes of a Robotic Manipulator	2.16
2.8 Yaw, Pitch, and Roll Motion	2.21
2.9 Horizontal and Vertical Precision	2.24
3.1 Summary of Moment of Inertia for X-axis	3.21
3.2 Summary of Moment of Inertia for Y-axis	3.30
3.3 Power Distributions	3.63
4.1 Accuracy of the Liquid Level	4.5
4.2 Accuracy of the Liquid Level for Each Adjustment	4.6
4.3 Accuracy of the Liquid Level if Timer is Used	4.7
4.4 Speed and Performance	4.14
4.5 Speed and Performance	4.18
4.6 Response Curve	4.23
4.7 Operation Timing Results	4.35
4.8 Robot Specifications	4.37



LIST OF FIGURES

Figure	Page
1.1 General Structure of Robolab	1.5
1.2 Software Structure of the Robolab	1.5
1.3 Mechanical Module of the Robolab	1.6
1.4 Electrical Module of the Robolab	1.7
2.1 Relative Cost-effectiveness of Soft Automation	2.3
2.2 Cartesian Robot	2.8
2.3 Cylindrical Robot	2.9
2.4 Spherical Robot	2.9
2.5 SCARA Robot	2.10
2.6 Articulated Robot	2.11
2.7 Robots Used in Industries	2.14
2.8 Reach and Stroke of a Cylindrical Robot	2.18
2.9 Yaw, Pitch and Roll of Tool	2.19
2.10 Adjacent Tool Positions	2.22
2.11 Horizontal Precision of a Cylindrical Robot	2.24
3.1 Design Approach for Software/Hardware and Their Implementation	3.2
3.2 Project Activities	3.3
3.3 Flowchart Design of the System	3.5
3.4 Block Diagram of Input and Output Modules	3.7
3.5 X-axis Module	3.10
3.6 Positions of Slot Sensors	3.11



3.7	Leadscrew Implemented in X-axis Module	3.11
3.8	Helical Coupling	3.12
3.9	Connections of a Helical Coupling	3.12
3.10	Graph of Efficiency Vs Friction Coefficient	3.17
3.11	Leadscrew	3.19
3.12	Y-axis Module	3.22
3.13	Slot Sensors on the Far Right Position	3.23
3.14	Slot Sensor on the Other End of Y-axis Module	3.23
3.15	Optical Sensors Attached on the Y-axis Module	3.23
3.16	Assembly of the Y-axis	3.24
3.17	Close-up View of the Y-axis	3.24
3.18	Ball Screws Using Recirculating Balls	3.25
3.19	Z-axis and End Effector Modules	3.31
3.20	Close-up View of the Z-axis Module	3.32
3.21	Close-up View of the Z-axis and End Effector Modules	3.33
3.22	Pipette Module	3.33
3.23	Close-up View of the Pipette Module	3.34
3.24	Connection between Cylinder and Slider of the Pipette Module	3.34
3.25	Vibrator Module	3.35
3.26	Jigs and Fixtures Module	3.36
3.27	Front End of a Conveyor System	3.37
3.28	Rear End of a Conveyor System	3.37
3.29	Location of an Optical Sensor in the Conveyor System	3.37
3.30	Block Diagram of Pneumatic System	3.40



3.31	Pneumatic Layout for the Cylinders	3.41
3.32	Pneumatic Layout for Pipette Suction	3.42
3.33	Control Diagram for the Whole System	3.43
3.34	Timing Diagram for Part of the System	3.44
3.35	Air Compressor Unit	3.45
3.36	Air Filter Unit	3.45
3.37	Locations of Stepper Motors in the Proposed Project	3.46
3.38	Input Buffer and Isolation Circuit	3.49
3.39	Manual Control	3.50
3.40	Manual Control Panel	3.51
3.41	Limit Sensors Circuitry	3.52
3.42	Stop Input Circuit	3.53
3.43	Boundary Sensors	3.53
3.44	Output Driver Circuit	3.54
3.45	Relay Outputs	3.55
3.46	Relays	3.56
3.47	The Controller	3.56
3.48	Main Control System	3.57
3.49	RS232 Serial Port	3.58
3.50	Solenoid Valves	3.59
3.51	Ventilation Fans	3.59
3.52	Terminals Block	3.59
3.53	Protection Unit	3.60
3.54	Power Protection Circuit in the Proposed Project	3.61



3.55	Power Supplies Distributions Schematic Diagram	3.62
3.56	Power Supplies Used in the Project	3.63
3.57	Power Supplies Distributions	3.64
3.58	Measurements of the DC Voltages	3.66
3.59	Illustration of Linear Positional Control	3.70
3.60	Generated Linear Interpolation	3.72
3.61	Generated Circular Interpolation	3.73
3.62	Illustration of Contoured Moves	3.75
3.63	Illustration for Trapezoidal Ramp	3.76
3.64	Illustration for 'S' Ramp	3.76
3.65	Mechanical System Integration for the Project	3.81
3.66	Fast Connectors for the Electrical Control Box	3.81
3.67	Electrical Control Box	3.82
3.68	System Integration of the Project	3.82
4.1	Pneumatic Layout Diagram for Pipette Module	4.3
4.2	Level Adjustment of the Pipette Module	4.4
4.3	Results of the Level Adjustment	4.5
4.4	Gripper and Pipette Modules	4.9
4.5	Specifications of the Leadscrew Transmission System	4.10
4.6	Motion Profile of the X-axis Stepper Motor	4.11
4.7	Torque-speed Characteristic of the X-axis Stepper Motor	4.11
4.8	Repeated Positioning Length	4.12
4.9	Specifications of the Leadscrew Transmission System	4.15
4.10	Motion Profile of the Y-axis Stepper Motor	4.15

4.11	Torque-speed Characteristic of the Y-axis Stepper Motor	4.16
4.12	Repeated Positioning Length	4.17
4.13	Specifications of the Conveyor Transmission System	4.19
4.14	Motion Profile of the Conveyor System Stepper Motor	4.20
4.15	Torque-speed Characteristic of the Conveyor System Stepper Motor	4.20
4.16	Electrical Protection	4.22
4.17	User Protection	4.22
4.18	Response Curve of an Optical Sensor	4.24
4.19	Normal State of the Pneumatic Simulation	4.25
4.20	Active State of the Pneumatic Simulation	4.26
4.21	Relationship between Torque and Speed	4.27
4.22	Graph of Velocity versus Time	4.30
4.23	Mechanical Structure of the Robolab	4.36
4.24	Electrical Wiring	4.37



LIST OF ABBREVIATIONS

AC	Alternative Current
ACL	Advanced Control Language
ADC	Analog to Digital Converter
ATS	Advanced Terminal Software
CB	Circuit Breaker
CP	Continuous Path
CPU	Central Processing Unit
3D	Three Dimension
DAC	Digital to Analog Converter
DC	Direct Current
DIR	Direction
ELCB	Earth Leakage Circuit Breaker
EPROM	Erasable Programmable Read Only Memory
GND	Ground
IC	Integrated Circuit
I/O	Input and Output
MCB	Miniature Circuit Breaker
MCU	Microcontroller Unit
MINT	Motion Interpreter
PC	Personal Computer
PLC	Programmable Logic Controller



PLS	Pulse
PM	Programmer and Monitor
RAM	Random Access Memory
RST	Reset



LIST OF SYMBOLS

A	Ampere
COM	Common
D	Diameter (mm)
F	Force (kg)
g	Gravity constant
g_m	Thread angle ($^{\circ}$)
h_{wormgear}	Efficiency of the leadscrew
Hz	Hertz
I	Current (A)
J	Moment of inertia (kg mm^2)
J_o	Effective moment of inertia
l	Length (mm)
m	Mass (kg)
m_k	Friction coefficient
p	Pitch (revs/mm)
ρ	Density (kg/ mm^3)
psi	Pound per square inch
r	Radius (mm)
r	Frictional angle ($^{\circ}$)
R	Resistance
rpm	Revolution per minute
t	Time (s)