# Nature-Inspired Coordination & Self-Organisation

Autonomous Systems
Sistemi Autonomi

Andrea Omicini
andrea.omicini@unibo.it

Dipartimento di Informatica – Scienza e Ingegneria (DISI) Alma Mater Studiorum – Università di Bologna

Academic Year 2017/2018

- Nature-inspired Coordination
- Examples
- 3 Tuples
- Trends



### Next in Line...

- Nature-inspired Coordination
- 2 Examples
- 3 Tuples
- 4 Trends



### Nature-inspired Models for SOS

### Complex natural systems

- such as physical, chemical, biochemical, biological, social systems
- natural system exhibit features
  - such as distribution, opennes, situation, fault tolerance, robustness, adaptiveness, . . .
- which we would like to understand, capture, then bring to computational systems

### Nature-inspired computing (NIC)

- for instance, NIC [Liu and Tsui, 2006] summarises decades of research activities, putting emphasis on
  - autonomy of components
  - self-organisation of systems

# Multi-Agent Systems for SOS

### MAS as complex systems [Omicini and Zambonelli, 2004]

- agents as sources of complexity
  - autonomy unpredictable behaviour sociality non-compositional behaviours
- situatedness unpredictable interaction with the environment
- multi-agent systems (MAS) as sources of complexity
  - multiplicity of interacting components
  - global vs. local structure and behaviour—macro vs. micro level

#### MAS for complex systems [Zambonelli and Omicini, 2004]

#### MAS as tools for

- modelling complex systems
- engineering complex system

### Interaction & Coordination?

#### Interaction

- most of the complexity of complex computational systems MAS included comes from interaction [Omicini et al., 2006]
- along with an essential part of their expressive power [Wegner, 1997]

#### **Coordination**

- since coordination is essentially the science of managing the space of interaction [Wegner, 1997]
- coordination models and languages [Ciancarini, 1996] provide abstractions and technologies for the engineering of complex computational systems [Ciancarini et al., 2000]

# Nature-inspired Coordination for MAS

### Coordination issues in natural systems

- coordination issues did not first emerge in computational systems
- [Grassé, 1959] noted that in termite societies "The coordination of tasks and the regulation of constructions are not directly dependent from the workers, but from constructions themselves."

### Coordination as the key issue

- many well-known examples of natural systems and, more generally, of complex systems – seemingly rely on simple yet powerful coordination mechanisms for their key features—such as self-organisation
- it makes sense to focus on nature-inspired coordination models as the core of complex nature-inspired MAS

### Next in Line...

- Nature-inspired Coordination
- Examples
- 3 Tuples
- 4 Trends



#### Focus on...

- Nature-inspired Coordination
- Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- 4 Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



# Stigmergy I

### Stigmergy in insect societies

- nature-inspired models of coordination are grounded in studies on the behaviour of social insects, like ants or termites
- [Grassé, 1959] introduced the notion of stigmergy as the fundamental coordination mechanism in termite societies
- in ant colonies, pheromones act as environment markers for specific social activities, and drive both the individual and the social behaviour of ants

# Stigmergy II

### Stigmergy in computational systems

- nowadays, stigmergy generally refers to a set of nature-inspired coordination mechanisms mediated by the *environment*
- digital pheromones [Parunak et al., 2002] and other signs made and sensed in a shared environment [Parunak, 2006] can be exploited for the engineering of adaptive and self-organising MAS

#### Chemical Coordination

### Chemical reactions as (natural) coordination laws

- inspiration comes from the idea that complex physical phenomena are driven by the (relatively) simple chemical reactions
- coordinating the behaviours of a huge amount of agents, as well as the global system evolution

### Chemical reactions as (computational) coordination laws

- Gamma [Banâtre and Le Métayer, 1990] is a chemistry-inspired coordination model—as for the CHAM (chemical abstract machine) model [Berry, 1992]
- coordination in Gamma is conceived as the evolution of a space governed by chemical-like rules, globally working as a rewriting system [Banătre et al., 2001]

#### Focus on...

- Nature-inspired Coordination
- 2 Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- 4 Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



#### Field-based Coordination

#### Computational fields as coordination laws

- field-based coordination models like Co-fields [Mamei and Zambonelli, 2006] are inspired by the way masses and particles move and self-organise according to gravitational/electromagnetic fields
- there, computational force fields generated either by the mobile agents or by the pervasive coordination infrastructure – propagate across the environment, and drive the actions and motion of the agent themselves

# (Bio)chemical Coordination

#### Chemical reactions as coordination laws

- chemical tuple spaces [Viroli et al., 2010] exploit the chemical metaphor at its full extent—beyond Gamma
- data, devices, and software agents are represented in terms of chemical reactants, and system behaviour is expressed by means of chemical-like laws
- which are actually time-dependent and stochastic
- embedded within the coordination medium
- biochemical tuple spaces [Viroli and Casadei, 2009] add *compartments*, diffusion, and stochastic behaviour of coordination primitives

Issues

#### Focus on...

- Nature-inspired Coordination
- 2 Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



# Basic Issues of Nature-inspired Coordination I

Issues

#### **Environment**

- environment is essential in nature-inspired coordination
  - it works as a mediator for agent interaction through which agents can communicate and coordinate indirectly
  - it is active featuring autonomous dynamics, and affecting agent coordination
  - it has a structure requiring a notion of locality, and allowing agents of any sort to move through a topology
- nowadays, everybody knows about the essential role of environment in a MAS [Weyns et al., 2007]
- ? do we also know how to design and engineer MAS environment?

C8 - NIC & Self-Org



# Basic Issues of Nature-inspired Coordination II

#### Stochastic behaviour

- complex systems typically require probabilistic models
  - don't know / don't care non-deterministic mechanisms are not expressive enough to capture all the properties of complex systems such as biochemical and social systems
  - probabilistic mechanisms are required to fully capture the dynamics of coordination in nature-inspired systems
  - coordination models should feature (possibly simple yet) expressive mechanisms to provide coordinated systems with stochastic behaviours
- ? do we know how to embed stochastic behaviours in a MAS?

### Next in Line...

- Nature-inspired Coordination
- 2 Examples
- 3 Tuples
- 4 Trends



#### The Ancestor

#### LINDA [Gelernter, 1985]

- LINDA is the ancestor of all tuple-based coordination models
  [Rossi et al., 2001]
- in LINDA, agents synchronise, cooperate, compete
  - based on tuples
  - available in the tuple spaces, working as the coordination media
  - by associatively accessing, consuming and producing tuples
- the same holds for any tuple-based coordination model

# LINDA is not a Nature-inspired Model

### Warning

LINDA is not a Nature-inspired Model

So, why LINDA?

Why tuple-based models?



# Why Tuple-based Models? I

#### Expressiveness

- LINDA is sort of a core coordination model
- making it easy to face and solve many typical problems of complex distributed systems
- complex coordination problems are solved with few, simple primitives
- whatever the model used to measure expressiveness of coordination, tuple-based languages are highly-expressive [Busi et al., 1998]

# Why Tuple-based Models? II

#### Environment-based coordination

- generative communication [Gelernter, 1985] requires permanent coordination abstractions
- so, the coordination infrastructure provides agents with tuple spaces as coordination services
  - coordination as a service (CaaS) [Viroli and Omicini, 2006]
- they can be interpreted as coordination artefacts shaping computational *environment* [Omicini et al., 2004]
  - and used with different levels of awareness by both intelligent and "stupid" agents [Omicini, 2012]
- as such, they can be exploited to support environment-based coordination [Ricci et al., 2005]

# Why Tuple-based Models? III

#### Extensibility

- whatever its expressiveness, LINDA was conceived as a coordination model for closed, parallel systems
- ullet so, in fact, some relevant problems of today open, concurrent systems cannot be easily solved with LINDA either in practice or in theory
- as a result, tuple-based models have been extended with new simple yet powerful mechanisms
- generating a plethora of tuple-based coordination models
   [Rossi et al., 2001]

# Why Tuple-based Models? IV

### Nature-inspired extensions

- LINDA may not be nature-inspired, but many of its extensions are
- many of the coordination models depicted before
  - stigmergy [Parunak, 2006]
  - field-based [Mamei and Zambonelli, 2004]
  - chemical [Viroli et al., 2010] and biochemical [Viroli and Casadei, 2009]
- along with many others, such as
  - cognitive stigmergy [Ricci et al., 2007]
  - pervasive ecosystems [Viroli et al., 2012]
- are actually nature-inspired tuple-based coordination models

# Toward Self-organising Coordination I

### Just some is not enough

- capturing just some of the principles and mechanisms of natural systems does not ensure to capture their essence
- for instance, chemical coordination models such as Gamma and CHAM exploit the raw schema of computation as chemical reaction, but are not expressive enough to fully reproduce any non-trivial chemical system
- in fact, e.g., even the simplest model for real chemical reactions requires a notion of reaction rate
- neither Gamma nor CHAM provide for such a notion, they are not expressive enough to fully match the behaviour of real chemical systems

# Toward Self-organising Coordination II

### Self-organising coordination [Viroli et al., 2009]

- most of the traditional coordination models feature abstractions enacting coordination laws that are typically reactive, (mostly) deterministic, and global as well
- in complex systems featuring self-\* properties, instead, coordination
  patterns typically appear at the global level by emergence, from
  probabilistic, time-dependent coordination laws based on local criteria
- in particular, many coordination models either implicitly or explicitly recognise that full expressiveness requires addressing the issues of time dependency and stochasticity

### Examples I

#### STOKLAIM

 STOKLAIM [De Nicola et al., 2006] — a stochastic extension of the LINDA-derived KLAIM model for mobile coordination [De Nicola et al., 1998] — adds distribution rates to coordination primitives—thus making it possible the modelling of non-deterministic real-life phenomena such as failure rates and inter-arrival times

#### SwarmLinda

SwarmLinda [Tolksdorf and Menezes, 2004] enhances LINDA implementation with swarm intelligence to achieve features such as scalability, adaptiveness, and fault-tolerance—by modelling tuple templates as ants, featuring probabilistic behaviour when looking for matching tuples in a distributed setting

# Examples II

### Time-aware ReSpecT

ReSpecT [Omicini and Denti, 2001] generally addresses time dependency
by capturing time events and supporting the definition and
enforcement of timed coordination policies [Omicini et al., 2005]—so,
ReSpecT-programmed tuple centres can work as time-dependent
abstractions for MAS coordination [Omicini et al., 2007]

# Enough?

#### No.

- in the overall, the above-mentioned models *fail* to capture all the *essential features* of nature-inspired coordination
- this is why many novel research lines stretch existing tuple-based models to achieve the expressive power required to model and build MAS with a complexity comparable to natural systems

[Omicini and Viroli, 2011]



### Next in Line...

- Nature-inspired Coordination
- 2 Examples
- 3 Tuples
- Trends



#### Focus on...

- Nature-inspired Coordination
- 2 Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- 4 Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



# Complexity as a Multi-disciplinary Notion

#### Complex systems everywhere

- the notion of *complexity* is definitely a *multi-disciplinary* one, ranging from physics to biology, from economics to sociology and organisation sciences
- systems that are said complex are both natural and artificial ones

### Natural vs. artificial complex systems

- we observe and model complex physical systems
- we design and build complex computational systems

#### Question

 which features do all complex systems share independently of their nature?

### Complexity & Interaction

... by a complex system I mean one made up of a large number of parts that interact in a non simple way [Simon, 1962]

### Laws of complexity

- some "laws of complexity" exists that characterise any complex system, independently of its specific nature [Kauffman, 2003]
- the precise source of what all complex systems share is still unknown in essence

#### Interaction

 we argue that interaction – its nature, structure, dynamics – is the key to understand some fundamental properties of complex systems of any kind

#### Interaction in Statistical Mechanics I

#### Independence from interaction

- some physical systems are described under the assumption of mutual independence among particles—that is, the behaviour of the particles is unaffected by their mutual interaction
  - e.g., ideal gas [Boltzmann, 1964]
- there, the probability distribution of the whole system is the product of those of each of its particles
- in computer science terms, the properties of the system can be compositionally derived by the properties of the individual components [Wegner, 1997]
- → neither macroscopic sudden shift nor abrupt change for the system as a whole: technically, those systems have no phase transitions—of course, while the "independence from interaction" hypothesis holds

#### Interaction in Statistical Mechanics II

#### Interacting systems

- introducing interaction among particles structurally *changes* the *macroscopic properties*, along with the *mathematical* ones
- interacting systems are systems where particles do not behave independently of each other
- the probability distribution of an interacting system does not factorise anymore
- in computer science terms, an interacting system is *non-compositional* [Wegner, 1997]



#### Interaction in Statistical Mechanics III

#### Interacting vs. non-interacting systems

- only interacting systems can describe real cases beyond the idealised ones
  - e.g., they can explain phase transitions like liquid-gas transition and much more, such as collective emerging effects
- while a system made of independent parts can be represented by isolated single nodes, an *interacting system* is better described by nodes connected by lines or higher-dimensional objects
- from the point of view of information and communication theories, an ideal non-interacting gas is a system of *non-communicating nodes*, whereas an interacting system is made of *nodes connected by channels*

# Complexity in Statistical Mechanics I

#### The case of magnetic particles

- the simplest standard prototype of an interacting system is the one made of magnetic particles
- there, individual particles can behave according to a magnetic field which leaves their probabilistic independence undisturbed
- at the same time, two magnetic particles interact with each other, and the strength of their interaction is a crucial tuning parameter to observe a phase transition
  - if interaction is weak, the effect of a magnetic field is smooth on the system
  - instead, if the interaction is strong in particular, higher than a threshold even a negligible magnetic field can cause a powerful cooperative effect on the system



## Complexity in Statistical Mechanics II

#### Interaction is not enough

- interaction is a necessary ingredient for complexity in statistical mechanics but definitely not a sufficient one
- complexity arises when the possible equilibrium states of a system grow very quickly with the number of particles, regardless of the simplicity of the laws governing each particle and their mutual interaction
- roughly speaking, complexity is much more related to size in number, rather than to complexity of the laws ruling interaction
- → we do not need complex interaction to make interaction lead to complexity

# From Statistical Mechanics to Social Systems I

#### Large numbers

- the key point in statistical mechanics is to relate the macroscopic observables quantities – like pressure, temperature, etc. – to suitable averages of microscopic observables—like particle speed, kinetic energy, etc.
- based on the *laws of large numbers*, the method works for those systems made of a large number of particles / basic components

## From Statistical Mechanics to Social Systems II

#### Beyond the boundaries

- methods for complex systems from statistical mechanics have expanded from physics to fields as diverse as biology [Kauffman, 1993], economics [Bouchaud and Potters, 2003, Mantegna and Stanley, 1999], and computer science itself [Mézard and Montanari, 2009, Nishimori, 2001]
- recently, they have been applied to social sciences as well: there is
  evidence that the complex behaviour of many observed
  socio-economic systems can be approached with the quantitative
  tools from statistical mechanics
  - e.g., Econophysics for crisis events [Stanley, 2008]



# From Statistical Mechanics to Social Systems III

#### Social systems as statistical mechanical systems

- a group of isolated individuals neither knowing nor communicating with each other is the typical example of a compositional social system
- no sudden shifts are expected in this case at the collective level, unless it is caused by strong external exogenous causes
- to obtain a *collective behaviour* displaying *endogenous* phenomena, the individual *agents* should meaningfully *interact* with each other
- the foremost issue here is that the nature of the interaction determines the nature of the collective behaviour at the aggregate level
  - e.g., a simple *imitative* interaction is capable to cause strong polarisation effects even in presence of extremely small external inputs

## Modelling vs. Engineering

#### Physical vs. computational systems

- physical systems are to be observed, understood, and possibly modelled
  - → for physical systems, the laws of interaction, and their role for complexity, are to be taken as given, to be possibly formalised mathematically by physicists
- computational systems are to be designed and built
  - → for computational systems, the laws of interaction have first to be defined through amenable abstractions and computational models by computer scientists, then exploited by computer engineers in order to build systems

## Coordinated Systems as Interacting Systems I

#### Coordination media for ruling interaction

- defining the abstractions for ruling the interaction space in computational systems basically means to define their coordination model [Gelernter and Carriero, 1992, Ciancarini, 1996, Ciancarini et al., 1999]
- global properties of complex coordinated systems depending on interaction can be enforced through the coordination model, essentially based on its expressiveness [Zavattaro, 1998, Denti et al., 1998]
  - for instance, tuple-based coordination models have been shown to be expressive enough to support self-organising coordination patterns for nature-inspired distributed systems [Omicini, 2013]



## Coordinated Systems as Interacting Systems II

#### The role of coordination models

Coordination models could be exploited


- to rule the interaction space
- so as to *define* new sorts of *global*, macroscopic *properties* for *computational systems*, possibly inspired by physical ones

## Coordinated Systems as Interacting Systems III

#### Research perspectives

One should understand

- how to relate methods from statistical mechanics with coordination models
- whether notions such as phase, phase transition, or any other macroscopic system property, could be transferred from statistical mechanics to computer science
- what such notions would imply for computational systems
- whether new, original notions could apply to computational systems
- which sort of coordination model could support such notions



### Socio-Technical Systems

#### Humans vs. software

- nowadays, a particularly-relevant class of social systems is represented by socio-technical systems (STS) [Whitworth, 2006]
- in STS
  - active components are mainly represented by humans
  - whereas interaction is almost-totally regulated by the software infrastructure
  - where software agents often play a key role
- this is the case, for instance, of *social platforms* like FaceBook [FaceBook, 2017] and LiquidFeedback [LiquidFeedback, 2017]



# Physical & Computational Social Systems I


#### A twofold view of socio-technical systems

- the nature of STS is twofold: they are both social systems and computational systems [Verhagen et al., 2013, Omicini, 2012]
- as complex social systems, their complex behaviour is in principle amenable of mathematical modelling and prediction through notions and tools from statistical mechanics
- as complex computational systems, they are designed and built around some (either implicit or explicit) notion of coordination, ruling the interaction within components of any sort—be them either software or human ones

# Physical & Computational Social Systems II

#### Computational systems meet physical systems

- in STS, macroscopic properties could be
  - described by exploiting the conceptual tools from physics
  - enforced by the coordination abstractions
- STS could exploit both
  - the notion of complexity by statistical mechanics, along with the mathematical tools for behaviour modelling and prediction, and
  - coordination models and languages to suitably shape the interaction space



# Physical & Computational Social Systems III

#### Vision

Complex socio-technical systems could be envisioned

- whose implementation is based on suitable coordination models
- whose macroscopic properties can be modelled and predicted by means of mathematical tools from statistical physics

thus reconciling the scientist and the engineer views over systems

#### Focus on...


- Nature-inspired Coordination
- 2 Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- 4 Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



#### Coordination for Simulation I

#### Simulation of complex systems is a multidisciplinary issue

- ... ranging from physics to biology, from economics to social sciences
- no complex system of any sort can be studied nowadays without the support of suitable simulation tools
- nowadays, experiments done in silico are at least as relevant as those in vitro and in vivo



#### Coordination for Simulation II

#### Interaction issues are prominent in complex systems

- coordination technologies potential core of agent-based simulation frameworks
- in particular, self-organising nature-inspired coordination models are well suited for the simulation of complex systems
- so, coordination middleware could play a central role in the development of rich agent-based simulation frameworks for complex systems

# Case Study: Simulating Intracellular Signalling Pathways I

#### Intracellular signalling pathways

- intracellular signalling involves several molecular processes along with a huge amount of signalling elements, including several kinds of proteins
- signal transduction pathways activated by G-proteins interact with one another to form a complex network that regulates diverse cellular components and controls a wide range of cellular processes
   [Neves et al., 2002]
- the Ras-regulated signal transduction pathways are a classical example of this kind of network [Downward, 2003]

# Case Study: Simulating Intracellular Signalling Pathways II

#### Interaction issues in intracellular signalling pathways

- to model intracellular signalling systems, complex interaction that governs their behaviour should be first of all considered and understood
- though determining the kinetic equations of the biochemistry involved in vital functions is important, managing *interactions* for the cell to make the correct physiological decisions is even more so
- simulation of intracellular signalling pathways could be framed as mostly a coordination issue

# Case Study: Simulating Intracellular Signalling Pathways III

#### Biochemical coordination

- biochemical tuple spaces [Viroli and Casadei, 2009] are the core of a model for self-organising coordination (BTS-SOC)
- a biochemical tuple space is a tuple space working as a compartment where biochemical reactions take place
- tuples in BTS-SOC are associated with an activity/pertinency value, resembling chemical concentration, and allowing chemical reactants to be represented as tuples
- biochemical laws are represented as coordination laws by the coordination abstraction, evolving tuple concentration over time according to a rate in the same way as chemical substances into a solution
- also, BTS-SOC laws allow for tuple diffusion, making it possible for products to cross compartment boundaries as a result of biochemical reactions




# Case Study: Simulating Intracellular Signalling Pathways IV

# Mapping cellular components and structures involved in intracellular signalling onto BTS-SOC abstractions [González Pérez et al., 2013]

| Cellular components and structures involved in intracellular signalling                                      | Computational abstractions of the BTS-SOC model                     |
|--|---|
| Extracellular milieu and intracellular compartments (i.e., membrane, juxtamembrane region, cytosol, nucleus) | Tuple centres   |
| Signalling components (i.e., membrane receptors, proteins, enzymes and genes)                                | Chemical reactions sets   |
| Signalling molecules (i.e., first and secondary messengers), activation and deactivation signals             | Reactants and concentrations recorded as tuples in the tuple centre |

# Case Study: Simulating Intracellular Signalling Pathways V



# Some Final Remarks on Trans-disciplinary Research I

- the results of trans-disciplinary research efforts may appear quite obvious, once they are seen a posteriori
- just above, a nature-inspired model developed in computational terms (biochemical tuple spaces) is exploited as a computational support to the simulation of a natural system (intracellular signalling pathways)
  - in other terms, from the natural world to the computational one, and back—and it works, as one might expect

## Some Final Remarks on Trans-disciplinary Research II

- however, one should also understand that trans-disciplinary research succeeds when each translation of findings between the different fields involved actually enriches the associated concepts and techniques
  - above, the BTS-SOC approach features the properties deriving from its biochemical inspiration along with those of tuple-based coordination for complex computation systems
  - when brought back to the 'natural domain' as a tool for biochemical simulation, BTS-SOC fits well for its natural inspiration, but its good performance in terms of expressive capabilities and computational efficiency also depends on its tuple-based structure

## Some Final Remarks on Trans-disciplinary Research III

- so, while natural inspiration does not per se ensure the appropriateness of a computational approach to natural system simulation, it may in principle provide a sound grounding for the simulation of natural systems
  - biochemical inspiration of the BTS-SOC model seems to couple well with the properties of tuple-based coordination
  - BTS-SOC turns out to be a suitable framework for the simulation of biochemical systems

#### Focus on...

- Nature-inspired Coordination
- 2 Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- 4 Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



## Probability

- probability measures how likely some event will occur
- at its core, probability provides a mathematical framework to describe casual events
- ... where casual essentially means non-deterministic
- by definition, probability deals with single occurrences of events
- from a scientific viewpoint, a probabilistic description per se has no predictive value: it cannot really predict the precise outcome of a phenomenon
- in any case, probability provides an a priori model for non-deterministic phenomena

## Statistics & Probability

- statistics describes / analyses / interprets phenomena starting from the data available about them
- whenever a phenomenon has no a priori mathematical model (at least, not yet), statistics is concerned with getting one a posteriori from the available data
- accordingly, statistics is concerned with several occurrences of (non-deterministic) events
- probability typically provides the mathematical tools to explain data
   build a model

## Stochastic Systems

- stochastic systems are non-deterministic systems
- a stochastic system is one whose states are determined probabilistically
- more generally, any phenomenon requiring probability for its description is (at least in part) stochastic by definition
- roughly speaking, a probabilistic model for a stochastic system provides a *predictive framework* for a non-deterministic system
- → we cannot predict the single occurrence of a non-deterministic event, but we can predict the overall outcome of repeated occurrences of a non-deterministic event

## Non-determinism, Coordination & Stochastic Behaviour

- autonomous systems such as adaptive and self-\* ones are stochastic systems at their very heart
- accordingly, a foremost feature of computational models for adaptive and self-\* systems is non-determinism
- in order to obtain stochastic behaviours of computational systems, suitable mechanisms for non-determinism should be provided
- since most of the complexity featured by adaptive and self-\* systems depends on the interaction among components, coordination models should feature non-deterministic coordination mechanisms for stochastic behaviour

#### Issues

- devising out some basic mechanisms for stochastic coordination
- finding a minimal set of primitives for most (all) of the most relevant stochastic systems
- showing how such mechanisms could be embedded as tuple-based co-ordination primitives, in order to address the general need of complex computational system engineering
- defining their formal semantics and implementing them as TuCSoN primitives

## Don't Care Non-determinism in Tuple-based Models

- LINDA features *don't know* non-determinism handled with a *don't* care approach:
  - - don't care nonetheless, the coordinated system is designed so as to keep on working whichever is the matching tuple returned
- instead, adaptive and self-organising systems require stochastic behaviours like "most of the time do this", "sometimes do that"
- possibly with some quantitative specification of "most of the time" and "sometimes"
- → as it is, non-determinism in tuple-based models does not fit the need of stochastic behaviour specification

## LINDA "Local" Nature – In Time & Space

- no context in a single getter operation, only a *local*, point-wise property affects tuple retrieval: that is, the conformance of a tuple to the template, independently of the *spatial* context
  - in fact, standard getter primitives return a matching tuple independently of the other tuples currently in the same space—so, they are "context unaware"
  - no history furthermore, in a sequence of getter operations, don't know non-determinism makes any prediction of the overall behaviour impossible—again, then, only a point-wise property can be ensured even in *time* 
    - sequences of standard getter operations present no meaningful distribution over time

#### LINDA: How to Roll a Dice?

- we define tuple space dice
- we represent a six-face dice as a collection of six tuples: face(1), ..., face(6)
- we roll a dice by rd-ing a face/1 tuple from dice:

! we do *not* obtain the overall (stochastic) behaviour of a dice: for instance, it may reasonably happen that rolling the dice 10<sup>9</sup> times always results in X / 1—that is, we get "1" 10<sup>9</sup> times in a row.

#### ULINDA: Probabilistic Non-determinism

- we define uniform coordination primitives (uin, urd) first mentioned in [Gardelli et al., 2007] – as the specialisation of LINDA getter primitives featuring probabilistic non-determinism instead of don't know non-determinism
- we call the new model ULINDA [Mariani and Omicini, 2013c]
- uniform primitives allow programmers to both specify and (statistically) predict the probability to retrieve one specific tuple among a bag of matching tuples
- uniform primitives are the "basic mechanisms enabling self-organising coordination"—that is, a minimal set of constructs able (alone) to impact the observable properties of a coordinated system

#### ULINDA: "Global" Nature

#### Situation & prediction

Uniform primitives replace don't know non-determinism with *probabilistic* non-determinism to

- situate a primitive invocation in space
  - uniform getter primitives return matching tuples based on the other tuples in the space—so, their behaviour is context-aware
- predict its behaviour in time
  - sequences of uniform getter operations tend to globally exhibit a uniform distribution over time

### ULINDA: How to Roll a Dice?

- again, we define tuple space dice
- again, we represent a six-face dice as a collection of six tuples:
   face(1), ..., face(6)
- we roll a dice by urd-ing a face/1 tuple from dice:

```
dice ? urd(face(X))
```

! now, we do obtain the overall (stochastic) behaviour of a dice:

```
context — at every roll, the six faces of the dice X / 1, ..., X / 6 have the same probability P = 1/6 to be selected
```

history — in the overall, repeating several times a roll, the six faces will tend to converge towards a uniform distribution

### Informal Semantics

### Operationally, uniform primitives behave as follows:

- when executed, a uniform primitive takes a snapshot of the tuple space, "freezing" its state at a certain point in time—and space, being a single tuple space the target of basic LINDA primitives
- ② the snapshot is then exploited to assign a probabilistic value  $p_i \in [0,1]$  to any tuple  $t_{i \in \{1..n\}}$  in the space—where n is the total number of tuples in the space
- there, non-matching tuples have value p=0, matching tuples have value p=1/m (where  $m \leq n$  is the number of matching tuples), and the overall sum of probability values is  $\sum_{i=1...n} p_i = 1$
- the choice of the matching tuple to be returned is then statistically based on the computed probabilistic values

### Formal Semantics I

[!] In order to define the semantics of (getter) uniform primitives, we rely upon a simplified version of the process-algebraic framework in [Bravetti, 2008], in particular the ↑ operator, dropping multi-level priority probabilities.

#### uin semantics

### Formal Semantics II

[!] As for standard LINDA getter primitives, the only difference between uniform reading (urd) and uniform consumption (uin) is the non-destructive semantics of the reading primitive—transition Exec-R.

#### urd semantics

[SYNCH-C] urd 
$$|\langle t_1, ..., t_n \rangle \xrightarrow{T} \operatorname{urd}_T . P \mid \langle t_1, ..., t_n \rangle \uparrow \{(t_1, v_1), ..., (t_n, v_n)\}$$

[CLOSE-C] urd  $|\langle t_1, ..., t_n \rangle \uparrow \{(t_1, v_1), ..., (t_n, v_n)\}$ 

urd  $|\langle t_1, ..., t_n \rangle \uparrow \{(t_1, p_1), ..., (t_n, p_n)\}$ 

[EXEC-R] urd  $|\langle t_1, ..., t_n \rangle \uparrow \{..., (t_i, p_i), ...\} \xrightarrow{t_j}_{p_i} P[t_i/T] \mid \langle t_1, ..., t_n \rangle$ 

# Expressiveness: ULINDA vs LINDA

In  $[{\tt Bravetti\ et\ al.,\ 2005}],$  authors demonstrate that  $LINDA\mbox{-}based$  languages  $\it cannot$  implement probabilistic models.

### PME proof

The gain in expressiveness brought by ULINDA is formally proven in [Mariani and Omicini, 2013a], where uniform primitives are shown to be strictly more expressive than standard LINDA primitives according to probabilistic modular embedding (PME) [Mariani and Omicini, 2013b].

In particular

uLinda 
$$\succeq_{p}$$
 Linda  $\land$  Linda  $\not\succeq_{p}$  uLinda  $\Longrightarrow$  uLinda  $\not\equiv_{o}$  Linda

#### where

- ≥<sub>p</sub> stands for "probabilistically embeds"
- $\equiv_o$  means "(PME) observational equivalence"

### Focus on...

- Nature-inspired Coordination
- 2 Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- 4 Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



# **Expressing Full Dynamics**

### Expressing the full dynamics of complex natural systems

- mostly, coordination models just capture some of the overall system dynamics
- which makes them basically fail
  - for instance, Gamma mimics chemical reactions, but does not capture essential issues in chemical processes such as reaction rates and concentration [Banâtre and Le Métayer, 1990, Banătre et al., 2001]
  - instead, (bio)chemical tuple spaces fully exploit the chemical metaphor by providing time-dependent and stochastic chemical laws
     [Viroli et al., 2010, Viroli and Casadei, 2009]
- more generally, the goal is to allow coordinated MAS to capture and express the full dynamics of complex natural systems

### Focus on...

- Nature-inspired Coordination
- 2 Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



### Core Mechanisms

### Understanding the basic elements of expressiveness

- LINDA is a glaring example of a minimal set of coordination mechanisms providing a wide range of coordination behaviours
- the goal is understanding the minimal set of coordination primitives required to design complex stochastic behaviours
- for instance, uniform coordination primitives that is, LINDA-like coordination primitives returning tuples matching a template with a uniform distribution [Gardelli et al., 2007] – seemingly capture the full-fledged dynamics of real chemical systems within the coordination abstractions

### Focus on...

- Nature-inspired Coordination
- 2 Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- 4 Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



Trends

# **Blending Metaphors**

## Mixing abstractions & mechanisms from different conceptual sources

- most natural systems, when observed in their whole complexity, exhibit *layers* each one featuring its own metaphors and mechanisms
- correspondingly, many novel approaches to complex MAS coordination integrate diverse sources of inspiration, e.g.:
  - TOTA [Mamei and Zambonelli, 2004] exploits mechanisms from both stigmergic and field-based coordination
  - the SAPERE coordination model for pervasive service ecosystems [Zambonelli et al., 2011, Viroli et al., 2012] integrates
    - the chemical metaphor for driving the evolution of coordination abstractions
    - biochemical abstractions for topology and diffusion
    - the notion of ecosystem in order to model the overall system structure and dynamics

#### Focus on...

- Nature-inspired Coordination
- 2 Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- 4 Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



# Predicting Complex Behaviours

### Engineering unpredictable systems around predictable abstractions

- coordination models are meant to harness the complexity of complex MAS [Ciancarini et al., 2000]
- coordination abstractions are often at the core of complex MAS
- while this does not make complex MAS generally predictable, it
  makes it possible in principle to make them partially predictable,
  based on the predictably of the core coordinative behaviour
- suitably-formalised coordination abstractions, along with a suitably-defined engineering methodology, could in principle ensure the predictability of given MAS properties within generally-unpredictable MAS

### Focus on...

- Nature-inspired Coordination
- 2 Examples
  - Early
  - Modern
  - Issues
- 3 Tuples
- 4 Trends
  - Coordination for Complex Systems
  - Coordination for Simulation
  - Coordination & Stochastic Systems
  - Full Dynamics
  - Core Mechanisms
  - Blending Metaphors
  - Predicting Complex Behaviours
  - Knowledge-oriented Coordination



# Knowledge-oriented Coordination I

### Integrating nature-inspired with knowledge-oriented coordination

- intelligent MAS in knowledge intensive environments as well as complex socio-technical systems, in general – require automatic understanding of data and information
- knowledge-oriented coordination exploits coordination abstractions enriched so as to allow for semantic interpretation by intelligent agents [Fensel, 2004, Nardini et al., 2013]
- for instance
  - chemical tuple spaces
  - SAPERE coordination abstractions and mechanisms
  - semantic tuple centres [Nardini et al., 2011]

all relay on the semantic interpretation of coordination items

# Knowledge-oriented Coordination II

### Self-organisation of knowledge

- explicit search of information is going to become ineffective while the amount of available knowledge grows at incredible rates
- knowledge should autonomously organise and flow from producers to consumers
- knowledge self-organisation for knowledge-intensive MAS

# Knowledge-oriented Coordination III

# MoK (Molecules of Knowledge) [Mariani and Omicini, 2012a]

- Molecules of Knowledge is a a nature-inspired coordination model promoting knowledge self-organisation, where
  - sources of knowledge continuously produce and inject atoms of knowledge in biochemical compartments
  - knowledge atoms may then aggregate in molecules and diffuse
  - knowledge producers, managers and consumers are modelled as catalysts, whose workspaces are biochemical compartments, and their knowledge-oriented actions become enzymes influencing atoms aggregation and molecules diffusion
  - so as to make relevant knowledge spontaneously aggregate and autonomously move towards potentially interested knowledge workers
- the first application scenario for experimenting with MoK is *news* management [Mariani and Omicini, 2012b]

### Conclusion I

### History and evolution

- starting from early chemical and stigmergic approaches, nature-inspired models of coordination evolved to become the potential core of complex MAS—such as pervasive, knowledge-intensive, and self-\* MAS
- in this talk we shorty surveyed their history, devise their main issues, and point out the most promising trends
- focussing in particular on tuple-based coordination models, and adopted a *systemic view* over MAS

### Conclusion II

#### In the overall...

- nature-inspired models of coordination already have a long history behind them
- and apparently a huge potential for development still to be explored
- to provide core abstractions and technologies for the engineering of complex MAS

- Nature-inspired Coordination
- 2 Examples
- Tuples
- Trends



### References I



Banătre, J.-P., Fradet, P., and Le Métayer, D. (2001). Gamma and the chemical reaction model: Fifteen years after. In Calude, C. S., Păun, G., Rozenberg, G., and Salomaa, A., editors, *Multiset Processing. Mathematical, Computer Science, and Molecular Computing Points of View*, volume 2235 of *LNCS*, pages 17–44. Springer.



Banâtre, J.-P. and Le Métayer, D. (1990). The GAMMA model and its discipline of programming. *Science of Computer Programming*, 15(1):55–77.



Berry, G. (1992).

The chemical abstract machine. *Theoretical Computer Science*, 96(1):217–248.



Boltzmann, L. (1964).

Lectures on Gas Theory.
University of California Press.



Bouchaud, J.-P. and Potters, M. (2003).

Theory of Financial Risk and Derivative Pricing: From Statistical Physics to Risk Management.

Cambridge University Press, Cambridge, UK, 2nd edition.

## References II



Bravetti, M. (2008).

Expressing priorities and external probabilities in process algebra via mixed open/closed systems.

Electronic Notes in Theoretical Computer Science, 194(2):31–57.



Bravetti, M., Gorrieri, R., Lucchi, R., and Zavattaro, G. (2005). Quantitative information in the tuple space coordination model. *Theoretical Computer Science*, 346(1):28–57.



Busi, N., Gorrieri, R., and Zavattaro, G. (1998). A process algebraic view of Linda coordination primitives. *Theoretical Computer Science*, 192(2):167–199.



Ciancarini, P. (1996).
Coordination models and languages as software integrators.

ACM Computing Surveys, 28(2):300–302.



Ciancarini, P., Omicini, A., and Zambonelli, F. (1999). Coordination technologies for Internet agents. *Nordic Journal of Computing*, 6(3):215–240.

### References III



Ciancarini, P., Omicini, A., and Zambonelli, F. (2000).

Multiagent system engineering: The coordination viewpoint.

In Jennings, N. R. and Lespérance, Y., editors, *Intelligent Agents VI. Agent Theories, Architectures, and Languages*, volume 1757 of *LNAI*, pages 250–259. Springer. 6th International Workshop (ATAL'99), Orlando, FL, USA, 15–17 July 1999. Proceedings.



De Nicola, R., Ferrari, G., and Pugliese, R. (1998).

KLAIM: A kernel language for agent interaction and mobility.

IEEE Transaction on Software Engineering, 24(5):315–330.



De Nicola, R., Latella, D., Katoen, J.-P., and Massink, M. (2006).

StoKlaim: A stochastic extension of Klaim.

Technical Report 2006-TR-01, Istituto di Scienza e Tecnologie dell'Informazione "Alessandro Faedo" (ISTI).



Denti, E., Natali, A., and Omicini, A. (1998).

On the expressive power of a language for programming coordination media.

In 1998 ACM Symposium on Applied Computing (SAC'98), pages 169–177, Atlanta, GA, USA, ACM.

Special Track on Coordination Models, Languages and Applications.

### References IV



Downward, J. (2003).

Targeting RAS signalling pathways in cancer therapy. *Nature Reviews Cancer*, 3(1):11–22.



FaceBook (2017).

Home page.

http://www.facebook.com.



Fensel, D. (2004).

Triple-space computing: Semantic web services based on persistent publication of information.

In Aagesen, F. A., Anutariya, C., and Wuwongse, V., editors, *Intelligence in Communication Systems*, volume 3283 of *LNCS*, pages 43–53.

IFIP International Conference (INTELLCOMM 2004), Bangkok, Thailand,



## References V



Gardelli, L., Viroli, M., Casadei, M., and Omicini, A. (2007).

Designing self-organising MAS environments: The collective sort case.

In Weyns, D., Parunak, H. V. D., and Michel, F., editors, *Environments for MultiAgent Systems III*, volume 4389 of *LNAI*, pages 254–271. Springer.

3rd International Workshop (E4MAS 2006), Hakodate, Japan, 8 May 2006. Selected Revised and Invited Papers.



Gelernter, D. (1985).

Generative communication in Linda.

ACM Transactions on Programming Languages and Systems, 7(1):80-112.



Gelernter, D. and Carriero, N. (1992).

Coordination languages and their significance.

Communications of the ACM, 35(2):97–107.



González Pérez, P. P., Omicini, A., and Sbaraglia, M. (2013).

A biochemically-inspired coordination-based model for simulating intracellular signalling pathways.

Journal of Simulation, 7(3):216-226.

Special Issue: Agent-based Modeling and Simulation.

## References VI



Grassé, P.-P. (1959).

La reconstruction du nid et les coordinations interindividuelles chez Bellicositermes natalensis et Cubitermes sp. la théorie de la stigmergie: Essai d'interprétation du comportement des termites constructeurs.

\*Insectes Sociaux\*, 6(1):41–80.



Kauffman, S. A. (1993).

The Origins of Order: Self-organization and Selection in Evolution.

Oxford University Press.



Kauffman, S. A. (2003). *Investigations*.



Oxford University Press.



LiquidFeedback (2017).

Home page.

http://liquidfeedback.org.



Liu, J. and Tsui, K. C. (2006).

Toward nature-inspired computing.

Communications of the ACM, 49(10):59-64.

## References VII

Proceedings.



Mamei, M. and Zambonelli, F. (2004).

Springer Series in Agent Technology. Springer.

Programming pervasive and mobile computing applications with the TOTA middleware. In *Pervasive Computing and Communications*, pages 263–273. 2nd IEEE Annual Conference (PerCom 2004), Orlando, FL, USA, 14–17 March 2004.



Mamei, M. and Zambonelli, F. (2006). Field-Based Coordination for Pervasive Multiagent Systems. Models, Technologies, and Applications.



Mantegna, R. N. and Stanley, H. E. (1999).

Introduction to Econophysics: Correlations and Complexity in Finance.
Cambridge University Press, Cambridge, UK.



### References VIII



Mariani, S. and Omicini, A. (2012a).

Molecules of Knowledge: Self-organisation in knowledge-intensive environments. In Fortino, G., Bădică, C., Malgeri, M., and Unland, R., editors, *Intelligent Distributed Computing VI*, volume 446 of *Studies in Computational Intelligence*, pages 17–22. Springer.

6th International Symposium on Intelligent Distributed Computing (IDC 2012), Calabria, Italy, 24-26 September 2012. Proceedings.



Mariani, S. and Omicini, A. (2012b).

Self-organising news management: The *Molecules of Knowledge* approach. In Fernandez-Marquez, J. L., Montagna, S., Omicini, A., and Zambonelli, F., editors, *1st International Workshop on Adaptive Service Ecosystems: Natural and Socially Inspired Solutions (ASENSIS 2012)*, pages 11–16, SASO 2012, Lyon, France.

Pre-proceedings.



Mariani, S. and Omicini, A. (2013a).

Probabilistic embedding: Experiments with tuple-based probabilistic languages. In 28th ACM Symposium on Applied Computing (SAC 2013), pages 1380–1382, Coimbra, Portugal.

Poster Paper.

### References IX



Mariani, S. and Omicini, A. (2013b).

Probabilistic modular embedding for stochastic coordinated systems.

In Julien, C. and De Nicola, R., editors, *Coordination Models and Languages*, volume 7890 of *LNCS*, pages 151–165. Springer.

15th International Conference (COORDINATION 2013), Florence, Italy, 3–6 June 2013. Proceedings.



Mariani, S. and Omicini, A. (2013c).

Tuple-based coordination of stochastic systems with uniform primitives.

In Baldoni, M., Baroglio, C., Bergenti, F., and Garro, A., editors, *From Objects to Agents*, volume 1099 of *CEUR Workshop Proceedings*, pages 8–15, Turin, Italy. Sun SITE Central Europe, RWTH Aachen University.

XIV Workshop (WOA 2013). Workshop Notes.



Mézard, M. and Montanari, A. (2009). *Information, Physics, and Computation*. Oxford University Press, Oxford, UK.

## References X



Nardini, E., Omicini, A., and Viroli, M. (2013).

Semantic tuple centres.

Science of Computer Programming, 78(5):569–582.

Special section: Self-Organizing Coordination.



Nardini, E., Omicini, A., Viroli, M., and Schumacher, M. I. (2011). Coordinating e-health systems with TuCSoN semantic tuple centres. *Applied Computing Review*, 11(2):43–52.



Neves, S. R., Ram, P. T., and Iyengar, R. (2002). G protein pathways. *Science*, 296(5573):1636–1639.



Nishimori, H. (2001).

Statistical Physics of Spin Glasses and Information Processing: An Introduction, volume 111 of International Series of Monographs on Physics.

Clarendon Press, Oxford, UK.

### References XI



Omicini, A. (2012).

Agents writing on walls: Cognitive stigmergy and beyond. In Paglieri, F., Tummolini, L., Falcone, R., and Miceli, M., editors, *The Goals of Cognition. Essays in Honor of Cristiano Castelfranchi*, volume 20 of *Tributes*, chapter 30, pages 565–578. College Publications, London.



Omicini, A. (2013).

Nature-inspired coordination for complex distributed systems.

In Fortino, G., Bădică, C., Malgeri, M., and Unland, R., editors, *Intelligent Distributed Computing VI*, volume 446 of *Studies in Computational Intelligence*, pages 1–6. Springer. 6th International Symposium on Intelligent Distributed Computing (IDC 2012), Calabria, Italy, 24-26 September 2012. Proceedings. Invited paper.



Omicini, A. and Denti, E. (2001).

From tuple spaces to tuple centres.

Science of Computer Programming, 41(3):277–294.

## References XII



Omicini, A., Ricci, A., and Viroli, M. (2005).

Time-aware coordination in ReSpecT.

In Jacquet, J.-M. and Picco, G. P., editors, *Coordination Models and Languages*, volume 3454 of *LNCS*, pages 268–282. Springer-Verlag.

7th International Conference (COORDINATION 2005), Namur, Belgium, 20–23 April 2005. Proceedings.



Omicini, A., Ricci, A., and Viroli, M. (2006).

The multidisciplinary patterns of interaction from sciences to Computer Science. In Goldin, D. Q., Smolka, S. A., and Wegner, P., editors, *Interactive Computation: The New Paradigm*, pages 395–414. Springer.



Omicini, A., Ricci, A., and Viroli, M. (2007). Timed environment for Web agents. Web Intelligence and Agent Systems, 5(2):161–175.



Omicini, A., Ricci, A., Viroli, M., Castelfranchi, C., and Tummolini, L. (2004). Coordination artifacts: Environment-based coordination for intelligent agents. In Jennings, N. R., Sierra, C., Sonenberg, L., and Tambe, M., editors, *3rd international Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS 2004)*, volume 1, pages 286–293, New York, USA. ACM.

## References XIII



Omicini, A. and Viroli, M. (2011).

Coordination models and languages: From parallel computing to self-organisation. *The Knowledge Engineering Review*, 26(1):53–59. Special Issue 01 (25th Anniversary Issue).



Omicini, A. and Zambonelli, F. (2004).

MAS as complex systems: A view on the role of declarative approaches. In Leite, J. A., Omicini, A., Sterling, L., and Torroni, P., editors, *Declarative Agent Languages and Technologies*, volume 2990 of *LNAI*, pages 1–17. Springer. 1st International Workshop (DALT 2003), Melbourne, Australia, 15 July 2003. Revised Selected and Invited Papers.



Parunak, H. V. D. (2006).

A survey of environments and mechanisms for human-human stigmergy. In Weyns, D., Parunak, H. V. D., and Michel, F., editors, *Environments for Multi-Agent Systems II*, volume 3830 of *LNCS*, pages 163–186. Springer.

## References XIV



Parunak, H. V. D., Brueckner, S., and Sauter, J. (2002). Digital pheromone mechanisms for coordination of unmanned vehicles. In Castelfranchi, C. and Johnson, W. L., editors, *1st International Joint Conference on Autonomous Agents and Multiagent systems*, volume 1, pages 449–450, New York, NY, USA ACM



Ricci, A., Omicini, A., Viroli, M., Gardelli, L., and Oliva, E. (2007). Cognitive stigmergy: Towards a framework based on agents and artifacts. In Weyns, D., Parunak, H. V. D., and Michel, F., editors, *Environments for MultiAgent Systems III*, volume 4389 of *LNCS*, pages 124–140. Springer. 3rd International Workshop (E4MAS 2006), Hakodate, Japan, 8 May 2006. Selected Revised and Invited Papers.



Ricci, A., Viroli, M., and Omicini, A. (2005).

Environment-based coordination through coordination artifacts.

In Weyns, D., Parunak, H. V. D., and Michel, F., editors, *Environments for Multi-Agent Systems*, volume 3374 of *LNAI*, pages 190–214. Springer.

1st International Workshop (E4MAS 2004). New York, NY, LISA, 19, July 2004. Revised.

1st International Workshop (E4MAS 2004), New York, NY, USA, 19 July 2004. Revised Selected Papers.

### References XV



Rossi, D., Cabri, G., and Denti, E. (2001).

Tuple-based technologies for coordination.

In Omicini, A., Zambonelli, F., Klusch, M., and Tolksdorf, R., editors, *Coordination of Internet Agents: Models, Technologies, and Applications*, chapter 4, pages 83–109. Springer.



Simon, H. A. (1962).

The architecture of complexity.

Proceedings of the American Philosophical Society, 106(6):467–482.



Stanley, H. E. (2008).

Econophysics and the current economic turmoil.

American Physical Society News, 17(11):8.

The Back Page.



Tolksdorf, R. and Menezes, R. (2004).

Using Swarm Intelligence in Linda Systems.

In Omicini, A., Petta, P., and Pitt, J., editors, *Engineering Societies in the Agents World IV*, volume 3071 of *LNCS*, pages 49–65. Springer.

4th International Workshops (ESAW 2003), London, UK, 29-31 October 2003. Revised Selected and Invited Papers.

### References XVI



Verhagen, H., Noriega, P., Balke, T., and de Vos, M., editors (2013). Social Coordination: Principles, Artefacts and Theories (SOCIAL.PATH), AISB Convention 2013, University of Exeter, UK. The Society for the Study of Artificial Intelligence and the Simulation of Behaviour.



Viroli, M. and Casadei, M. (2009).
Biochemical tuple spaces for self-organising coordination.
In Field, J. and Vasconcelos, V. T., editors, *Coordination Languages and Models*, volume 5521 of *LNCS*, pages 143–162. Springer, Lisbon, Portugal.
11th International Conference (COORDINATION 2009), Lisbon, Portugal, June 2009.
Proceedings.



Viroli, M., Casadei, M., Nardini, E., and Omicini, A. (2010).

Towards a chemical-inspired infrastructure for self-\* pervasive applications.

In Weyns, D., Malek, S., de Lemos, R., and Andersson, J., editors, *Self-Organizing Architectures*, volume 6090 of *LNCS*, chapter 8, pages 152–176. Springer.

1st International Workshop on Self-Organizing Architectures (SOAR 2009), Cambridge, UK, 14-17 September 2009, Revised Selected and Invited Papers.

## References XVII



Viroli, M., Casadei, M., and Omicini, A. (2009).

A framework for modelling and implementing self-organising coordination. In Shin, S. Y., Ossowski, S., Menezes, R., and Viroli, M., editors, 24th Annual ACM Symposium on Applied Computing (SAC 2009), volume III, pages 1353–1360, Honolulu, Hawai'i. USA. ACM.



Viroli, M. and Omicini, A. (2006).

Coordination as a service.

Fundamenta Informaticae, 73(4):507-534.

Special Issue: Best papers of FOCLASA 2002.



Viroli, M., Pianini, D., Montagna, S., and Stevenson, G. (2012). Pervasive ecosystems: a coordination model based on semantic chemistry. In Ossowski, S., Lecca, P., Hung, C.-C., and Hong, J., editors, 27th Annual ACM Symposium on Applied Computing (SAC 2012), Riva del Garda, TN, Italy. ACM.



Wegner, P. (1997).

Why interaction is more powerful than algorithms.

Communications of the ACM, 40(5):80-91.

## References XVIII



Weyns, D., Omicini, A., and Odell, J. J. (2007).

Environment as a first-class abstraction in multi-agent systems.

Autonomous Agents and Multi-Agent Systems, 14(1):5-30.

Special Issue on Environments for Multi-agent Systems.



Whitworth, B. (2006).

Socio-technical systems.

In Ghaou, C., editor, Encyclopedia of Human Computer Interaction, pages 533-541. IGI Global.



Zambonelli, F., Castelli, G., Ferrari, L., Mamei, M., Rosi, A., Di Marzo, G., Risoldi, M., Tchao, A.-E., Dobson, S., Stevenson, G., Ye, Y., Nardini, E., Omicini, A., Montagna, S., Viroli, M., Ferscha, A., Maschek, S., and Wally, B. (2011).

Self-aware pervasive service ecosystems.

Procedia Computer Science, 7:197–199.

Proceedings of the 2nd European Future Technologies Conference and Exhibition 2011 (FET 11).



Zambonelli, F. and Omicini, A. (2004).

Challenges and research directions in agent-oriented software engineering. Autonomous Agents and Multi-Agent Systems, 9(3):253-283.

Special Issue: Challenges for Agent-Based Computing.

### References XIX



Zavattaro, G. (1998).

On the incomparability of Gamma and Linda. Technical Report SEN-R9827, CWI, Amsterdam, The Netherlands.



# Nature-Inspired Coordination & Self-Organisation

Autonomous Systems
Sistemi Autonomi

Andrea Omicini
andrea.omicini@unibo.it

Dipartimento di Informatica – Scienza e Ingegneria (DISI) Alma Mater Studiorum – Università di Bologna

Academic Year 2017/2018