



Sengupta, Ayan and Pollmann, Stefan and Hanke, Michael (2018) Spatial band-pass filtering aids decoding musical genres from auditory cortex 7T fMRI. *F1000Research*, 7 . p. 142. ISSN 2046-1402

Access from the University of Nottingham repository:

http://eprints.nottingham.ac.uk/51286/1/3c414e9c-2e04-4e6b-aa33-a56e20aade30_13689_-_Ayan_Sengupta_V2.pdf

Copyright and reuse:

The Nottingham ePrints service makes this work by researchers of the University of Nottingham available open access under the following conditions.

This article is made available under the Creative Commons Attribution licence and may be reused according to the conditions of the licence. For more details see: <http://creativecommons.org/licenses/by/2.5/>

A note on versions:

The version presented here may differ from the published version or from the version of record. If you wish to cite this item you are advised to consult the publisher's version. Please see the repository url above for details on accessing the published version and note that access may require a subscription.

For more information, please contact eprints@nottingham.ac.uk



RESEARCH NOTE

REVISED Spatial band-pass filtering aids decoding musical genres from auditory cortex 7T fMRI [version 2; referees: 2 approved]

Ayan Sengupta^{1,2}, Stefan Pollmann^{2,3}, Michael Hanke^{3,4}

¹Sir Peter Mansfield Imaging Centre, School of Physics and Astronomy, University of Nottingham, Nottingham, UK
²Department of Experimental Psychology, Institute of Psychology, Otto-von-Guericke University, Magdeburg, Germany
³Psychoinformatics Lab, Institute of Psychology, Otto-von-Guericke University, Magdeburg, Germany
⁴Center for Behavioral Brain Sciences, Magdeburg, Germany

v2 First published: 02 Feb 2018, 7:142 (doi: 10.12688/f1000research.13689.1)
 Latest published: 04 Apr 2018, 7:142 (doi: 10.12688/f1000research.13689.2)

Abstract

Spatial filtering strategies, combined with multivariate decoding analysis of BOLD images, have been used to investigate the nature of the neural signal underlying the discriminability of brain activity patterns evoked by sensory stimulation – primarily in the visual cortex. Previous research indicates that such signals are spatially broadband in nature, and are not primarily comprised of fine-grained activation patterns. However, it is unclear whether this is a general property of the BOLD signal, or whether it is specific to the details of employed analyses and stimuli. Here we applied an analysis strategy from a previous study on decoding visual orientation from V1 to publicly available, high-resolution 7T fMRI on the response BOLD response to musical genres in primary auditory cortex. The results show that the pattern of decoding accuracies with respect to different types and levels of spatial filtering is comparable to that obtained from V1, despite considerable differences in the respective cortical circuitry.

Open Peer Review

Referee Status:

	Invited Referees	
	1	2
REVISED version 2 published 04 Apr 2018	 report	
	↑	
version 1 published 02 Feb 2018	? report	 report

- 1 **Cyril R. Pernet** , The University of Edinburgh, UK
- 2 **David G. Norris** , Radboud University Nijmegen, Netherlands

Discuss this article

Comments (0)

Corresponding author: Ayan Sengupta (Ayan.Sengupta@nottingham.ac.uk)

Author roles: **Sengupta A:** Conceptualization, Formal Analysis, Investigation, Methodology, Software, Validation, Visualization, Writing – Original Draft Preparation, Writing – Review & Editing; **Pollmann S:** Conceptualization, Funding Acquisition, Writing – Review & Editing; **Hanke M:** Conceptualization, Data Curation, Formal Analysis, Funding Acquisition, Investigation, Methodology, Project Administration, Resources, Software, Supervision, Validation, Visualization, Writing – Original Draft Preparation, Writing – Review & Editing

Competing interests: No competing interests were disclosed.

How to cite this article: Sengupta A, Pollmann S and Hanke M. **Spatial band-pass filtering aids decoding musical genres from auditory cortex 7T fMRI [version 2; referees: 2 approved]** *F1000Research* 2018, 7:142 (doi: [10.12688/f1000research.13689.2](https://doi.org/10.12688/f1000research.13689.2))

Copyright: © 2018 Sengupta A *et al.* This is an open access article distributed under the terms of the [Creative Commons Attribution Licence](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited. Data associated with the article are available under the terms of the [Creative Commons Zero "No rights reserved" data waiver](#) (CC0 1.0 Public domain dedication).

Grant information: AS and SP were supported by a grant from the German Research Council (DFG) awarded to S.~Pollmann (PO~548/15-1), MH was supported by funds from the German federal state of Saxony-Anhalt and the European Regional Development Fund (ERDF), Project: Center for Behavioral Brain Sciences. This research was, in part, also supported by the German Federal Ministry of Education and Research (BMBF) as part of a US-German collaboration in computational neuroscience (CRCNS; awarded to J.V. Haxby, P. Ramadge, and M. Hanke), co-funded by the BMBF and the US National Science Foundation (BMBF 01GQ1112; NSF 1129855).

The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

First published: 02 Feb 2018, 7:142 (doi: [10.12688/f1000research.13689.1](https://doi.org/10.12688/f1000research.13689.1))

REVISED Amendments from Version 1

This revision has addressed the concerns raised by the reviewers of this article. Following are the details:

Minor changes including typos like 'gaussian' -> 'Gaussian', 'prior masking' -> 'prior to masking' etc. have been performed according to Prof. Norris's comments. It has been explicitly mentioned that 'axial' slices were acquired. Moreover, the conversion of units from 'FWHM' to 'cycles/mm' has been properly referred to. The probable reason for auditory decoding performing better than visual decoding is also discussed in the Results and Conclusion section.

In order to address Dr. Pernet's comments, explicit mentions in the manuscript have been made to highlight the use of inclusion of temporal derivatives in the design matrix. In addition, the appropriateness of applying repeated random sampling instead of leave-one-out cross validation is also discussed in the manuscript.

See referee reports

Introduction

We recently reported¹ that spatial band-pass filtering of 7 Tesla BOLD fMRI data boosts accuracy of decoding visual orientations from human V1. We observed this result in comparison to data without any dedicated spatial filtering applied, and spatially low-pass filtered data – a typical preprocessing strategy for BOLD fMRI. This effect was present across a range of tested spatial acquisition resolutions, ranging from 0.8 mm to 2 mm isotropic voxel size (Figure 4 in 1). The bandpass spatial filtering procedure was performed by a difference-of-Gaussians (DoG) filter similar to Supplementary Figure 5 in 1. The frequency bands indicated the presence of orientation-related signal in a wide range of spatial frequencies as indicated by above-chance decoding performance for nearly all tested bands. Maximum decoding performance was observed for a band of 5–8 mm full width at half maximum (FWHM), indicating that low spatial frequency fMRI components also contribute to noise with respect to orientation discrimination.

This finding raises the question whether this reflects a specific property of early visual cortex and the particular stimuli used in 1, or whether it represents a more general aspect of BOLD fMRI data with implications for data preprocessing of decoding analyses. Here, we investigate this question by applying the identical analysis strategy from 1 to a different public 7 Tesla BOLD fMRI dataset², with the aim of decoding the musical genres of short audio clips from the early auditory cortex.

Methods

As this study aims to replicate previously reported findings, by employing a previously published analysis strategy on an existing dataset, the full methodological details are not repeated here. Instead the reader is kindly referred to 2, 3 for comprehensive descriptions of the data, and to 1 for details on the

analysis strategy and previous findings. Only key information and differences are reported below.

Stimulus and fMRI data

Data were taken from a published dataset² which were repeatedly analyzed previously^{4,5}, and publicly available from the studyforrest.org project of 20 participants passively listening to five natural, stereo, high-quality music stimuli (6 s duration; 44.1 kHz sampling rate) for each of five different musical genres: 1) Ambient, 2) Roots Country 3) Heavy Metal, 4) 50s Rock'n'Roll, and 5) Symphonic, while fMRI data were recorded in a 7 Tesla Siemens scanner (1.4 mm isotropic voxel size, TR=2 s, matrix size 160×160, 36 axial slices, 10% interslice gap). fMRI data were scanner-side corrected for spatial distortions⁶. Stimulation timing and frequency were roughly comparable to 1: 25 vs. 30 trials per run, 10 s vs. 8 s minimum inter-trial stimulus onset asynchrony in a low event-related design, 8 vs. 10 acquisition runs. Subject 20 was excluded from the analysis due to incomplete data.

Region of interest (ROI) localization

Analogous to 1, ROIs were localized separately for each individual brain. ROIs were left and right transversetemporal gyri, as defined by the structural Desikan-Killiany atlas⁷ from the previously published Freesurfer-based cortex parcellations for all studyforrest.org participants³. This ROI approximates the location of primary auditory cortex, including Brodmann areas 41 and 42 (Figure 1A). The average number of voxels in the ROI across participants was 1412 (std=357).

fMRI data analysis

Motion-corrected and distortion-corrected BOLD images from the publicly available dataset² were analyzed. Images for each participant, available from the dataset as the filename pattern of `sub*/BOLD/task002_run*/bold_dico_bold7Tp1_to_subjbold7Tp1.nii.gz` were already aligned across acquisition runs. Analogous to 1, BOLD images were masked to the defined bilateral ROI, and voxelwise BOLD response were univariately modelled for each run using the GLM implementation in NiPy [v0.3;⁸] while accounting for serial correlation with an autoregressive term (AR1). The GLM design matrix included hemodynamic response regressors, one for each genre and its corresponding temporal derivatives for improved parameter estimation⁹, six nuisance regressors for motion (translation and rotation), and polynomial regressors (up to 2nd-order) modeling temporal signal drift as regressors of no-interest. The β weights thus computed for each run were Z-scored per voxel. Multivariate decoding was performed on these Z-scored β weights using linear support vector machines [SVM; PyMVPA's LinearCSVMC implementation of the LIBSVM classification algorithm;^{10,11} in a within-subject leave-one-run-out cross-validation of 5-way multi-class classification of musical genres. Leave-one-out cross-validation was performed in order to enable comparison with previous results although it has been recently argued that repeated random splits are a superior validation




Figure 1. (A) Localization of early auditory cortex (transverse temporal gyrus) as shown in coronal slice of a participant (sub-16). (B) Confusion matrix showing the mean performance of the LinearCSVM classifier across all participants in decoding musical genres from early auditory cortex in spatially unfiltered data. (C) Classification accuracy of decoding musical genres across different types and levels of spatial Gaussian filtering. The theoretical chance performance of 20% is shown by the dashed line. This figure has been generated from original analysis of the dataset made publicly available² under the terms of the Public Domain Dedication and License.

scheme¹². The hyper-parameter C of the SVM classifier was scaled to the norm of the data. Decoding was performed using the entire bilateral ROI.

In-line with 1, 13, complete BOLD images were spatially filtered prior to masking and GLM-modeling, as prior results suggest negligible impact of alternative filtering strategies (see Figure S4 in 1). The magnitude of spatial filtering used is expressed in terms of the size of the Gaussian filter kernel(s) described by their FWHM in mm (a conversion of this unit to (cycles/mm) is shown in Supplementary Figure 5 in 1). The `image_smooth()` function in the `nilearn` package¹⁴ was used to implement all spatial smoothing procedures. The implementations of Gaussian *low-pass* (LP), and *high-pass* (HP) filters, as well as the DoG filters for *bandpass* (BP) and *bandstop* (BS) filtering are identical to those of¹ (1 mm FWHM filter size difference).

Results and conclusions

Figure 1 shows the mean accuracy across 19 participants for classifying the genre of music clips from BOLD response patterns of bilateral early auditory cortex. Compared to visual orientation decoding from V1¹, the mean accuracy of decoding musical genres without dedicated spatial filtering exhibits a substantially higher baseline (for 1.4 mm unfiltered data, mean orientation decoding accuracy was around 35%, whereas mean decoding of musical genres was at around 65%). However, the general pattern of accuracies across all filter sizes and filter types strongly resembles the results of orientation decoding

from V1. The superior decoding performance here, in comparison to oriented gabor gratings used for visual decoding, could be the result of the richer naturalistic stimuli with features like pitch, timbre, and speech lead to more separable fMRI activation patterns across genres. LP filtering led to a steady decline of performance with increasing filter size, but does not reach chance level even with a 20 mm smoothing kernel. In contrast to LP filtering, HP filtered data yielded superior decoding results for filter sizes of 4 mm and larger. Congruent with 1, BP filtering led to maximum decoding accuracy in the ≈ 5 –8 mm FWHM band. The accuracy achieved on BP filtered data at 6mm FWHM was significantly higher than that without any dedicated spatial filtering (McNemar test with continuity correction¹⁵: $\chi^2=33.22$, $p<10^{-6}$). BS filtering led to an approximately constant performance regardless of the base filter size, on the same level as with no dedicated spatial filtering.

In line with Gardumi *et al.*¹⁶, these results suggest that BOLD response patterns informative for decoding musical genre from early auditory cortex are spatially distributed and are represented at different spatial scales. However, despite their broad-band nature, relevant information seems to be concentrated in the spatial frequency band corresponding to a ≈ 5 –8 mm DoG filter. Most notably, the present findings show a striking similarity to the visual orientation decoding accuracy patterns in V1¹. The origin and spatial scale of signals beneficial for decoding BOLD response patterns are an intensely debated topic in the literature, and various studies have looked at this question in the context of anatomical or topographical

structure of visual cortex^{13,17–19}. There are substantial differences between the auditory and visual cortex in terms of anatomy, synaptic physiology, and the circuitry of cortical layers and their connections with other cortical areas and subcortical nuclei²⁰. The present results indicate that these differences have little impact on the spatial characteristics of those BOLD signal components that are relevant for decoding visual orientation or genre of music. In summary, these findings call for further investigations of neural and physiological signals underlying decoding models that are common across sensory domains, and individual cortical areas. The increasing availability of diverse open brain imaging data can help to aid the evaluation of generality and validity of explanatory models.

Data and software availability

OpenfMRI.org: High-resolution 7-Tesla fMRI data on the perception of musical genres. Accession number: [ds000113b](https://openfmri.org/ds000113b).

Article sources for 7-Tesla fMRI data on the perception of musical genres are available: <https://doi.org/10.5281/zenodo.18767>²¹

“Forrest Gump” data release source code is available: <https://doi.org/10.5281/zenodo.18770>²²

The codes used in this study for analysis are made openly available: <https://doi.org/10.5281/zenodo.1158836>²³

Competing interests

No competing interests were disclosed.

Grant information

AS and SP were supported by a grant from the German Research Council (DFG) awarded to S. Pollmann (PO 548/15-1), MH was supported by funds from the German federal state of Saxony-Anhalt and the European Regional Development Fund (ERDF), Project: Center for Behavioral Brain Sciences. This research was, in part, also supported by the German Federal Ministry of Education and Research (BMBF) as part of a US-German collaboration in computational neuroscience (CRCNS; awarded to J.V. Haxby, P. Ramadge, and M. Hanke), co-funded by the BMBF and the US National Science Foundation (BMBF 01GQ1112; NSF 1129855).

The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

References

- Sengupta A, Yakupov R, Speck O, et al.: **The effect of acquisition resolution on orientation decoding from V1 BOLD fMRI at 7T.** *Neuroimage*. 2017; **148**: 64–76. [PubMed Abstract](#) | [Publisher Full Text](#)
- Hanke M, Dinga R, Häusler C, et al.: **High-resolution 7-Tesla fMRI data on the perception of musical genres – an extension to the studyforrest dataset [version 1; referees: 2 approved with reservations].** *F1000Res*. 2015; **4**: 174. [Publisher Full Text](#)
- Hanke M, Baumgartner FJ, Ibe P, et al.: **A high-resolution 7-Tesla fMRI dataset from complex natural stimulation with an audio movie.** *Sci Data*. 2014; **1**: 140003. [PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Güçlü U, Thielen J, Hanke M, et al.: **Brains on beats.** In *Advances in Neural Information Processing Systems*. 2016; 2101–2109. [Reference Source](#)
- Casey MA: **Music of the 7Ts: Predicting and Decoding Multivoxel fMRI Responses with Acoustic, Schematic, and Categorical Music Features.** *Front Psychol*. 2017; **8**: 1179. [PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- In MH, Speck O: **Highly accelerated PSF-mapping for EPI distortion correction with improved fidelity.** *MAGMA*. 2012; **25**(3): 183–192. [PubMed Abstract](#) | [Publisher Full Text](#)
- Desikan RS, Ségonne F, Fischl B, et al.: **An automated labeling system for subdividing the human cerebral cortex on MRI scans into gyral based regions of interest.** *Neuroimage*. 2006; **31**(3): 968–980. [PubMed Abstract](#) | [Publisher Full Text](#)
- Millman KJ, Brett M: **Analysis of functional magnetic resonance imaging in Python.** *Comput Sci Eng*. 2007; **9**(3): 52–55. [Publisher Full Text](#)
- Pernet CR: **Misconceptions in the use of the General Linear Model applied to functional MRI: a tutorial for junior neuro-imagers.** *Front Neurosci*. 2014; **8**: 1. [PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Chang CC, Lin CJ: **LIBSVM: A library for support vector machines.** *ACM Trans Intell Syst Technol*. 2011; **2**(3): 27. [Publisher Full Text](#)
- Hanke M, Halchenko YO, Sederberg PB, et al.: **PyMVPA: A Unifying Approach to the Analysis of Neuroscientific Data.** *Front Neuroinform*. 2009; **3**: 3. [PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Varoquaux G, Raamana PR, Engemann DA, et al.: **Assessing and tuning brain decoders: Cross-validation, caveats, and guidelines.** *Neuroimage*. 2017; **145**(Pt B): 166–179. [PubMed Abstract](#) | [Publisher Full Text](#)
- Swisher JD, Gatenby JC, Gore JC, et al.: **Multiscale pattern analysis of orientation-selective activity in the primary visual cortex.** *J Neurosci*. 2010; **30**(1): 325–30. [PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Pedregosa F, Varoquaux G, Gramfort A, et al.: **Scikit-learn: Machine learning in Python.** *J Mach Learn Res*. 2011; **12**: 2825–2830. [Reference Source](#)
- Edwards AL: **Note on the correction for continuity in testing the significance of the difference between correlated proportions.** *Psychometrika*. 1948; **13**(3): 185–187. [PubMed Abstract](#) | [Publisher Full Text](#)
- Gardumi A, Ivanov D, Hausfeld L, et al.: **The effect of spatial resolution on decoding accuracy in fmri multivariate pattern analysis.** *Neuroimage*. 2016; **132**: 32–42. [PubMed Abstract](#) | [Publisher Full Text](#)
- Freeman J, Brouwer GJ, Heeger DJ, et al.: **Orientation decoding depends on maps, not columns.** *J Neurosci*. 2011; **31**(13): 4792–804. [PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Alink A, Krugliak A, Walther A, et al.: **fMRI orientation decoding in V1 does not require global maps or globally coherent orientation stimuli.** *Front Psychol*. 2013; **4**: 493. [PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Freeman J, Heeger DJ, Merriam EP: **Coarse-scale biases for spirals and orientation in human visual cortex.** *J Neurosci*. 2013; **33**(50): 19695–703. [PubMed Abstract](#) | [Publisher Full Text](#) | [Free Full Text](#)
- Linden JF, Schreiner CE: **Columnar transformations in auditory cortex? A comparison to visual and somatosensory cortices.** *Cereb Cortex*. 2003; **13**(1): 83–89. [PubMed Abstract](#) | [Publisher Full Text](#)
- Hanke M: **paper-f1000_pandora_data: Initial submission (Version submit_v1).** *Zenodo*. 2015. [Data Source](#)
- Hanke M, v-iacovella, Häusler C: **gumpdata: Matching release for pandora data paper publication (Version pandora_release1).** *Zenodo*. 2015. [Data Source](#)
- Sengupta A: **psychoinformatics-de/studyforrest-paper-auditorydecoding: v1.0 (Version v1.0).** *Zenodo*. 2018. [Data Source](#)

Open Peer Review

Current Referee Status:  

Version 2

Referee Report 04 April 2018

doi:[10.5256/f1000research.15721.r32703](https://doi.org/10.5256/f1000research.15721.r32703)

 **Cyril R. Pernet** 

Neuroimaging Sciences, Centre for Clinical Brain Sciences, The University of Edinburgh, Edinburgh, UK

As expected, one cannot really address the issue of LOO with 7-8 betas but it's now mentioned and that's all I really wanted to see.

Competing Interests: No competing interests were disclosed.

I have read this submission. I believe that I have an appropriate level of expertise to confirm that it is of an acceptable scientific standard.

Version 1

Referee Report 09 March 2018

doi:[10.5256/f1000research.14869.r30542](https://doi.org/10.5256/f1000research.14869.r30542)

 **David G. Norris** 

Donders Institute for Brain, Cognition and Behaviour, Radboud University Nijmegen, Nijmegen, Netherlands

This article explores the effect of spatial filtering on the decoding accuracy of BOLD fMRI data. The authors conclude that a spatial bandpass filter corresponding to a difference of Gaussians of 6mm improves the decoding accuracy.

Abstract: 'Reported evidence' is clumsy phrasing how about something like 'previous research'. Use of 'matches' is also ambivalent: do you mean the analysis was similar or the results? Please state the main result and not just that it is similar to that obtained for V1.

Introduction: The term spatial frequency is used frequently, whereas the difference of Gaussians is described in terms of a FWHM. The units of spatial frequency are 1/mm, so if you are describing band pass filters, cut-offs etc in terms of spatial frequency then please convert to the correct units.

Stimulus and fMRI data: Please give slice orientation of fMRI acquisition. I believe it was axial, but Figure 1 could mislead people into thinking it was coronal.

Figure 1 caption: gaussian->Gaussian.

fMRI data analysis: prior masking -> prior to masking

Results and Conclusions: These are given with little discussion. Why do you think the decoding accuracy is so much higher for music than for V1. Some discussion of existing literature would also be welcome, also of papers which do not reach the same conclusion as the authors (ref 1).

References

1. Gardumi A., Ivanov D., Hausfeld L., Valente G., Formisano E., Uludağ K.: The effect of spatial resolution on decoding accuracy in fMRI multivariate pattern analysis. *Neuroimage*. 2016. 32-42 [Publisher Full Text](#)

Is the work clearly and accurately presented and does it cite the current literature?

Partly

Is the study design appropriate and is the work technically sound?

Yes

Are sufficient details of methods and analysis provided to allow replication by others?

Partly

If applicable, is the statistical analysis and its interpretation appropriate?

Yes

Are all the source data underlying the results available to ensure full reproducibility?

Yes

Are the conclusions drawn adequately supported by the results?

Yes

Competing Interests: No competing interests were disclosed.

I have read this submission. I believe that I have an appropriate level of expertise to confirm that it is of an acceptable scientific standard.

Author Response 28 Mar 2018

Ayan Sengupta, Sir Peter Mansfield Imaging Centre, University of Nottingham, UK

This article explores the effect of spatial filtering on the decoding accuracy of BOLD fMRI data

Abstract: 'Reported evidence' is clumsy phrasing how about something like 'previous research'

The required phrases have been changed accordingly.

Introduction: The term spatial frequency is used frequently, whereas the difference of Gaussian

The unit of spatial frequency (FWHM) is kept unaltered in order to maintain parity with other previous papers (e.g. [Sengupta et al. 2017](#)). It is now explicitly referred to in the manuscript.

Stimulus and fMRI data: Please give slice orientation of fMRI acquisition. I believe it was axial,

The words 'axial slices' are now mentioned in the description of the acquisition protocol.

Figure 1 caption: gaussian->Gaussian.

The change is incorporated into the manuscript.

fMRI data analysis: prior masking -> prior to masking

This change is done.

Results and Conclusions: These are given with little discussion. Why do you think the decoding

We thank the reviewer for pointing this point in the manuscript. These points are now discussed in the manuscript.

Competing Interests: No competing interests were disclosed.

Referee Report 08 February 2018

doi:10.5256/f1000research.14869.r30541



Cyril R. Pernet

Neuroimaging Sciences, Centre for Clinical Brain Sciences, The University of Edinburgh, Edinburgh, UK

This is a good note, replicating previous results from vision to audition - and therefore showing that band-pass is an effective strategy, not specific to visual columns.

Method:

- You set a GLM to get beta estimates per genre for each run, and use this (z-scored) for decoding. You mention that you included temporal derivatives, were these ones used in any form? (note you can also correct the hrf amplitude estimates using the temporal derivative <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3896880/>)
- You used a within-subject leave-one-run-out cross-validation; as you know I'm sure, Gael showed that LOO tends to be biased (<https://arxiv.org/abs/1606.05201>). If I understand correctly, that means that the classification is done with 7 betas per class, predict 1 (and rotate). Obviously, that is an issue as K-folds will lead to an even smaller number of beta to use. I don't know if that's addressable here, but worth mentioning the issue (and even better do an alternative sampling scheme if you think it's feasible).

Is the work clearly and accurately presented and does it cite the current literature?

Yes

Is the study design appropriate and is the work technically sound?

Yes

Are sufficient details of methods and analysis provided to allow replication by others?

Partly

If applicable, is the statistical analysis and its interpretation appropriate?

Partly

Are all the source data underlying the results available to ensure full reproducibility?

Yes

Are the conclusions drawn adequately supported by the results?

Yes

Competing Interests: No competing interests were disclosed.

I have read this submission. I believe that I have an appropriate level of expertise to confirm that it is of an acceptable scientific standard, however I have significant reservations, as outlined above.

Author Response 28 Mar 2018

Ayan Sengupta, Sir Peter Mansfield Imaging Centre, University of Nottingham, UK

This is a good note, replicating previous results from vision to audition - and therefore showing

Method:

You set a GLM to get beta estimates per genre for each run, and use this (z-scored) for deconvolution

The GLM was performed in NiPy [v0.3;8] while accounting for serial correlation with an autoregressive first-order model

You used a within-subject leave-one-run-out cross-validation; as you know I'm sure, Gael should have

We thank the reviewer for raising this issue with the cross-validation procedure. We agree that the leave-one-run-out

Competing Interests: No competing interests were disclosed.

The benefits of publishing with F1000Research:

- Your article is published within days, with no editorial bias
- You can publish traditional articles, null/negative results, case reports, data notes and more
- The peer review process is transparent and collaborative
- Your article is indexed in PubMed after passing peer review
- Dedicated customer support at every stage

For pre-submission enquiries, contact research@f1000.com

F1000Research