

Technical University of Denmark



System perspective in material flow analysis for LCA studies

Pivnenko, Kostyantyn; Astrup, Thomas Fruergaard

Publication date:
2018

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Pivnenko, K., & Astrup, T. F. (2018). System perspective in material flow analysis for LCA studies. Poster session presented at 2nd Conference on Life Cycle Assessment of Waste, Copenhagen, Denmark.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

System perspective in material flow analysis for LCA studies



Kostyantyn Pivnenko (kosp@env.dtu.dk) and Thomas F. Astrup

INTRODUCTION

Plastics are produced in large volumes and used in many industrial sectors. However, there is a lack of comprehensive understanding of plastic flows from a system perspective. Material Flow Analysis (MFA) accounts for material inputs, outputs and stocks for a selected material. MFA is essential when performing a Life Cycle Assessment (LCA) of waste management systems. This work illustrates a system perspective when performing MFA of plastics in Europe.

METHODOLOGY

Flows of plastics in the European Union (EU) were estimated for a variety of polymers used in selected industrial sectors (packaging, agriculture, etc.). An example of polypropylene (PP) polymer is presented here. Both pre-consumer and post-consumer plastic waste was considered when quantifying flows of plastics in different waste management alternatives. Data presented here represent preliminary results of an ongoing research.




Figure 1. Overview of polypropylene (PP) flows in the EU.

RESULTS AND CONCLUSIONS

- Approximately 12,000,000 tonnes of PP polymer are annually produced in the EU and 20% are exported
- Roughly half of PP is used in packaging, followed by “other” (20%) and automotive (15%) sectors
- The six industrial sectors considered generate more than 5,000,000 tonnes of PP waste in the EU
- Approximately 40% of the (pre- and post-consumer) waste PP is collected for reprocessing and recycling
- Collection efficiency of the waste PP varies between 20% and 50% depending on industrial sector
- Almost 20% of the collected waste PP is exported outside of the EU for further sorting and reprocessing
- Less than 20% of PP consumed in the EU comes from recycled plastics (assuming no imports of recycled PP)
- LCA can be used to optimize environmental performance of the waste plastic management system
- Results of a potential LCA will depend on the choice of a material being displaced by recycled PP
- Potential chemical contamination of PP waste (e.g., BFRs (Pivnenko et al., 2017)) should be considered