

## Modeling the Effect of Surface Energy On Stressed Grain Growth In Cubic Polycrystalline Bodies

## M. Jamshidian<sup>a</sup>, P. Thamburaja<sup>b, c</sup>, T. Rabczuk<sup>d</sup>

- <sup>a</sup> Department of Mechanical Engineering, Isfahan University of Technology, Isfahan 84156-83111, Iran
- <sup>b</sup> Department of Mechanical & Materials Engineering, Universiti Kebangsaan Malaysia (UKM), Bangi 43600, Malaysia
  - <sup>c</sup> Faculty of Mechanical Engineering, Universiti Malaysia Pahang, 26600 Pekan, Pahang, Malaysia
- <sup>d</sup> Institute of Structural Mechanics, Bauhaus-University Weimar, Marienstrasse 15, 99423 Weimar, Germany

## **ABSTRACT**

A recently-developed constitutive theory of stressed grain growth is augmented to include the effect of excess surface energy via a surface effect state variable. The new constitutive theory is implemented into a coupled finite-element and phase-field computational framework. Through three-dimensional simulations, the new constitutive model is shown to be capable of predicting the experimental data of the annealing-induced texture transition in polycrystalline copper thin films of different thicknesses attached to a polyimide substrate. Our simulations show that the grain growth driving force arising from the through-film thickness grain boundary curvature plays a prominent role in such a transitional behavior.

KEYWORDS: Grain growth; Surface energy; Constitutive theory; Phase-field; Computer simulations

DOI: 10.1016/j.scriptamat.2015.11.005