

Experimental Investigation of Thermal Conductivity and Electrical Conductivity of BioGlycol - Water Mixture Based Al_2O_3 Nanofluid

M.Kh. Abdolbaqi^a, W.H. Azmi^{a, b, ,}, Rizalman Mamat^{a, b,}, K.V. Sharma^{c, 2,}, G. Najafi^{d,}

^a Faculty of Mechanical Engineering, Universiti Malaysia Pahang, 26600 Pekan, Pahang, Malaysia

^b Automotive Engineering Centre, Universiti Malaysia Pahang, 26600 Pekan, Pahang, Malaysia

^c Centre for Energy Studies, Department of Mechanical Engineering, JNTUH College of Engineering
Kukatpally, Hyderabad 500085, India

^d arbiat Modares University, Jalale-E-Aleahmad Highway, Tehran, Iran

ABSTRACT

Nanofluid as a new brand of cooling fluid consisting of nanometer-sized particles dispersed in base fluid. In this study, the thermal conductivity and electrical conductivity of BioGlycol (BG)–water (W) mixed nanofluids containing Al_2O_3 nanoparticles were studied. Nanofluids with 0.5 to 2.0% concentrations were prepared by the two-step method. The nanofluids demonstrated excellent stability over the temperature range of 30 to 80 °C after using the long term sonication process. Comparisons of the experimental data with many existing models illustrated that they do not display good agreement. Therefore, a new nonlinear model has been developed with 5% maximum deviation for the thermal conductivity of nanofluids as a function of temperature and volume concentration. The results of BG:W mixtures have displayed improvement in thermal performance of 7.5% in comparison with Propylene glycol (PG):W in similar circumstances. The thermal conductivity of nanofluid increased as a function of volume concentration and temperature. The maximum thermal conductivity enhancement using 40:60% (BG:W) mixture ratio was twice as high as 60:40% in the same conditions. Electrical conductivity was observed to decrease as the volume concentration increased. Thermo-electrical conductivity ratio (TEC) has been evaluated theoretically based on thermal and electrical conductivity results.

KEYWORDS: Nanofluids; BioGlycol; Aluminium oxide; Thermal conductivity; Electrical conductivity

DOI: [10.1016/j.applthermaleng.2016.03.074](https://doi.org/10.1016/j.applthermaleng.2016.03.074)