




ELSEVIER

Contents lists available at [ScienceDirect](http://ScienceDirect)

## Case Studies in Thermal Engineering

journal homepage: [www.elsevier.com/locate/csite](http://www.elsevier.com/locate/csite)



# Numerical study on turbulent forced convective heat transfer using nanofluids TiO<sub>2</sub> in an automotive cooling system



Adnan M. Hussein<sup>a,b,\*</sup>, H.K. Dawood<sup>c,d,\*\*</sup>, R.A. Bakara<sup>a</sup>, K. Kadirgamaa<sup>a</sup>

<sup>a</sup> Faculty of Mechanical Engineering, University Malaysia Pahang, 26600 Pekan, Pahang, Malaysia

<sup>b</sup> Al-Haweija Institute, Northern Technical University, Iraq

<sup>c</sup> Mechanical Engineering Department, College of Engineering, Universiti Tenaga Nasional, Jalan IKRAM-UNITEN, 43000 Kajang, Selangor, Malaysia

<sup>d</sup> Department of Mechanical Engineering, College of Engineering, University of Anbar, Ramadi, Anbar, Iraq

## ARTICLE INFO

## ABSTRACT

Friction factor  
Nusselt number  
Turbulent Convective Heat Transfer  
Car radiator

transfer of TiO<sub>2</sub> nanoparticles dispersed in water in a car radiator was numerically determined. Four different nanofluid volume concentrations (1%, 2%, 3% and 4%) were used, and the resulting thermal properties were evaluated. The Reynolds number and inlet temperature ranged from 10000 to 100000 and from 60 to 90 °C, respectively. The results showed that the friction factor decreases as the Reynolds number increases and increases as the volume concentration increases. Additionally, the Nusselt number increases as the Reynolds number and volume concentration of the nanofluid increases. The TiO<sub>2</sub> nanofluid at low concentrations can enhance the heat transfer efficiency up to 20% compared with that of pure water. There was good agreement among the CFD analysis and experimental data available in the literature.

