Contents lists available at ScienceDirect

Nano Energy

journal homepage: www.elsevier.com/locate/nanoen

Review

Advances in hole transport materials engineering for stable and efficient perovskite solar cells

Zinab H. Bakr^{a,b,1}, Qamar Wali^a, Azhar Fakharuddin^{c,d,*}, Lukas Schmidt-Mende^c, Thomas M. Brown^e, Rajan Jose^{a,*}

^a Nanostructured Renewable Energy Materials Laboratory, Faculty of Industrial Science & Technology, Universiti Malaysia Pahang, Kuantan, Malaysia

^b Physics Department, Faculty of Science, Assiut University, Assiut, Egypt

^c Department of Physics, University of Konstanz, D-78457, Konstanz, Germany

^d Nanosciences and Technology Department, National Center for Physics, Quaid-i-Azam University, Islamabad, Pakistan

e CHOSE (Centre for Hybrid and Organic Solar Energy), Department of Electronic Engineering, University of Rome Tor Vergata, via del Politecnico 1, Rome 00133, Italy

ARTICLE INFO

ABSTRACT

Stability of perovskite solar cells Open circuit voltage film solar cells. HTMs and electron transporting materials (ETMs) are important constituents in PSCs as they selectively transport charges within the device, influence photovoltaic parameters, determine device stability and also influence its cost. This article critically approaches role of structure, electrochemistry, and physical properties of varied of choice of HTMs categorized diversely as small and long polymers, organometallic, and inorganic on the photovoltaic parameters of PSCs conceived in various device configurations. Achievements in tailoring the properties of HTMs to best fit for PSCs are detailed; a well-designed HTM suppresses carrier recombination by facilitating the passage of holes but blocking electrons at the HTM/perovskite interface. Moreover, in many PSCs the HTM acts as the first line of defense to external degrading factors such as humidity, oxygen and photon dose, the extent of which depends on its hydrophobicity, permeability, and density.





