



Article

Experimental Investigation of Thermal Fatigue Die Casting Dies by Using Response Surface Modelling

Hassan Abdulrissoul Abdulhadi ^{1,3,*}, Syarifah Nur Aqida Syed Ahmad ¹, Izwan Ismail ², Mahadzir Ishak ¹ and Ghusoon Ridha Mohammed ^{1,3}

¹ Faculty of Mechanical Engineering, University Malaysia Pahang, Pekan 26600, Malaysia; aqida@ump.edu.my (S.N.A.S.A.); mahadzir@ump.edu.my (M.I.); ghusoon_ridha@yahoo.com (G.R.M.)

² Faculty of Manufacturing Engineering, University Malaysia Pahang, Pekan 26600, Malaysia; izwanismail@ump.edu.my

³ Baghdad-Institute, Foundation of Technical Education, Baghdad 10074, Iraq

* Correspondence: PMM14001@stdmail.ump.edu.my; Tel.: +60-129-457-483

Academic Editor: Filippo Berto

Received: 7 March 2017; Accepted: 25 April 2017; Published: 26 May 2017

Abstract: Mechanical and thermal sequences impact largely on thermo-mechanical fatigue of dies in a die casting operations. Innovative techniques to optimize the thermo-mechanical conditions of samples are major focus of researchers. This study investigates the typical thermal fatigue in die steel. Die surface initiation and crack propagation were stimulated by thermal and hardness gradients, acting on the contact surface layer. A design of experiments (DOE) was developed to analyze the effect of as-machined surface roughness and die casting parameters on thermal fatigue properties. The experimental data were assessed on a thermo-mechanical fatigue life assessment model, being assisted by response surface methodology (RSM). The eminent valuation was grounded on the crack length, hardness properties and surface roughness due to thermal fatigue. The results were analyzed using analysis of variance method. Parameter optimization was conducted using response surface methodology (RSM). Based on the model, the optimal results of 26.5 μm crack length, 3.114 μm surface roughness, and 306 $\text{HV}_{0.5}$ hardness properties were produced.

Keywords: response surface methodology; machining parameters; design of experiments; thermal fatigue