INTERNATIONAL JOURNAL OF GREEN ENERGY
https://doi.org/10.1080/15435075.2017.1334659

Dry reforming of methane over oil palm shell activated carbon and ZSM-5 supported cobalt catalysts

Izirwan Izhab[a], Nor Aishah Saidina Amin [b], and Mohd Asmadi[b]

[a]Chemical Reaction Engineering Group (CREG), Energy Research Alliance, Faculty of Chemical Engineering, Universiti Teknologi Malaysia, Johor Bahru, Johor, Malaysia; [b]Faculty of Chemical Engineering and Natural Resources, Universiti Malaysia Pahang, Lebuhraya Tun Razak, Gambang Kuantan, Pahang, Malaysia

ABSTRACT

In this study, cobalt supported oil palm shell activated carbon (Co/OPS-AC) and ZSM-5 zeolite (Co/ZSM-5) catalysts have been prepared for dry reforming of methane. Cobalt ratios of 6.0 and 14.0 wt% were deposited via wet impregnation method to the OPS-AC and ZSM-5 catalysts. The catalysts were characterized by XRD, N_2 adsorption–desorption isotherms, BET surface area, SEM, FESEM-EDX, TPR-H_2, and TPD-NH_3. The dry reforming of methane was performed using a micro reactor system under the condition of 10,000 ml/h.g-cat, 3 atm, CH_4/CO_2 ratio of 1.2:1.0 and temperature range from 923 K to 1023 K. The gaseous products were analyzed by gas chromatography (GC) with thermal conductivity detector (TCD) and further quantified to determine the conversions of CH_4 and CO_2, and the yields of CO and H_2. Experimental results revealed both catalysts exhibited lower conversions of CO_2 and CH_4 with the increase in temperature from 923 K to 1023 K. The reduced conversions may be due to the formation of carboneous substance on the catalyst known as coking. Comparatively, Co/OPS-AC gave higher conversions of CO_2 and CH_4 as well as higher yields of H_2 and CO as it has a higher surface area than Co/ZSM-5 which subsequently rendered higher activity for the reforming of methane. With the increasing cobalt loadings and reaction temperature, OPS-AC(14) catalyst exhibited improved activity and H_2/CO ratio. Based on these results, cobalt supported OPS activated carbon catalyst was suggested to be more effective for CO_2 and CH_4 conversions.

KEYWORDS

Activated carbon support; cobalt catalyst; methane dry reforming; oil palm shell; ZSM-5 support

CONTACT Nor Aishah Saidina Amin noraishah@cheme.utm.my Chemical Reaction Engineering Group (CREG), Energy Research Alliance, Faculty of Chemical Engineering, Universiti Teknologi Malaysia, 81310 Johor Bahru, Johor, Malaysia.

Color versions of one or more of the figures in the article can be found online at www.tandfonline.com/LJGE.