

Dual-band wearable fluidic antenna with metasurface embedded in a PDMS substrate

Muhammad Nazrin Ramli¹ · Ping Jack Soh¹  · Mohd Faizal Jamlos^{1,2} · Herwansyah Lago¹ · Norazizan Mohd Aziz¹ · Azremi Abdullah Al-Hadi¹

Received: 15 August 2016 / Accepted: 1 January 2017 / Published online: 8 February 2017
© Springer-Verlag Berlin Heidelberg 2017

Abstract A flexible fluidic antenna with an artificial magnetic conductor (AMC) plane is presented in this work. The overall structure is embedded in polydimethylsiloxane (PDMS), while the radiator is fabricated using eutectic gallium indium alloy (EGaIn) conductor. This radiator operating over an AMC plane is designed based on a rectangular patch which is integrated with slot and slits to enable dual-band WLAN ISM (2.4 and 5.8 GHz) operation, while maintaining a compact form. The integration of the AMC plane behind the proposed antenna reduced backward radiation towards the human users and improved gains. The evaluation of the antenna integrated with the AMC plane indicated satisfactory performance in terms of reflection coefficient, bandwidth and radiation patterns.

implementing a metasurface on the reverse side of the antenna [2, 3]. The most suitable metasurface for wearable antennas is the artificial magnetic conductor (AMC) metasurface, which is designed to filter propagation of a predefined sets of frequencies towards a certain direction. In recent years, more innovative solutions have been proposed to allow these AMC planes to be implemented on stretchable substrates [4, 5].

✉ Ping Jack Soh
pjsoh@unimap.edu.my

¹ Advance Communication Engineering (ACE) CoE, School of Computer and Communication Engineering, Universiti Malaysia Perlis, Pauh Putra Campus, 02600 Arau, Perlis, Malaysia

² Faculty of Mechanical Engineering, Universiti Malaysia Pahang, Pekan, Pahang, Malaysia