

# Analysis of combustion characteristics, engine performance and exhaust emissions of diesel engine fueled with upgraded waste source fuel



Abdullah Adam <sup>a,\*</sup>, Nur Atiqah Ramlan <sup>b</sup>, Nur Fauziah Jaharudin <sup>a</sup>,  
Herzwan Hamzah <sup>a</sup>, Mohd Fahmi Othman <sup>a</sup>, Anes Abdulla G. Mrwan <sup>a</sup>

<sup>a</sup> Faculty of Mechanical Engineering/Automotive Engineering Centre, Universiti Malaysia Pahang, 26600 Pekan, Pahang, Malaysia

<sup>b</sup> Vehicle System Engineering, Malaysia-Japan International Institute of Technology, Universiti Teknologi Malaysia, Kuala Lumpur, Malaysia

## ARTICLE INFO

Article history:

Received 9 November 2016

Received in revised form

13 March 2017

Accepted 4 April 2017

## ABSTRACT

Utilization of the waste products as an alternative fuel could reduce the dependence on fossil fuel. The three types of upgraded waste source fuels discussed in this paper were tire derived fuel (TDF), waste plastic disposal fuel (WPD) and upgraded waste cooking oil (UWCO). The detailed combustion pressure showed that kinematic viscosity and cetane number played an important role in determining the combustion quality. TDF's high

[View metadata, citation and similar papers at core.ac.uk](#)

brought to you by CORE

provided by UMP Institutional Repository

Keywords:

Diesel

Upgraded waste source fuel

Waste cooking oil

Particulate matter

Performance

Emissions

torque compared to diesel fuel (DF). WPD produced the lowest NOx due to its low pressure curve during combustion. TDF had produced the highest exhaust emissions (CO, CO<sub>2</sub>, NO and NOx). Particulate matter (PM) emissions by UWCO blends were lower than DF. UWCO's soot concentration was 40% lower than DF and increased to 62.5% from low to high engine speed operation.

© 2017 Hydrogen Energy Publications LLC. Published by Elsevier Ltd. All rights reserved.