CARBON MEMBRANES DERIVED FROM POLYMER BLEND OF POLYETHERIMIDE AND POLYETHYLENE GLYCOL FOR GAS SEPARATION

WAN NURUL HUDA BINTI WAN ZAINAL

UNIVERSITI SAINS MALAYSIA 2015

CARBON MEMBRANES DERIVED FROM POLYMER BLEND OF POLYETHERIMIDE AND POLYETHYLENE GLYCOL FOR GAS SEPARATION

by

WAN NURUL HUDA BINTI WAN ZAINAL

Thesis submitted in fulfilment of the requirements

for the degree of

Doctor of Philosophy

November 2015

ACKNOWLEDGEMENTS

In the name of Allah, the Most Gracious and the Most Merciful.

Alhamdulillah, all praises to Allah for the strengths and His blessing in completing

this thesis. I am using this opportunity to express my deepest gratitude to my

supervisors, Associate Professor Dr. Mohd Azmier Ahmad, Associate Professor Dr.

Tan Soon Huat and Dr. Muhamad Nazri Murat, for their aspiring guidance,

invaluably constructive criticism, friendly advice and support during the last four

years.

I would like to express my appreciation to the Dean School of Chemical

Engineering, Deputy Dean (Research), lecturers and staffs for their support and help

towards my postgraduate affair. Indeed, their willingness in sharing ideas,

knowledge and skills are deeply appreciated. I am grateful to the Ministry of

Education for providing me scholarship through MyPhD and Universiti Sains

Malaysia for providing the USM Membrane Cluster Grant and Postgraduate

Research Grant Scheme.

Most importantly, none of this could have happened without the continued

support and encouragement from my family especially my parents, Mr. Wan Zainal

Wan Muhammad and Mrs. Saloma Husin, my siblings, aunt and my friends. To

those who indirectly contributed in this research, your kindness means a lot to me.

May Allah richly bless all of you.

Wan Nurul Huda binti Wan Zainal

November 2015

ii

TABLE OF CONTENTS

| Ackn | nowledgements | ii |
|-------|--|-------|
| Table | e of Contents | iii |
| List | of Tables | х |
| List | of Figures | xii |
| List | of Plates | xviii |
| List | of Abbreviations | xix |
| List | of Symbols | xxii |
| Abstı | rak | XXV |
| Abst | ract | xxvii |
| | | |
| СНА | PTER 1 - INTRODUCTION | |
| 1.1 | Gas Separation Technology | 1 |
| 1.2 | Membrane Technology for Gas Separation | 3 |
| 1.3 | Carbon Membrane for Gas Separation | 6 |
| 1.4 | Problem Statement | 8 |
| 1.5 | Research Objectives | 11 |
| 1.6 | Scope of the Study | 12 |
| 1.7 | Organization of the Thesis | 13 |
| | | |
| СНА | PTER 2 – LITERATURE REVIEW | |
| 2.1 | Carbon Membrane | 15 |
| 2 2 | Gas Transport in Carbon Membrane | 19 |

| 2.3 | Precurso | or of Carbon M | embrane | 24 |
|-----|----------|--------------------------------------|---------------------------------|----|
| 2.4 | Modific | ation of Carbo | n Membrane | 30 |
| | 2.4.1 | Partial Pyro | lyzed Membrane | 30 |
| | 2.4.2 | Polymer Pre | ecursor Modified-derived Carbon | 32 |
| | | Membrane | | |
| | 2.4.3 | Mixed Matr | ix Carbon Membrane | 33 |
| | 2.4.4 | Polymer Ble | end-derived Carbon Membrane | 35 |
| 2.5 | Support | ed Carbon Mer | mbrane | 40 |
| | 2.5.1 | Membrane | Support | 40 |
| | 2.5.2 | Precursor S | election | 41 |
| | 2.5.3 | Polymeric N | Membrane Preparation | 41 |
| | 2.5.4 | Pre-treatme | nt | 42 |
| | 2.5.5 | Carbonizati | on | 43 |
| | | 2.5.5 (a) | Carbonization Temperature | 44 |
| | | 2.5.5 (b) | Carbonization Heating Rate | 49 |
| | | 2.5.5 (c) | Carbonization Soaking Time | 50 |
| 2.6 | Membra | ne Aging and | Regeneration of Carbon Membrane | 51 |
| 2.7 | Gas Per | meation Perfor | mance of the Carbon Membrane | 53 |
| | 2.7.1 | Permeation | Temperature and Feed Pressure | 53 |
| | 2.7.2 | CO ₂ /CH ₄ Se | eparation | 54 |
| | 2.7.3 | CO ₂ /N ₂ Sep | aration | 55 |
| | 2.7.4 | O ₂ /N ₂ Separ | ration | 57 |
| | 2.7.5 | Robeson Plo | ot | 58 |
| 2.8 | Conclud | ling Remarks | | 60 |

CHAPTER 3 – MATERIALS AND METHODS

| 3.1 | Material | S | | 62 |
|-----|----------|---|--------------------|----------|
| 3.2 | Equipme | Equipment | | |
| 3.3 | Preparat | ion of PEG/PEI Carbon Membr | anes | 64 |
| | 3.3.1 | Preparation of Membrane Su | pport | 65 |
| | 3.3.2 | Preparation of Al ₂ O ₃ Interme | diate Layer | 66 |
| | 3.3.3 | Preparation of Polymer Solut | ion | 67 |
| | 3.3.4 | Preparation of Supported | d PEG/PEI Car | rbon 68 |
| | | Membrane | | |
| | 3.3.5 | Preparation of Unsupport | ed PEG/PEI Car | rbon 68 |
| | | Membrane | | |
| 3.4 | Carboni | zation | | 68 |
| 3.5 | Gas Pen | meability and Separation Studie | S | 70 |
| | 3.5.1 | Single Gas Permeability | | 70 |
| | | 3.5.1 (a) Experimental Set | -up and Procedure | 70 |
| | | 3.5.1 (b) Single Gas Pe | rmeability and I | deal 72 |
| | | Selectivity Calcu | lations | |
| | 3.5.2 | Binary Gas Permeability and | Separation Studies | 73 |
| | | 3.5.2 (a) Experimental Set | -up and Procedure | 73 |
| | | 3.5.2 (b) Analysis with Ga | s Chromatography | 75 |
| | | 3.5.2 (c) Permeability | and Select | ivity 75 |
| | | Calculations | | |
| 3.6 | Paramet | er Studies | | 76 |
| | 3.6.1 | Effect of Different Polymer I | Blend Ratio | 76 |

| | 3.6.2 | Parameter Studies in Carbonization Process | 77 |
|------|------------|---|----|
| | | 3.6.2 (a) Effect of Carbonization Temperature | 77 |
| | | 3.6.2 (b) Effect of Carbonization Heating Rate | 77 |
| | | 3.6.2 (c) Effect of Carbonization Soaking Time | 78 |
| | 3.6.3 | Parameter Studies in Single Gas Permeability Test | 78 |
| 3.7 | Carbon N | Membranes Characterization | 78 |
| | 3.7 (a) | Thermal Gravimetric Analysis | 79 |
| | 3.7 (b) | Fourier Transform Infra-Red | 79 |
| | 3.7 (c) | Scanning Electron Microscopy | 80 |
| | 3.7 (d) | X-ray Diffraction | 80 |
| | 3.7 (e) | Elemental Analysis | 81 |
| | 3.7 (f) | Atomic Force Microscopy | 81 |
| | 3.7 (g) | N ₂ Adsorption-Desorption | 81 |
| 3.8 | Regenera | ation of the Carbon Membrane | 82 |
| 3.9 | Micropo | re Size Estimation Model | 82 |
| | 3.9.1 | Model Assumption | 83 |
| | 3.9.2 | Model Development | 83 |
| СНАР | PTER 4 – R | RESULTS AND DISCUSSIONS | |
| 4.1 | Modifica | ation of Alumina Support with Al ₂ O ₃ Intermediate | 87 |
| | Layer | | |
| | 4.1 (a) | N ₂ Adsorption-Desorption Analysis of Al ₂ O ₃ | 89 |
| | | Intermediate Layer | |

| | 4.1 (b) | Surface M | Morphology of Al ₂ O ₃ Intermediate Layer | 90 |
|-----|-----------|-------------|---|-----|
| | | and Alum | ina Support | |
| | 4.1 (c) | Gas Perme | eation Performance of Alumina Support | 91 |
| 4.2 | Effect of | Polymer Ble | end Ratio and Carbonization Parameters on | 92 |
| | Carbon N | Membranes I | Performance and Structure | |
| | 4.2.1 | Effect of I | Different Polymer Blend Ratio | 92 |
| | | 4.2.1 (a) | Thermal Gravimetric | 92 |
| | | 4.2.1 (b) | Surface Morphology | 95 |
| | | 4.2.1 (c) | N ₂ Adsorption-Desorption | 97 |
| | | 4.2.1 (d) | Single Gas Permeation Performance and | 98 |
| | | | Ideal Selectivity | |
| | 4.2.2 | Effect of (| Carbonization Temperature | 104 |
| | | 4.2.2 (a) | Microstructure of Carbon Membrane | 104 |
| | | 4.2.2 (b) | Surface Chemistry of Carbon Membrane | 106 |
| | | 4.2.2 (c) | Surface Morphology of Carbon | 108 |
| | | | Membrane | |
| | | 4.2.2 (d) | Single Gas Permeation Performance and | 111 |
| | | | Ideal Selectivity | |
| | 4.2.3 | Effect of C | Carbonization Heating Rate | 119 |
| | | 4.2.3 (a) | Microstructure of Carbon Membrane | 119 |
| | | 4.2.3 (b) | Surface Morphology of the Carbon | 121 |
| | | | Membrane | |
| | | 4.2.3 (c) | Single Gas Permeation Performance and | 122 |
| | | | Ideal Selectivity | |

| | 4.2.4 | Effect of C | Carbonizatio | n Soaking Tim | e | | 129 |
|------|------------|---------------|-----------------------|-----------------|---------|----------|-----|
| | | 4.2.4 (a) | Surface | Morphology | of | Carbon | 129 |
| | | | Membrane | • | | | |
| | | 4.2.4 (b) | Single Gas | s Permeation Pe | erform | ance and | 131 |
| | | | Ideal Selec | etivity | | | |
| 4.3 | Characte | rizations and | l Gas Separa | tion Performan | ce of P | PEG/PEI- | 137 |
| | 650-R1-2 | 2h Carbon M | Iembrane | | | | |
| | 4.3.1 | Characteri | ization | | | | 137 |
| | | 4.3.1 (a) | Elemental | Analysis | | | 137 |
| | | 4.3.1 (b) | N ₂ Adsorp | tion-Desorption | n | | 138 |
| | | 4.3.1 (c) | Surface | Гороgraphy (| Atomi | c Force | 139 |
| | | | Microscop | y) | | | |
| | 4.3.2 | Compariso | on of Perme | ation Performa | ince o | f Carbon | 141 |
| | | Membrane | es | | | | |
| | 4.3.3 | Effect of l | Permeation (| Conditions on C | Gas Pe | rmeation | 142 |
| | | Performan | nce | | | | |
| | | 4.3.3 (a) | Effect of P | Permeation Ten | nperati | ıre | 142 |
| | | 4.3.3 (b) | Effect of F | eed Pressure | | | 145 |
| 4.4 | Binary G | as Permeabi | ility of PEG/ | PEI Carbon M | embra | ne | 146 |
| 4.5 | Effect of | Membrane | Aging | | | | 150 |
| 4.6 | Micropo | re Size Estin | nation | | | | 154 |
| | | | | | | | |
| СНАР | PTER 5 – C | CONCLUSIO | ONS AND R | ECOMMEND | ATIO] | NS | |
| 5.1 | Conclusi | ons | | | | | 156 |

| 5.2 | Recommendations | 157 |
|------------|-----------------|-----|
| | | |
| REFERENCES | | 159 |
| APPE | ENDICES | |
| LIST | OF PUBLICATIONS | |

LIST OF TABLES

| | | Page |
|-----------|---|------|
| Table 2.1 | Molecular dimensions and molecular weight of gas | 22 |
| | penetrants | |
| Table 2.2 | Carbon membranes derived from various polymer | 28 |
| | precursors | |
| Table 2.3 | Mixed matrix carbon membranes | 34 |
| Table 2.4 | Carbon membranes derived from polymer blend | 37 |
| | precursor | |
| Table 2.5 | Carbonization temperatures studied in the preparation | 46 |
| | of the supported carbon membranes | |
| Table 3.1 | List of chemicals used for the research | 63 |
| Table 3.2 | List of gases | 63 |
| Table 3.3 | List of equipment | 64 |
| Table 3.4 | Operating conditions of the gas chromatography | 75 |
| Table 3.5 | Preparation of the polymer precursor at different PEG | 77 |
| | compositions | |
| Table 3.6 | List of equipment used for the characterization | 79 |
| Table 4.1 | Single gas permeability of the alumina support | 92 |
| Table 4.2 | Surface area and micropore volume of PEI and | 98 |
| | PEG/PEI carbon membranes | |
| Table 4.3 | Functional groups observed in the FTIR spectra of the | 108 |
| | PEG1/PEI film and carbon membranes | |

| Table 4.4 | Results of the elemental analysis of the PEI and | 138 |
|-----------|--|-----|
| | PEG/PEI precursors and carbon membranes | |
| Table 4.5 | Comparison of the permeation performance of the | 141 |
| | carbon membranes | |
| Table 4.6 | Comparison of gas transport properties between single | 147 |
| | and binary gas for CO ₂ /CH ₄ separation | |
| Table 4.7 | Comparison of gas transport properties between single | 147 |
| | and binary gas for CO ₂ /N ₂ separation | |
| Table 4.8 | Comparison of gas transport properties between single | 147 |
| | and binary gas for O ₂ /N ₂ separation | |

LIST OF FIGURES

| | | Page |
|------------|--|------|
| Figure 1.1 | Milestones in the industrial application of membrane | 4 |
| | gas separation systems (Bernardo and Clarizia, 2013) | |
| Figure 1.2 | Typical molecular sieving mechanism (Ismail et al., | 7 |
| | 2011) | |
| Figure 2.1 | Schematic structure of carbonized membrane | 16 |
| | (Kusakabe et al., 1998) | |
| Figure 2.2 | Non-graphitising carbon structure (McEnaney, 1999) | 16 |
| Figure 2.3 | Idealized "slit-like" carbon structure (Steel and Koros, | 17 |
| | 2003) | |
| Figure 2.4 | Bimodal PSD of carbon membranes (Steel, 2000) | 18 |
| Figure 2.5 | (a) XRD pattern of the phenolic resin (PR) carbon | 18 |
| | membrane (Zhang et al., 2014) and (b) SEM | |
| | micrograph of the polyimide (PI) carbon membrane | |
| | (Tseng et al., 2009) | |
| Figure 2.6 | Gas transport mechanisms in porous membrane | 20 |
| Figure 2.7 | Concept of the polymer blending for carbon | 36 |
| | membranes fabrication (Ozaki et al., 1997) | |
| Figure 2.8 | Schematic sketch represent the aging in the carbon | 52 |
| | membranes (Xu et al., 2014) | |
| Figure 2.9 | Upper bound correlation of the (a) CO ₂ /CH ₄ , (b) | 59 |
| | CO ₂ /N ₂ and (c) O ₂ /N ₂ (Robeson, 2008) | |

| Figure 3.1 | Flowchart of the study | 62 |
|------------|---|----|
| Figure 3.2 | Schematic diagram of the supported carbon membrane | 65 |
| Figure 3.3 | Flowchart of the supported PEG/PEI carbon | 66 |
| | membranes preparation | |
| Figure 3.4 | Schematic diagram of carbonization experimental set- | 69 |
| | up | |
| Figure 3.5 | Carbonization profile for the carbon membranes | 70 |
| | preparation | |
| Figure 3.6 | Schematic diagram of the single gas permeability test | 71 |
| | set-up | |
| Figure 3.7 | Schematic diagram of the membrane permeation cell | 72 |
| Figure 3.8 | Schematic diagram of the binary gas permeability test | 74 |
| | set-up | |
| Figure 3.9 | Schematic diagram of a gas molecule permeates | 85 |
| | through a cylindrical pore (Lee et al., 2011) | |
| Figure 4.1 | N ₂ adsorption-desorption isotherm of Al ₂ O ₃ | 90 |
| | intermediate layer | |
| Figure 4.2 | Pore size distribution of Al ₂ O ₃ intermediate layer | 90 |
| Figure 4.3 | Weight loss and derivative weight versus temperature | 93 |
| | of (a) PEI (b) PEG1/PEI (c) PEG2/PEI (d) PEG3/PEI | |
| | and (e) PEG4/PEI films | |
| Figure 4.4 | Single gas permeability of carbon membranes derived | 99 |
| | from different PEG:PEI blend ratio | |

| Figure 4.5 | Ideal selectivity of carbon membranes derived from | 101 | |
|-------------|---|-----|--|
| | different blend ratios | | |
| Figure 4.6 | Trade-off relationship between (a) CO ₂ permeability 10 | | |
| | and CO ₂ /CH ₄ selectivity, (b) CO ₂ permeability and | | |
| | CO_2/N_2 selectivity and (c) O_2 permeability and O_2/N_2 | | |
| | selectivity of carbon membranes derived at different | | |
| | polymer blend ratios | | |
| Figure 4.7 | XRD pattern of (a) PEG1/PEI-700 (b) PEG1/PEI-650 | 105 | |
| | (c) PEG1/PEI-600 (d) PEG1/PEI-550 and (e) | | |
| | PEG1/PEI film | | |
| Figure 4.8 | FTIR spectra of (a) PEG1/PEI-700 (b) PEG1/PEI-650 | 107 | |
| | (c) PEG1/PEI-600 (d) PEG1/PEI-550 and (e) | | |
| | PEG1/PEI film | | |
| Figure 4.9 | Single gas permeability of (a) CO ₂ , (b) O ₂ , (c) N ₂ and | 112 | |
| | (d) CH ₄ as a function of carbonization temperature for | | |
| | PEI and PEG1/PEI carbon membranes | | |
| Figure 4.10 | Ideal selectivity of (a) CO ₂ /CH ₄ , (b) CO ₂ /N ₂ and (c) | 115 | |
| | $\mathrm{O}_2/\mathrm{N}_2$ of the PEI and PEG1/PEI carbon membranes | | |
| | derived at different carbonization temperatures | | |
| Figure 4.11 | Trade-off relationship between (a) CO ₂ permeability | 117 | |
| | and CO ₂ /CH ₄ ideal selectivity, (b) CO ₂ permeability | | |
| | and CO_2/N_2 ideal selectivity and (c) O_2 permeability | | |
| | and O ₂ /N ₂ ideal selectivity of the PEI and PEG1/PEI | | |

| | carbon membranes derived at different carbonization | |
|-------------|---|-----|
| | temperatures | |
| Figure 4.12 | XRD pattern of (a) PEG1/PEI-R1 (b) PEG1/PEI-R3 | 120 |
| | (c) PEG1/PEI-R5 and (d) PEG1/PEI-R7 | |
| Figure 4.13 | Single gas permeability of (a) CO ₂ , (b) O ₂ , (c) N ₂ and | 123 |
| | (d) CH ₄ as a function of carbonization heating rate of | |
| | the PEI and PEG1/PEI carbon membranes | |
| Figure 4.14 | Ideal selectivity of (a) CO ₂ /CH ₄ , (b) CO ₂ /N ₂ and (c) | 126 |
| | O ₂ /N ₂ of the PEI and PEG1/PEI carbon membranes | |
| | derived at different carbonization heating rates | |
| Figure 4.15 | Trade-off relationship between (a) CO ₂ permeability | 128 |
| | and CO ₂ /CH ₄ ideal selectivity, (b) CO ₂ permeability | |
| | and CO ₂ /N ₂ ideal selectivity and (c) O ₂ permeability | |
| | and O_2/N_2 ideal selectivity of the PEI and PEG1/PEI | |
| | carbon membranes derived at different carbonization | |
| | heating rates | |
| Figure 4.16 | Single gas permeability of (a) CO ₂ , (b) O ₂ , (c) N ₂ and | 131 |
| | (d) CH ₄ as a function of carbonization soaking time | |
| | for the PEI and PEG1/PEI carbon membranes | |
| Figure 4.17 | Ideal selectivity of (a) CO ₂ /CH ₄ , (b) CO ₂ /N ₂ and (c) | 134 |
| | O ₂ /N ₂ of the PEI and PEG1/PEI carbon membranes | |
| | derived at different carbonization soaking times | |
| Figure 4.18 | Trade-off relationship between (a) CO ₂ permeability | 136 |
| | and CO ₂ /CH ₄ ideal selectivity, (b) CO ₂ permeability | |

| | and CO ₂ /N ₂ ideal selectivity and (c) O ₂ permeability | |
|-------------|---|-----|
| | and O ₂ /N ₂ ideal selectivity of the PEI and PEG1/PEI | |
| | carbon membranes derived at different carbonization | |
| | soaking times | |
| Figure 4.19 | MSD of the PEG/PEI carbon membrane estimated | 139 |
| | from H-K method | |
| Figure 4.20 | Single gas performance through the PEG/PEI carbon | 142 |
| | membrane as a function of permeation temperatures | |
| Figure 4.21 | Relationship between the activation energy and gas | 144 |
| | kinetic diameter | |
| Figure 4.22 | Ideal selectivity of the PEG/PEI carbon membrane as | 144 |
| | a function permeation temperatures | |
| Figure 4.23 | Single gas performance through the PEG/PEI carbon | 145 |
| | membrane at different feed pressure | |
| Figure 4.24 | Ideal selectivity of the PEG/PEI carbon membrane at | 146 |
| | different feed pressure | |
| Figure 4.25 | Trade-off relationship between (a) CO ₂ permeability | 149 |
| | and CO ₂ /CH ₄ ideal selectivity, (b) CO ₂ permeability | |
| | and CO ₂ /N ₂ ideal selectivity and (c) O ₂ permeability | |
| | and O ₂ /N ₂ ideal selectivity of the PEG/PEI carbon | |
| | membrane for single and binary gas mixtures | |
| Figure 4.26 | Single gas permeability of fresh, aged and regenerated | 150 |
| | of PEG/PEI carbon membrane | |

| Figure 4.27 | Ideal selectivity of the fresh, aged and regenerated of | |
|-------------|---|-----|
| | the PEG/PEI carbon membrane | |
| Figure 4.28 | Trade-off relationship between (a) CO ₂ permeability | 153 |
| | and CO ₂ /CH ₄ ideal selectivity, (b) CO ₂ permeability | |
| | and CO ₂ /N ₂ ideal selectivity and (c) O ₂ permeability | |
| | and O_2/N_2 ideal selectivity of fresh, aged and | |
| | regenerated PEG/PEI carbon membrane | |
| Figure 4.29 | Normalized permeabilities as a function of gas kinetic | 155 |
| | diameter of the PEG/PEI carbon membrane | |

LIST OF PLATES

| | | Page |
|-----------|--|------|
| Plate 4.1 | Surface of PEG/PEI carbon membranes (a) without | 88 |
| | Al ₂ O ₃ intermediate layer and (b) with Al ₂ O ₃ intermediate | |
| | layer after carbonization | |
| Plate 4.2 | Schematic structure and cross section of the derived | 88 |
| | carbon membranes | |
| Plate 4.3 | SEM micrographs of (i) surface and (ii) cross section of | 91 |
| | Al ₂ O ₃ intermediate layer | |
| Plate 4.4 | SEM micrographs of (i) surface and (ii) cross section of | 96 |
| | (a) PEI (b) PEG1/PEI (c) PEG2/PEI (d) PEG3/PEI and | |
| | (e) PEG4/PEI carbon membranes | |
| Plate 4.5 | SEM micrographs of (i) surface and (ii) cross section of | 109 |
| | (a) PEG1/PEI membrane (b) PEG1/PEI-550 (c) | |
| | PEG1/PEI-600 (d) PEG1/PEI-650 and (e) PEG1/PEI-700 | |
| Plate 4.6 | SEM micrographs of (i) surface and (ii) cross section of | 121 |
| | (a) PEG1/PEI-R1 (b) PEG1/PEI-R3 (c) PEG1/PEI-R5 | |
| | and (d) PEG1/PEI-R7 | |
| Plate 4.7 | SEM images of (i) surface and (ii) cross section of (a) | 130 |
| | PEG1/PEI-1h (b) PEG1/PEI-2h (c) PEG1/PEI-3h | |
| Plate 4.8 | The three dimensional AFM surface images of (a) PEI | 140 |
| | and (b) PEG/PEI carbon membranes | |

LIST OF ABBREVIATIONS

6FDA 2,2'-bis(3,4-dicarboxyphenyl) hexafluoropropane

dianhydride

AFM Atomic force microscopy

APB 1,3-Bis(3-aminophenoxy) benzene

BET Brunauer-Emmet-Teller

BJH Barrett-Joyner-Halenda

BPDA Biphenyltetracarboxylic dianhydride

BTDA Benzophenone tetracarboxylic dianhydride

CA Cellulose acetate

CM Carbon membrane

DAM Diamino mesitylene

DDBT Dimethyldibenzothiophene sulfone

FA Furfuryl alcohol

FFV Fractional free volume

HCN Hydrogen cyanide

HFCM Hollow fiber carbon membrane

H-K Horvath-Kawazoe

IUPAC International Union of Pure and Applied Chemistry

MFI Mordenite framework inverted

MMSCFD Million metric standard cubic feet per day

MSD Micropore size distribution

MWNT Multi-walled carbon nanotube

NDA Naphthalene dicarboxylic acid

NMP N-methyl-2-pyrrolidone

NPC Nanoporous carbon

ODA Oxydianiline

PAN Polyacrylonitrile

PEG Polyethylene glycol

PEI Polyetherimide

PFA Polyfurfuryl alcohol

PFNR Phenol formaldehyde novolac resin

PFR Phenol formaldehyde resin

PI Polyimide

PPES poly(phthalazinone ether sulfone)

PPESK poly(phthalazinone ether sulfone ketone)

PPM Partially pyrolyzed membrane

PPO Poly(phenylene oxide)

PPy Polypyrrole

PR Phenolic resin

PSA Pressure swing adsorption

PSD Pore size distribution

PVB Poly(vinylbutyral)

PVDC-AC Polyvinylidene chloride-acrylate terpolymer

PVDC-PVC Poly(vinylidene chloride)-polyvinyl chloride

PVP Polyvinylpyrrolidone

RFR Resorcinol-formaldehyde resin

RF Resin formaldehyde

SEM Scanning electron microscopy

SPAEK Sulfonated poly(aryl ether ketone)

Tg Glass transition temperature

TGA Thermal gravimetric analysis

TMS Trimethylsilyl

TrisAPB tris-1,3-Bis(3-aminophenoxy) benzene

TSA Thermal swing adsorption

XRD X-ray diffraction

LIST OF SYMBOLS

| | | Unit |
|-------------------------------|--|---------------------|
| A | Membrane area | cm^2 |
| Ag | Silver | - |
| Al_2O_3 | Alumina | - |
| Ar | Argon | - |
| Ao | Cross-sectional area of the pore | cm ² |
| A_i | Cross-sectional area of the pore | cm ² |
| b | Equilibrium adsorption constant | Pa ⁻¹ |
| C | Carbon | - |
| C ₃ H ₆ | Propene | - |
| C ₃ H ₈ | Propane | - |
| CH ₄ | Methane | - |
| CO | Carbon monoxide | - |
| CO_2 | Carbon dioxide | - |
| D | Diffusion coefficient | $m^2 s^{-1}$ |
| d | Dimension spacing | nm |
| $d_{\it eff}$ | Effective diffusion space | nm |
| d_k | Diameter of permeating gas | nm |
| d_p | Pore diameter | nm |
| dc/dx | Concentration gradient of the gas across | mol m ⁻⁴ |
| | the membrane | |
| E_a | Apparent activation energy | kJ/mol |

| f_P | Normalized gas permeability | - |
|-----------------|---|-------------------------------------|
| Н | Hydrogen | - |
| H_2 | Hydrogen gas | - |
| l | Thickness of the membrane material | cm |
| J | Flux of gas through the membrane | $mol m^{-2} s^{-1}$ |
| M | Molecular weight of the gas | g/mol |
| N | Nitrogen | - |
| N_2 | Nitrogen gas | - |
| N_p | Number of pores | - |
| n | Integral number | - |
| NH ₃ | Ammonia | - |
| NO_x | Nitrogen oxides | - |
| 0 | Oxygen | - |
| O_2 | Oxygen gas | - |
| P | Permeability | barrer |
| P/l | Permeance | GPU |
| p | Pressure | Pa |
| p feed | Pressure at feed stream | cmHg |
| Q | Volumetric flow rate of gas at standard | cm^3/s |
| | temperature and pressure | |
| R | Gas constant | J K ⁻¹ mol ⁻¹ |
| T | Absolute temperature | K |
| t | Time | S |
| V | Volume of permeate gas | cm ³ |