

Contents lists available at ScienceDirect

International Journal of Mechanical Sciences

journal homepage: www.elsevier.com/locate/ijmecsci

An analytical and numerical approach to multiscale ductility constraint based model to predict uniaxial/multiaxial creep rupture and cracking rates

N.A. Alang^{a,b}, K. Nikbin^{a,*}^a Department of Mechanical Engineering, Imperial College London, Exhibition Road, London SW7 2AZ, United Kingdom^b Faculty of Mechanical Engineering, University Malaysia Pahang, 26600, Pahang, Malaysia

ARTICLE INFO

Keywords:

Constraint
Cracks
Creep
Damage
Ductility
Fractures mechanics
Multiaxial

ABSTRACT

Uniaxial damage modelling use constituent components of the stress/strain measured data which have inherent scatter. Models developed for this purpose have also attempted to address the issues related to failure mechanisms within a multiaxial stress state context. This paper presents the multiscale approach to constraint by using the relationship between Monkman-Grant (MG) uniform failure strain and local sub-grain stress state to predict creep damage and rupture under uniaxial/multiaxial conditions. In essence, a global geometric constraint and a time-dependent local sub-grain constraint is defined with the latter controlling the failure response of the geometry. The model compliments and is in agreement with the established NSW model is also used to predict the lower/upper bound of cracking rates in crack dominated geometries. The model is employed into a finite element (FE) to assess its capability to numerically predict the rupture of plain and multiaxial notched bar specimens based on appropriate void growth models. For verification, creep constitutive properties of long term data from uniaxial and multiaxial tests on Grade 92 martensitic steels from various databases, where available, are used to establish the procedure. Given the level of scatter in the data and fabrication and testing uncertainties that cannot be accounted for in such databases, it is shown that the model is sufficiently simple and robust to be developed for use in conservatively predicting very long term failure times.

Crown Copyright © 2017 Published by Elsevier Ltd. All rights reserved.

* Corresponding author.

E-mail addresses: n.alang13@imperial.ac.uk (N.A. Alang), k.nikbin@imperial.ac.uk (K. Nikbin).<https://doi.org/10.1016/j.ijmecsci.2017.11.030>

Received 3 August 2017; Received in revised form 6 November 2017; Accepted 21 November 2017

Available online 22 November 2017

0020-7403/Crown Copyright © 2017 Published by Elsevier Ltd. All rights reserved.