



City Research Online

City, University of London Institutional Repository

Citation: Rodriguez, C., Vidal, A., Koukouvinis, P. ORCID: 0000-0002-3945-3707, Gavaises, M. ORCID: 0000-0003-0874-8534 and McHugh, M. A. (2018). Simulation of transcritical fluid jets using the PC-SAFT EoS. *Journal of Computational Physics*, 374, doi: 10.1016/j.jcp.2018.07.030

This is the accepted version of the paper.

This version of the publication may differ from the final published version.

Permanent repository link: <http://openaccess.city.ac.uk/20290/>

Link to published version: <http://dx.doi.org/10.1016/j.jcp.2018.07.030>

Copyright and reuse: City Research Online aims to make research outputs of City, University of London available to a wider audience. Copyright and Moral Rights remain with the author(s) and/or copyright holders. URLs from City Research Online may be freely distributed and linked to.

City Research Online:

<http://openaccess.city.ac.uk/>

publications@city.ac.uk

Accepted Manuscript

Simulation of transcritical fluid jets using the PC-SAFT EoS

C. Rodriguez, A. Vidal, P. Koukouviniis, M. Gavaises, M.A. McHugh


PII: S0021-9991(18)30491-1
DOI: <https://doi.org/10.1016/j.jcp.2018.07.030>
Reference: YJCPH 8155

To appear in: *Journal of Computational Physics*

Received date: 1 February 2018
Revised date: 11 July 2018
Accepted date: 12 July 2018

Please cite this article in press as: C. Rodriguez et al., Simulation of transcritical fluid jets using the PC-SAFT EoS, *J. Comput. Phys.* (2018), <https://doi.org/10.1016/j.jcp.2018.07.030>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



Highlights

- A numerical framework to simulate transcritical and supercritical flows utilising the compressible form of the Navier–Stokes equations coupled with the Perturbed Chain Statistical Associating Fluid Theory (PC-SAFT) equation of state (EoS) is presented.
- Both conservative and quasi-conservative formulations have been tested.
- Advection test cases and shock tube problems are included to show the overall performance of the developed framework.
- Two-dimensional simulations of nitrogen and dodecane jets are presented to demonstrate the multidimensional capability of the developed model.

Simulation of transcritical fluid jets using the PC-SAFT EoS

C. Rodriguez ^{a,*}, A. Vidal ^a, P. Koukouvinis ^a, M. Gavaises ^a, M. A. McHugh ^b

^a School of Mathematics, Computer Science & Engineering, Department of Mechanical Engineering & Aeronautics, City University London, Northampton Square EC1V 0HB, United Kingdom

^b Department of Chemical and Life Science Engineering, 601 West Main Street, Richmond, VA 23284, USA

*Corresponding author: Carlos.Rodriguez@city.ac.uk

Abstract

The present paper describes a numerical framework to simulate transcritical and supercritical flows utilising the compressible form of the Navier-Stokes equations coupled with the Perturbed Chain Statistical Associating Fluid Theory (PC-SAFT) equation of state (EoS); both conservative and quasi-conservative formulations have been tested. This molecular model is an alternative to cubic EoS which show low accuracy computing the thermodynamic properties of hydrocarbons at temperatures typical for high pressure injection systems. Liquid density, compressibility, speed of sound, vapour pressures and density derivatives are calculated with more precision when compared to cubic EoS. Advection test cases and shock tube problems are included to show the overall performance of the developed framework employing both formulations. Additionally, two-dimensional simulations of nitrogen and dodecane jets are presented to demonstrate the multidimensional capability of the developed model.

Keywords: Supercritical, transcritical, PC-SAFT EoS, double-flux model, Riemann problem

Nomenclature

List of abbreviations

AAD	Average Absolute Deviation
CFD	Computational Fluid Dynamics
CFL	Courant–Friedrichs–Lewy
ENO	Essentially Non-Oscillatory
EoS	Equation of State
FC	Fully Conservative
HLLC	Harten-Lax-van Leer-Contact
LES	Large Eddy Simulation
PR	Peng-Robinson
PC-SAFT	Perturbed Chain Statistical Associating Fluid Theory
QC	Quasi-Conservative
RK2	Second-order Runge–Kutta
SRK	Soave-Redlich-Kwong

46	SSP-RK3	Third-order strong-stability-preserving Runge–Kutta
47	TVD	Total Variation Diminishing
48	WENO	Weighted Essentially Non-Oscillatory

49

50 *List of Symbols*

51	\tilde{a}^{es}	Reduced Helmholtz free energy [-]
52	c	Sound speed [m s^{-1}]
53	d	Temperature-dependent segment diameter [\AA]
54	g	Radial distribution function [-]
55	I	Integrals of the perturbation theory [-]
56	k_B	Boltzmann constant [J/K]
57	m	Number of segments per chain [-]
58	\bar{m}	Mean segment number in the system [-]
59	p	Pressure [Pa]
60	R	Gas constant [$\text{J mol}^{-1} \text{K}^{-1}$]
61	T	Temperature [K]
62	x_i	Mole fraction of component i [-]
63	Z	Compressibility factor [-]
64	\mathbf{U}	Conservative variable vector
65	\mathbf{F}	x-convective flux vector
66	\mathbf{G}	y-convective flux vector
67	\mathbf{F}_V	x-diffusive flux vector
68	\mathbf{G}_V	y-diffusive flux vector

69

70 *Greek Letters*

71	ε	Depth of pair potential [J]
72	η	Packing fraction [-]
73	ρ	Density [kg/m^3]
74	ρ_m	Total number density of molecules [$1/\text{\AA}^3$]
75	σ_d	Segment diameter [\AA]

76

77 *Superscripts*

78	disp	Contribution due to dispersive attraction
79	hc	Residual contribution of hard-chain system
80	hs	Residual contribution of hard-sphere system
81	id	Ideal gas contribution

82

83

84

85

86

87

88

89 1. Introduction

90 Transcritical and supercritical states occur in modern combustion engines that operate at
91 pressures higher than the critical pressure of the fuels utilised. In Diesel engines for example,
92 the liquid fuel is injected into air at pressure and temperature conditions higher than the
93 critical point of the fuel [1]. The liquid injection temperature is lower than the fuel critical
94 temperature but as the liquid is heated, it may reach supercritical temperature before full
95 vaporisation. This is known as a transcritical injection. Similarly, in liquid rocket engines,
96 cryogenic propellants are injected into chambers under conditions that exceed the critical
97 pressure and temperature of the propellants.

98 A single-species fluid or a mixture reaches a supercritical state when the pressure and
99 temperature surpass its critical properties. In the critical region, repulsive interactions
100 overcome the surface tension resulting in the existence of a single-phase that exhibits
101 properties of both gases and liquids (e.g., gas-like diffusivity and liquid-like density). A
102 diffuse interface method is commonly employed in supercritical and transcritical jet
103 simulations to capture the properties of the flow [2]–[4]. Several difficulties should be
104 overcome for simulating the mixing of the jets using a diffused interface [5]. The presence of
105 large density gradients between the liquid-like and the gas-like regions, the need of using a
106 real-fluid EoS, or the spurious pressure oscillations generated in conservative schemes are the
107 main challenges.


108 High order reconstruction methods are usually applied to capture the large density
109 gradients. The authors of [6] performed a two-dimensional large-eddy simulation (LES) of
110 supercritical mixing and combustion employing a fourth-order flux-differencing scheme and a
111 total-variation-diminishing (TVD) scheme in the spatial discretization. In [7] a fourth-order
112 central differencing scheme with fourth-order scalar dissipation was applied in order to
113 stabilize the simulation of a cryogenic fluid injection and mixing under supercritical
114 conditions. Moreover, [8] employed an eighth-order finite differencing scheme to simulate
115 homogeneous isotropic turbulence under supercritical pressure conditions, while in [9] a
116 density-based sensor was utilized, which switches between a second-order ENO (Essentially
117 non-oscillatory) and a first-order scheme to suppress oscillations. In the present study a fifth-
118 order WENO (Weighted Essentially Non-Oscillatory) scheme [10] is applied due to its high
119 order accuracy and non-oscillatory behaviour.

120 Cubic EoS models like PR (Peng-Robinson) [11] and SRK (Soave-Redlich-Kwong) EoS
121 [12] are usually used in supercritical and transcritical simulations. In the studies reported in
122 [4], [13]–[15] the SRK EoS was employed in order to close the Navier Stokes equations and
123 compute the fluid properties under supercritical and transcritical conditions. Moreover, the
124 works reported in [3], [9], [16], [17] modeled the non-ideal fluid behavior applying the PR
125 EoS. However, cubic models commonly present low accuracy computing the thermodynamic
126 properties of hydrocarbons at temperatures typical for injection systems [2]. To overcome
127 this, the Statistical Association Fluid Theory Equation of State (SAFT EoS) can be employed.
128 This molecular model is based on the perturbation theory, as extensively studied in [18]–[21]
129 by Wertheim. The authors of [22], [23] developed this EoS by applying Wertheim's theory
130 and extending it to mixtures. Figure 1 shows a schematic representation of the terms
131 considered in the SAFT equation. Each molecule is represented by segments of equal size,
132 assumed to form a repulsive, hard sphere reference fluid. Next, the attractive interactions
133 between segments are added to the model. The segment-segment energy needed to form a
134 chain between the hard-sphere fluid segments is included and, if the segments exhibit
135 associative interactions, such as hydrogen bonding, a term for this interaction is also added.

136 Among the different variants of the SAFT model, the PC-SAFT is the one implemented
 137 here. In this model, hard chains are used as the reference fluid instead of hard spheres. While
 138 the SAFT EoS computes segment-segment attractive interactions, the PC-SAFT EoS
 139 computes chain-chain interactions, which improves the thermodynamic description of chain-
 140 like, fluid mixtures [24].

141 Several papers have been published pointing out the advantages of the SAFT models
 142 with respect to the cubic EoS commonly used in CFD simulations. For example, [25]
 143 describes how the PC-SAFT model is better than cubic EoS for predicting gas phase
 144 compressibility factors and oil phase compressibilities. In [26] the superiority of the PC-
 145 SAFT performance is demonstrated relative to the Cubic Plus Association (CPA) EoS in
 146 correlating second order derivative properties, like speed of sound, dP/dV and dP/dT
 147 derivatives, heat capacities and the Joule–Thomson coefficient in the alkanes investigated.
 148 Similarly, [27] points out the superiority of the SAFT-BACK EoS over the PR EOS,
 149 particularly at high-density conditions, for computing second order derivative properties such
 150 as sound velocity and isobaric and isochoric properties. The study of [28] states that cubic
 151 EoS predict a linear increase of the Z factor (compressibility factor) with pressure, while the
 152 PC-SAFT EoS shows a better pressure dependence. Finally, [29] shows how the sPC-SAFT
 153 (simplified PC-SAFT) is more precise than SRK and CPA to compute the speed of sound of
 154 normal alkanes and methanol.

155 If a fully conservative (FC) formulation is employed along with a real-fluid EoS,
 156 spurious pressure oscillations may appear; the work of [4] has related this problem to
 157 computational stability issues, turbulence, and acoustics accuracy loss. The same authors of
 158 [4] developed a quasi-conservative (QC) scheme solving a pressure evolution equation
 159 instead of the energy conservation equation, while [30] developed a quasi-conservative
 160 framework where the artificial dissipation terms in the mass, momentum and energy
 161 equations are related and the pressure differential is considered to be zero. In [31] the double
 162 flux model was developed to avoid spurious pressure oscillations in simulations of
 163 compressible multicomponent flows that employ a perfect gas EoS; [32] extended it to
 164 reactive flows; and finally, [3], [17], [33] extended the double flux model to real-fluids and
 165 transcritical conditions. However, recently it has been reported that the large energy
 166 conservation error in quasi-conservative schemes maybe produce an unphysical quick heat-up
 167 of the jet [2].



168 **Figure 1. Schematic representation of the attractive and repulsive contributions of the SAFT EoS**
 169 **and the PC-SAFT EoS [24]**
 170

171 The novelty of the approach described here is the coupling of the PC-SAFT EoS with
 172 the Navier-Stokes equations, which it is not present in the literature. During the last years
 173 conservative and quasi-conservative formulations have been employed in the simulation of

174 supercritical and transcritical jets. For this reason, two codes have been developed employing
 175 both schemes: the conservative and the so-called quasi-conservative approach, where the
 176 double flux model of [3], [17], [33] is utilized. The aim of this research is not to solve the
 177 spurious pressure oscillations characteristic of FC schemes when real-fluid EoS are applied or
 178 the energy conservation error of QC formulations but to present how the Navier-Stokes
 179 equations can be closed with the PC-SAFT in both scenarios. Advection test cases and shock
 180 tube problems are included to show the overall performance of the developed framework
 181 using both formulations. Moreover, two-dimensional simulations of nitrogen and dodecane
 182 jets are presented to demonstrate the capability of the code to predict fluid mixing.

183

184 2. Numerical Method

185 The Navier-Stokes equations for a non-reacting multi-component mixture containing N
 186 species in a x - y 2D Cartesian system are given by:

187

$$188 \frac{\partial \mathbf{U}}{\partial t} + \frac{\partial \mathbf{F}}{\partial x} + \frac{\partial \mathbf{G}}{\partial y} = \frac{\partial \mathbf{F}_v}{\partial x} + \frac{\partial \mathbf{G}_v}{\partial y} \quad (1)$$

189

190 The vectors of eq. 1 are:

$$191 \mathbf{U} = \begin{bmatrix} \rho Y_1 \\ \vdots \\ \rho Y_N \\ \rho u \\ \rho v \\ \rho E \end{bmatrix}, \mathbf{F} = \begin{bmatrix} \rho u Y_1 \\ \vdots \\ \rho u Y_N \\ \rho u^2 + p \\ \rho u v \\ (\rho E + p)u \end{bmatrix}, \mathbf{G} = \begin{bmatrix} \rho v Y_1 \\ \vdots \\ \rho v Y_N \\ \rho v u \\ \rho v^2 + p \\ (\rho E + p)v \end{bmatrix}, \mathbf{F}_v = \begin{bmatrix} J_{x,1} \\ \vdots \\ J_{x,N} \\ \sigma_{xx} \\ \sigma_{xy} \\ u\sigma_{xx} + v\sigma_{xy} - q_x \end{bmatrix}, \quad (2)$$

$$192 \mathbf{G}_v = \begin{bmatrix} J_{y,1} \\ \vdots \\ J_{y,N} \\ \sigma_{yx} \\ \sigma_{yy} \\ u\sigma_{yx} + v\sigma_{yy} - q_y \end{bmatrix}$$

193

194 where ρ is the fluid density, u and v are the velocity components, p is the pressure, E is the
 195 total energy, J_i is the mass diffusion flux of species i , σ is the deviatoric stress tensor and q
 196 is the diffusion heat flux vector.

197

198 The finite volume method has been applied in this work for obtaining a numerical
 199 solution to the above equations. The PC-SAFT EoS is implemented to simulate supercritical
 200 and transcritical states. The developed numerical framework considers a condition of
 201 thermodynamic equilibrium in each cell. Phase separations or metastable thermodynamic
 202 states are beyond the scope of this research and are not considered.

203

203 2.1 Formulations

204

205

Since PC-SAFT EoS is rarely used in CFD simulations, two codes have been
 developed employing different formulations (conservative and quasi-conservative) to

206 determine which one is more appropriate for the simulation of transcritical and supercritical
207 fluid jets.

208 **2.1.1 Conservative formulation**

209 Operator splitting [34] is adopted to divide the physical processes into hyperbolic and
210 parabolic sub-steps. The global time step is computed using the CFL (Courant–Friedrichs–
211 Lewy) criterion of the hyperbolic operator.

212

213 ***Hyperbolic sub-step***

214 The HLLC (Harten-Lax-van Leer-Contact) solver is used to solve the Riemann
215 problem. The conservative variables are interpolated onto the cell faces using a fifth-order
216 WENO scheme [10] due to its high order accuracy and non-oscillatory behaviour. TVD
217 (Total Variation Diminishing) limiters [34] are applied to avoid oscillations near
218 discontinuities. Time integration is performed using a SSP-RK3 (third-order strong-stability-
219 preserving Runge–Kutta) method [35].

220

221 ***Parabolic sub-step***

222 The method developed in [36] is applied to calculate the values of the dynamic
223 viscosity and thermal conductivity of the mixture. The model of [37] is implemented to
224 compute the diffusion coefficient. A RK2 (second-order Runge–Kutta) scheme is employed
225 to perform the time integration of this sub-step. Linear interpolation is performed for
226 computing the conservative variables, enthalpy and temperature on faces from cell centres.

227

228 **2.1.2 Quasi-conservative formulation**

229 The physical processes are divided into hyperbolic and parabolic sub-steps using
230 operator splitting as well [34]. The CFL criterion of the hyperbolic operator is used to
231 compute the global time step.

232

233 ***Hyperbolic sub-step***

234 The double flux model of [3], [17], [33] has been implemented. The HLLC solver is
235 used to solve the Riemann problem. In the one-dimensional cases presented, the primitive
236 variables are interpolated onto the cell faces using a fifth-order WENO scheme [10]. In the
237 two-dimensional cases, a sensor that compares the value of the density in the faces and the
238 centre of the cells is employed to determine in which regions a more dissipative scheme must
239 be applied [3]. If the sensor is activated, TVD limiters [34] are employed. The solution is
240 then blended with a first-order scheme (90% WENO). Time integration is performed using a
241 SSP-RK3 method [35].

242

243 The following steps were followed to implement the double flux model [3], [17], [33]:

244 1) In each cell are stored the values of γ^* (eq.3) and e_0^* (eq.4).

$$245 \quad \gamma^* = \frac{\rho c^2}{p} \quad (3)$$

$$246 \quad e_0^* = e - \frac{pv}{\gamma^* - 1} \quad (4)$$

247 where p is the pressure, c is the sound speed, e is the internal energy and v is the
248 specific volume.

249

250 2) Runge-Kutta scheme

251 • Step 1: The fluxes at the faces are computed using the primitive variables. The total
252 energy in the left (L) and right (R) states are computed using eq.5.

$$253 \quad (\rho E)_{L,R}^n = \frac{p_{L,R}^n}{\gamma_j^{*,n} - 1} + \rho_{L,R}^n e_{0,j}^{*,n} + \frac{1}{2} \rho_{L,R}^n \mathbf{u}_{L,R}^n \cdot \mathbf{u}_{L,R}^n \quad (5)$$

254 • Step 2: Update conservative variables using the RK scheme

255 • Step 3: Update primitive variables (using the double flux model to compute the
256 pressure).

257
258 3) Update total energy: The total energy is updated from primitive variables based on the EoS
259 (eq.6). Only at this point the PC-SAFT EoS is used to compute the internal energy, sound
260 speed, temperature and enthalpy.

$$261 \quad \rho E = \rho e + \frac{1}{2} \rho \mathbf{u} \cdot \mathbf{u} \quad (6)$$

262

263 **Parabolic sub-step**

264 The diffusion fluxes are calculated conservatively in the same way that is explained in the
265 conservative formulation.

266

267 **2.2 PC-SAFT EoS subroutine**

268 A different subroutine has been developed for each formulation because of the different
269 inputs of the EoS subroutine.

270

271 **Conservative formulation**

272 The thermodynamic variables computed in the CFD code by the PC-SAFT EoS are
273 the temperature, pressure, sound speed and enthalpy. The algorithm inputs are the density,
274 internal energy, molar fractions and three pure component parameters per component
275 (number of segments per chain, energy parameter of each component and segment diameter),
276 see Table 1. The density and the internal energy are obtained from the conservative variables
277 of the CFD code. The molar fractions are computed using the mass fractions employed in the
278 continuity equations and the molar weights of the components. The pure component
279 parameters are specified in the initialization of the simulation. A detailed description of the
280 PC-SAFT EoS can be found in the Appendix A.

281 The Newton-Raphson method is employed to compute the temperature that is needed
282 to calculate the value of all other thermodynamic variables. The temperature dependent
283 function used in the iterative method is the internal energy. Initially, a temperature value is
284 assumed (for example the value of the temperature from the previous time RK sub-step or
285 from the previous time step) to initialize the iteration process. In most cells, this value is close
286 to the solution. Then the compressibility factor is calculated as the sum of the ideal gas
287 contribution (considered to be 1), the dispersion contribution and the residual hard-chain
288 contribution (Appendix A):

289

$$290 \quad Z = 1 + Z^{hc} + Z^{disp} \quad (7)$$

291

292 The pressure is then calculated using eq.8 once the compressibility factor is known [38]:

$$293 \quad p = Z k_B T \rho_m (10^{10})^3 \quad (8)$$

294 where k is the Boltzmann constant and ρ_m is the total number density of molecules.

295 Finally, the internal energy is estimated as the sum of the ideal internal energy and the
 296 residual internal energy. The ideal internal energy is computed using the ideal enthalpy. The
 297 residual internal energy is calculated using eq.9 [39]:

$$298 \quad \frac{e^{res}}{RT} = -T \left(\frac{\partial \tilde{a}^{res}}{\partial T} \right)_{\rho, x_i} \quad (9)$$

300 where \tilde{a}^{res} is the reduced Helmholtz free energy.

301

302 If the difference between the internal energy computed with the PC-SAFT model and the
 303 value obtained from the conservative variables is bigger than 0.001J/kg, the Newton-Raphson
 304 method is applied to calculate a new value of the temperature and the aforementioned steps
 305 are repeated, see Appendix D.

306

307 ***Quasi-conservative formulation***


308 The thermodynamic variables computed in the CFD code by the PC-SAFT EoS are the
 309 temperature, internal energy, sound speed and enthalpy. The algorithm inputs are the density,
 310 pressure, molar fractions and three pure component parameters per component. The density
 311 and mass fractions (used to compute the molar fractions) are obtained from the conservative
 312 variables. The pressure is obtained employing the double flux model. The temperature is
 313 iterated until the difference between the pressure computed with the PC-SAFT model and the
 314 value obtained from the double flux model is lower than 0.001Pa, see Appendix D.

315

316 **2.3 Peng-Robinson EoS and PC-SAFT EoS comparison**

317 The most attractive feature of the PC-SAFT EoS is the better prediction of derivative
 318 properties such as compressibility and speed of sound. [27] shows the inaccuracy of cubic
 319 models to predict second derivative properties such as isobaric heat capacity and sound
 320 velocity in hydrocarbons at high density ranges. In the case of the sonic fluid velocity, the
 321 AAD% (Average Absolute Deviation) by PR EoS for methane, ethane, and propane are
 322 28.6%, 14.7%, and 61.2%, respectively.

323 Figure 2 presents a comparison of the thermodynamic properties of n-dodecane at
 324 6MPa computed using the PC-SAFT EoS and the Peng-Robinson EoS. NIST Refprop [40]
 325 has been used as reference due to its extensive validation with experimental data. While the
 326 results of both EoS are quite similar at density values lower than 550 Kg/m³ there is a
 327 significant difference at higher densities, especially in the sound speed. Cubic models
 328 commonly present low accuracy computing the thermodynamic properties of hydrocarbons at
 329 temperatures typical for injection systems [2]. However, the PC-SAFT EoS shows an
 330 accuracy similar to NIST without the need of an extensive model calibration as only three
 331 parameters are needed to model a specific component. Another advantage is the possibility of
 332 computing the thermodynamic properties of mixtures; NIST has limited mixture
 333 combinations.



334 **Figure 2: Comparison of thermodynamic properties of n-dodecane at 6MPa computed using the**
 335 **PC-SAFT EoS and the Peng-Robinson EoS: (a) density, (b) sound speed, (c) internal energy**

336 3. Results

337 Initially, advection test cases and shock tube problems are solved to validate the
 338 hyperbolic part of the numerical framework employing the conservative and quasi-
 339 conservative formulations, while the parabolic part is omitted. Following, two-dimensional
 340 simulations of transcritical and supercritical nitrogen and dodecane jets are presented,
 341 including the parabolic part, to prove the multi-dimensional capability of the code.

342

343 3.1. One-dimensional cases

344 3.1.1 Advection test cases

345 *Conservative formulation*


346 Figure 3 shows the results of the supercritical Advection Test Case 1, see Table 2.
 347 Nitrogen is used as working fluid (The critical properties of nitrogen are $p_{c,N_2} = 3.4$ MPa and
 348 $T_{c,N_2} = 126.2$ K). The computational domain is $x \in [0, 1]$ m; the initial conditions in $0.25\text{m} < x$
 349 $< 0.75\text{m}$ are $\rho = 250$ kg/m³, $p = 5$ MPa, and $T = 139.4$ K; in the rest of the domain are $\rho = 45.5$
 350 kg/m³, $p = 5$ MPa, and $T = 367.4$ K. The advection velocity applied is 50m/s; periodic boundary
 351 conditions are utilized; a uniform grid spacing of 0.01m is employed; the simulated time is
 352 $t = 0.02\text{s}$; and the CFL is set to be 0.5. Four spatial discretization schemes are compared: fifth-
 353 order WENO, second-order (based on the Minmod limiter), first order and a blend of the
 354 fifth-order WENO and the first-order schemes (95% WENO and rest 1st order).

355 The oscillations are more severe when high-order reconstruction schemes are applied.
 356 By blending a high-order scheme and a low-order model, dissipation can be used to smooth
 357 the numerical solution. If the advection test case is initialized using a smooth profile no
 358 spurious pressure oscillation appear in the solution as the sharp jumps in the thermodynamic
 359 properties between cells are avoided, see Figure 4. The smooth initial interface was generated
 360 as described in [13] using eq.10.


$$361 \quad q = q_L(1 - f_{sm}) + q_R f_{sm} \quad (10)$$

$$362 \quad f_{sm} = \frac{(1 + \text{erf}[\Delta R / \varepsilon])}{2} \quad (11)$$

363 Where L and R refers to the left and right states respectively and ΔR is the distance from the
 364 initial interface. $\varepsilon = C_\varepsilon \Delta x$, where Δx is the grid spacing and C_ε is a free parameter to
 365 determine the interface smoothness set to be 8.
 366




367 **Figure 3. Advection Test Case 1 (N₂), FC formulation, CFL = 0.5, u = 50 m/s, 100 cells,**
 368 **t=0.02 s. Comparison of the (a) density, (b) temperature, (c) pressure and (d) x-velocity**
 369 **between the analytical and the numerical solution.**
 370



371 **Figure 4. Advection Test Case 1 (N₂), FC formulation, CFL = 0.5, u = 50 m/s, 300 cells,**
 372 **t=0.01 s. Comparison of the (a) density, (b) temperature, (c) pressure and (d) x-velocity**
 373 **between the analytical and the numerical solution.**

374 **Quasi-conservative formulation**

375 Figure 5 presents the results of the transcritical Advection Test Case 1 solved using the
 376 QC formulation. The advection velocity applied is 50m/s; periodic boundary conditions are
 377 applied; a uniform grid spacing of 0.01m is used; the simulated time is $t=0.02s$; and the CFL
 378 is set to be 1. Unlike the fully conservative scheme, spurious pressure oscillations are not
 379 present in the solution.
 380



381 **Figure 5. Advection Test Case 1 (N₂), FC and QC formulations, CFL(FC) = 0.5,**
 382 **CFL(QC)=1.0, $u = 50$ m/s, 100 cells, $t=0.02$ s. Comparison of the (a) density, (b)**
 383 **temperature, (c) pressure and (d) x-velocity between the analytical and the numerical**
 384 **solution.**
 385

386 Figure 6 presents the results of the transcritical Advection Test Case 2 where nitrogen
 387 is used as working fluid, see Table 2. The computational domain is $x \in [0, 1]$ m; the initial
 388 conditions in $0.25 \text{ m} < x < 0.75 \text{ m}$ are $\rho=804.0 \text{ kg/m}^3$, $p=4 \text{ MPa}$, and $T=84.41 \text{ K}$; in the rest of
 389 the domain the initial conditions are $\rho=45.5 \text{ kg/m}^3$, $p=4 \text{ MPa}$, and $T=299.0 \text{ K}$. The advection
 390 velocity utilized is 100 m/s; periodic boundary conditions are used; the computational domain
 391 is $x \in [0, 1]$ m; 150 cells are employed; the simulated time is $t=0.01 \text{ s}$; a fifth-order WENO
 392 discretization scheme is used; and the CFL is set to be 1.0. It can be observed how large
 393 density gradients are solved without spurious pressure oscillations applying the double flux
 394 model.

395 Figure 7 shows the results of the transcritical advection of n-dodecane at supercritical
 396 pressure and subcritical temperature ($p_{c,n\text{-dodecane}}=1.817 \text{ MPa}$, $T_{c,n\text{-dodecane}}=658.1 \text{ K}$) in
 397 supercritical nitrogen, Advection Test Case 3 (Table 2). The computational domain is $x \in$
 398 $[0,1]$ m; the initial conditions in $0.25\text{m} < x < 0.75\text{m}$ are $\rho_{n\text{-dodecane}}=700.0 \text{ kg/m}^3$, $p_{n\text{-dodecane}}=$
 399 6MPa , and $T_{n\text{-dodecane}}=360.1 \text{ K}$; in the rest of the domain $\rho_{N_2}=20.0 \text{ kg/m}^3$, $p_{N_2}=6 \text{ MPa}$, and T_{N_2}
 400 $=965.7 \text{ K}$. The advection velocity utilized is 100 m/s; periodic boundary conditions are used;
 401 150 cells are employed; the simulated time is $t=0.01 \text{ s}$; a fifth-order WENO discretization
 402 scheme is used; and the CFL is set to be 1.0. Unlike conservative codes, velocity and pressure
 403 equilibriums are preserved in multicomponent cases if the double flux model is applied.

404

Table 1. PC-SAFT pure component parameters [38]

	m	$\sigma[\text{\AA}]$	$\epsilon/k[\text{K}]$
NITROGEN	1.2053	3.3130	90.96
DODECANE	5.3060	3.8959	249.21

405

406

407

Table 2. 1D Test Cases

ADVECTION TEST CASES			
CASE 1	Pressure [MPa]	Density [kg/m ³]	Temperature [K]
0.25 m < x < 0.75 m	N ₂ , 5	N ₂ , 250	N ₂ , 139.4
0.25 m > x or x > 0.75 m	N ₂ , 5	N ₂ , 45.5	N ₂ , 367.4
CASE 2			
0.25 m < x < 0.75 m	N ₂ , 4	N ₂ , 804	N ₂ , 84.4
0.25 m > x or x > 0.75 m	N ₂ , 4	N ₂ , 45.5	N ₂ , 299.0
CASE 3			
0.25 m < x < 0.75 m	n-dodecane, 6.0	n-dodecane, 700.0	n-dodecane, 360.1
0.25 m > x or x > 0.75 m	N ₂ , 6.0	N ₂ , 20.0	N ₂ , 965.7
SHOCK TUBE PROBLEM			
PROBLEM	Pressure [MPa]	Density [kg/m ³]	Temperature [K]
x < 0.5 m	n-dodecane, 13.0	n-dodecane, 700.0	n-dodecane, 372.8
x > 0.5 m	n-dodecane, 6.0	n-dodecane, 150.0	n-dodecane, 944.4

408


409

410


Table 3. 2D Test Cases

CASE A	Pressure [MPa]	Density [kg/m ³]	Temperature [K]
JET	N ₂ , 4.0	N ₂ , 804.0	N ₂ , 84.4
CHAMBER	N ₂ , 4.0	N ₂ , 45.5	N ₂ , 299.5
CASE B			
JET	N ₂ , 4.0	N ₂ , 440.0	N ₂ , 127.0
CHAMBER	N ₂ , 4.0	N ₂ , 44.5	N ₂ , 305.0
CASE C			
JET	n-dodecane, 11.1	n-dodecane, 450.0	n-dodecane, 687.2
CHAMBER	N ₂ , 11.1	N ₂ , 37.0	N ₂ , 972.9

411



412 Figure 6. Advection Test Case 2 (N₂), QC formulations, CFL = 1.0, $u = 150$ m/s, 100 cells,
 413 $t=0.01$ s. Comparison of the (a) density, (b) temperature, (c) pressure and (d) x-velocity
 414 between the analytical and the numerical solution.
 415
 416



417 Figure 7. Advection Test Case 3 (N₂ - Dodecane), QC formulations, CFL = 1.0, $u = 100$
 418 m/s, 150 cells, $t=0.01$ s. Comparison of the (a) density, (b) temperature, (c) pressure and
 419 (d) x-velocity between the analytical and the numerical solution.
 420
 421
 422


423 **Energy conservation error in the quasi-conservative formulation**

424 The evolution of the energy conservation error of the Advection Test Case 2 is presented in
 425 Figure 8 . The error has been evaluated employing eq.12 [3].
 426

$$427 \quad \mathcal{E} = \left| \frac{\int_{\Omega} [(\rho E)(t) - (\rho E)(0)] dx}{\int_{\Omega} (\rho E)(0) dx} \right| \quad (12)$$


428 where \mathcal{E} is the relative error of the total energy respect to initial conditions and Ω is the
 429 computational domain.
 430

431 The energy conservation error is higher using the PC-SAFT EoS than Peng-Robinson EoS.
 432 This is related to the fact that the profiles of γ^* and e_0^* are smoother employing the cubic
 433 model. There are shaper jumps in the internal energy and speed of sound employing the PC-
 434 SAFT EoS, see Figure 10. The error in the conservation of the energy depends on the jumps
 435 in the variables $1/(\gamma^* - 1)$ and e^* [3]. A convergence of the error to 0 exists increasing the
 436 refinement.



437

438 **Figure 8. Relative energy conservation error computed using eq.10 of the QC formulation for the**
 439 **Advection Test Case 2 (Transcritical nitrogen) using the Peng-Robinson EoS (PR) and the PC-**
 440 **SAFT EoS. N is the number of cells employed.**
 441



442

443

444

Figure 9. Relative energy conservation error computed using eq.10 of QC formulation for the
Advection Test Case 3 using the PC-SAFT EoS. N is the number of cells employed.




Figure 10. Advection Test Case 2 (N_2), QC formulation, CFL = 1.0, $u = 150$ m/s, 100 cells, $t=0.01$ s. Comparison of γ^* and e_0^* computed using the Peng Robinson EoS (PR EoS) and the PC-SAFT in the Advection Test Case 2.

Figure 9 presents the evolution of the energy conservation error of the Advection Test Case 3. Because of the different thermodynamic properties of the components, a higher energy conservation error than in the single-species cases appears. Although, a convergence to 0 is observed in one-dimensional cases increasing the refinement like in the single-species cases.


3.1.2 Shock tube problems

The Euler equations are solved in this validation so a direct comparison with the exact solver can be done. The exact solution has been computed using the methodology described in [41].


Quasi-conservative formulation

The domain is $x \in [0, 1]$ m. The working fluid employed is dodecane. A fifth-order WENO scheme is employed to interpolate the primitive variables onto the cell faces. 800 equally spaced cells were used. Wave transmissive boundary conditions are implemented in the left and right sides. The double flux model is applied. The pressure exceeds the critical value in all the domain while there is a transition in the temperature from subcritical to supercritical from left to right. The initial conditions in the left state are $\rho_L=700$ kg/m³, $p_L=13$ MPa, $u_L=0$ m/s; and in the right state are $\rho_R=150$ kg/m³, $p_R=6$ MPa, $u_R=0$ m/s. The simulated time is $t=0.2$ ms.

Figure 11 displays the results obtained for density, temperature, pressure and velocity. Despite being a quasi-conservative scheme, the double flux model [3], [17], [33] can solve strong shock waves in transcritical cases with a high degree of accuracy without generating spurious pressure oscillations.



473
474
475
476
Figure 11. Shock Tube Problem 1 (Dodecane), QC formulation, CFL = 1.0, 800 cells, $t=0.2$ ms. Comparisons of (a) density, (b) temperature, (c) velocity and (d) pressure profiles: exact solution and numerical solution.




477
478
479
480
Figure 12. Shock Tube Problem 1 (Dodecane), FC formulation, CFL = 0.5, 4000 cells, $t=0.2$ ms. Comparisons of (a) density, (b) temperature, (c) velocity and (d) pressure profiles: exact solution and numerical solution.

481 **Conservative formulation**

482 The same shock tube problem described before is solved. A fifth-order WENO
 483 scheme is employed to interpolate the conservative variables onto the cell faces. Large
 484 spurious pressure oscillations appear in the solution because of the sharp jumps in the
 485 thermodynamic properties between cells, see Figure 12.

487 **Comparison with the Peng-Robinson EoS (Quasi-conservative formulation)**

488 Figure 13 shows the density, temperature, pressure, velocity, sound speed and
 489 internal energy of the same shock tube problem solved in a larger domain $x \in [0, 2]$ m using
 490 the PC-SAFT and the Peng-Robinson EoS. The simulated time is $t=0.3$ ms. The quasi-
 491 conservative formulation has been employed. 800 equally spaced cells were used. A
 492 significant difference can be observed in the results between the two EoS. Due to the high
 493 deviation in the sound speed computed by the Peng-Robinson EoS in the high-density region,
 494 the expansion wave travels much faster using the cubic model. Moreover, the calculated
 495 temperatures are much lower using the Peng-Robinson EoS in the high-density region.
 496



497 **Figure 13. Shock Tube Problem 2 (Dodecane), QC formulation, CFL = 1.0, 800 cells,**
 498 **$t=0.3$ ms. Comparison of the (a) density, (b) temperature, (c) pressure, (d) x-velocity, (e)**
 499 **sound speed, (f) internal energy between the numerical solutions obtained using the**
 500 **Peng-Robinson EoS and the PC-SAFT EoS.**

501 3.2 Two-dimensional cases


502 Planar two-dimensional simulations of transcritical and supercritical jets are presented
 503 in this section. The initial conditions are summarized in Table 3. The parabolic sub-step is
 504 included into these simulations, without sub-grid scale modelling for turbulence or
 505 heat/species diffusion.

506

507 *Transcritical nitrogen injection (Quasi-Conservative formulation, Case A)*

508 A structured mesh is applied with a uniform cell distribution. The cell size is 0.043 mm
 509 $\times 0.043 \text{ mm}$. The domain used is $30\text{mm} \times 15\text{mm}$. Transmissive boundary conditions are
 510 applied at the top, bottom and right boundaries while a wall condition is employed at the left
 511 boundary. A flat velocity profile is imposed at the inlet. The case is initialized using a
 512 pressure in the chamber of 4 MPa , the density of the nitrogen in the chamber is 45.5 kg/m^3
 513 and the temperature is 299.5 K . The temperature of the jet is 84.4 K and the density is 804.0
 514 kg/m^3 . A summary of the initial conditions can be found in Table 3. The velocity of the jet is
 515 100 m/s and the diameter of the exit nozzle is 1.0 mm .

516



517 **Figure 14. 2D Test Case A, CFL = 1.0, 245000 cells, QC formulation. Density results of the**
 518 **simulation of the planar cryogenic nitrogen jet at various times.**
 519

519

520 When the jet enters the elevated temperature environment of the chamber, the
 521 velocity gradients at the jet surface generate a vortex rollup that finally breakup into ligament-
 522 shaped structures, see Figure 14. The Kelvin Helmholtz instability can be observed in the
 523 shear layer, which is similar to a gas/gas turbulent mixing case. No droplets are formed at
 524 these conditions. The jet is quickly heated to a gas-like supercritical state after the injection
 525 takes place. It must be highlighted that the mesh resolution is not enough to resolve all the
 526 scales (the aim of these simulations is to test the developed numerical framework). Moreover,
 527 2D simulation cannot resolve turbulence. Figure 17 shows the density, temperature, pressure
 528 and sound speed results at $4 \times 10^{-4} \text{ s}$.


529

530 Figure 15 shows a scatter plot of pressure as a function of density for the planar
 531 cryogenic nitrogen jet. The simulated case remains in the hyperbolic region of the governing
 532 equations with a real-valued speed of sound (Appendix B). The mixing trajectory passes close
 533 to the critical point with a few individual points inside the saturation curve, which means that
 phase separation does not occur [42]. The larger fluctuations caused by the confined domain


534 or the two-dimensionality of the case could be the reason why a small number of cells are in
535 the unstable region [3].

536 Although one of reasons of the prevailing usage of cubic EoS is their efficiency,
537 practical simulations can be performed using the PC-SAFT EoS. The quasi-conservative
538 formulation is computationally less expensive than the conservative scheme because the PC-
539 SAFT EoS has to be used only once in the hyperbolic operator in each time step. The
540 computational time is 65-70% higher using the PC-SAFT EoS than utilizing the PR EoS.
541 Figure 16 shows the time taken by the code to solve the transcritical nitrogen injection case
542 depending on the number of cells used (only one core is used to perform the simulation).


543 The PC-SAFT EoS is implemented using loops that depend on the number of
544 components solved, which means that it takes more time to compute the properties of
545 mixtures. However, knowing the mass fractions it is possible to determine how many
546 components are present in a cell a priori. The PC-SAFT is then only solved for that specific
547 number of components. Most cells along the simulation in the combustion chamber contain
548 only nitrogen. For this reason, a significant increment on time has not been observed
549 performing two-component simulations.



550
551 **Figure 15. Scatter plot of pressure as a function of density for the transcritical nitrogen jet (Case**
552 **A). The vapor dome, non-convex region and the region with complex speed of sound (SOS) are**
553 **included.**



554
555 **Figure 16. Computational time employed to compute the solution of the transcritical nitrogen jet**
556 **(Case A) at $t = 4 \times 10^{-4}$ employing a variable number of cells.**
557



558 **Figure 17. 2D Test Case A, CFL = 1.0, 245000 cells, QC formulation. Results of the simulation**
 559 **of the planar cryogenic nitrogen jet at $t = 4 \times 10^{-4}$ s using the quasi-conservative formulation: (a)**
 560 **density, (b) temperature, (c) pressure, (d) sound speed.**
 561


562 **Supercritical nitrogen injection (Conservative formulation, Case B)**

563 The case is initialized using a pressure in the chamber of 4 MPa, the density of the
 564 nitrogen in the chamber is 45.5 kg/m³ and the density of the jet is 440.0 kg/m³ (Table 3). The
 565 velocity of the jet is 50 m/s. The spatial reconstruction is carried out using a blending of the
 566 fifth-order WENO and the first-order schemes (95% fifth-order WENO). The CFL number is
 567 set at 0.4. Transmissive boundary conditions are applied at the top, bottom and right
 568 boundaries while a wall condition is employed at the left boundary. A flat velocity profile is
 569 imposed at the inlet.


570 If sharp interface methods (i.e. front tracking method) are not applied, the interfaces
 571 are not sharp one-point jumps but smooth as they are resolved [43]. This is the reason why the
 572 wiggles that appear in this 2D simulation are not as severe as in the 1D cases presented in
 573 Section 3.1 initialized using a sharp interface, see Figure 18. The study of [43] shows how
 574 smooth interfaces can reduce the spurious pressure oscillations.

575 The minimum pressure encountered along the simulation is higher than the nitrogen
 576 critical pressure so there are no cells in the vapor-liquid equilibrium region. The heat-up of
 577 the jet follows the same density-temperature trajectory employing a FC or a QC formulation
 578 in single-species cases, see Figure 19. In the works of [2], [44] a different behaviour in
 579 multicomponent cases can be observed, where QC formulations follow an isobaric-isochoric
 580 mixing model for binary mixtures while conservative schemes follow an isobaric-adiabatic
 581 mixing model.

582



583 **Figure 18. 2D Test Case B, CFL = 0.4, 180000 cells, FC formulation. Results of the simulation of**
 584 **the supercritical nitrogen jet at $t = 7.84 \times 10^{-4}$ s: (a) density, (b) pressure.**



585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615

Figure 19. 2D Test Case B solved using the FC and QC formulations. Scattered data of density and temperature. The nitrogen vapor dome is included.

Supercritical dodecane injection (Conservative formulation, Case C)

Dodecane/nitrogen mixtures are Type IV as stated by [45], which means that the critical temperature of the mixture is an intermediate value of the critical temperature of both components and the mixture critical pressure is higher than the critical pressure of either component, see Figure 23. A simulation of a dodecane jet where VLE (Vapor-Liquid Equilibrium) conditions are avoided injecting the dodecane at a temperature higher than its critical value has been included to prove the multi-species capability of the code. To check that any cell is in a thermodynamic metastable state, the vapor-liquid saturation curves were computed (Appendix C).


A structured mesh is applied with a uniform cell distribution. The cell size is $8.3\mu\text{m} \times 8.3\mu\text{m}$. The domain used is $5\text{mm} \times 2.5\text{mm}$. Transmissive boundary conditions are applied at the top, bottom and right boundaries while a wall condition is employed at the left boundary. A flat velocity profile is imposed at the inlet. The case is initialized using a pressure in the chamber of 11.1 MPa, the density and the temperature of the nitrogen in the chamber are 37.0 kg/m^3 and 973 K (high-load Diesel operation conditions [46]) respectively. The density and temperature of the jet are 450.0 kg/m^3 and 687 K (Table 3). The velocity of the jet is 200 m/s and the diameter of the exit nozzle is 0.1 mm.

As in the transcritical nitrogen case ligament-shaped structures appear and the Kelvin Helmholtz instability can be observed in the shear layer, see Figure 20. The jet is quickly heated-up from a liquid-like supercritical state to a gas-like supercritical state. Some spurious oscillations appear in the pressure field because of the high non-linearity of the EoS. The quasi-conservative formulation was not employed because of the incorrect prediction of the jet heat-up that appear in multi-component cases [2], [44].


A comparison of averaged scattered data of composition and temperature and an isobaric-adiabatic mixing process can be seen in Figure 21. As [44] stated, fully conservative schemes describe an isobaric-adiabatic mixing process. The isobaric-adiabatic line in the Figure 21 was computed using eq.13-14 and the initial conditions of this case.

$$616 \quad \dot{m}_3 = \dot{m}_1 + \dot{m}_2 \quad (13)$$

$$617 \quad \dot{m}_3 h_3 = \dot{m}_1 h_1 + \dot{m}_2 h_2 \quad (14)$$



618 **Figure 20. 2D Test Case C, CFL = 0.5, 180000 cells, FC formulation. Results of the simulation of**
 619 **the supercritical dodecane jet at $t = 2.5 \times 10^{-5}$ s: (a) density, (b) temperature, (c) pressure, (d)**
 620 **sound speed.**
 621



622
623
624

Figure 21. Scattered data of composition and temperature of the planar dodecane jet Case C. Solid lines are dodecane-nitrogen phase boundaries from VLE at 4.5 MPa and 6 MPa.

625

4. Conclusions

626 The Perturbated Chain Statistical Associating Fluid Theory (PC-SAFT) is utilized to close the
627 Navier-Stokes equations using both a conservative and a quasi-conservative formulation,
628 where the double flux model of [3], [17], [33] is applied. The PC-SAFT EoS presents a
629 precision similar to NIST without the need of an extensive calibration as only three
630 parameters are needed to model a specific component. It is presented as an alternative to the
631 commonly used cubic EoS that present a low accuracy for computing the thermodynamic
632 properties of hydrocarbons at temperatures typical for high pressure injection systems.
633 Advection test cases and shock tube problems have been used to validate the hyperbolic
634 operator of the developed numerical framework. The conservative formulation generates
635 spurious pressure oscillations, like it has been reported with other diffuse interface density-
636 based codes employing a real-fluid EoS. Due to fact that the interfaces are not sharp one-point
637 jumps but smooth, as they are resolved in 2D simulations, the wiggles generated do not
638 compromise the stability of the simulation. The quasi-conservative scheme can model
639 transcritical single- and multicomponent cases without spurious pressure oscillations. Errors
640 in the energy conservation that appear employing this formulation may produce an unphysical
641 quick heat-up of the injected jet in multicomponent cases. Two-dimensional simulations of
642 nitrogen and dodecane jets have been presented to demonstrate the multidimensional and
643 multicomponent capability of the numerical framework.

644

Acknowledgments

645 This project has received funding from the European Union Horizon-2020 Research
646 and Innovation Programme with grant Agreement No 675528.

647
648
649
650
651

652 **Appendix A PC-SAFT EoS**

653 The PC-SAFT EoS is expressed as the sum of all the residual Helmholtz free energy
 654 contributions. These contributions correspond to the distinct types of molecular interactions.
 655 The residual Helmholtz free energy is computed using eq.15 [38].

$$657 \quad \tilde{a}^{res} = \tilde{a}^{hc} + \tilde{a}^{disp} \quad (15)$$

658
 659 The hard-chain term, \tilde{a}^{hc} , for a mixture of nc components, is given in eq. 16

$$660 \quad \tilde{a}^{hc} = \bar{m}\tilde{a}^{hs} - \sum_i^{nc} x_i (m_i - 1) \ln g_{ii}^{hs}(\sigma_{di}) \quad (16)$$

661 where \bar{m} is the number of segments for a multicomponent mixture (eq. 17), x_i is the mole
 662 fraction of every component i in the fluid, \tilde{a}^{hs} is the hard sphere contribution (eq. 18), g_{ii}^{hs} is
 663 the radial distribution function of the hard-sphere fluid (eq.23) and m_i is the number of
 664 segments per chain of every component.

665
 666 The number of segments for a multicomponent mixture is:

$$667 \quad \bar{m} = \sum_i^{nc} x_i m_i \quad (17)$$

668 The hard sphere contribution is:

$$669 \quad \tilde{a}^{hs} = \frac{1}{\zeta_0} \left[\frac{3\zeta_1\zeta_2}{(1-\zeta_3)} + \frac{\zeta_2^3}{\zeta_3(1-\zeta_3)^2} + \left(\frac{\zeta_2^3}{\zeta_3^2} - \zeta_0 \right) \ln(1-\zeta_3) \right] \quad (18)$$

670 ζ_n is defined as:

$$671 \quad \zeta_n = \frac{\pi}{6} \rho_m \sum_i x_i m_i d_i^n \quad n \in \{0, 1, 2, 3\} \quad (19)$$

672 where ρ_m is the molecular density and d_i is the temperature-dependent segment diameter of
 673 component i (eq.21).

$$674 \quad \rho_m = \frac{6}{\pi} \eta \left(\sum_i x_i m_i d_i^3 \right)^{-1} \quad \text{being } \eta = \zeta_3 \quad (20)$$

$$675 \quad d_i = \sigma_{di} \left[1 - 0.12 \exp\left(-3 \frac{\varepsilon_i}{kT}\right) \right] \quad (21)$$

676 where k is the Boltzmann constant, T is the temperature and ε_i is the depth of pair potential
 677 of the component.

678

679 The mixture parameters σ_{ij} and ε_{ij} which are defined for every pair of unlike segments are
680 modeled using a Berthelot-Lorentz combining rule.

$$681 \quad \sigma_{ij} = \frac{1}{2}(\sigma_i + \sigma_j) \quad (22)$$

$$682 \quad \varepsilon_{ij} = \sqrt{\varepsilon_i \varepsilon_j} (1 - k_{ij}) \quad (23)$$

683 where k_{ij} is the binary interaction parameter.

684

685 The radial distribution function of the hard-sphere fluid is:

$$686 \quad g_{ij}^{hs} = \frac{1}{(1 - \zeta_3)} + \left(\frac{d_i d_j}{d_i + d_j} \right) \frac{3\zeta_2}{(1 - \zeta_3)^2} + \left(\frac{d_i d_j}{d_i + d_j} \right)^2 \frac{3\zeta_2^2}{(1 - \zeta_3)^3} \quad (24)$$

687 The dispersion term is defined as:

$$688 \quad \tilde{a}^{disp} = -2\pi\rho_m I_1(\eta, \bar{m}) \overline{m^2 \varepsilon \sigma_d^3} - \pi\rho_m \bar{m} C_1 I_2(\eta, \bar{m}) \overline{m^2 \varepsilon^2 \sigma_d^3} \quad (25)$$

689 where $\eta = \zeta_3$ is the reduced density, I_1 and I_2 are integrals approximated by simple power
690 series in density

$$691 \quad I_1(\eta, \bar{m}) = \sum_{i=0}^6 a_i(\bar{m}) \eta^i \quad (26)$$

$$692 \quad I_2(\eta, \bar{m}) = \sum_{i=0}^6 b_i(\bar{m}) \eta^i \quad (27)$$

693 The coefficients a_i and b_i depend on the chain length:

$$694 \quad a_i(\bar{m}) = a_{0i} + \frac{\bar{m}-1}{m} a_{1i} + \frac{\bar{m}-1}{m} \frac{\bar{m}-2}{m} a_{2i} \quad (28)$$

$$695 \quad b_i(\bar{m}) = b_{0i} + \frac{\bar{m}-1}{m} b_{1i} + \frac{\bar{m}-1}{m} \frac{\bar{m}-2}{m} b_{2i} \quad (29)$$

696 Where $a_{0i}, a_{1i}, a_{2i}, b_{0i}, b_{1i}, b_{2i}$ are constants [38].

697 C_1 is defined as:

$$698 \quad C_1 = \left(1 + Z^{hc} + \rho \frac{\partial Z^{hc}}{\partial \rho} \right)^{-1} = \left(1 + \frac{8\eta - 8\eta^2}{(1-\eta)^4} + (1-\bar{m}) \frac{20\eta - 27\eta^2 + 12\eta^3 - 2\eta^4}{[(1-\eta)(2-\eta)]^2} \right)^{-1} \quad (30)$$

699 The terms $\overline{m^2 \varepsilon \sigma_d^3}$ and $\overline{m^2 \varepsilon^2 \sigma_d^3}$ are defined as:

$$700 \quad \overline{m^2 \varepsilon \sigma_d^3} = \sum_i^{nc} \sum_j^{nc} x_i x_j m_i m_j \left(\frac{\varepsilon_{ij}}{kT} \right) \sigma_{ij}^3 \quad (31)$$

$$701 \quad \overline{m^2 \varepsilon^2 \sigma_d^3} = \sum_i^{nc} \sum_j^{nc} x_i x_j m_i m_j \left(\frac{\varepsilon_{ij}}{kT} \right)^2 \sigma_{ij}^3 \quad (32)$$

702 **Compressibility factor**

703 Then the compressibility factor is calculated as the sum of the ideal gas contribution
704 (considered to be 1), the dispersion contribution and the residual hard-chain contribution [38]:

$$705 \quad Z = 1 + Z^{hc} + Z^{disp} \quad (33)$$

$$706 \quad Z^{hs} = \frac{\zeta_3}{(1-\zeta_3)} + \frac{3\zeta_1\zeta_2}{\zeta_0(1-\zeta_3)^2} + \frac{3\zeta_2^3 - \zeta_3\zeta_2^3}{\zeta_0(1-\zeta_3)^3} \quad (34)$$

$$707 \quad Z^{hc} = \bar{m} Z^{hs} - \sum_i x_i (m_i - 1) (g_{ii}^{hs})^{-1} \rho_m \frac{\partial g_{ii}^{hs}}{\partial \rho_m} \quad (35)$$

$$708 \quad Z^{disp} = -2\pi\rho_m \frac{\partial(\eta I_1)}{\partial \eta} \overline{m^2 \varepsilon \sigma_d^3} - \pi\rho_m \bar{m} \left[C_1 \frac{\partial(\eta I_2)}{\partial \eta} + C_2 \eta I_2 \right] \overline{m^2 \varepsilon^2 \sigma_d^3} \quad (36)$$

709 where:

$$710 \quad C_2 = \frac{\partial C_1}{\partial \eta} = -C_1^2 \left(\frac{-4\eta^2 + 20\eta + 8}{(1-\eta)^5} + (1-\bar{m}) \frac{2\eta^3 + 12\eta^2 - 48\eta + 40}{[(1-\eta)(2-\eta)]^3} \right) \quad (37)$$

$$711 \quad \rho \frac{\partial g_{ij}^{hs}}{\partial \rho} = \frac{\zeta_3}{(1-\zeta_3)^2} + \left(\frac{d_i d_j}{d_i + d_j} \right) \left(\frac{3\zeta_2}{(1-\zeta_3)^2} + \frac{6\zeta_2\zeta_3}{(1-\zeta_3)^3} \right) + \left(\frac{d_i d_j}{d_i + d_j} \right)^2 \left(\frac{4\zeta_2^2}{(1-\zeta_3)^3} + \frac{6\zeta_2^2\zeta_3}{(1-\zeta_3)^4} \right) \quad (38)$$

$$712 \quad \frac{\partial(\eta I_1)}{\partial \eta} = \sum_{j=0}^6 a_j(\bar{m})(j+1)\eta^j \quad (39)$$

$$713 \quad \frac{\partial(\eta I_2)}{\partial \eta} = \sum_{j=0}^6 b_j(\bar{m})(j+1)\eta^j \quad (40)$$

714

715 **Derivative of the Helmholtz free energy respect to temperature.**

716 The temperature derivative of \tilde{a}^{res} is the sum of two contributions.

717

$$718 \quad \left(\frac{\partial \tilde{a}^{res}}{\partial T} \right)_{\rho, x_i} = \left(\frac{\partial \tilde{a}^{hc}}{\partial T} \right)_{\rho, x_i} + \left(\frac{\partial \tilde{a}^{disp}}{\partial T} \right)_{\rho, x_i} \quad (41)$$

719 The temperature derivative of the Helmholtz free energy hard-chain reference contribution is:
720

$$721 \quad \left(\frac{\partial \tilde{a}^{hc}}{\partial T} \right)_{\rho, x_i} = \bar{m} \left(\frac{\partial \tilde{a}^{hs}}{\partial T} \right)_{\rho, x_i} - \sum_i x_i (m_i - 1) (g_{ii}^{hs})^{-1} \left(\frac{\partial g_{ii}^{hs}}{\partial T} \right)_{\rho, x_i} \quad (42)$$

722
723 The temperature derivative of the Helmholtz free energy residual contribution of the hard-
724 sphere system is:
725

$$726 \quad \left(\frac{\partial \tilde{a}^{hs}}{\partial T} \right)_{\rho, x_i} = \frac{1}{\zeta_0} \left[\frac{3(\zeta_{1,T} \zeta_2 + \zeta_1 \zeta_{2,T})}{(1-\zeta_3)} + \frac{3\zeta_1 \zeta_2 \zeta_{3,T}}{(1-\zeta_3)^2} + \frac{3\zeta_2^2 \zeta_{2,T}}{\zeta_3 (1-\zeta_3)^2} + \frac{\zeta_2^3 \zeta_{3,T} (3\zeta_3 - 1)}{\zeta_3^2 (1-\zeta_3)^3} + \right. \quad (43)$$

$$\left. \left(\frac{3\zeta_2^2 \zeta_{2,T} \zeta_3 - 2\zeta_2^3 \zeta_{3,T}}{\zeta_3^3} \right) \ln(1-\zeta_3) + \left(\zeta_0 - \frac{\zeta_2^3}{\zeta_3} \right) \frac{\zeta_{3,T}}{(1-\zeta_3)} \right]$$

727
728 with abbreviations for two temperature derivatives:

$$729 \quad \zeta_{n,T} = \frac{\partial \zeta_n}{\partial T} = \frac{\pi}{6} \rho \sum_i x_i m_i n d_{i,T} (d_i)^{n-1} \quad n \in \{0, 1, 2, 3\} \quad (44)$$

$$730 \quad d_{i,T} = \frac{\partial d_i}{\partial T} = \sigma_i \left(3 \frac{\varepsilon_i}{kT^2} \right) \left[-0.12 \exp \left(-3 \frac{\varepsilon_i}{kT} \right) \right]$$

731
732 The temperature derivative of the radial pair distribution function is:

$$733 \quad \frac{\partial g_{ii}^{hs}}{\partial T} = \frac{\zeta_{3,T}}{(1-\zeta_3)^2} + \left(\frac{1}{2} d_{i,T} \right) \frac{\zeta_2}{(1-\zeta_3)^2} + \left(\frac{1}{2} d_i \right) \left(\frac{3\zeta_{2,T}}{(1-\zeta_3)^2} + \frac{6\zeta_2 \zeta_{3,T}}{(1-\zeta_3)^3} \right) + \quad (45)$$

$$\left(\frac{1}{2} d_i d_{i,T} \right) \frac{2\zeta_2^2}{(1-\zeta_3)^3} + \left(\frac{1}{2} d_i \right)^2 \left(\frac{4\zeta_2 \zeta_{2,T}}{(1-\zeta_3)^3} + \frac{6\zeta_2^2 \zeta_{3,T}}{(1-\zeta_3)^4} \right)$$

734
735 The temperature derivative of the Helmholtz free energy contribution due to dispersive
736 attraction is:
737

$$738 \quad \left(\frac{\partial \tilde{a}^{disp}}{\partial T} \right)_{\rho, x_i} = -2\pi\rho \left(\frac{\partial I_1}{\partial T} - \frac{I_1}{T} \right) \overline{m^2 \varepsilon \sigma_d^3} - \pi\rho \bar{m} \quad (46)$$

$$\left[\frac{\partial C_1}{\partial T} I_2 + C_1 \frac{\partial I_2}{\partial T} - 2C_1 \frac{I_2}{T} \right] \overline{m^2 \varepsilon^2 \sigma_d^3}$$

739
740 with
741

$$742 \quad \frac{\partial I_1}{\partial T} = \sum_{i=0}^6 a_i(\bar{m}) i \zeta_{3,T} \eta^{i-1} \quad (47)$$

743

$$744 \quad \frac{\partial I_2}{\partial T} = \sum_{i=0}^6 b_i(\bar{m}) i \zeta_{3,T} \eta^{i-1} \quad (48)$$

745

$$746 \quad \frac{\partial C_1}{\partial T} = \zeta_{3,T} C_2 \quad (49)$$

747

748 **Estimation of enthalpy and sound speed.**

749 The enthalpy is used to compute the thermal diffusion vector in the parabolic sub-step. It is
 750 computed as the sum of the ideal contribution (obtained by integrating the ideal heat capacity
 751 at constant pressure with respect to the temperature) and the residual enthalpy [38]:

$$752 \quad \frac{\hat{h}^{res}}{RT} = -T \left(\frac{\partial \tilde{a}^{res}}{\partial T} \right)_{\rho, x_i} + (Z-1) \quad (50)$$

753

754 Sound speed is computed using the equation applied by [47]:

$$755 \quad c = \sqrt{\frac{C_p}{C_v} \left(\frac{\partial P}{\partial \rho_m} \right)_T} \quad (51)$$

756 where C_p and C_v are the heat capacities at constant pressure and volume respectively [39].

757

758 The derivatives needed to compute the sound speed are:

$$759 \quad \left(\frac{\partial P}{\partial \rho_m} \right)_{T, x_i} = \left(\frac{\partial P}{\partial \eta} \right)_{T, x_i} \left(\frac{\partial \eta}{\partial \rho_m} \right)_{T, x_i} \quad (52)$$

$$760 \quad \left(\frac{\partial \eta}{\partial \rho_m} \right)_{T, x_i} = \frac{\pi}{6} \left(\sum_i x_i m_i d_i^3 \right) \quad (53)$$

$$761 \quad \left(\frac{\partial P}{\partial \eta} \right)_{T, x_i} = k_B T (10^{10})^3 \left[\rho_m \left(\frac{\partial Z}{\partial \eta} \right)_{T, x_i} + Z \left(\frac{\partial \rho_m}{\partial \eta} \right)_{T, x_i} \right] \quad (54)$$

762

$$763 \quad \left(\frac{\partial \rho_m}{\partial \eta} \right)_{T, x_i} = \frac{6}{\pi} \left(\sum_i x_i m_i d_i^3 \right)^{-1} \quad (55)$$


$$764 \quad \left(\frac{\partial Z}{\partial \eta} \right)_{T, x_i} \text{ can be found in [48].} \quad (56)$$

765 **Appendix B Hyperbolicity of Euler system with PC-SAFT EoS**

766 The hyperbolicity of the Euler system relies on a real speed of sound [3]. Using the
 767 PC-SAFT, the speed of sound is always real outside of the vapor-liquid equilibrium state.
 768 Inside the vapor-liquid equilibrium region, the spinodal curves (determined by
 769 $(\partial p / \partial v)_T = 0$) enclose the unstable / non-convex region where a complex speed of sound
 770 could be found, see Figure 22.


771 **Appendix C Pressure-composition phase diagram for the $N_2+C_{12}H_{26}$**
 772 **system**

773 The calculation of the number of phases present in a mixture in a certain condition is
 774 a recognized problem in the utilization of any EoS. In some cases, the number of phases is
 775 assumed a priori and then the composition in every phase is calculated by imposing
 776 equilibrium conditions. However, this technique often leads to divergence in the iterative
 777 methods used to achieve these. In our case, this is solved by an isothermal flash calculation
 778 after a stability analysis using the Tangent Plane Criterion Method proposed by [49] and
 779 applied to the PC-SAFT EoS by [50], see Figure 23.
 780



781
 782
 783

Figure 22. The vapor dome, non-convex region and the region with complex speed of sound of dodecane computed using the PC-SAFT EoS.



784

785

Figure 23. Experimental [51] and calculated pressure-composition phase diagram for the N_2 (1)
+ $\text{C}_{12}\text{H}_{26}$ (2) system. Solid lines: PC-SAFT EoS with $k_{ij} = 0.144$

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816 **Appendix D PC-SAFT EoS subroutines**817 **Algorithm 1: Fully conservative formulation**

818

Inputs {
 From conservative variables: ρ, e, Y_i
 Temperature from the previous time step
 Specific values of each component: $\sigma, \varepsilon / K, k_{ij}, m$
 }
 1) Compute the mole fraction of each component

 DO
 if $[(\text{abs}(e(\text{CSV}) - e(\text{PC-SAFT})) > 0.001)] \text{ then}$
 2) Compute segment diameter of each component (eq.21)
 3) Compute mean segment number (eq.17)
 4) Compute the coefficients a_i and b_i (eq.28-29)
 5) Compute abbreviations (eq.31-32)
 5) Compute ζ_n (eq.19)
 6) Compute radial distribution function of the hard sphere fluid (eq.24)
 7) Compute contribution of the hard sphere fluid to the compressibility factor (eq.34)
 8) Compute contribution of the hard chain to the compressibility factor (eq.35)
 9) Compute dispersion contribution to the compressibility factor (eq.36)
 10) Compute total compressibility (eq.33)
 11) Compute pressure (eq.8)
 12) Compute partial derivative of the Helmholtz free energy respect to temperature
 13) Compute residual internal energy
 14) Compute residual enthalpy
 15) Compute sonic fluid velocity
 16) Compute ideal enthalpy
 17) Compute ideal internal energy
 18) Compute total enthalpy
 19) Compute total internal energy
 20) Compute the new temperature using the Newton-Raphson method. The temperature
 dependent function used is the internal energy
 ELSE
 RETURN
 END IF
 END DO

819

820

821

822

823

824

825

826

827 **Algorithm 2: Quasi-conservative formulation**

828

Inputs {
 From conservative variables: ρ, Y_i
 From double flux model: p
 Temperature from the previous time step
 Specific values of each component: $\sigma, \varepsilon / K, k_{ij}, m$

1) Compute the mole fraction of each component

DO

if [(abs (p(double flux model)-p(PC-SAFT)) > 0.001)] then

 2) Compute segment diameter of each component (eq.21)

 3) Compute mean segment number (eq.17)

 4) Compute the coefficients a_i and b_i (eq.28-29)

 5) Compute abbreviations (eq.31-32)

 5) Compute ζ_n (eq.19)

 6) Compute radial distribution function of the hard sphere fluid (eq.24)

 7) Compute contribution of the hard sphere fluid to the compressibility factor (eq.34)

 8) Compute contribution of the hard chain to the compressibility factor (eq.35)

 9) Compute dispersion contribution to the compressibility factor (eq.36)

 10) Compute total compressibility (eq.33)

Algorithm {

 11) Compute pressure (eq.8)

 12) Compute partial derivative of the Helmholtz free energy respect to temperature

 13) Compute residual internal energy

 14) Compute residual enthalpy

 15) Compute sonic fluid velocity

 16) Compute ideal enthalpy

 17) Compute ideal internal energy

 18) Compute total enthalpy

 19) Compute total internal energy

 20) Compute the new temperature using the Newton-Raphson method. The temperature dependent function used is the pressure

ELSE

 RETURN

END IF

END DO

829

830

831

832

833

834

835

836

837

838

839 **References**

- 840 [1] S. Ashley, “Supercritical fuel injection and combustion,” *SAE article*, 2010.
- 841 [2] J. Matheis and S. Hickel, “Multi-component vapor-liquid equilibrium model for LES
842 of high-pressure fuel injection and application to ECN Spray A,” *Int. J. Multiph. Flow*,
843 vol. 99, pp. 294–311, 2017.
- 844 [3] P. C. Ma, Y. Lv, and M. Ihme, “An entropy-stable hybrid scheme for simulations of
845 transcritical real-fluid flows,” *J. Comput. Phys.*, vol. 340, no. March, pp. 330–357,
846 2017.
- 847 [4] H. Terashima and M. Koshi, “Approach for simulating gas-liquid-like flows under
848 supercritical pressures using a high-order central differencing scheme,” *J. Comput.*
849 *Phys.*, vol. 231, no. 20, pp. 6907–6923, 2012.
- 850 [5] P. C. Ma and M. Ihme, “ILASS-Americas 29th Annual Conference on Liquid
851 Atomization and Spray Systems, Atlanta, GA, May 2017,” no. May, 2017.
- 852 [6] J. C. Oefelein and V. Yang, “Modeling High-Pressure Mixing and Combustion
853 Processes in Liquid Rocket Engines,” *J. Propuls. Power*, vol. 14, no. 5, pp. 843–857,
854 1998.
- 855 [7] N. Zong, H. Meng, S. Y. Hsieh, and V. Yang, “A numerical study of cryogenic fluid
856 injection and mixing under supercritical conditions,” *Phys. Fluids*, vol. 16, no. 12, pp.
857 4248–4261, 2004.
- 858 [8] L. Selle and T. Schmitt, “Large-Eddy Simulation of Single-Species Flows Under
859 Supercritical Thermodynamic Conditions,” *Combust. Sci. Technol.*, vol. 182, no. 4–6,
860 pp. 392–404, 2010.
- 861 [9] J.-P. Hickey and M. Ihme, “Supercritical mixing and combustion in rocket
862 propulsion,” no. Chehroudi 2012, pp. 21–36, 2013.
- 863 [10] G.-S. Jiang and C.-W. Shu, “Efficient Implementation of Weighted ENO Schemes,” *J.*
864 *Comput. Phys.*, vol. 126, no. 1, pp. 202–228, 1996.
- 865 [11] H. J. Berg, R. I. D. D.-Y. Peng, and D. B. Robinson, “A New Two-Constant Equation
866 of State,” *J. Ind. Eng. Chem. J. Phys. Chem. Ind. Eng. Chem. Fundam. J. Agric. Sci.*
867 *Van Stralen, S. J. O. Int. J. Heat Mass Transf. I O*, vol. 51, no. 107, pp. 385–1082,
868 1972.
- 869 [12] G. Soave, “Equilibrium constants from a modified Redlich-Kwong equation of state,”
870 *Chem. Eng. Sci.*, 1972.
- 871 [13] H. Terashima, S. Kawai, and N. Yamanishi, “High-Resolution Numerical Method for
872 Supercritical Flows with Large Density Variations,” *AIAA J.*, vol. 49, no. 12, pp.
873 2658–2672, 2011.
- 874 [14] H. Terashima and M. Koshi, “Characterization of cryogenic nitrogen jet mixings under
875 supercritical pressures,” *51st AIAA Aerosp. Sci. Meet. Incl. New Horizons Forum*
876 *Aerosp. Expo. 2013*, no. January, pp. 2–11, 2013.
- 877 [15] H. Terashima and M. Koshi, “Strategy for simulating supercritical cryogenic jets using
878 high-order schemes,” *Comput. Fluids*, vol. 85, pp. 39–46, 2013.
- 879 [16] J.-P. Hickey, P. C. Ma, M. Ihme, and S. Thakur, “Large Eddy Simulation of Shear
880 Coaxial Rocket Injector: Real Fluid Effects.”
- 881 [17] P. C. Ma, L. Bravo, and M. Ihme, “Supercritical and transcritical real-fluid mixing in
882 diesel engine applications,” 2014, pp. 99–108.
- 883 [18] M. S. Wertheim, “Fluids with highly directional attractive forces. I. Statistical
884 thermodynamics,” *J. Stat. Phys.*, vol. 35, no. 1–2, pp. 19–34, 1984.
- 885 [19] M. S. Wertheim, “Fluids with highly directional attractive forces. II. Thermodynamic
886 perturbation theory and integral equations,” *J. Stat. Phys.*, vol. 35, no. 1–2, pp. 35–47,
887 1984.
- 888 [20] M. S. Wertheim, “Fluids with highly directional attractive forces. III. Multiple
889 attraction sites,” *J. Stat. Phys.*, vol. 42, no. 3–4, pp. 459–476, 1986.
- 890 [21] M. S. Wertheim, “Fluids with Highly Directional Attractive Forces . IV . Equilibrium
891 Polymerization,” vol. 42, pp. 477–492, 1986.
- 892 [22] W. G. Chapman, K. E. Gubbins, G. Jackson, and M. Radosz, “SAFT: Equation-of-

- 893 state solution model for associating fluids,” *Fluid Phase Equilib.*, vol. 52, no. C, pp.
894 31–38, 1989.
- 895 [23] W. G. Chapman, G. Jackson, and K. E. Gubbins, “Phase equilibria of associating
896 fluids,” *Mol. Phys.*, vol. 65, no. 5, pp. 1057–1079, Dec. 1988.
- 897 [24] N. Khare Prasad, “Predictive Modeling of Metal-Catalyzed Polyolefin Processes,”
898 2003.
- 899 [25] S. Leekumjorn and K. Krejbjerg, “Phase behavior of reservoir fluids: Comparisons of
900 PC-SAFT and cubic EOS simulations,” *Fluid Phase Equilib.*, vol. 359, pp. 17–23,
901 2013.
- 902 [26] A. J. de Villiers, C. E. Schwarz, A. J. Burger, and G. M. Kontogeorgis, “Evaluation of
903 the PC-SAFT, SAFT and CPA equations of state in predicting derivative properties of
904 selected non-polar and hydrogen-bonding compounds,” *Fluid Phase Equilib.*, vol. 338,
905 pp. 1–15, 2013.
- 906 [27] M. Salimi and A. Bahramian, “The prediction of the speed of sound in hydrocarbon
907 liquids and gases: The Peng-Robinson equation of state versus SAFT-BACK,” *Pet.
908 Sci. Technol.*, vol. 32, no. 4, pp. 409–417, 2014.
- 909 [28] K. S. Pedersen and C. H. Sørensen, “PC-SAFT Equation of State Applied to
910 Petroleum Reservoir Fluids,” *SPE Annu. Tech. Conf. Exhib.*, vol. 1, no. 4, pp. 1–10,
911 2007.
- 912 [29] X. Liang, B. Maribo-Mogensen, K. Thomsen, W. Yan, and G. M. Kontogeorgis,
913 “Approach to improve speed of sound calculation within PC-SAFT framework,” *Ind.
914 Eng. Chem. Res.*, vol. 51, no. 45, pp. 14903–14914, 2012.
- 915 [30] T. Schmitt, L. Selle, A. Ruiz, and B. Cuenot, “Large-Eddy Simulation of Supercritical-
916 Pressure Round Jets,” *AIAA J.*, vol. 48, no. 9, pp. 2133–2144, 2010.
- 917 [31] R. Abgrall and S. Karni, “Computations of compressible multifluids,” *J. Comput.
918 Phys.*, vol. 169, pp. 594–623, 2001.
- 919 [32] G. Billet and R. Abgrall, “An adaptive shock-capturing algorithm for solving unsteady
920 reactive flows,” *Comput. Fluids*, vol. 32, no. 10, pp. 1473–1495, 2003.
- 921 [33] P. C. Ma, Y. Lv, and M. Ihme, “Numerical methods to prevent pressure oscillations in
922 transcritical flows,” no. 1999, pp. 1–12, 2017.
- 923 [34] R. W. Houim and K. K. Kuo, “A low-dissipation and time-accurate method for
924 compressible multi-component flow with variable specific heat ratios,” *J. Comput.
925 Phys.*, vol. 230, no. 23, pp. 8527–8553, 2011.
- 926 [35] R. J. Spiteri and S. J. Ruuth, “A New Class of Optimal High-Order Strong-Stability-
927 Preserving Time Discretization Methods,” *SIAM J. Numer. Anal.*, vol. 40, no. 2, pp.
928 469–491, 2002.
- 929 [36] T. H. Chung, M. Ajlan, L. L. Lee, and K. E. Starling, “Generalized multiparameter
930 correlation for nonpolar and polar fluid transport properties,” *Ind. Eng. Chem. Res.*,
931 vol. 27, no. 4, pp. 671–679, Apr. 1988.
- 932 [37] M. R. Riazi and C. H. Whitson, “Estimating diffusion coefficients of dense fluids,”
933 *Ind. Eng. Chem. Res.*, vol. 32, no. 12, pp. 3081–3088, 1993.
- 934 [38] J. Gross and G. Sadowski, “Perturbed-Chain SAFT: An Equation of State Based on a
935 Perturbation Theory for Chain Molecules,” *Ind. Eng. Chem. Res.*, vol. 40, no. 4, pp.
936 1244–1260, 2001.
- 937 [39] M. Farzaneh-Gord, M. Roozbahani, H. R. Rahbari, and S. J. Haghghat Hosseini,
938 “Modeling thermodynamic properties of natural gas mixtures using perturbed-chain
939 statistical associating fluid theory,” *Russ. J. Appl. Chem.*, vol. 86, no. 6, pp. 867–878,
940 2013.
- 941 [40] E. W. Lemmon, M. L. Huber, and M. O. McLinden, “NIST reference fluid
942 thermodynamic and transport properties–REFPROP.” version, 2002.
- 943 [41] N. Kyriazis, P. Koukouvini, and M. Gavaises, “Numerical investigation of bubble
944 dynamics using tabulated data,” *Int. J. Multiph. Flow*, vol. 93, no. Supplement C, pp.
945 158–177, 2017.
- 946 [42] D. T. Banuti, P. C. Ma, and M. Ihme, “Phase separation analysis in supercritical
947 injection using large-eddy simulation and vapor-liquid equilibrium,” *53rd*

- 948 *AIAA/SAE/ASME Jt. Propuls. Conf. 2017*, no. July, 2017.
- 949 [43] S. Kawai and H. Terashima, “A high-resolution scheme for compressible
950 multicomponent flows with shock waves,” *Int. J. Numer. Methods Fluids*, vol. 66, no.
951 10, pp. 1207–1225, Aug. 2011.
- 952 [44] P. C. Ma, H. Wu, D. T. Banuti, and M. Ihme, “Numerical analysis on mixing
953 processes for transcritical real-fluid simulations,” *2018 AIAA Aerosp. Sci. Meet.*, no.
954 January, 2018.
- 955 [45] J. M. H. L. Sengers and E. Kiran, *Supercritical Fluids: Fundamentals for Application*.
956 Kluwer Academic Publishers, 1994.
- 957 [46] G. Lacaze, A. Misdariis, A. Ruiz, and J. C. Oefelein, “Analysis of high-pressure
958 Diesel fuel injection processes using LES with real-fluid thermodynamics and
959 transport,” *Proc. Combust. Inst.*, vol. 35, no. 2, pp. 1603–1611, 2015.
- 960 [47] N. Diamantonis and I. Economou, “Evaluation of SAFT and PC-SAFT EoS for the
961 calculation of thermodynamic derivative properties of fluids related to carbon capture
962 and sequestration,” no. June 2011, pp. 1–32, 2011.
- 963 [48] R. Privat, R. Gani, and J. N. Jaubert, “Are safe results obtained when the PC-SAFT
964 equation of state is applied to ordinary pure chemicals?,” *Fluid Phase Equilib.*, vol.
965 295, no. 1, pp. 76–92, 2010.
- 966 [49] M. L. Michelsen, “THE ISOTHERMAL FLASH PROBLEM. PART I. STABILITY,”
967 *Fluid Phase Equilib.*, vol. 9, 1982.
- 968 [50] and A. R. Justo-García, Daimler N., Fernando García-Sánchez, “Isothermal
969 multiphase flash calculations with the PC-SAFT equation of state,” in *AIP Conference*
970 *Proceedings*, 2008, vol. 979, pp. 195–214.
- 971 [51] D. N. Justo-garcía, B. E. García-flores, and F. García-s, “Vapor - Liquid Equilibrium
972 Data for the Nitrogen þ Dodecane System at Temperatures from (344 to 593) K and
973 at Pressures up to 60 MPa,” pp. 1555–1564, 2011.
- 974