

WestminsterResearch

<http://www.westminster.ac.uk/westminsterresearch>

**Enhancing electricity production from wastewater using
microbial fuel cells**

Fapetu, S., Keshavarz, T., Clements, M.O. and Kyazze, G.

A paper presented at the Postgraduate Fair, University of Westminster, New Cavendish Street, London, 28 April 2016.

The WestminsterResearch online digital archive at the University of Westminster aims to make the research output of the University available to a wider audience. Copyright and Moral Rights remain with the authors and/or copyright owners.

Whilst further distribution of specific materials from within this archive is forbidden, you may freely distribute the URL of WestminsterResearch: (<http://westminsterresearch.wmin.ac.uk/>).

In case of abuse or copyright appearing without permission e-mail repository@westminster.ac.uk

Enhancing electricity production from wastewater using microbial fuel cells

S. Fapetu, T. Keshavarz, M. Clements, and G. Kyazze

Microbial fuel cells represent a promising technology for simultaneous wastewater treatment and renewable electricity production. However, the electricity recovery is still poor, typically <10% of what is theoretically possible and the extracellular electron transfer mechanisms are poorly understood.

The use of co-cultures to improve substrate (glucose) turnover rate and hence electricity recovered was investigated initially. A co-culture of *Shewanella oneidensis* and *Clostridium beijerinckii* gave a maximum power density (P_{\max}) of 87 mWm⁻² (67% COD reduction) compared to 60 mWm⁻² for *C. beijerinckii* alone and 48 mWm⁻² for *S. oneidensis* alone. Co-culturing *Geobacter sulphurreducens*, *C. beijerinckii* and *Saccharomyces cerevisiae* gave the highest P_{\max} value of 80 mWm⁻² (41% COD reduction) compared to other strain combinations.

Another study investigated the contribution of direct electron transfer mechanism on electricity production by physically retaining *Shewanella oneidensis* cells close to or away from the anode electrode using a dialysis membrane (as well as immobilisation of the cells in alginate). Pyruvate was used as the substrate. The outcome of this study indicated a P_{\max} value of 114±6 mWm⁻² when cells were retained close to the anode, 3.5 times more than when the cells were separated from the anode. Without the membrane P_{\max} was 129±6 mWm⁻² (57% COD reduction).

To understand the role played by c-type cytochromes MtrA, MtrB and MtrC in extracellular electron transfer in *S. oneidensis*, the genes *mtrA*, *mtrB*, *mtrC* and their combinations were heterologously expressed in non-electrogenic bacteria (*Escherichia coli*; glucose as substrate). The *mtrCAB* transformant gave the highest P_{\max} of 24 mWm⁻² compared to 1 mWm⁻² for the wild type although cell growth was slower.

The results demonstrate the importance of co-cultures and of the MtrCAB pathway (direct electron transfer mechanism) in improving bacterial electricity production.