

Open Research Online

The Open University's repository of research publications and other research outputs

An eco-profile of building materials

Thesis

How to cite:

Cooper, David L. (1997). An eco-profile of building materials. PhD thesis The Open University.

For guidance on citations see [FAQs](#).

© 1996 The Author

Version: Version of Record

Copyright and Moral Rights for the articles on this site are retained by the individual authors and/or other copyright owners. For more information on Open Research Online's [data policy](#) on reuse of materials please consult the policies page.

oro.open.ac.uk

AN ECO-PROFILE OF BUILDING MATERIALS

Thesis presented in candidature for the award
of the degree of Doctor of Philosophy

by

D.L. Cooper BSc, MSc, CChem, FRSC

Faculty of Technology
Materials discipline

The Open University

Author's no: M7025981

31 December 1996

Date of submission: 6th January 1997

Date of award: 12th June 1997

To the memory of my father and mother

CONTENTS

	Page
ACKNOWLEDGEMENTS	
ABSTRACT	
Chapter 1 INTRODUCTION	1
1.1 Background	1
1.2 Scope of study	4
Chapter 2 METHODOLOGY	7
2.1 Overview	7
2.2 Life-cycle inventory	8
2.2.1 Ideal industrial systems	8
2.2.2 Practical industrial systems	11
2.2.3 Assessing the system performance	13
2.2.4 Partitioning or co-product allocation	16
2.3 Capital items	24
2.4 Human resources	24
2.5 Sources of information	25
2.6 Data collection	27
2.6.1 Confidentiality of data	27
2.6.2 Incomplete or absent data	28
2.6.3 Specificity of data	28
2.6.4 Accuracy and reporting of data	29
2.6.5 Variation in data format	30
2.6.6 Type of plant	30
2.7 Calculations	31
2.7.1 Procedure for calculating performance characteristics	32
2.7.2 Carbon dioxide calculations	33
2.8 Presentation of results	35
2.8.1 Gross energy data	36
2.8.2 Gross raw materials data	40
2.8.3 Gross emissions data	40
2.8.4 Conclusion	40
Chapter 3 FUELS	42
3.1 Introduction	42
3.2 Feedstock energy	43
3.3 Fuel production and delivery energy	44
3.4 Fuel producing industries	45
3.4.1 U.K. Natural gas production and supply	46
3.4.1.1 Air emissions from the combustion of natural gas	47
3.4.1.2 Gross energy for the production and supply of natural gas	48
3.4.2 U.K. Grid electricity supply	48
3.4.3 Gross inputs and outputs associated with fuel production, delivery and use	50

	Page	
Chapter 4	TRANSPORT	51
4.1	Introduction	51
4.2	Road transport	52
4.2.1	Direct fuel consumption	52
4.2.2	Vehicle construction inputs	54
4.2.3	Vehicle maintenance inputs	54
4.2.3.1	Lubricants	55
4.2.3.2	Spares	55
4.2.3.3	Garaging	56
4.2.4	Inputs to the construction and maintenance of transport facilities	57
4.2.5	Gross inputs and outputs	57
Chapter 5	ECO-PROFILE OF BUILDING MATERIALS	59
5.1	Introduction	59
5.2	Cement production	60
5.2.1	Process details	61
5.2.1.1	Raw materials inputs	62
5.2.1.2	Direct fuel consumption	63
5.2.1.3	Transport operations	64
5.2.1.4	Air emissions	65
5.2.1.5	Emissions to water	67
5.2.1.6	Solid waste	68
5.2.1.7	Gross inputs and outputs	68
5.3	Basis for comparison between eco-profiles	70
5.3.1	Gross energy	70
5.3.2	Raw materials	71
5.3.3	Air emissions	71
5.3.4	Water emissions	72
5.3.5	Solid waste	72
Chapter 6	MATERIAL INPUTS TO BUNGALOW AND DETACHED HOUSES	73
6.1	Introduction	73
6.2	Artistic impressions and floor plans	69
6.3	Assumptions used in the calculation of material inputs	76
6.4	Material inputs to bungalow construction	77
6.5	Material inputs to detached house construction	78
Chapter 7	ECO-PROFILES OF BUILDING CONSTRUCTION	79
7.1	Introduction	79
7.2	Gross inputs and outputs	79
7.3	Sensitivity analysis of material inputs	84

	Page	
Chapter 8	A COMPARISON OF ALTERNATIVE BUILDING MATERIALS	88
8.1	Introduction	88
8.2	Roof tiles	89
8.3	Window frames/doors	92
8.4	Underground sewer pipes and gulleys	100
8.5	Roof drainage materials	105
8.6	Lintels - single and combined	109
8.7	Building blocks	115
8.8	Insulation materials	117
8.9	Effect of substituting alternative materials on house eco-profiles	119
Chapter 9	CONCLUSIONS	123
9.1	Overview	123
9.2	Eco-profiles of house construction	123
9.3	Eco-profiles of alternative building materials	125
9.4	Effect of alternative building materials on house eco-profiles	126
9.5	Recommendations for further work	126
Appendices	Introduction	128
	GROSS INPUTS AND OUTPUTS ASSOCIATED WITH: FUELS	
1.	The production and delivery of fuels - per MJ	129
2.	The production and delivery of fuels - per MJ	130
3.	The production and delivery of fuels - per MJ	131
	TRANSPORT	
4.	Road transport - per vehicle-km	132
5.	Waterborne transport - per tonne-km	133
6.	Rail freight transport - per tonne-km	134
	MINERALS	
7.	The production and road delivery of building sand - per kg	135
8.	The production and road delivery of flat glass sand - per kg	136
9.	The production and road delivery of fibre glass sand - per kg	137
10.	The production and bulk road delivery of limestone - per kg	138
11.	Clay winning and on-site delivery - roof tile manufacture - per kg	139
12.	Clay winning and on-site delivery - clay brick manufacture - per kg	140
13.	The production and bulk road delivery of gypsum -per kg	141
14.	The production and bulk road delivery of dolomite - per kg	142
15.	The production and bulk road delivery of ulexite - per kg	143
16.	The production and bulk road delivery of milled granite - per kg	144
	LIMESTONE PRODUCTS	
17.	The production and road delivery of bagged hydrated lime - per kg	145
18.	The production and road delivery of block form mastic asphalt - per kg	146

	Page
19. The production, road delivery and laying of mastic asphalt floor - kg per sq.metre	147
 STRUCTURAL CLAY PRODUCTS	
20. The production and road delivery of clay facing bricks - per kg	148
21. The production and road delivery of clay facing bricks - kg per sq.m single leaf wall	149
22. The production and road delivery of clay roof tiles - per kg	150
23. The production and road delivery of clay roof tiles - kg per sq.metre	151
24. The production and road delivery of 100 mm vitrified clay pipes - per metre	152
25. The production and road delivery of a vitrified clay gulley - per gulley	153
 CONCRETE AND MORTAR PRODUCTS	
26. The production and road delivery of ready mixed concrete (20MPa) - per kg	154
27. The production and road delivery of ready mixed concrete (30MPa) - per kg	155
28. The production and road delivery of ready mixed mortar - per kg	156
29. The production and road delivery of concrete roof tiles - per kg	157
30. The production and road delivery of concrete roof tiles - kg per sq.metre	158
31. The production and road delivery of dense concrete blocks - per kg	159
32. The production and road delivery of dense concrete blocks - per sq.metre	160
33. The production and road delivery of aerated concrete blocks - per kg	161
34. The production and road delivery of aerated concrete blocks - per sq.metre	162
35. The production and road delivery of pre-stressed concrete lintels (255 mm x 75 mm) per metre	163
36. The production and road delivery of reinforced concrete lintels (100 mm x 143 mm) per 1.5 metre	164
37. The production and road delivery of reinforced concrete lintels (125 mm x 143 mm) per 1.5 metre	165
38. The production and road delivery of dual lintel systems per 1.5 metre	166
 GYPSUM PLASTER PRODUCTS	
39. The production and delivery of bagged finishing plaster - per kg	167
40. The production and road delivery of 12.5 mm plasterboard per sq.metre	168

	Page
GLASS PRODUCTS	
41.	The production and road delivery of 6 mm flat glass - per sq.metre 169
42.	The production and road delivery of glass fibre wool 150 mm depth - per sq.metre 170
43.	The production and road delivery of glass fibre wool 50 mm depth - per sq.metre 171
TIMBER AND TIMBER PRODUCTS	
44.	The production and road delivery of kiln dried sawn timber (UK Sitka spruce) - per kg 172
45.	The production and road delivery of kiln dried sawn timber lintels (UK Sitka spruce) - per 1.5 metre 173
46.	The production and road delivery of kiln dried sawn timber (Swedish Redwood) - per kg 174
47.	The production and road delivery of wooden window frames and doors (Swedish Redwood) - per kg 175
48.	The production and road delivery of wooden window frames/ doors & door frames - per item 176
METALS AND METAL PRODUCTS	
49.	The production and road delivery of electrolytically refined copper metal - per kg 177
50.	The production and road delivery of lead metal - per kg 178
51.	The production and road delivery of zinc metal - per kg 179
52.	The production and road delivery of cold rolled steel - per kg 180
53.	The production and road delivery of RSJs - per 1.5 metre 181
54.	The production and road delivery of pickled hot rolled steel coil - per kg 182
55.	The production and road delivery of hot dip galvanised steel (610 g/m ²) - per kg 183
56.	The production and road delivery of galvanised steel coil - per kg 184
57.	The production and road delivery of insulated galvanised steel combined lintels - per 1.5 metre 185
58.	The production and rail delivery of 6063 aluminium alloy ingot - per kg 186
59.	The production and road delivery of extruded 6063 aluminium alloy ingot - per kg 187
60.	The production and road delivery of anodised 6063 aluminium profiles - per kg 188
61.	The production and road delivery of polyester resin powder coated 6063 aluminium profiles - per kg 189
62.	The production and road delivery of anodised aluminium casement window frames (1200 mm x 1200 mm) - per frame 190
63.	The production and road delivery of powder painted aluminium casement window frames (1200 mm x 1200 mm) - per frame 191

	Page	
64.	The production and road delivery of anodised aluminium external kitchen door and frame (762 mm x 1981 mm) - per door/frame	192
65.	The production and road delivery of powder painted aluminium external kitchen door and frame (762 mm x 1981 mm) - per door/frame	193
66.	The production and road delivery of 100 mm half round cast aluminium rainwater guttering - per metre	194
67.	The production and delivery of 68 mm aluminium drainpipe - per metre	195
 PLASTICS AND PLASTIC PRODUCTS		
68.	The production and road delivery of suspension PVC granules - per kg	196
69.	The production and road delivery of a PVC formulation used in the production of window/door frame profiles - per kg	197
70.	The production and road delivery of a PVC formulation used in the production of surface rainwater drainage systems - per kg	198
71.	The production and road delivery of a PVC formulation used in the production of sewage pipes - per kg	199
72.	The production and road delivery of extruded PVC window/door frame profiles - per kg	200
73.	The production and road delivery of PVC casement window frames (1200 mm x 1200 mm) - per frame	201
74.	The production and road delivery of PVC external kitchen door and frame (762 mm x 1981 mm) - per door/frame	202
75.	The production and road delivery of a 68 mm PVC drainpipe - per metre	203
76.	The production and road delivery of a 100 mm half round PVC rainwater gutter - per metre	204
77.	The production and road delivery of a 110 mm diameter PVC sewer pipe - per metre	205
78.	The production and road delivery of a PVC bottle gulley - per gulley	206
79.	The production and road delivery of polyethylene granules (all grades) - per kg	207
80.	The production and road delivery of polyethylene damp proof course - per sq.metre	208
81.	The production and delivery of polyethylene damp proof membrane - per kg	209
82.	The production and road delivery of expanded polystyrene (EPS) foam - per kg	210
83.	The production and road delivery of expanded polystyrene (EPS) insulation slab, 50 mm depth - per sq.metre	211
84.	The production and road delivery of rigid polyurethane foam - per kg	212
85.	The production and road delivery of rigid polyurethane foam, 50 mm depth - per sq.metre	213

	Page
MISCELLANEOUS	
86. The production and road delivery of pulverised fuel ash - per kg	214
BUILDING CONSTRUCTION	
87. The construction of a three bedroom bungalow and a four bedroom detached house - per building	215
88. The construction of a three bedroom bungalow - per sq.metre floor space	216
89. The construction of a four bedroom detached house - per sq.metre floor space	217
90. The construction of a three bedroom bungalow and a four bedroom detached house - per building (revised)	218
91. The construction of a three bedroom bungalow - per sq.metre floor space (revised)	219
92. The construction of a four bedroom detached house - per sq.metre floor space (revised)	220
REFERENCES	221

Acknowledgements

The nature of this research required the help and co-operation of many people. It is a pleasure to acknowledge the help of those involved. In particular, I am deeply indebted to my supervisor Dr. P.R. Lewis for his help, guidance and encouragement at all times.

It is with sincere gratitude that I thank Dr. I. Boustead for the use of *The Boustead Model* to complete life-cycle inventory calculations, and for his ready assistance, generous support and expert guidance at all stages of this work. His informed advice and constructive criticism have been essential for the completion of this study.

The primary data used in this research have been supplied in confidence from commercial sources. I am particularly grateful for the co-operation of the numerous companies concerned. Without their generous help this work would not have been possible.

Finally, I wish to thank my wife Kath for her patience and for the support which she and our children Helen, Andrea and James have given.

Abstract

This research examines the environmental parameters associated with the production and delivery of building materials in the U.K. in 1991. Using primary data supplied from commercial sources, an eco-profile is produced for each material by calculating the gross inputs of energy and raw materials and gross outputs of solid waste, air and water emissions. The production sequences are traced from raw materials in the ground through to the final product and extend to include transport operations and the production and delivery of fuels and ancillary materials.

The results are used to complete eco-profiles for the construction of a three bedroom bungalow house and a four bedroom two storey detached house. It is shown that per square metre of floor space, the construction of the two storey detached house produces considerable reductions in the burdens on the environment.

Eco-profiles are used to compare the environmental burdens associated with alternative building materials. The effect of alternative building materials on the eco-profiles of house construction is discussed. It is shown that significant reductions in the gross inputs and outputs may be made by substituting dense concrete blocks for clay bricks.

B. Cooper

The Open University
RESEARCH DEGREES CENTRE
04 JUL 1997 EX12

RESEARCH DEGREES CENTRE
LIBRARY AUTHORISATION FORM

Please return this form to the The Research Degrees Centre with the two bound copies of your thesis to be deposited with the University Library.
All students should complete Part 1. Part 2 only applies to PhD students.

Student: COOPER D.L PI: M7025981

Degree: Ph.D

Thesis title: AN ECO-PROFILE OF BUILDING MATERIALS

Part 1 Open University Library Authorisation [to be completed by all students]

I confirm that I am willing for my thesis to be made available to readers by the Open University Library, and that it may be photocopied, subject to the discretion of the Librarian.

Signed: David L Cooper Date: 2 July 1997

Part 2 British Library Authorisation [to be completed by PhD students only]

If you want a copy of your PhD thesis to be available on loan to the British Library Thesis Service as and when it is requested, you must sign a British Library Doctoral Thesis Agreement Form. Please return it to the Research Degrees Centre with this form. The British Library will publicise the details of your thesis and may request a copy on loan from the University Library. Information on the presentation of the thesis is given in the Agreement Form.

The University has agreed that your participation in the British Library Thesis Service should be voluntary. Please tick either (a) or (b) to indicate your intentions.

[a] I am willing for the Open University to loan the British Library a copy of my thesis. A signed Agreement Form is attached.

[b] I do not wish the Open University to loan the British Library a copy of my thesis.

Signed: David L Cooper Date: 2 July 1997

Chapter 1

INTRODUCTION

1.1 Background

Industrial processes may be described as systems characterised by the consumption of energy and raw materials and the production of finished goods and waste material. In the early years of industrialisation when raw materials were considered to be plentiful, it is unlikely that much attention was given to the conservation of energy and mineral resources or to the impact on the environment of waste solids, liquids and gases. As industrialised societies developed, economic considerations alone, rather than environmental pressures forced individual companies to monitor energy consumption and waste production. Little consideration was given to the possible depletion of energy or mineral resources, or to the effect on the environment of toxic or unsightly waste. Indeed, uncontrolled air emissions, discharges to water, and indiscriminate dumping of solid waste were common features of industrial processes until relatively recent times.

The steady rise in the number of industrialised economies, coupled with a growing world population, made increasing demands on the world's finite resources and produced a corresponding increase in waste materials. Worries that continued economic growth could not be sustained indefinitely without a severe depletion of these resources surfaced in the 1960s. These concerns prompted a number of modelling studies^{1,2,3} all of which warned that depletion of fossil fuels and scarce materials, together with attendant pollution problems, posed a serious threat to future economic growth and development. Furthermore, it was thought that rising levels of thermal waste energy might cause global warming and subsequent climatological changes. Although these studies were received with some

reservations, they stimulated a fresh interest in the efficiencies of industrial processes.

Operations such as mineral extraction, fuel production, manufacturing processes, transport and disposal of waste material, hitherto treated as separate unrelated entities, were now considered together for the first time as belonging to *extended industrial systems*. In this context, an *extended industrial system* is defined as one which starts with raw materials in the ground, and incorporates all the separate processes and operations associated with the manufacture and use of a product, up to and including eventual disposal at the end of its useful life.

Since fuel consumption and production rates by individual factories were already closely monitored, the calculation of energy consumption per unit of output was relatively straightforward. Consequently, initial interest in extended industrial systems focused on the use of energy, especially fossil fuels, and the term *energy analysis* was used to describe this work. In order to complete an energy analysis for a given industrial process, it is first necessary to construct flow charts and to calculate mass balances detailing material flows into, across, and out of the production system. Thus, an important consequence of energy analysis investigations was the provision of additional information on raw materials requirements and solid waste emissions.

One of the first attempts at describing the behaviour of extended industrial systems was reported to the World Energy Conference in 1969,⁴ and concerned the calculation of the cumulative energy requirements for the production of chemicals. The stimulus provided by the oil shortages in the early 1970s prompted further studies across a range of industrial systems including some of relevance to this work.⁵⁻³⁹ However, interest in energy analysis

declined somewhat in the late 1970s as oil supplies were restored and as many countries reduced their dependence on external supplies of fossil fuels by increasing their nuclear capacity.

An increasing awareness of environmental issues became evident in Europe during the 1980s. For example, in 1985 an EC Directive on Liquid Food Containers⁴⁰ was passed which compelled member countries to monitor solid waste production as well as the consumption of energy and raw materials, and in 1990 the British Government produced an Environment White Paper⁴¹ setting out Britain's environmental strategy. More recently, in 1994 an EC Directive on Packaging and Packaging Waste⁴² was passed which enlarged the provisions of the 1985 Directive on Liquid Food Containers and compelled member states to monitor the production, recovery and recycling of packaging waste and the consumption of raw materials for all packaging materials. During this period the problems of acid rain, the potential for global warming, ozone depletion, and the continuing damage to the marine environment focused international attention on air and water pollutants, and air and water emissions were soon added to energy, raw materials and solid waste considerations.

The calculation of air and water emissions for industrial processes can be made using the methodology already developed for calculating energy consumption and raw materials requirements.⁴³ Consequently, *energy analysis* evolved to encompass a wider remit and became known by a variety of names such as *resource analysis*, *resource and environmental profile analysis*, *cradle to grave analysis*, *cradle to gate analysis*, *eco-balance*, *eco-profile*, and *life-cycle analysis*. However, an eco-profile or cradle to gate

analysis falls short of a complete life-cycle analysis since it does not include the use or final disposal of the finished product.

1.2 Scope of study

Although energy analysis studies of building materials were reported in the 1970s* and early 1980s,** with the exception of a recent Austrian ecological study comparing materials used in window frame manufacture,⁴⁴ a Canadian study comparing gross energy consumption and carbon dioxide emissions during building construction,⁴⁵ and a limited Danish study,⁴⁶ there has been little published interest since then in extending the work to include waste emissions, and so complete an eco-profile or life-cycle analysis. Further stimulus to research in this field has been provided by the following developments.

- ◆ Changes in building regulations, which now emphasise the importance of energy conservation in building design. Consequently, double glazed windows, insulated concrete building blocks, and insulation materials such as expanded polystyrene foam and polyurethane foam, have become standard features of modern house construction.
- ◆ The introduction of new materials, such as PVC, which have provided an alternative to traditional building materials such as timber in window frames, cast iron and aluminium in rainwater drainage systems, and metals and clay in underground piping systems.
- ◆ Significant quantities of fresh information have appeared recently, providing eco-profiles for the manufacture of the following raw materials used in the

* See endnotes 8, 11, 12, 13, 14, 15, 16, 17, 19, 21, 22, 23, 24, 25, 26, 27, 28, 29, 31

** See endnotes 32, 34, 35, 36, 37, 38, 39

construction industry: aluminium and steel,⁴⁷ thermoplastics such as polyethylene and polypropylene,⁴⁸ polystyrene,⁴⁹ polyvinylchloride,⁵⁰ and polyurethane precursors.⁵¹

- ♦ Likely alterations to the efficiencies of fuel production and delivery, and the energy requirements of transport over the years.

In the light of these developments there is a perceived need to generate new information concerning building materials. The purpose of this research is to satisfy this need, and, by treating building materials as belonging to extended industrial systems, to complete an eco-profile of both new and traditional building materials. Data from commercial sources are to be collected and processed so that a computer model may be constructed. Initially the model will be used to complete eco-profiles for different building materials, but eventually it is intended to pull the separate sets of data together in the final model to complete and compare eco-profiles for the construction of two types of modern building, a three bedroom bungalow house, and a four bedroom two storey detached house. The sensitivity of the final outcome to the use of alternative building materials will also be investigated. The conclusions of this type of research may be of interest and use to architects, builders and others involved in building design and construction.

In constructing eco-profiles it is important to state clearly the limits of the analysis and the elements to be included or excluded. The eco-profiles for the two types of building to be considered in this research have been limited to include only those materials used in the construction of the house shells, and do not include external services such as water supplies and drainage systems beyond the boundaries of the house, or internal fittings such as baths,

sinks, wall tiles, kitchen units and electricity cables. Moreover, they are not concerned with the competing aesthetic qualities of the different building materials.

In the following chapters it is proposed to examine life-cycle analysis methodology in detail, and to update both fuel production and delivery efficiencies and the energy requirements of transport, before moving on to complete eco-profiles of different building materials.

Chapter 2

METHODOLOGY

2.1 Overview

The basis of *life-cycle assessment* methodology, upon which much of this chapter relies, has been discussed in detail elsewhere.^{52, 53} Essentially, there are three separate but inter-related stages to any life-cycle assessment.

1. *The life-cycle inventory*: a catalogue of the inputs of raw materials and energy into an extended system, and the outputs of solid, liquid, and gaseous material from that system.
2. *The life-cycle impact analysis*: an assessment of the environmental impact of the inputs and outputs identified in the inventory stage.
3. *The life-cycle improvement analysis*: an evaluation of ways in which the environmental impacts may be reduced.


The methodology for the preparation of the first stage, the life-cycle inventory, is well understood and has received most attention during the last twenty years. The inventory stage supplies information which may be used to assess the impact on the environment in the second stage, the impact analysis. At present, this stage of life-cycle assessment is less developed as the full effects of environmental releases are unknown or incompletely understood. The final stage, the improvement analysis, is perhaps the most difficult to deal with, since any strategies designed to mitigate environmental releases rely on a full understanding of the interconnecting linkages between the source and the effect. Moreover, although efficiency gains may reduce the overall impact on the environment, it is difficult to selectively reduce the production of any one waste product without producing another.

For example, the removal of gaseous discharges of sulphur dioxide, a precursor of acid rain, from coal burning power stations is only achieved at present by the production of solid waste calcium sulphate and carbon dioxide, a greenhouse gas. In this case a useful product is formed, but this may not always be the case. Since a methodology to deal with the impact and improvement analysis stages is not yet fully developed, this research will focus on the inventory stage of life-cycle assessment.

2.2 Life-cycle inventory

2.2.1 Ideal industrial systems

Life-cycle analysis is based on the concept of a *system* which is defined as a set of operations acting together to perform a defined function. It must be stressed that whilst industry is concerned with products, life-cycle analysis is concerned with systems; however, for those systems producing a single product, such as flat glass manufacture, then the system can be identified with the product.



A schematic representation of a simple industrial system is depicted in Figure 2.1, from which it can be seen that the system boundary acts as an interface between the system and the system environment. The system environment acts both as a source of raw materials and energy inputs, and a sink for outputs of waste energy, waste material, and useful products. Of course in a full life-cycle analysis there is ultimately no useful product, simply waste material. In general, the total energy input to a system will eventually be converted into waste heat, and since the energy input is known, there is no need to monitor this output. The only exception to this generalisation may occur in exothermic or endothermic chemical processes, when energy may be produced or absorbed respectively as a result of chemical interactions. However, since the free energy change of the reaction is usually small in comparison with the total energy input, it may be ignored.

The collection of operations to be included within a system, and the position of the system boundary, is determined by the system function, which must be clearly defined. Sometimes a physical boundary can be identified. For example, a machine producing PVC profiles for use in window frames could be considered as a system if the system boundary was the machine itself. Similarly, the system boundary may be drawn around all the operations in a given factory. However, a physical boundary is not always suitable or easily recognised. For example, it is impossible to construct a physical boundary around systems which include external transport operations, or around complex industrial systems which are broken down and considered as a notional set of sub-systems existing only for the purposes of the analysis.

Although the system itself is of most interest, it is impossible to correctly describe the system without reference to its function, or to compare two systems unless they are serving the same function. For example, it is incorrect and misleading to compare a system designed to produce clay bricks with one producing flat glass. They are different systems with different technologies serving different functions. Moreover, other factors such as age of plant, technology used, and country of manufacture must be stated to complete the system description.


Life-cycle analysis methodology is rooted in thermodynamics and other physical laws of nature rather than economic considerations. Of particular importance are the law of conservation of mass, the law of conservation of energy and thermodynamic sign conventions, which when applied to the analysis of industrial systems may be summarised as follows.

1. *Law of conservation of energy*: the total energy inputs to a system must equal the total energy outputs from that system.
2. *Law of conservation of mass*: the total mass inputs to a system must equal the total mass outputs from that system.
3. *Thermodynamic sign convention*: material and energy flows *into* a system are positive, whilst flows of material and energy *out* of a system are negative.

Strict adherence to thermodynamic sign conventions and the physical laws of nature is essential when constructing energy and mass balances for a system, and failure to apply these rules will invalidate the analysis.


2.2.2 Practical industrial systems

In practice, industrial systems are composed of interdependent sequences of sub-systems obtaining inputs from upstream operations, which in turn produce outputs for the next downstream operation. It is important to note that sub-systems must possess the same characteristics as the larger system to which they belong; that is, their functions must be clearly defined and they must conform to the same physical laws of nature. Many manufacturing systems consist of a linear sequence of sub-systems, whereas extended industrial systems are more likely to consist of non-linear networks of sub-systems. Since extended systems include all operations concerned with the production of fuels and materials they consist of the three main groups of operations shown in Figure 2.2.




These operations are the main production sequence, the fuel producing industries, and the supporting ancillary industries. Transport operations pervade most industrial operations and have been excluded for reasons of clarity, not because they are considered unimportant. The main production sequence is usually identified without difficulty. For example, if the extended industrial system is defined as the production of PVC window frames the

operations to be included within the main production sequence are the linear sequence of sub-systems depicted in Figure 2.3.



The supporting ancillary industries supply additional materials, which in this example would include steel, PVC formulation additives such as titanium dioxide, chalk and heat stabilisers, labels, pallets and bags. It is interesting to note that if PVC granules, used for the production of PVC profiles, are delivered in bags which are also produced from PVC, as shown by the process route in Figure 2.4, then the packaging of PVC granules makes a further demand on upstream operations producing PVC.



The inputs of ancillary materials are usually collected along with the data for the unit operations in the main process sequence. However, for a complete analysis, the production of ancillary materials must always be traced back to the extraction of raw materials and fuel in the ground. Sometimes such data are unknown or difficult to extract, and it is tempting to ignore these contributions if the inputs are small. However, small inputs may make a significant contribution to the final outcome and their omission may introduce errors. Thus, the case for omission should be proved rather than assumed. Any data omission must be clearly stated in order to avoid any ambiguity.

The fuel producing industries, which will be discussed in more detail in Chapter 3, consist of a non-linear network of sub-systems, each producing fuels such as coal, natural gas, oil fuels, coke and electricity used by the main process route and the production of ancillary materials.

2.2.3 Assessing the system performance

The performance of a system may be considered as a function of the inputs of raw materials and energy, or the outputs of useful products and waste emissions as shown in the idealised simple system of Figure 2.1. The only exception is waste heat production which is rarely monitored, as discussed in Section 2.2.1.

The inputs are of interest to conservationists since they are a measure of the demand on the resources required to sustain the system, whilst the outputs are of use to environmentalists concerned with possible pollution effects. It should be noted that in a full life-cycle analysis


all the outputs may be considered as potential pollutants, including useful products at the end of their useful lives.

For any given period of time the rate of flow of materials through the system will control the size of the inputs and outputs. To overcome this dependency it is convenient to normalise the system parameters with respect to a physical measure of the flows through the system. For unit industrial operations, mass of usable product is the normal physical measure of system output, but any suitable means such as volume or area may be used. In the fuel producing industries, however, energy output is frequently used.

Thus, for a simple idealised system with total energy input E , producing a mass of usable product M_p , the normalised system energy requirement per unit output is E/M_p . Similarly, if the air, water and solid waste emissions are A , W , and S , respectively, the normalised air, water and solid waste emissions are A/M_p , W/M_p , and S/M_p respectively.

The calculation of system parameters for a system consisting of a linear sequence of idealised sub-systems A, B and C, as depicted in Figure 2.5, is performed in an identical manner. The sequence shows that sub-system A requires an energy input E_1 to process a mass input m_1 . In turn, sub-system B consumes an energy input E_2 in processing a mass input m_2 . This process is repeated by sub-system C to produce a final mass of usable product m_4 . Consider the derivation of the normalised system energy, E_s , as an example. The system energy, E , is the sum of the three separate energy inputs to the three sub-systems A, B, and C. Thus,

$$E = E_1 + E_2 + E_3$$



and the normalised system energy may be written as

$$E_s = \frac{(E_1 + E_2 + E_3)}{m_4}$$

Whereas linear sequences of operations are frequently used in manufacturing processes, extended industrial systems are more likely to consist of non-linear networks. The calculation of system parameters for such networks can be a very tedious and complex task, and before cheap computing power became readily available it was often convenient to convert such networks into simplified pseudo-linear sequences. Unfortunately, calculations based on pseudo-linear sequences are only approximate and prone to errors. Although calculations associated with networked operations provide more accurate solutions they are more difficult to compute by hand. However, they present little problem for computers, and are solved using the process of iteration, where notional values are first assigned to each operation and the whole system then evaluated. The new calculated values are then substituted for the original values, and the whole system evaluated once again. The revised values are then substituted once more, and the process repeated. This procedure is applied

until the calculated values converge to a value within the level of accuracy required, which is typically after about four or five iterations.

The above discussion relates to the production of a single product. However, when more than one product is produced it is necessary to partition or allocate the system parameters between the different products. The various methods of partitioning will be examined in Section 2.2.4.

2.2.4 Partitioning or co-product allocation

As discussed earlier, the inputs to and outputs from a simple industrial system producing a single product can be identified with that product, and the calculation of normalised inputs and outputs for such systems is a relatively simple matter. In contrast, inputs and outputs for systems producing more than one product, are identified with the system, not any one product, and a different procedure must be adopted to analyse such systems. The accepted technique is to consider the system as a series of sub-systems, each producing a single product, all of which, acting together, are equivalent to the original system. A suitable partitioning parameter is then applied to the overall system so that the inputs and outputs can be apportioned to the separate single product sub-systems. The partitioning parameter will vary from one system to another, but must correspond as closely as possible with the physical or chemical processes taking place within the original system. It is important that economic parameters, such as the market value of products, which are subject to external influences of supply and demand, are never used to partition systems based on physical processes. Physical systems are governed by the laws of science and are completely independent of economic considerations.

The basis on which most systems are partitioned is as follows:


- ♦ mass - for physical processes when the co-products are materials
- ♦ energy - for physical processes when the co-products are fuels
- ♦ stoichiometry - for chemical processes.

Nonetheless, it must be noted that for systems in which a specific input is identified with a specific product, it is appropriate to use more than one partitioning parameter. The method of partitioning for each of the above parameters may be understood by considering the following examples.


1. The thermal cracking of naphtha
2. The co-production of coke and manufactured gas from coal,
3. The electrolysis of brine to produce chlorine, hydrogen and sodium hydroxide.

1. The thermal cracking of naphtha

In this example, a naphtha cracker uses an energy input, E , to process a material input of naphtha, mass M , and produce outputs of ethylene, propylene, unspecified other products, and waste material of masses m_1 , m_2 , m_3 , and W respectively, as shown in Figure 2.6.



For the purpose of partitioning, the cracking process may be considered as three separate sub-systems contained within the cracking column, as shown in Figure 2.7.



Mass is the simplest parameter to partition the inputs and outputs for this system. Thus, since the

$$\text{total mass of useful product} = M_p = m_1 + m_2 + m_3$$

$$\text{total mass of naphtha input} = M = M_1 + M_2 + M_3$$

$$\text{total mass of waste material} = W = W_1 + W_2 + W_3$$

$$\text{total energy input} = E = E_1 + E_2 + E_3$$

the materials input attributable to the three sub-systems producing ethylene, propylene and other products will be

Ethylene sub-system: $M_1 = Mm_1/M_p$

Propylene sub-system: $M_2 = Mm_2/M_p$

'Others' sub-system: $M_3 = Mm_3/M_p$

Similarly, the allocation of energy, E_1 , and waste, W_1 to ethylene production will be:

$$E_1 = Em_1/M_p$$


and $W_1 = Wm_1/M_p$

and so on for propylene and other products.


2. The co-production of coke and manufactured gas from coal

Coke and manufactured gas are produced by the pyrolysis of coal in the absence of air.

Suppose an energy input, E , is required for the pyrolysis, as shown in Figure 2.8. A coal input of mass M produces coke and manufactured gas of masses m_1 and m_2 and energy content E_1 and E_2 respectively, plus waste material of total mass W .



In energy systems partitioning is normally carried out on an energy basis rather than a mass basis. Thus, just as thermal cracking was considered as three separate sub-systems in the previous example, for the purposes of partitioning, coal pyrolysis may be considered as two separate sub-systems producing coke and manufactured gas, as shown in Figure 2.9.



Thus, since the

$$\text{total mass input of coal} = M = M_c + M_g$$

$$\text{total mass of waste material} = W = W_1 + W_2$$

$$\text{total energy input} = E = E_c + E_g$$

$$\text{total energy output} = E_1 + E_2$$

the energy input attributable to the two sub-systems producing coke and manufactured gas, E_c and E_g respectively, will be,

Coke sub-system:
$$E_c = \frac{E.E_1}{(E_1 + E_2)}$$

Manufactured gas sub-system:
$$E_g = \frac{E.E_2}{(E_1 + E_2)}$$

Similarly, the allocation of coal input, M_c , and waste, W_1 , to coke production will be,

$$M_c = \frac{M.E_1}{(E_1 + E_2)}$$

and

$$W_1 = \frac{W.E_1}{(E_1 + E_2)}$$

and so on for manufactured gas.


3. The electrolysis of brine to produce chlorine, hydrogen and sodium hydroxide

Although it is tempting to apply mass partitioning to chemical processes the allocation of inputs between the various products may produce erroneous results. The difficulties of applying mass partitioning may be understood by considering the electrolysis of brine. In this process an input of electrical energy is used with mass inputs of sodium chloride and

water to produce chlorine gas, hydrogen gas and aqueous sodium hydroxide, as depicted in Figure 2.10. The overall chemical equation for the electrolysis is given below.



From the stoichiometry of the equation, and the relative atomic masses of the elements involved, it is possible to calculate the theoretical mass of the products from the reacting masses of sodium chloride and water as shown in Table 2.1. Thus, a hypothetical plant might consume 117 kg sodium chloride and 36 kg water for the production of 71 kg of chlorine, 2 kg hydrogen and 80 kg sodium hydroxide.



	INPUTS			OUTPUTS			
	Sodium chloride	Water	Total	Chlorine	Hydrogen	Sodium hydroxide	Total
Number of moles	2	2		1	1	2	
Mass (kg). No. moles x Relative Molecular Mass ¹ x 10 ³	117	36	153	71	2	80	153

¹ Relative Atomic Masses: Na = 23, H = 1, Cl = 35.5, O = 16

The peculiar problems associated with mass partitioning are highlighted by considering the allocation of the above sodium chloride inputs between the three products as shown in Table 2.2.


Table 2.2 Allocation of sodium chloride between products for the hypothetical electrolysis plant described in Table 2.1	
Allocation of sodium chloride input (kg)	Product (kg)
$(117 \times 71)/153 = 54.29$	Chlorine Cl ₂ = 71
$(117 \times 2)/153 = 1.53$	Hydrogen H ₂ = 2
$(117 \times 80)/153 = 61.18$	Sodium hydroxide NaOH = 80
Total = 117	Total = 153

The results of this allocation are inadmissible for the following reasons.

1. The only source of chlorine is sodium chloride, yet it would appear that more chlorine is produced than is present in the original sodium chloride.
2. The allocation of sodium chloride to the production of hydrogen is inconsistent with the chemistry of the reaction, which shows that hydrogen is derived entirely from the water input, and not from sodium chloride.
3. Similarly, the chlorine content of sodium chloride is incorrectly allocated to the production of sodium hydroxide, a product which does not contain chlorine.

Clearly, the application of mass partitioning to chemical processes produces incorrect results, and another technique based on the chemistry of the reacting species is preferred. Such a technique is known as stoichiometric partitioning.


The application of stoichiometric partitioning to the electrolysis of brine may be understood by first rewriting the overall chemical equation in terms of the reacting ionic species.



From this equation it is possible to identify the reacting species with particular products, as shown in Table 2.3 and Figure 2.11.

Table 2.3 Stoichiometric partitioning for a hypothetical electrolysis plant producing chlorine, hydrogen and sodium hydroxide								
	INPUTS - reacting species				OUTPUTS			
	Sodium chloride		Water		Chlorine gas	Hydrogen gas	Sodium hydroxide	
	Sodium ions Na ⁺	Chloride ions Cl ⁻	Hydrogen ions H ⁺	Hydroxide ions OH ⁻	Cl ₂	H ₂	Na ⁺ ions	OH ⁻ ions
Number of moles	2	2	2	2	1	1	2	2
Mass (kg). No. moles x Relative Formula Mass ¹ x 10 ³	46	71	2	34	71	2	46	34

¹ Relative Atomic Masses: Na = 23, H=1, Cl = 35.5, O = 16



Thus:

71 kg Cl⁻_(aq) ions produce 71 kg Cl_{2(g)}

2 kg H⁺_(aq) ions produce 2 kg H_{2(g)}

46 kg Na⁺_(aq) ions and 34 kg OH⁻_(aq) ions produce 80 kg NaOH_(aq)

Notwithstanding the use of stoichiometric partitioning for inputs of sodium chloride, not all inputs and outputs may be allocated in this way; for example, energy inputs. In such cases it is appropriate to partition on a mass basis.

2.3 Capital items

The construction of the plant and equipment required for industrial systems to function will consume considerable quantities of fuel and raw materials, and produce commensurate quantities of waste material. The data associated with these operations should strictly be included in the life-cycle inventory of the product, but their effect is insignificant when compared with the inventory flows of the product throughput during the lifetime of the plant. For example, consider a hammer mill weighing 29 tonnes used in a clay preparation plant. If it is assumed that the machine is constructed entirely from steel with a gross production energy of 32 MJ/kg, then the total capital energy is 9.3×10^5 MJ. If the hammer mill has a life expectancy of twenty years and processes clay at the rate of 1,500 tonnes per day, and if the clay processing energy is 1.0 MJ/kg, then the energy associated with the clay throughput is 1.5×10^6 MJ per day or 7.5×10^9 MJ over the lifetime of the machine. From these figures it can be shown that the capital energy makes a contribution of 0.01 % to the processing energy during the lifetime of the machine, which is much less than the accuracy of industrial data, and is therefore ignored in this work.

2.4 Human resources

Humans inputs make an important contribution to manufacturing processes and should strictly be considered part of the life-cycle inventory of manufactured goods. These contributions arise from two sources:

- ◆ food consumption
- ◆ transport to work.

An average human consumes about 40 kcal (0.1672 MJ) of food per kg live body weight per day.⁵⁴ For an average human of mass 80 kg the food intake has an energy of 13.4 MJ,

80 % of which is used to generate body heat and to maintain other body functions. Thus, only 20 %, or 2.7 MJ, is available for external work. It is useful to compare this energy with the energy associated with manufacturing operations. For example, consider the clay preparation plant discussed earlier. Suppose ten humans are employed in all the operations involved from the extraction of clay in the ground through to the operation of the hammer mill. The total energy available for human work is (10×2.7) MJ or 27 MJ per day, which adds only 0.002 % to the daily processing energy of 1.5×10^6 MJ.

The contribution arising from transport to work is higher and may be estimated as follows. Suppose a worker travels alone to work by car. If the petrol consumption of the car is 10.6 km per litre (approx. 30 m.p.g), and the gross energy of petrol is 36 MJ per litre, the energy of a return journey of 48 km will be 163 MJ. Thus, if it is assumed that the workforce of ten humans employed in the chain of operations starting with clay in the ground through to the hammer mill, all make similar journeys to work, an additional daily energy contribution of 1,630 MJ, or 0.1 %, should be added to the daily processing energy of 1.5×10^6 MJ.

The small increases in the daily processing energy attributed to food intake and transport to work are well below the accuracy of industrial data and consequently both these contributions will be ignored in this work.

2.5 Sources of information

The three main sources of data used in life-cycle assessment studies are:

1. published statistics
2. published literature
3. commercial sources

The first source of information is published statistics, which are normally available from government sources, trade associations or research councils. The use of such information suffers from a number of disadvantages. First, and most seriously, the data are presented in an aggregated form, from which it is usually impossible to separate and identify a particular source. Second, since the method by which the raw data is collected and the number of contributors involved are often unknown, there is an element of doubt concerning the accuracy of such figures. Nonetheless, published statistics are sometimes the best or only source of information and have been used as required in this work; for example, when deriving fuel production and delivery efficiencies.

The second source of information is open literature publications, which, unlike published statistics, are relatively free from aggregation problems and uncertainties regarding accuracy. Nonetheless, a potential problem may arise if public statistics have been used in the derivation of reported values. Although published work often provides useful values for unknown production parameters, especially when such information is withheld for reasons of confidentiality, it is sometimes dated by advances in technology and may refer to obsolete processes. Moreover, the time delay between data collection and publication creates a further limitation. Despite these disadvantages, open literature values have been used when necessary in this research.

Commercial organisations are the third source of information, and have been used extensively throughout this research, especially for gathering primary data for the production of building materials. Personal contact and the supply of up-to-date data, in the form requested, are the main advantages of this source of information. Data sources have

been acknowledged throughout this report except when confidentiality is an issue. It is important to note that some of the data in this work have been obtained from single sources and values should not be considered as representative.

2.6 Data collection

The gathering of reliable comprehensive data from commercial sources is a particularly difficult exercise. Some of the major obstacles in this area are:

- ◆ confidentiality of data
- ◆ incomplete or absent data
- ◆ specificity of data
- ◆ accuracy of data
- ◆ variation in data format
- ◆ type of plant

A further insight into each of these problems is provided below.

2.6.1 Confidentiality of data

The issue of confidentiality does not arise when life-cycle inventories are completed for internal use within an organisation. However, when undertaken for external use, as in the case of this research, some or all of the data may be withheld for reasons of commercial confidence, thus making a meaningful analysis difficult or impossible. Some methods of dealing with incomplete data are examined below.

2.6.2 Incomplete or absent data

Data gaps may arise out of issues of confidentiality as described above, or, as in the case of air and water emissions, because producers are chiefly concerned with conforming to environmental pollution regulations and only monitor selected discharges. In the latter case, if partial data sets are available from a number of different producers then an average but more complete data set can be estimated. Alternatively, in the case of regulated discharges, if it is assumed that a producer is satisfying environmental regulations then an upper limit may be placed on any known emission. Although it is always preferable to use actual data, in those instances where a primary data source remains unavailable, as with a monopoly supplier withholding for confidential reasons, then secondary source data such as theoretical or open literature values may be substituted. This solution is more acceptable when the missing input is far removed from the major production sequence and makes a relatively small contribution to the final result. Nonetheless, it is important in such cases to perform a sensitivity analysis to assess how the degree of variation in the secondary source data affects the overall conclusions.

2.6.3 Specificity of data

Data from primary sources may differ considerably for the manufacture of the same product. Such variations may be site-specific or process-specific and depend on factors such as the period of time over which measurements are made, the age and efficiency of the manufacturing plant, the technology used, and in some instances on the type of material input. The clay brick industry provides examples of both types of variation. Since the chemical composition of clay may vary from one brickwork to another, both fuel consumption and air emissions may be affected, thereby giving rise to site-specific variation.

For example, for brickworks using the same type of kiln, clay with a high carbon content will consume less fuel during firing,⁵⁵ whilst emissions of sulphur dioxide would be higher for clays with a relatively high sulphur content.^{56,57} On the other hand, process-specific variation may accompany a change in technology. For instance, a reduction in fuel consumption would be expected for any given clay if an intermittent kiln was replaced by the more efficient continuous kiln.⁵⁵

Where a sufficient number of independent data sources is available an industry average may be calculated. This is especially useful for external inventories when confidentiality may be an issue. Because the choice of data can affect the final outcome of life-cycle analysis it is important when constructing a life-cycle inventory to provide full details of the data source, and to indicate whether case-specific or average data is used. Where average data are preferred, the range of values should be quoted and a sensitivity analysis performed to assess how the variation in input data affects the final result.

2.6.4 Accuracy and reporting of data

It has been reported that the accuracy with which manufacturers record energy use and material flows is at best correct to within 5 %, and over periods of time less than twelve months a figure of 10 % is thought to be more appropriate.⁵³ Some possible explanations for such discrepancies are material losses, weighing errors, stock changes and materials in transit. A further difficulty, superimposed on inaccurate record keeping, may occur in plants subject to short term fluctuations in the production rate but with a fixed rate of fuel consumption, and arises out of the usual practice in life-cycle analysis of normalising inputs and outputs in terms of unit product output; for example, energy consumption in terms of

MJ/kg of product. For instance, a plant producing timber products may need to maintain a constant level of humidity throughout the factory irrespective of the production rate. This can only be achieved by consuming fuel at a constant rate. Thus, short term variations in the rate of production will produce corresponding short term variations in fuel consumption when expressed in terms of MJ/kg of product. However, by taking readings over a long period of time such as twelve months, fluctuations in the production rate are smoothed out to give a more accurate and reliable value. It is always better, therefore, to collect data measured over as long a period as possible, preferably twelve months as a minimum. Although the accuracy of data is at best correct to within 5 %, in order to avoid rounding errors all intermediate calculations in this work are quoted to four decimal places.

2.6.5 Variation in data format

Manufacturers record data in a number of different formats. In most cases there is little difficulty in expressing these data on an appropriate unit output basis. The exceptions are air and water emissions which are normally required by regulatory authorities to be expressed in concentration terms such as mg/m³ or mg/l. Unless the emission flow rate is known it is difficult to express these concentrations in terms of unit product output. In the case of air emissions, however, an approximate solution to this problem is possible for processes using a gaseous fuel, by assuming that the emission flow rate is the same as the known rate of gas consumption, plus an allowance of about 5 % for air intake.

2.6.6 Type of plant

The degree of difficulty in collecting data will be related to the complexity of the manufacturing process being investigated. Petrochemical plants, for example, are extremely

complex installations simultaneously manufacturing many different products on the one site. Moreover, in the petrochemical industry, it is not uncommon for a network of different plants on adjacent sites to trade surplus energy and materials with each other in the interests of efficiency, and some may share common facilities such as steam raising or effluent treatment plants to add to the complexity. In these situations it is very difficult to trace accurately material flows and partition energy usage or waste material production between the various products. By comparison, many small producers, such as a clay brickworks, have a relatively independent existence and operate uncomplicated plants with few co-products. Data collection for this type of plant is a relatively simple exercise.

2.7 Calculations

The performance characteristics of industrial systems are calculated using the procedure described in Section 2.7.1 together with data for each of the following inputs and outputs.

1. Energy
2. Fuels
3. Feedstocks
4. Raw materials consumption
5. Emissions to air
6. Emissions to water
7. Solid waste production

Most data rely directly on physical measurements. However, some outputs, such as emissions of carbon dioxide, are seldom measured directly, and are calculated instead. The method of calculating carbon dioxide emissions is described in Section 2.7.2.

2.7.1 Procedure for calculating performance characteristics

1. Starting from raw materials in the ground, a detailed flow chart for all the operations up to the final product is drawn up. In constructing the flow chart it is worth noting that most processing sequences may be conveniently represented as three main groups, processing, packaging and delivery, as shown in Figure 2.12.




Figure 2.12 Simplified flow chart for industrial manufacturing systems

2. The output from the final operation is set to unity
3. Using material conversion efficiencies and the mass inputs to each unit operation a mass balance linking the unit operations in the process sequence is calculated.
4. Normalised inputs and outputs to each unit operation are calculated as described in Section 2.2.3 and 2.2.4
5. By multiplying the normalised data by the mass output the contribution made by each unit operation to the overall system is calculated.
6. Finally, the separate contributions from each unit operation are added together to obtain gross inputs and outputs for the whole system.


Instead of calculating stages 5 and 6 by hand, the normalised inputs and outputs for each unit operation, as calculated in stage 4, may be used as input data in a computer model, which is then used to complete the calculations in stages 5 and 6. The calculation procedure outlined above may be illustrated with the following simple example relating to gross energy usage. The calculation of other gross inputs and outputs is carried out in a similar manner.

Consider a three stage linear sequence of unit operations, A, B and C, producing 1 kg of product as shown in Figure 2.13. The material conversion efficiencies and normalised energy input for operations A, B, and C are as shown.

By completing a mass balance calculation using the material conversion efficiencies, it can be shown that a mass input of 1.4619 kg to unit operation A is required to produce a downstream output of 1 kg of product from unit operation C. The gross energy, E , for the system may be derived from the normalised energy input to each unit operation as follows.

$$E = [(2 \times 1.3158) + (3 \times 1.0526) + (4 \times 1)]$$


$$= 9.79 \text{ MJ/kg}$$



2.7.2 Carbon dioxide calculations

Carbon dioxide is formed when carbon or carbon compounds are burned in a plentiful supply of air or oxygen, or from chemical reactions such as the thermochemical decomposition of carbonates such as calcium carbonate (limestone). Emission levels may be calculated from the stoichiometry of the chemical reaction describing its formation. For

example, assuming complete combustion, the carbon content of fossil fuels, such as coal, will burn in air producing carbon dioxide according to the following equation.



Formula masses 12.01 32.00 44.01

Formula masses have been calculated using the relative atomic masses of carbon and oxygen as 12.01 and 16.00 respectively.

Using formula masses it can be deduced that:

12.01 kg carbon produces 44.01 kg carbon dioxide

or, 1 kg carbon produces 3.664 kg carbon dioxide.

This relationship is used to calculate carbon dioxide emissions arising from the complete combustion of a hydrocarbon fuel such as coal. For example:

Let the carbon content of coal = 80 %

Then the mass of carbon present in 1 kg of coal = 0.80 kg

Mass of carbon dioxide produced on complete combustion of 1 kg coal = 0.80×3.664
= 2.93 kg


Maximum carbon dioxide emissions are only produced when a fuel burns completely.

However, in many combustion reactions it is unlikely that sufficient oxygen is present for the conversion of all the carbon to carbon dioxide. In these circumstances some carbon monoxide, and possibly some soot (pure carbon) is formed. In such cases the theoretical carbon dioxide emissions are too high and must be reduced by subtracting the carbon dioxide equivalent of carbon monoxide and carbon respectively.

The carbon dioxide equivalent of carbon has already been derived as:

1 kg carbon is equivalent to 3.664 kg carbon dioxide (see above).

The carbon dioxide equivalent of carbon monoxide is calculated from the equation describing its conversion to carbon dioxide as shown below.



Formula masses 28.01 16.00 44.01

Again, using formula masses:

28.01 kg carbon monoxide produces 44.01 kg carbon dioxide

or, *1 kg carbon monoxide is equivalent to 1.571 kg carbon dioxide*

2.8 Presentation of results

The results of the life-cycle inventory calculations will form a data set for each operation or system under each of the seven main performance characteristics listed in Section 2.7.

For each of these characteristics, data may be expressed as *unit data* for isolated operations, or as *gross data*. The term *gross data* refers to the cumulative total of all inputs and outputs beginning with the extraction of raw materials from the earth through to the final production sequence. Since life-cycle inventory calculations are ultimately concerned with gross data, the results of this research will be presented in this form, and tabulated as shown in the exemplar set of results for polyethylene film production in Table 2.4 on p. 39. Unless otherwise stated, all data in this work are recorded in SI units, for example, tonne, kg, mg for mass and MJ for energy.

It is useful to consider the format of Table 2.4. Firstly, it is designed to present gross energy data in terms of the fuel producing industries under the heading *Energy*. A second objective is to provide a complete set of input-output data under the headings *Primary fuels*, *Primary feedstocks*, *Raw materials*, *Air emissions*, *Water emissions*, and *Solid waste*.

The input-output data set represents the total burdens on the environment for the system

being considered. A further explanation and interpretation of the contents of the table are given below.

2.8.1 Gross energy data

The gross energy data are presented both in terms of the fuel producing industries under the heading *Energy*, and as the sum of the fuel and feedstock inputs under the headings *Primary fuels* and *Primary feedstocks*. Although the two methods of presentation show different details, the total energy consumption is the same in both cases. Any differences between the two totals are small and attributed to iteration or rounding errors. The significance of the two representations is developed in the following paragraphs.

When considered in terms of the fuel producing industries the gross energy data have been grouped together as *electricity, oil fuels, and other fuels*. The *electricity industry* is given particular attention because of its relatively low production efficiency, the lowest of all the fuel supply industries. The *oil industry* supplies a variety of different fuels, each derived from crude oil, and each with the same production efficiency. For these reasons the oil industry is given special consideration. For simplicity the remaining fuel producing industries, such as coal, coke, natural gas, and biological fuels are considered together under the heading *Other fuels*, although further subdivisions for each fuel are possible. Energy data for each fuel producing industry are broken down further as *production and delivery energy, delivered energy and feedstock energy*.

- ♦ The *production and delivery energy*, or indirect energy, is the energy used by the fuel producing industries in primary fuel extraction from the ground, subsequent

processing and delivery to the consumer. It is dependent on the country in which the fuel is produced and delivered. For example, in 1991, U.K. grid electricity was produced and supplied with an efficiency of approximately 30 %, compared to 48 % in Sweden. This implies that for every unit of electricity delivered, another 2.3 units of energy were consumed by the electricity producing industry in the U.K., compared to 1.08 units in Sweden. Variations in the efficiencies of electricity production and supply, from one country to another, are accounted for by the mix of primary fuels and the generating techniques used.

- ♦ The *delivered energy*, or direct energy, is the energy delivered to and used by the consumer.
- ♦ The *feedstock energy* is the energy content of fuel containing materials that are used as a material input, and not as a fuel. For example, wood in the paper industry. No entry is possible for electricity since by its very nature it cannot be a feedstock.

Feedstock energy is to be examined in more detail in Chapter 3.

In contrast to the *production and delivery energy*, both *delivered energy* and *feedstock energy* are independent of country, but are governed by the demand for energy and the technology used by the consumer. For example, in Table 2.4 the sum of the delivered energies attributed to *electricity*, *oil*, and *other* fuels (28.13 MJ), and the total *oil* and *other* fuel feedstocks (48.70 MJ), are dependent on the process technology. For the same technology these values will remain unchanged from one country to another. The opposite is true, however, for the total *production and delivered energy* (22.96 MJ), which is dependent on the fuel production industries of each country. Thus, by ignoring the country dependent production and delivery energies, it is possible to compare technologies or plants

using the same technology, between different countries. Comparisons of this nature highlight an important advantage of this mode of presentation.

The second format used for presenting gross energy data is as inputs of *Primary fuels and Primary feedstocks*. Here the energy requirements are considered in terms of primary fuels and feedstocks that are extracted from the ground. The fuel and feedstock entries under coal, oil, gas, etc. do not refer to the respective fuel producing industries, but to the quantities of coal, oil and gas, etc. removed from the ground. This format has the advantage of identifying the primary energy resources required to sustain the system. Moreover, by separating the non-renewable fossil fuels coal, oil and gas, it allows the dependence on fossil fuels to be examined. This type of information is of particular interest to environmentalists, for example, when considering the depletion of fossil fuel reserves. Finally, it enables the contribution from nuclear fuels and renewable fuels such as hydro-electricity, wood and biomass to be considered. Thus, for example, it is evident from Table 2.4 that the production of 1 kg of polyethylene film is heavily dependent on fossil fuels (45.89 MJ) and feedstocks (48.71 MJ). In contrast, the contribution from nuclear fuels (4.95 MJ) and hydro-electricity (0.24 MJ) is small by comparison. As with the first format, primary fuel data are separated from feedstock data, which, it should be noted, are the same in both formats.

Table 2.4 Gross inputs and outputs associated with the production of 1 kg polyethylene film		
Totals may not agree because of rounding errors		
Energy	Units	
Electricity - production & delivery	MJ	14.08
Electricity - delivered	MJ	5.96
Oil fuels - production & delivery	MJ	4.49
Oil fuels - delivered	MJ	7.75
Oil fuels - feedstock	MJ	24.05
Other fuels - production & delivery	MJ	4.39
Other fuels - delivered	MJ	14.42
Other fuels - feedstock	MJ	24.65
Total energy	MJ	99.79
Primary fuels		
Coal	MJ	12.66
Oil	MJ	12.51
Gas	MJ	20.72
Hydro	MJ	0.24
Nuclear	MJ	4.95
Lignite	MJ	0.00
Total fuels	MJ	51.07
Primary feedstocks		
Coal	MJ	0.02
Oil	MJ	24.04
Gas	MJ	24.64
Total feedstock	MJ	48.71
Total fuels & feedstock	MJ	99.78
Raw materials		
Bauxite	mg	312
Brine	mg	3
Clay	mg	20
Fe-Mn	mg	5
Iron ore	mg	1,329
Lead	mg	1
Limestone	mg	580
Met coal	mg	463
Sand	mg	5
Water	mg	2,555,400
NaCl	mg	7,140
Air	mg	108
Sulphur	mg	7
Air emissions		
Dust	mg	5,563
CO	mg	1,456
CO ₂	mg	2,972,300
SO _x	mg	16,295
NO _x	mg	14,195
HCl	mg	208
HF	mg	8
HC	mg	21,958
CHO	mg	5
Organics	mg	5
Metals	mg	2
CH ₄	mg	2,152
Hydrogen	mg	1
Water emissions		
COD	mg	1,022
BOD	mg	154
Acid	mg	90
NO ₃ -	mg	5
Metal ions	mg	312
NH ₄ ⁺	mg	5
Cl-	mg	122
Dissolved organics	mg	20
Dissolved solids	mg	408
Suspended solids	mg	702
Hydrocarbons	mg	104
Detergent/oil	mg	102
Other N	mg	10
SO ₄ ⁻	mg	10
Phenol	mg	2
Phosphate/P ₂ O ₅	mg	5
Solid waste		
Mineral waste	mg	75,585
Slag/ash	mg	23,091
Industrial waste	mg	3,319
Regulated chemicals	mg	71
Unregulated chemicals	mg	2,040

2.8.2 Gross raw materials

The gross raw materials data refer to the cumulative totals of the primary raw materials extracted from the ground, and are a measure of the depletion of the Earth's resources.

2.8.3 Gross emission data

Similarly, the gross emission data refer to the cumulative totals of waste material arising from all operations in the production sequence starting with raw materials in the ground through to the point of use by the consumer, and include air emissions, water emissions, and solid waste production. Such information is of interest to environmentalists concerned with potential pollution problems.

Although it is possible to consider emissions as originating from one or more of the following general sources; *fuel production, fuel burning, transport, process operations, and biomass*, the results of this research present the emission data in an aggregated form.

Nonetheless, it is instructive to examine the origins of some of these emissions in more detail, as shown in Table 2.5 where a selection of emissions is identified by type, source and specimen operation.

2.8.4 Conclusion

Finally, it must be emphasised that despite the sole reference in the input-output table headings to the final production sequence, the data refer to the cumulative totals associated with the final product, and include all the production sequences starting with raw materials in the ground through to the point of use of the final product by the consumer. It is incorrect to interpret the data as referring exclusively to the final production sequence.

Table 2.5 Examples of emission data identified by type, source and specimen operation

Emission type	Source	Specimen operation
<u>Air emissions</u>		
CH ₄	Fuel production	Coal mining, natural gas extraction & delivery
CO ₂ , SO ₂ , NO _x , HC, dust	Fuel production	Combustion of coal used in electricity generation
Ditto	Fuel burning	Combustion of coal by consumer
CO ₂ , NO _x	Fuel burning	Combustion of natural gas by consumer
CO ₂ , NO _x , HC, dust, lead	Transport	Combustion of oil fuels used in transport operations
CO ₂	Biomass	Combustion of wood
Ditto	Process	Thermochemical decomposition of limestone during cement manufacture
HCl	Process	Flat glass manufacture
N ₂ O	Process	Production of nitric acid and adipic acid
H ₂	Process	Production of aerated concrete blocks Electrolysis of brine
SO ₂ , HC	Process	Oil refining & cracking operations
HF, SO ₂ , NO _x	Process	Firing of clay during clay brick manufacture
<u>Water emissions</u>		
Suspended solids	Fuel production Process	Coal washing Cement manufacture (wet process)
COD, COD and phenol	Fuel production	Oil refining
Dissolved solids, salt	Process	Solvay process (sodium carbonate production)
Acid & metals	Process	Iron blast furnace
Fe, Sn, Cr	Process	Galvanising of steel
Na ⁺ and Cl ⁻ ions	Process	PVC manufacture
<u>Solid waste</u>		
Mineral waste	Fuel production Process	Earth/rock removal during coal mining Ditto - other mining operations
Slags/ash	Fuel production Process	Coal mining operations Combustion of coal in furnaces
Regulated waste	Process	Toxic or corrosive waste from chemical processes
Unregulated waste	Process	Non-toxic waste from chemical processes
Industrial waste	Process	Any other solid waste



Chapter 3

FUELS

3.1 Introduction

Fuels are an important element of life-cycle assessment studies and are of special interest both as an energy resource material and as a source of air emissions on combustion. They may be described as materials from which energy may be derived, and fall into two distinct groups, primary and secondary. Primary fuels include nuclear fuels, fossil fuels such as coal, natural gas, and oil, and renewable fuels such as wood. Secondary fuels such as electricity, coke, and manufactured gas are derived from primary fuels.

With the exception of nuclear fuels and electricity, most fuels contain carbon and hydrogen and owe their importance to the exothermic chemical reactions taking place with oxygen on burning.



The energy released on combustion of unit quantity of fuel is called the calorific value. For fuels containing hydrogen, two types of calorific value are often quoted; the gross calorific value and the net calorific value. The gross calorific value is defined as the heat evolved when all the products of combustion are cooled to standard conditions of temperature and pressure (i.e. a temperature of 25° C and 1 atmosphere pressure), and will include the latent heat of vaporisation of water and the heat associated with the temperature change on cooling the water to 25°C. The latter is sometimes known as the sensible heat of water. The net calorific value is the heat evolved when the water remains in the gaseous state. The net value does not include the latent heat of vaporisation or sensible heat, and is therefore less than the gross value. For example, the gross calorific value of methane is 53.42 MJ/kg

compared to the net value of 48.16 MJ/kg,⁵⁸ a difference of approximately 10 %. Gross calorific values are used in this work since they represent the maximum energy obtainable from a given fuel.

3.2 Feedstock energy

The inputs of raw materials to industrial operations are frequently referred to as *feedstocks*. Accounting for inorganic feedstocks is a relatively straightforward procedure since the total input will eventually appear as waste material or usable product. However, some organic feedstocks can be used as either a fuel input or as a material input, for example, oil products in the petrochemical industry or wood in the paper industry. When these materials are used as a fuel the energy content, or *fuel energy*, is destroyed for ever with the release of thermal energy and the evolution of gaseous emissions. Such use represents a permanent depletion of energy resources. In contrast, if used as a material input the energy content remains intact and 'locked up' in the final product. This 'locked up' energy is described as *feedstock energy* or *rolled-up feedstock energy*. Moreover, since the material is not burned no air emissions are produced.

Although feedstock energy may be regarded as a withheld or stored resource, part of it may be recovered along with associated air emissions, by burning at the end of the useful life of the product. Nonetheless, the fuel content of the product is not necessarily equal to the input feedstock energy and may differ for two reasons. First, the chemical structure of the materials may alter during the process, and since the energy content is dependent on chemical structure the available energy will also change. The second reason for the difference arises from material losses during processing.

Thus, *feedstock energy is calculated as the energy content (gross calorific value) of the input material, not the output.*

In some industries, such as the petrochemical or timber-producing industries, waste materials are often used as fuels. On these occasions feedstock energy is converted into fuel energy altering the balance between fuel and feedstock, and suitable adjustments must be made to the life-cycle inventory.

In recognition of their different characteristics, fuel energy and feedstock energy must be accounted for separately when analysing the total energy input to a process.


3.3 Fuel production and delivery efficiency

The processing of a primary fuel into a usable form, or its conversion into a secondary fuel, requires an input of energy. A further energy input is required for its subsequent delivery to the point of use by the consumer. If E_c and E_p represent the energy content of the fuel, and the processing and delivery energy respectively, the total energy extracted from the ground will be $(E_c + E_p)$. The quantity, E_c , represents the maximum energy available to the consumer and is termed the **direct** or **delivered** energy content. Using the above notation, the fuel production and delivery efficiency, α , may be expressed as:

$$\alpha = \frac{E_c}{E_c + E_p}$$

Conversion losses ensure that the production and delivery efficiency of a secondary fuel will always be less than that of the primary fuel from which it was derived. The overall production route for any fuel may be regarded as a linear sequence of operations, each with

its own energy conversion efficiency, α_n . For example, electricity production may be regarded as a four stage sequence as depicted in Figure 3.1.



Using the conversion efficiencies for each operation, the overall efficiency, η , will be given by

$$\eta = \alpha_1 \cdot \alpha_2 \cdot \alpha_3 \cdot \alpha_4$$

The production and delivery efficiency for each fuel will vary depending on the energy required for processing and delivery. For fossil fuels, little variation is noted from one country to another, and most figures lie in the range 80 % to 95 % depending on the fuel. However, a large variation is found between countries for electricity generation. For those countries with hydro-electric power, efficiencies as high as 80 % are recorded, whereas the efficiency of thermally generated electricity is seldom better than about 35 %.

3.4 Fuel producing industries

The energy required to support manufacturing processes is supplied by the fuel producing industries. Therefore, as a necessary pre-requisite to further analysis and before the gross inputs and outputs to manufacturing processes can be calculated, it is proposed to consider the fuel producing industries as belonging to extended industrial systems, and, by using recent data, to complete a life-cycle analysis for the production, processing, delivery and

use of each of the following fuels; natural gas, oil fuels, coal, coke, manufactured gas and electricity. The analyses relate to 1991, a recent year for which a full set of data is available. The life-cycle inventory calculations will generate the gross inputs and outputs associated with 1 MJ of each fuel.

Taking natural gas as an example, the production and supply of all primary fuels and secondary fuels such as coke and manufactured gas, from natural resources in the ground to the final point of use by the consumer, can be regarded as a simple linear sequence of the four main operations represented schematically in Figure 3.2. Since the process sequences and the preparation of the life-cycle inventories are similar for each of these fuels, only one fuel, natural gas, will be discussed in detail. The process sequence for electricity is slightly different and is considered separately.




Figure 3.2 Process sequence for the production and delivery of natural gas

3.4.1 U.K Natural gas production and supply

U.K. natural gas is extracted mostly from offshore gas or oil wells situated on the U.K. Continental Shelf. The extraction involves drilling and pumping operations together with associated gas losses or own use, summarised by Makhijani and Lichtenberg⁵ as including gas used for pipeline power, pipeline losses and gases vented and wasted. Table 3.1 provides details of the UK Natural Gas Production & Supply for 1991, plus unit inputs and outputs for the operations *Natural gas processing* and *Natural gas delivery*.

Table 3.1 UK Natural gas production & supply: unit inputs and outputs						
Source: Tables 20,24,40,41,48 - Digest of UK Energy Statistics 1992			Unit inputs and outputs/MJ gas			
Production & supply	TJ	TJ	Nat. gas processing		Nat. gas delivery	
			Fuel use MJ	Air emissions mg	Fuel use or loss MJ	Air emissions mg
Indigenous	2,143,390					
Imports	264,719					
Gross availability before disposal		2,408,109				
Disposal						
Own use- drilling & pumping*						
- Indigenous	-46,870					
- Imported (estimate)	-5,665					
		-52,535 A	A/B =	see Table 3.2		
		2,355,574 B	0.02230			
To others	-116					
Crude oil extraction	-86,757					
		-86,873				
Net availability before delivery		2,268,701				
Delivery						
Offshore distribution losses-CH ₄ (estimated)	-96,157					
Onshore distribution losses -CH ₄	-72,856					
		-169,013 C			C/E =	$\frac{C \times 10^6}{54.1144^{**} \times E}$
Onshore own use	-10,860			0.08026	= 1483.2	
		-10,860 D		D/E =	see Table 3.2	
				0.005157		
Input to storage (-)	16,975					
		16,975				
Net supply for onshore consumption		2,105,803 E				
Other inputs						
a) Onshore electricity use***						
- natural gas extraction		85.56 F	F/B =			
			0.000036			
- delivery		936 G		G/E =	0.00044	
b) Onshore gas oil use		2,258 H		H/E =	0.00107	

* 133,627 TJ (3.444 m³) - Table 24, apportioned between crude oil and natural gas extraction

** Calorific value of natural gas = 54.1144 MJ/kg

*** 1976.4 TJ - Table 48, apportioned between onshore crude oil and natural gas extraction

3.4.1.1 Air emissions from the combustion of natural gas

Natural gas is burned as a fuel during the operations *Natural gas processing*, *Natural gas delivery* and *Natural gas use*. The unit air emissions during combustion are shown in

Table 3.2

Emission type	per 0.02230 MJ <i>Natural gas processing</i>	per 0.005157 MJ <i>Natural gas delivery</i>	per MJ ⁴⁷ <i>Natural gas use</i>
Dust	1.73	0.40	77.55
CO ₂	1,133.29	262.08	50,820.00
SO _x	0.26	0.06	11.88
NO _x	16.20	3.75	726.66
HC	10.28	2.38	460.88
CO	0.01	0.00	0.33
CH ₄	0.07	0.02	3.10

3.4.1.2 Gross energy for the production and supply of natural gas

The gross energy requirement for the production and delivery of 1 MJ natural gas in the ground to the consumer, calculated from the above input values, is shown in Table 3.3 below.

Production & delivery energy MJ	Delivered energy MJ	Feedstock energy MJ	Total energy MJ	Production efficiency %
0.1125	1.0000	0.0000	1.1125	89.89

The production efficiency, η , is calculated as:

$$\begin{aligned} \eta &= \frac{\text{Total delivered energy}}{\text{Total primary energy input}} \times 100 \\ &= \frac{1}{1.1125} \times 100 \\ &= 89.89 \% \end{aligned}$$

3.4.2 UK grid electricity supply

For any given fuel the process sequence for the production and delivery of electricity may be represented by the simplified flow chart shown in Figure 3.1. Moreover, for each fuel used, the overall efficiency for the production and delivery of electricity, η , has already been defined in Section 3.3 as:

$$\eta = \alpha_1 \cdot \alpha_2 \cdot \alpha_3 \cdot \alpha_4$$

However, grid electricity from the public supply is a blend of electricity produced from different fuels, each with its own production efficiency, and may include imported

electricity. The overall average production efficiency, E , depends on the efficiency of electricity production from each fuel and the size of its contribution to the grid. Details of the fuel inputs to electricity generation and supply for 1991, and a further breakdown calculating the gross energy and overall efficiency for production and delivery are shown in Table 3.4.

Table 3.4 Electricity generated and supplied (TWh) 1991* Major generating companies plus autoproducers Numbers may not agree because of rounding errors								
	Thermal				Non-thermal		Imports	Total
	Coal + others	Heavy fuel oil	Natural gas	Man' gas	Nuclear	Hydro & wind		
Fuel input A	587.437	83.708	13.692	7.409				
Electricity generated B	208.992	30.345	4.132	1.928	70.543	6.865		322.805
Less own use	10.409	1.511	0.206	0.096	7.782	0.107		-20.111
Electricity supplied gross	198.583	28.834	3.926	1.832	62.761	6.758		302.694
Less use in pumped storage	1.391	0.202	0.027	0.013	0.439	0.037		-2.109
Electricity supplied net C	197.192	28.632	3.899	1.819	62.322	6.721		300.585
Plus net imports							16.422	16.422
Total available to grid D								317.007
Less transmission & distribution losses								-26.152
Electricity available to energy sector & final users E								290.855
Less energy sector consumption								- 9.794
Total electricity to final users								281.061
Efficiency of fuel production & supply α_1, α_2 - from Table 3.5	0.9700	0.8740	0.8989	0.8271				
Generating efficiency** $\alpha_3 = B/A$	0.3558	0.3625	0.3018	0.2602	0.3500	0.8000		
Efficiency of net supply $F = C/B$	0.9435	0.9435	0.9435	0.9435	0.8835	0.9790		
Transmission & distribution efficiency $G = E/D$								0.9175
Overall distribution efficiency $\alpha_4 = F \times G$	0.8657	0.8657	0.8657	0.8657	0.8106	0.8983		
$\eta = \alpha_1 \alpha_2 \alpha_3 \alpha_4$	0.2986	0.2743	0.2348	0.1863	0.2837	0.7186	0.3563	
Fractional input to grid ρ	0.6220	0.0903	0.0123	0.0057	0.1966	0.0212	0.0518	
Primary fuel requirement ρ/η (Gross energy)	2.0829	0.3293	0.0524	0.0308	0.6930	0.0295	0.1454	3.3632
Average production efficiency, E , = 1/Gross energy = 1/3.3632 =								0.2973
* Digest of UK Energy Statistics 1993 Table 48 OECD Energy Statistics Of OECD countries 1991-1992 p230 OECD Electricity Information 1993								
** Notional fuel production, supply and generating efficiencies ($\alpha_1, \alpha_2, \alpha_3$) ^{47, 59} : Hydro = 0.8000, Nuclear = 0.3500								

3.4.3 Gross inputs and outputs associated with fuel production, delivery and use

Complete inventories of the gross inputs and outputs associated with fuel production, delivery and use are shown in Appendices 1, 2 and 3. The fuel production and delivery efficiencies are of particular interest and may be derived from the gross energy inputs as shown in Table 3.5 below.

Table 3.5 Gross energies for various fuels/ MJ					
Fuel	Quantity	Production & delivery energy	Delivered energy	Gross energy	Production & delivery efficiency %
		A	B	C = A + B	B/C
Coal - average industrial (UK)	1 kg	0.98	28.01	28.99	96.62
Coal - power station average	1 kg	0.77	25.01	25.78	97.00
Coke	1 kg	5.02	25.42	30.44	83.51
Grid electricity	1 kWh	8.51	3.60	12.11	29.73
Natural gas	1 therm	11.86	105.44	117.30	89.89
Manufactured gas	1 therm	22.04	105.44	127.48	82.71
Heavy fuel oil	1 litre	5.91	40.98	46.89	87.40
Medium fuel oil	1 litre	5.90	40.92	46.82	87.40
Light fuel oil	1 litre	5.79	40.18	45.97	87.40
Gas oil	1 litre	5.46	37.84	43.30	87.40
Kerosine	1 litre	5.27	36.53	41.80	87.40
Diesel	1 litre	5.44	37.71	43.15	87.40
Gasoline	1 litre	5.19	35.97	41.16	87.40
LPG propane	1 kg	7.32	50.00	57.32	87.23
LPG butane	1 kg	7.22	49.30	56.52	87.23
Lubricating oil	1 litre	5.79	40.18	45.97	87.40
Grease	1 kg	6.14	42.60	48.74	87.40

Chapter 4

TRANSPORT

4.1 Introduction

Transport operations play a vital and all pervading role in most industrial operations, providing an essential link in the supply of raw materials or semi-finished goods to the manufacturer, and, after processing, in the delivery of finished goods to the consumer.

As a consequence they are an important element in the life-cycle inventories of extended industrial systems and cannot be overlooked.

The gross inputs and outputs associated with transport systems may be considered as arising from three separate contributions.

1. The fuel energy required to power the vehicle, which represents the largest proportion of energy.
2. The energy and materials required to construct and maintain vehicles.
3. The energy and materials needed to construct and maintain transport facilities such as roads and railway tracks.

Earlier reports have focused narrowly on the energy requirements of transport,^{7, 43, 60, 61, 62} but the purpose of this chapter is to broaden the perspective by incorporating all the above inputs and outputs into the life-cycle inventories of the road, rail and waterborne freight transport systems used by the processes described in this research. Of these, road transport is the most important in terms of goods moved (tonne.km), and since the preparation of the life-cycle inventories is similar for all forms of transport, will be considered as an example in

the following pages. The results of the life-cycle inventory calculations for the three forms of transport are shown in Appendices 4, 5 and 6.

4.2 Road transport

4.2.1 Direct fuel consumption

The direct fuel consumption of road vehicles depends on a number of inter-related factors, the most important of which are speed, payload, and gross vehicle weight. Ideally, fuel consumption figures should relate to a particular type of vehicle operating under a known conditions of speed, loading etc. However, because of the wide variations in speed and type of service, it is convenient to consider 'average' figures. The figures used in this work are derived from published^{63,64} or confidential sources, and based on a mix of urban and motorway conditions with vehicles carrying a maximum payload. Table 4.1 gives details of gross fuel consumption for the different types of commercial vehicles. From Table 4.1 it is clear that increasing vehicle size, measured in terms of maximum payload or gross vehicle weight, produces a considerable increase in fuel consumption (MJ/vehicle km). If the fuel consumption data are plotted against maximum payload as shown in Figure 4.1 it would appear that larger vehicles, particularly articulated vehicles, are less energy efficient.

However, if fuel consumption expressed in terms of MJ/tonne.km is re-plotted as shown in Figure 4.2, it is clear that the reverse is true and larger vehicles are much more energy efficient. Similar conclusions have been reported by Boustead and Hancock⁴³ albeit with slightly higher fuel consumption.

Fig 4.1 Gross fuel consumption per vehicle-kilometre vs maximum payload for diesel road vehicles





Fig 4.2 Gross fuel consumption per tonne-kilometre vs maximum payload for diesel road vehicles



It is useful, therefore, at this point to consider the choice of units when defining the energy requirements of transport. The most commonly used unit is MJ/tonne.km. However, energy values expressed in this way are sensitive to variations in load. This is particularly the case for road transport, where it is generally more convenient to express energy requirements as MJ/vehicle km. In contrast, the energy requirements of rail and waterborne transport are less load sensitive, and for these systems it is more usual to retain the former unit and to calculate energy consumption as MJ/tonne.km.

4.2.2 Vehicle construction inputs

Notional values for construction inputs have been estimated by adopting the procedure used by Makhijani and Lichtenberg.⁵ If it is assumed that 80 % of the mass of a typical unladen vehicle is steel, then a reasonable approximation for the construction energy can be made by assuming that the remaining 20 % is also steel. It is argued that the gross energy requirement of the remaining 20 % of materials, copper, aluminium, alloys and plastics, plus an allowance for the assembly energy, approximates to the same value obtaining if these materials are considered as steel. Estimated values of the gross construction energies for different vehicles are shown in Table 4.1 on p. 57.

4.2.3 Vehicle maintenance inputs

Vehicle maintenance inputs is a catch-all term for the energy and materials required to service and maintain a vehicle in a safe and roadworthy condition. It includes lubricant consumption, spares usage and garaging. Values for maintenance inputs have been derived from data obtained from published^{63,64} and commercial sources. Details of gross maintenance energies arising from the sources described below are shown in Table 4.1.

4.2.3.1 Lubricants

Values of lubricant consumption have been calculated from data supplied by a large fleet operator. Using these figures it can be shown that 99 % of all oil used for lubrication is consumed by engine oil changes during servicing or for topping up sumps. Gearbox and axle oil account for the remaining 1 %. Grease usage is extremely small representing about 0.5 % of all lubricants in energy terms. Moreover, since engine oil is changed at regular service intervals, there is little variation in lubricant consumption between the different types of vehicle.

4.2.3.2 Spares

The main components that may need replacing during a vehicle's lifetime are large items such as engines, gearboxes and differentials, smaller parts such as batteries and occasional restoration of paintwork and tyres. On modern vehicles major components such as engines or gearboxes usually have a working lifetime well in excess of the vehicle's and will rarely require replacing. For a large fleet the frequency of replacement is likely to be so low that the total production energy of the replaced components per total fleet km is assumed to be negligible. In contrast, paintwork and smaller components such as lead acid batteries will rarely last the lifetime of a vehicle and may need replacing more than once. Tyres have a high gross energy requirement and are frequently replaced, and must therefore be included with paint and lead acid batteries as inventory inputs.

Battery and paint usage by a large fleet operator have been combined with details of battery and paint composition, obtained from commercial sources, to calculate inputs of polypropylene, sulphuric acid, lead and paint.

Tyre usage depends on many variables such as size, route used, position on the vehicle and vehicle type. However, for the purpose of this work, average tyre lifetimes quoted in published literature⁶³ will be used. Using confidential information from commercial sources detailing the inputs and outputs to radial tyre production, and the assumptions listed below, an estimate of the 'average' tyre usage per vehicle km has been made.

- ◆ the typical tyre usage pattern by commercial vehicles is 2/3 new : 1/3 retread⁶⁵
- ◆ the total life of a retreaded tyre is 1.7 times the first life⁶⁵
- ◆ the 'average' tyre is considered to be a hybrid based on 2/3 new plus 1/3 retread tyre
- ◆ 'average tyre life' = $(2/3 \times \text{first lifetime}) + (1/3 \times 1.7 \times \text{first lifetime})$
- ◆ material inputs to produce a 12 R 22.5 tyre of mass 65.56 kg, suitable for use on a 38 tonne articulated vehicle, are based on a typical composition of: 45 % polymers, 23 % carbon black, 22 % steel and 10 % others (eg. sulphur, oils, antioxidants)
- ◆ material inputs to retreading are similar by proportion to the quantities used in the tread of the new tyre, less 10 % for incomplete removal of the original tread.
- ◆ the manufacturing inputs to produce such a tyre, are considered as 2/3 new tyre inputs plus 1/3 retread tyre inputs
- ◆ the 12 R 22.5 tyre is used for all vehicles with adjustments for tyre size (mass)

4.2.3.3 Garaging

Contributions to maintenance from garaging are attributed to

- ◆ electricity for lighting and powering tools and equipment
- ◆ fuels such as kerosine or natural gas used for space heating

Inventory inputs have been calculated using details of electricity and natural gas consumption obtained from a large fleet operator.

4.2.4 Inputs to the construction and maintenance of transport facilities

Whilst it is desirable in principle to include the inputs and outputs associated with the construction and maintenance of road transport facilities, the major difficulties in making an accurate apportionment between the different road users make it necessary to ignore these contributions.

4.2.5 Gross inputs and outputs

A summary of the gross energy requirements of road transport is shown in Table 4.1. The gross inputs and outputs for the main vehicle types used in this research are detailed in Appendices 4, 5 and 6.

Vehicle type/payload	Fuel energy	Maintenance energy				Construction energy	Gross energy
		Lubrication	Tyres	Garaging	Paint & batteries		
Rigid < 1 tonne	3.42	0.04	0.20	0.34	0.01	0.28	4.30
Rigid (1-2) tonne	4.88	0.04	0.37	0.34	0.01	0.37	6.01
Rigid (2-3) tonne	5.11	0.04	0.49	0.34	0.01	0.59	6.59
Rigid (4-5) tonne	7.19	0.04	0.61	0.34	0.01	0.61	8.82
Rigid (5-8) tonne	8.71	0.04	0.57	0.34	0.01	0.91	10.59
Rigid (8-9) tonne	9.04	0.04	0.53	0.34	0.01	0.95	10.92
Rigid (10-12) tonne	10.16	0.04	0.52	0.34	0.01	0.63	11.70
Rigid (13-21) tonne	12.31	0.04	1.20	0.34	0.01	0.87	14.77
Rigid 17.5 tonne concrete mixer	22.16	0.04	1.05	0.34	0.01	0.85	24.46
Rigid tipper 4 tonne	8.71	0.04	0.38	0.34	0.01	0.78	10.27
Rigid tipper 10.75 tonne	10.16	0.04	0.95	0.34	0.01	0.84	12.34
Rigid tipper 16.5 tonne	12.19	0.04	1.05	0.34	0.01	1.27	14.91
Rigid tipper 21 tonne	15.24	0.04	1.42	0.34	0.01	1.47	18.53
Articulated 17 tonne	13.54	0.04	0.78	0.34	0.01	0.67	15.39
Articulated (18-25) tonne	16.20	0.04	1.11	0.34	0.01	0.99	18.70
Articulated 30 tonne	19.70	0.04	1.47	0.34	0.01	1.12	22.69

Garaging includes grid electricity & natural gas use
Construction includes steel

The gross fuel energy shown in Table 4.1 refers to vehicles carrying a maximum payload. However, many vehicles carry partial loads, with some delivering a full load and returning empty. Moreover, vehicles carrying low density loads, such as PVC pipes, may exceed the

regulatory volume limits before exceeding the permitted axle loading. Therefore, for many vehicles it is difficult to estimate the fuel input. Thus, for simplicity, unless otherwise stated, fully laden vehicles are assumed throughout this research. For unladen vehicles the fuel consumption is calculated using the following empirical relationship.⁴³

$$\text{Unladen fuel consumption} = 0.7 \times \text{Fully laden fuel consumption}$$

Chapter 5

ECO-PROFILE OF BUILDING MATERIALS

5.1 Introduction

The purpose of this chapter is to complete an eco-profile analysis for the different building materials used in modern house construction. For convenience these inputs may be grouped together as follows.

- ◆ Mineral compounds such as sand, limestone, clay, gypsum and others
- ◆ Limestone products such as hydrated lime and asphalt
- ◆ Cement
- ◆ Structural clay products
- ◆ Concrete and mortar products
- ◆ Plaster products
- ◆ Flat glass and glass fibre wool
- ◆ Timber and timber products
- ◆ Metals
- ◆ Plastics
- ◆ Miscellaneous products such as pulverised fuel ash

Although the production detail will vary for each material or product, the repetitive process sequence - *Processing - Packaging - Delivery*, as shown in Figure 2.12, is common to all.

It is proposed to consider the detailed production of cement as an example, and to record schematic flow diagrams and the gross inputs and outputs associated with the remaining materials or products in Appendices 7 to 86. A further aim is to discuss the basis on which eco-profiles between different building types and between alternative building materials may be considered.


5.2 Cement production

The starting materials for cement production are minerals containing calcium carbonate - CaCO_3 , silica - SiO_2 , alumina - Al_2O_3 , and iron oxide - Fe_2O_3 . The two main raw materials are limestone and clay or limestone and marl, although in the plant studied in this report a mixture of limestone, sand and shale was used.

The manufacturing details for cement production have been described elsewhere.^{34, 66}

Although no two plants are identical they all involve the following common stages.


1. A preliminary reduction in the particle size of the raw materials as a preparation for intimate mixing.
2. A further reduction in particle size during milling as the raw materials are mixed and blended to produce a raw feed of uniform chemical composition. Cement is said to be manufactured by the *wet or dry process* depending on whether water is included with the raw materials at this stage, although *semi-wet* and *semi-dry* variants exist with a medium moisture content. The raw mix is known as '*slurry*' in the wet process and '*raw meal*' in the dry process. The distinct advantage of the dry process is the saving of energy by eliminating the need to evaporate unnecessary water in the kiln.
3. Heating of the raw mix in a kiln where any water is driven off and calcium carbonate is dissociated to form calcium oxide, which reacts at high temperatures with the oxides of aluminium, silicon, and iron to form cement *clinker*.
4. Addition of gypsum - CaSO_4 , to the clinker to retard the setting time of the finished cement, followed by a milling stage to grind the clinker to a specified size.
5. Packing and delivery of the finished cement.



5.2.1 Process details

The following discussion relates to processes within the cement works and does not include the extraction, processing and delivery of raw materials other than water. For the site used in this study about 680,000 tonnes of cement are produced annually, of which 49.23 % is produced using two wet kilns and 50.77 % from one dry kiln running parallel with each other. Raw material supplies of limestone, sand and shale are delivered an average distance of 9 km by road, and water is pumped a distance of 6.4 km from a nearby borehole.

Simplified schematic flow diagrams showing mass flows for both the wet and dry processes are shown in Figures 5.1 and 5.2 respectively.



5.2.1.1 Raw materials inputs

The mass flows shown in Figures 5.1 and 5.2 have been calculated on the following basis.

1. The typical chemical composition of a raw mix is approximately 80 % calcium carbonate, 14.5 % silicon oxide, 3 % aluminium oxide, 1.3 % iron oxide and smaller amounts of magnesium, potassium and sodium oxides, which is provided for in the plant investigated by a limestone : sand : shale ratio of 9 : 1 : 1.
2. The water content of the fluid slurry in the wet process is 30 %
3. The loss on ignition during the calcination process in the kiln is 40 %
4. 10 % by mass of coal used as kiln fuel is deposited as ash in the clinker
5. The gypsum content of the finished cement is 5 %

In addition, both wet and dry processes consume 0.7703 kg of coolant water per kg of finished cement.

5.2.1.2 Direct fuel consumption

Tables 5.1 and 5.2 provide details of direct fuel consumption, averaged over twelve months, for the production of cement by the wet and dry processes respectively.

Table 5.1 Direct fuel consumption - wet process MJ/kg				
	Fuel			Total
	Electricity	Heavy fuel oil	Coal	
Feed processing				
Limestone crushing	0.0083			0.0083
Shale crushing	0.0013			0.0013
Slurry mill	0.1757			0.1757
Clinker production - kiln				
Coal mill	0.0178			0.0178
Kiln power & fuel	0.0826	0.2140	4.6445	4.9411
Cement processing				
Drag chain to cement mill	0.0043			0.0043
Cement mill (o.p.c)	0.1656			0.1656
Loading packing	0.0093			0.0093
Ancillary processes				
Crane store	0.0028			0.0028
Heating & lighting	0.0107			0.0107
Workshops & labs	0.0053			0.0053
Offices & canteen	0.0006			0.0006
Transport depot	0.0009			0.0009
Water pumps	0.1854			0.1854
Total	0.6705	0.2140	4.6445	5.5291

Table 5.2 Direct fuel consumption - dry process MJ/kg				
	Fuel			Total
	Electricity	Heavy fuel oil	Coal	
Feed processing				
Limestone crushing	0.0084			0.0084
Shale crushing	0.0013			0.0013
Raw mill	0.1235			0.1235
Clinker production - kiln				
Coal mill	0.0140			0.0140
Kiln power & fuel	0.0756	0.0976	3.6613	3.8345
Cement processing				
Drag chain to cement mill	0.0043			0.0043
Cement mill (o.p.c)	0.1656			0.1656
Loading packing	0.0093			0.0093
Ancillary processes				
Crane store	0.0028			0.0028
Heating & lighting	0.0107			0.0107
Workshops & labs	0.0053			0.0053
Offices & canteen	0.0006			0.0006
Transport depot	0.0009			0.0009
Water pumps	0.1008			0.1008
Total	0.5230	0.0976	3.6613	4.2819

5.2.1.3 Transport operations

Cement is delivered to customers by road and rail. The relative proportions delivered in bulk or bagged form, for each mode of transport, are shown in Table 5.3 below.

Table 5.3 Delivery of cement by road and rail			
	% Bulk	% Bagged	Average distance of single journey (km)
Road - 20.0 t payload rigid vehicle	66.7	30.3	46.8
Rail - average load 401.5 t	3	0	161

Road transport inputs

$$\begin{aligned} \text{Number of vehicle.km per kg of cement} &= \frac{46.78 \times 1.7}{20,000} \\ &= 0.00397 \text{ vehicle.km/kg} \end{aligned}$$

(The multiplier of 1.7 arises from fuel saving made by vehicles returning empty⁴³)

Rail transport inputs

$$\begin{aligned} \text{Number of tonne.km per kg of cement} &= \frac{401.5 \times 161 \times 2}{401.5 \times 1,000} \\ &= 0.322 \text{ tonne.km/kg} \end{aligned}$$

5.2.1.4 Air emissions

The air emissions associated with the production of cement arise from as follows.

1. Dust produced from the comminution, handling and processing of the material components which finally form cement.
2. Carbon dioxide and other gases produced by thermochemical reactions involving raw materials in the kiln.
3. Combustion products from coal and heavy fuel oil use in the kiln.

It is very difficult to obtain accurate reliable data from producers and in the circumstances estimated air emissions have been calculated as shown below.

a) Dust

Estimates for dust emissions at various points in the cement plant have been made using reference data for air and gas volumes vented for the purposes of cleaning and filtering,⁶⁶ in conjunction with the UK regulatory upper emission limits.⁶⁷ All gas volumes are expressed as being measured at 15°C and 1 atmosphere pressure without correction for water vapour content.⁶⁷

Using the dust emissions from the wet process kiln as an example:

Regulatory upper limit = 460 mg/m³ of vented air

Vent rate of exit gases from wet process kiln = 2.8 - 3.5 m³/kg clinker

Assuming a vent rate of 3.0 m³/kg clinker, the upper limit dust emission is

$$= (3 \times 460) = 1,380 \text{ mg per kg clinker}$$

or $= 1,311 \text{ mg per kg cement}$

The total estimated dust emissions for the wet and dry processes are shown in Table 5.4

Table 5.4 Dust emissions produced during cement production - mg/kg cement		
	Wet process	Dry process
Shale crushing	0	0
Raw mill		1,793
Coal mill	85	134
Kiln	1,311	874
Cement mill	1,150	1,150
Packing/loading	168	168
Total	2,715	4,120

b) Emissions produced by thermochemical changes to raw materials in the kiln

Carbon dioxide production

If the input of limestone is considered as 100 % calcium carbonate then the production of carbon dioxide from the thermal dissociation taking place during calcination may be calculated from the stoichiometry of the equation:



From the equation it can be seen that 1 mole (100 g) of calcium carbonate produces 1 mole (44 g) of carbon dioxide on dissociation. Thus, an input of 1.2702 kg of limestone (wet process - see Figure 5.1 on p. 61) will produce

$$\begin{aligned} & 1.2702 \times \frac{44}{100} \text{ kg of carbon dioxide} \\ & = 0.5589 \text{ kg} \end{aligned}$$

Similarly, an input of 1.275 kg of limestone (dry process) will produce 0.5610 kg carbon dioxide.

Other emissions

Other possible emissions include sulphur dioxide and hydrogen sulphide from sulphide impurities, and hydrogen fluoride from fluorides such as calcium fluoride. However, in the absence of plant data it is only possible to estimate an upper limit for controlled emissions

such as hydrogen sulphide. Using the regulatory upper limit of 5 ppm v/v for hydrogen sulphide,⁶⁷ and a vent rate of 2.0 and 3.0 m³/kg clinker for the dry and wet rotary kilns respectively, the hydrogen sulphide emissions may be calculated as:

Dry process = 13.45 mg/kg cement

Wet process = 20.19 mg/kg cement

c) Products arising from the combustion of fuels

The gaseous emissions from the combustion of coal and heavy fuel oil used as kiln fuels, as shown in Table 5.5, have been calculated from reported emission data for fuel use.⁴⁷

Table 5.5 Total air emissions from the combustion of coal and heavy fuel oil used as kiln fuels in cement production - mg/kg cement		
Emission type	Wet process	Dry process
dust	1,859	1,465
CO	303	238
CO ₂	383,814	297,375
SO _x	4,945	3,798
NO _x	1,433	1,106
HCl	93	73
HF	3	3
HC	91	65
CH ₄	5	4

5.2.1.5 Emissions to water

The only reported emissions to water are discharges of suspended solids amounting to 50 mg/litre, which may be apportioned to the wet and dry processes respectively as:

Wet process = 9.48 mg/kg cement

Dry process = 5.08 mg/kg cement

5.2.1.6 Solid waste

Apart from dust emissions, very little solid waste is acknowledged during cement production, any filtered solid material being recycled. However, 600 mg/litre of solid matter is filtered from the water supply, which, when apportioned between the wet and dry processes becomes:

Wet process = 861.42 mg/kg cement

Dry process = 462.18 mg/kg cement

5.2.1.7 Gross inputs and outputs

Since cement produced by the wet process is indistinguishable from cement produced by the dry process, it is appropriate to calculate weighted mean values for the inputs and outputs associated with each process. It is these values that will be used later in the calculation of the gross inputs and outputs associated with cement based construction materials such as concrete. The gross energy requirements for the production and delivery of cement by the wet and dry processes are shown in Table 5.6 in terms of the contributing operations. The gross inputs and outputs associated with the production and bulk road delivery of cement are shown in Table 5.7.

Operation	Wet process	Dry process	Weighted average - wet/dry processes ¹	%
Raw materials - processing & delivery	0.1919	0.1926	0.1923	2.86
Feed processing	0.6231	0.4477	0.5340	7.95
Clinker production - kiln				
- Coal milling	0.0597	0.0471	0.0533	0.79
- Kiln fuel	5.0519	3.9012	4.4677	66.47
- Kiln power	0.2778	0.2542	0.2658	3.95
Cement processing	0.6027	0.6027	0.6027	8.97
Ancillary processes	0.6919	0.4072	0.5473	8.14
Delivery - road transport			0.0587	0.87
Total	7.4989	5.8526	6.7218	100.00

¹ based on wet/dry ratio of 49.23/50.77

From Table 5.6 it is clear that fuel usage makes the largest contribution to the overall gross energy requirement, and, as expected, the need to drive water from the raw slurry before clinker formation makes the wet process more energy intensive than the dry process. These results compare favourably with the 1980 industry-wide average gross energy requirement of 6.75 MJ/kg before delivery.³⁴

Energy		MJ	
Electricity - production & delivery		1.51	
Electricity - delivered		0.64	
Oil fuels - production & delivery		0.03	
Oil fuels - delivered		0.24	
Other fuels - production & delivery		0.15	
Other fuels - delivered		4.15	
Total energy		6.72	

Primary fuels		MJ	
Coal		5.55	
Oil		0.51	
Gas		0.07	
Hydro		0.03	
Nuclear		0.55	
Total fuels		6.71	

Primary feedstocks		MJ	
Coal		0.01	
Total feedstocks		0.01	
Total fuels & feedstocks		6.72	

Raw materials		mg	
Bauxite		4	
Gypsum		50,000	
Fe-Mn		2	
Iron ore		700	
Limestone		1,272,900	
Met coal		288	
Sand		141,558	
Water		2,145,800	
Shale		141,557	
Air		42	
Sulphur		3	

Water emissions		mg	
COD		1	
Acid		4	
Metals		1	
Suspended solids		4,933	
HC		1	

Solid waste		mg	
Mineral waste		71,370	
Slags/ash		3,018	
Industrial waste		142,192	

Air emissions		mg	
Dust		6,051	
CO		433	
CO ₂		1,039,000	
SO _x		6,141	
H ₂ S		17	
NO _x		1,889	
HCl		110	
HF		5	
HC		209	
CH ₄		1,459	

5.3 Basis for comparison between eco-profiles

Later in this work it is proposed to make comparisons between the eco-profiles of the two types of building under consideration (Chapter 7), and between alternative building materials (Chapter 8). The eco-profiles contained in the Appendices provide gross input-output data sets under the headings *Energy*, *Raw materials*, *Air emissions*, *Water emissions*, and *Solid waste*. It is useful to establish the basis on which comparisons are to be made for entries under these headings.

Whilst it may make sense to compare aggregate gross energy totals, it is meaningless and incorrect to compare aggregate totals of raw material inputs, air emissions, water emissions and solid waste. Any comparison must be between identical inputs and outputs. However, since it is unmanageable to consider all possible comparisons, it is necessary to be selective and to choose major or significant inputs or outputs.

5.3.1 Gross energy

Gross energy inputs may be compared either in terms of the fuel producing industries or as primary fuels and feedstocks as discussed in Section 2.8.1. However, it is proposed to use the gross energy totals as the basis for comparison since these values represent the total energy resources to be extracted from the ground from all sources to support the systems being compared.

5.3.2 Raw materials

Comparisons between raw material inputs are relatively simple for systems consuming similar materials; for example, the three bedroom bungalow and the four bedroom detached houses. It is clear from Appendix 87 that in these cases the two inventories share many common raw materials in roughly similar proportions. Water apart, sand, clay and limestone are the most dominant inputs and are selected for the purpose of comparison. Water inputs, although significant, are not included for comparison since water is a renewable resource and apart from small quantities involved in chemical reactions is naturally re-cycled.

In contrast, it is meaningless to compare the raw material inputs to systems producing alternative building materials when the inventories contain different dominant materials. For example, consider the eco-profiles for anodised aluminium and PVC window frame production, Appendices 62 and 73 respectively. Ignoring water inputs, the dominant input to aluminium window frame production is bauxite, whilst the dominant inputs to PVC window frame production are crude oil feedstock and sodium chloride. Since it is impossible to compare bauxite with crude oil feedstock or sodium chloride, it is pointless to consider such comparisons.

5.3.3 Air emissions

It is proposed to restrict comparisons between air emissions to carbon dioxide and sulphur dioxide only. Carbon dioxide is selected since it is by far the most abundant air emission, but also because it is subject to regulatory control as a known greenhouse gas. Sulphur dioxide is chosen because it is also subject to regulatory control as a precursor of acid rain.

5.3.4 Water emissions

Examination of the eco-profiles detailed in Appendices 7 - 92 shows that with few exceptions discharges of suspended solids are consistently the most significant water emission. For this reason it is proposed to limit comparisons between water emissions to suspended solids only.

5.3.5 Solid waste

Although considerable quantities of solid waste are recorded in the above eco-profiles, most is used as landfill, returned to earth or used for other purposes such as hardcore. Apart from small quantities of toxic chemicals, solid waste is relatively unimportant and is not subject to regulatory control. Consequently it is not proposed to include solid waste as a basis for comparison.

Chapter 6

MATERIAL INPUTS TO BUNGALOW AND DETACHED HOUSES

6.1 Introduction

The purpose of this chapter is to examine the building specifications for the two buildings under consideration. Detailed plans and inventories of the material inputs to a three bedroom bungalow house and a four bedroom detached house have been supplied by a reputable construction company. Artistic impressions and floor plans for each building are shown in Section 6.2. The assumptions used to calculate the material inputs to each building are shown in Section 6.3, whilst the material inputs supplied 'as used' by the construction company are detailed in Sections 6.4 and 6.5 respectively.

6.2 Artistic impressions and floor plans





Figure 6.1 Floor plan and sketch of three bedroom bungalow



Room sizes (mm)

Lounge	4,699	x	3,810
Dining	2,997	x	2,794
Kitchen	3,302	x	2,997
Utility	1,880	x	1,600
Bedroom 1	4,089	x	2,997
Bedroom 2	3,607	x	2,997
Bedroom 3	2,896	x	2,692
Bedroom 4	2,692	x	2,692
Bathroom	2,388	x	1,676
En-suite	1,981	x	1,676

Total floor area - 122.3 m²




Figure 6.2 Floor plan and sketch of four bedroom detached house

6.3 Assumptions used in the calculations of material inputs

Table 6.1 Assumptions used in the calculation of the material inputs for the construction of a three bedroom bungalow house and a four bedroom detached house (based on architect's specifications)	
Foundations	Concrete strip footings minimum 200 mm thick, projecting 150 mm to each side of loadbearing walls.
Ground floor	15 mm asphalt floor covering on successive layers of: concrete (100 mm), <i>visqueen</i> (polyethylene) dampproof membrane, sand (50 mm), and compacted hardcore (150 mm)
External walls	290 mm cavity walls: 100 mm facing brick 50 mm cavity, 140 mm thermal block inner leaf, maximum U value 0.6 W/m ² °C. Galvanised steel wall ties at maximum 450 mm vertical centres, 900 mm horizontal centres. Cavities filled with weak concrete mix up to ground level. Horizontal damp proof course (dpc) minimum 150 mm above ground level and to vertical cavity closures. Cavities closed at eaves and all openings.
Internal walls	100 mm brick or 100 mm structural block loadbearing walls built off strip foundations and fully bonded to adjoining loadbearing walls.
Internal partitions	75 x 50 mm soft wood studs at 450 mm vertical centres with 12.5 mm plasterboard skimmed to both sides. Built off dpc at ground floor.
Internal finishes	13 mm lightweight plaster and skim to walls. Galvanised bead to all external angles.
External soft wood finish	All exposed softwood treated with 2 coats of stain finish or primer, undercoat and gloss paint.
Eaves and barges	225 x 25 mm fascia board with 9 mm ply eaves soffit projecting 200 mm. 175 x 25 mm barge board on 100 x 38 mm soft wood ladder frame. 38 x 38 mm soft wood batten fixing for 9 mm ply soffit projecting 200 mm.
Lintels/ steelwork	All lintels made from galvanised pressed steel. Minimum 150 mm end bearings. Steel beams and purlins to Structural Engineers design.
Flashings	Lead flashings used at all abutments with minimum 150 mm upstand and minimum 150 mm over roof tiles.
Projecting bay	Standard window built into 100 x 50 mm soft wood framing bolted to brick jamb and supported on soft wood brackets. Mild steel straps fixing cill joists to inner-leaf. 60 mm thick fibreglass quilt between framing. 9 mm ply soffit, 19 mm thick soft wood tongue and groove cladding to sides.
Roof	Concrete interlocking roof tiles on 38 x 25 mm soft wood battens. Rafters at 600 mm centres. 100 x 25 mm soft wood diagonal, longitudinal, ceiling and chevron bracing. 30 x 5 mm galvanised mild steel straps at maximum 2 m centres with 75 x 50 mm soft wood blocking noggins fixed to external gable walls at ceiling and roof level. 150 mm fibreglass quilt insulation laid between ceiling members. (maximum U value 0.35 W/m ² °C). Ceiling finish foil backed 12.5 mm plasterboard and skim.
External plumbing	100 mm PVC deepflow gutters and 68 mm diameter downpipes to back inlet gullies. 100 mm diameter PVC single stack soil vent pipe (svp), terminal minimum 900 mm above window heads.
Bungalow only Vaulted roof	50 mm face pine boarding with clear varnish, or foil backed plasterboard with skim. 50 mm insulation battens between rafters giving 50 mm air gap. (Maximum U value 0.35 W/m ² °C).
Detached house only a) stairs	13 equal risers to 2625 mm, 225 mm treads, maximum pitch 42°. Clear headroom to be minimum 2 m vertical, handrail height to be 840 mm above pitch line and 900 mm to landings. Maximum space between vertical ballusters 95 mm. Minimum clear width of stair and landings 800 mm.
b) upper floors	127 x 19 mm tongue and groove floorboards on soft wood joists.

6.4 Material inputs to bungalow construction

Table 6.2 Material inputs to the construction of a three bedroom bungalow - 'as used' by builder (including a 5 % waste allowance on bulk items)			
Materials	Quantity	Units	Mass kg
Minerals			
Limestone hardcore	31,920	kg	31,920
Quarry building sand	14,532	kg	14,532
Cement			
Bagged ordinary Portland cement	3,150	kg	3,150
Structural clay products			
65 mm facing and common brick	31,973	kg	31,973
100 mm diameter underground drainage pipes	31	m	408
Yard gulleys	6	units	63
Limestone products			
Block form mastic asphalt floor covering 15 mm deep	103	m ²	3,708
Concrete and mortar products			
Ready mixed concrete, 20 MPa - for footings/cavity fill	31,253	kg	31,253
Ready mixed concrete, 30 MPa - for floor	37,559	kg	37,559
Ready mixed cement:lime:sand mortar	5,250	kg	5,250
Concrete roof tiles	144	m ²	8,064
Concrete chimney flue set	2,400	kg	2,400
Dense concrete blocks - structural blockwork (440x215x100) mm	37.8	m ²	7,333
Aerated concrete blocks (440x215x140) mm	119	m ²	12,495
Pre-stressed concrete lintels (255x75) mm	2.75	m	125
Plaster/plasterboard			
Plaster - bagged	1,394	kg	1,394
Plasterboard 12.5 mm	230	m ²	2,070
Timber			
Floorboards/joists/rafters/studding - unseen (UK produce)	3,675	kg	3,675
Window frames, door frames and doors - seen (imported timber)	564	kg	564
Glazing			
Flat glass - 6 mm double glazing	8.3	m ²	124.5
Metals items			
Galvanised steel items: hangers, straps, angle beading	69	kg	69
Steel beams	175	kg	175
Galvanised pressed steel lintels	17.1	m	152
Leadwork	157.5	kg	157.5
Copper pipes and copper hot water cylinder - hot/cold water supply	27	kg	27
Plastic/polymeric items			
Polyethylene damproof membrane	24	kg	24
Polyethylene damproof course	25.8	m ²	13
PVC guttering/pipework	31.5	kg	31.5
Paintwork (solids)	22.7	kg	22.7
Insulation			
Fibreglass roof insulation, 150 mm	87	m ²	261
Total mass input (including 5 % waste on bulk items)			198,993
Less 5 % waste			-9,277
Mass of finished bungalow			189,716

6.5 Material inputs to detached house construction

Table 6.3 Material inputs to the construction of a four bedroom detached house - 'as used' by builder (including 5 % waste allowance on bulk items)			
Materials	Quantity	Units	Mass kg
Minerals			
Limestone hardcore	26,880	kg	26,880
Quarry building sand	15,120	kg	15,120
Cement			
Bagged ordinary Portland cement	4,200	kg	4,200
Structural clay products			
65 mm facing and common brick	40,163	kg	40,163
100 mm diameter underground drainage pipes	30	m	395
Yard gulleys	4	units	42
Limestone products			
Block form mastic asphalt floor covering 15 mm deep	49	m ²	1,764
Concrete and mortar products			
Ready mixed concrete, 20 MPa - for footings/cavity fill	36,015	kg	36,015
Ready mixed concrete, 30 MPa - for floor	30,870	kg	30,870
Ready mixed cement:lime:sand mortar	6,300	kg	6,300
Concrete roof tiles	110	m ²	6,160
Concrete chimney flue set	2,400	kg	2,400
Dense concrete blocks - structural blockwork (440x215x100) mm	34.6	m ²	6,712
Aerated concrete blocks (440x215x140) mm	227	m ²	27,013
Pre-stressed concrete lintels (255x75) mm	3.46	m	158
Plaster/plasterboard			
Plaster - bagged	3,271	kg	3,271
Plasterboard 12.5 mm	274	m ²	2,466
Timber			
Floorboards/joists/rafters/studding - unseen (UK produce)	3,961	kg	3,961
Window frames, door frames and doors - seen (imported timber)	895	kg	895
Glazing			
Flat glass - 6 mm double glazing	13.4	m ²	201
Metals items			
Galvanised steel items: hangers, straps, angle beading	122	kg	122
Steel beams	125	kg	125
Galvanised pressed steel lintels	25.1	m	262
Leadwork	105	kg	105
Copper pipes and copper hot water cylinder - hot/cold water supply	36	kg	36
Plastic/polymeric items			
Polyethylene damproof membrane	18	kg	18
Polyethylene damproof course	16.8	m ²	8.4
PVC guttering/pipework	59	kg	59
Paintwork (solids)	31.5	kg	31.5
Insulation			
Fibreglass roof insulation, 150 mm	61	m ²	183
Total mass input (including 5 % waste on bulk items)			215,936
Less 5 % waste			-10,069
Mass of finished house			205,867

Chapter 7

ECO-PROFILES OF BUILDING CONSTRUCTION


7.1 Introduction

In this chapter the gross inputs and outputs associated with the construction of the specified bungalow house and detached house will be examined and comparisons made between the two types of building.

A further objective is to consider the relative proportions of both individual and collective inputs and outputs and to highlight any of significance. Finally, for each building, the sensitivity of the eco-profiles to a change in the magnitude of significant material inputs will be assessed.

7.2 Gross inputs and outputs

The gross inputs and outputs associated with the construction of the bungalow and detached house are detailed in Appendix 87. In most cases the inputs and outputs associated with house construction are greater than those associated with the bungalow. This is perhaps to be expected since the mass of the house (205,867 kg) exceeds that of the bungalow (189,716 kg). However, if the data are expressed in terms of floor space area (see Appendices 88 and 89), then the reverse is generally true. Gross energy data are used in Figure 7.1 to illustrate this reversal and to prove that for the two buildings in question, per unit area of floor space, the construction of the two storey detached house produces a considerable saving in gross energy consumption compared to the single storey bungalow house.



Input/Output	per building			per m ² floor space		
	Bungalow	House	% change	Bungalow ¹	House ²	% change
Gross inputs						
Energy (GJ)	552.30	662.52	19.96	6.35	5.42	-14.65
<u>Raw materials (g)</u>						
Sand	50,200,500	50,239,200	0.08	577,017	410,787	-28.81
Limestone	99,960,400	97,004,400	-2.96	1,149,000	793,168	-30.97
Clay	54,984,300	68,858,000	25.23	632,004	563,025	-10.91
Gross outputs (g)						
<u>Air emissions</u>						
Carbon dioxide	39,716,100	49,738,500	25.24	456,507	406,692	-10.91
Sulphur dioxide	312,146	403,472	29.26	3,588	3,299	-8.05
<u>Water emissions</u>						
Suspended solids	609,786	927,472	52.10	7,009	7,584	8.20
¹	Floor area: 87.0 m ²					
²	Floor area: 122.3 m ²					

The gross inputs and outputs for the construction of the two buildings summarised in Table 7.1 indicate this saving to be 14.65 %. Similarly, reductions of 28.81 %, 30.97 % and 10.91 % are shown for raw material inputs of sand, limestone and clay respectively. Moreover, reductions of 10.91 % and 8.05 % are noted for carbon dioxide and sulphur

dioxide emissions respectively. In contrast, and against the general trend, suspended solid discharges increase by 8.20 %.

For an explanation of these figures it is necessary to appreciate that reductions in the gross inputs and outputs per square metre of floor space, from bungalow to house, occur because the increases in the gross inputs and outputs per building are less than the corresponding 40.57 % increase in floor area. In contrast, values in excess of this figure, as observed for suspended solid discharges (52.10 %), generate increases in the gross inputs and outputs per square metre of floor space.

Such evidence suggests that for a given floor area an increase in building height may be synonymous with a decrease in environmental impact, and that further reductions in gross inputs and outputs may be possible in the construction of multi-storey buildings. Whilst this may be true for buildings constructed from the same materials and in roughly the same proportions, such as the bungalow and detached houses in this study, it is unsound and misleading to apply this principle to all buildings in all circumstances. In the case of multi-storey buildings, it is more than likely that the increase in load with height will be met by an increase in the use of high strength materials such as steel. Since steel has a high gross energy requirement and its production makes a significant environmental impact, the suggested reduction in gross inputs and outputs may not be realised.

It is interesting to note that the gross energy inputs given in Table 7.1 fall within the range of values reported by other workers as shown in Table 7.2. These figures will of course

depend on the type of buildings, the choice of materials used, the accuracy of input data, material omissions, and the country of origin. It is against this background that comparisons should be made.

Building type	Gross energy GJ/m²	Country	Year	Endnote reference
Standard 3 bedroom semi-detached	1.93	U.K.	1972	6
Standard 3 bedroom semi-detached	3.97	U.K.	1974	8
Conventional house bungalow	1.60	U.K.	1975	12
Timber frame house bungalow	0.87	U.K.	1975	12
Low flat dwellings	3.02	U.K.	1975	12
High flat dwellings	2.29	U.K.	1975	12
3 storey Community college	7.59	U.S.A.	1975	14
Brick veneer dwelling	1.32	Australia	1975	19
2 storey houses - brick/block loadbearing walls	1.24 - 2.27	U.K.	1976	23
- loadbearing crosswalls & lightweight infills	1.21 - 1.83	U.K.	1976	23
4 storey block of flats - vertical brick/block	1.70 - 2.68	U.K.	1976	23
9 storey block of flats - reinforced concrete loadbearing structures	4.19 - 4.80	U.K.	1976	23
Terrace house	7.03	U.K.	1977	26
Mid-terrace house	7.25	U.K.	1978	28
Theoretical models	1.23 - 7.41	U.S.A.	1983	35
Timber frame house	3.20	N. Zealand	1983	37
2 storey houses - Timber foundations & frame	2.21	Canada	1992	45
- Concrete foundation & clay brick veneer	4.12	Canada	1992	45
- Concrete foundation & aluminium sidings	3.30	Canada	1992	45
- Concrete foundations & concrete block wall	2.83	Canada	1992	45

Moreover, it should also be noted that with the exception of Marcea and Lau's⁽⁴⁵⁾ limited work on carbon dioxide emissions, little interest has been shown by these workers in extending this type of study beyond gross energy considerations into a fully developed eco-profile or life-cycle analysis. The present work, using a superior iterative calculation technique, is the first attempt to do so. It is this uniqueness and originality that set it apart from earlier studies.

At this point it is appropriate to examine in more detail the gross input and output data shown in Appendices 88 and 89. The following observations are noted.

- ♦ An increase in gross energy consumption is accompanied by an overall increase in waste production and raw material consumption. This is perhaps to be expected since gross energy consumption is a good indicator of human activity, which in this case involves the conversion of raw materials into finished buildings and the production of waste materials.
- ♦ The most significant raw material input is water which accounts for about 60 % of the total mass input. However, apart from a small quantity retained by concrete products during curing processes, most water is used as a coolant, a solvent, a medium for chemical reactions, an eluent, or simply lost through evaporation and not carried forward with the finished product or considered as a waste product. Other significant contributions include clay, limestone and sand which taken together account for about 36 % of the total mass input.
- ♦ Carbon dioxide is the most significant gaseous emission accounting for over 97 % of all air emissions. It is a known greenhouse gas and its importance arises from its global warming potential.
- ♦ Although solid waste is not to be considered as a basis for comparison, the proportions of total waste production attributed to solid waste for bungalow and detached house construction are 52.49 % and 50.20 % respectively.
- ♦ Emissions to water are small compared to air emissions. Suspended solids are the most significant discharge and account for about 99 % of all water emissions.
- ♦ There is an apparent mass imbalance between raw material inputs on the one hand and outputs of waste matter and finished buildings on the other. Possible explanations for this apparent breach of the Law of Conservation of Mass are:

- a) raw materials such as water, compressed air and separated nitrogen are included in the raw material inventory, but not in the waste product inventory,
- b) air emissions such as carbon dioxide, carbon monoxide, sulphur dioxide, and oxides of nitrogen are included in the air emissions inventory, but arise from the combustion of fuels which are not included in the raw material inventory. It should be noted, however, that although 73 % of carbon dioxide emissions are produced from fuel combustion, the remaining 27 % is produced from the thermochemical decomposition of limestone during cement and lime manufacture, and is therefore accounted for in the raw material inventory.

7.3 Sensitivity analysis of material inputs

In many instances a choice exists between alternative building materials serving the same function. For example, roof tiles made from clay or concrete, or window frames made from wood or PVC. It is useful, therefore, to consider the effect on the eco-profiles of each building of using different materials. To do this it is necessary, as a first step, to consider the relative contributions to the gross inputs and outputs made by the building materials specified in the builder's schedules given in Tables 6.2 and 6.3. Rather than examine all the gross inputs and outputs, it is sufficient for this exercise to study the gross energy inputs alone. It is immaterial whether these inputs are expressed *per building* or *per m² of floor area*, the % contributions remains the same. The results of these analyses are shown in Tables 7.3 and 7.4 and provide an opportunity to identify any dominant material inputs and to assess the sensitivity of the eco-profiles to a change in material input.

Table 7.3 Gross energy inputs to bungalow construction attributed to material inputs - per building				
Material inputs	Gross energy /GJ		%	
Minerals				
Limestone hardcore	5.17		0.94	
Quarry building sand	1.63		0.29	
		6.80		1.23
Cement				
Bagged ordinary Portland cement	22.38		4.05	
		22.38		4.05
Structural clay products				
65 mm facing and common brick	156.76		28.38	
100 mm diameter underground drainage pipes	2.56		0.46	
Clay gulleys	0.83		0.15	
		160.14		28.99
Limestone products				
Block form mastic asphalt floor covering 15 mm deep	31.80		5.76	
		31.80		5.76
Concrete and mortar products				
Ready mixed concrete, 20 MPa - for footings/cavity fill	23.37		4.23	
Ready mixed concrete, 30 MPa - for floor	33.20		6.01	
Ready mixed cement:lime:sand mortar	5.88		1.06	
Concrete roof tiles	19.49		3.53	
Concrete chimney flue set	3.84		0.69	
Dense concrete blocks - structural blockwork (440x215x100) mm	6.79		1.23	
Aerated concrete blocks (440x215x140) mm	57.37		10.39	
Pre-stressed concrete lintels (255x75) mm	0.26		0.05	
		150.20		27.19
Plaster/plasterboard				
Plaster - bagged	3.82		0.69	
Plasterboard 12.5 mm	12.66		2.29	
		16.48		2.98
Timber				
Floorboards/joists/rafters/studding - unseen (UK produce)	86.73		15.70	
Window frames, door frames and doors - seen (imported timber)	22.24		4.03	
		108.97		19.73
Glazing				
Flat glass - 6 mm double glazing	3.64		0.66	
		3.64		0.66
Metals items				
Galvanised steel items: hangers, straps, angle beading	2.51		0.45	
Steel beams	5.71		1.03	
Galvanised combined steel lintels	6.27		1.14	
Leadwork	8.03		1.45	
Copper pipes and copper hot water cylinder - hot/cold water supply	1.63		0.30	
		24.15		4.37
Plastic/polymeric items				
Polyethylene damproof membrane	2.42		0.44	
Polyethylene damproof course	1.31		0.24	
PVC guttering/pipework	2.37		0.43	
Paintwork (solids)	11.23		2.03	
		17.33		3.14
Insulation				
Fibreglass roof insulation, 150 mm	10.42		1.89	
		10.42		1.89
Totals		552.31		99.99

Table 7.4 Gross energy inputs to detached house construction attributed to material inputs - per building				
Material inputs	Gross energy /GJ		%	
Minerals				
Limestone hardcore	4.35		0.66	
Quarry building sand	1.70		0.26	
		6.05		0.92
Cement				
Bagged ordinary Portland cement	29.84		4.50	
		29.84		4.50
Structural clay products				
65 mm facing and common brick	196.91		29.72	
100 mm diameter underground drainage pipes	2.48		0.37	
Clay gulleys	0.55		0.08	
		199.94		30.17
Limestone products				
Block form mastic asphalt floor covering 15 mm deep	15.13		2.28	
		15.13		2.28
Concrete and mortar products				
Ready mixed concrete, 20 MPa - for footings/cavity fill	26.93		4.06	
Ready mixed concrete, 30 MPa - for floor	27.29		4.12	
Ready mixed cement:lime:sand mortar	7.06		1.07	
Concrete roof tiles	14.89		2.25	
Concrete chimney flue set	3.84		0.58	
Dense concrete blocks - structural blockwork (440x215x100) mm	6.22		0.94	
Aerated concrete blocks (440x215x140) mm	109.44		16.52	
Pre-stressed concrete lintels (255x75) mm	0.33		0.05	
		195.98		29.59
Plaster/plasterboard				
Plaster - bagged	8.96		1.35	
Plasterboard 12.5 mm	15.08		2.28	
		24.04		3.63
Timber				
Floorboards/joists/rafters/studding - unseen (UK produce)	93.48		14.11	
Window frames, door frames and doors - seen (imported timber)	35.29		5.33	
		128.77		19.44
Glazing				
Flat glass - 6 mm double glazing	5.91		0.89	
		5.91		0.89
Metals items				
Galvanised steel items: hangers, straps, angle beading	4.44		0.67	
Steel beams	4.08		0.62	
Galvanised combined steel lintels	10.83		1.64	
Leadwork	5.35		0.81	
Copper pipes and copper hot water cylinder - hot/cold water supply	2.17		0.33	
		26.87		4.07
Plastic/polymeric items				
Polyethylene damproof membrane	1.80		0.27	
Polyethylene damproof course	0.85		0.13	
PVC guttering/pipework	4.44		0.67	
Paintwork (solids)	15.59		2.35	
		22.68		3.42
Insulation				
Fibreglass roof insulation, 150 mm	7.31		1.10	
		7.31		1.10
Totals		662.52		100.01

It is clear from these results that the dominant material inputs belong to the *Structural clay products*, *Concrete and mortar products*, and *Timber* categories which collectively account for over 75 % of the total gross energy inputs. Within these categories unseen timber products, clay bricks and aerated concrete blocks make the largest contributions and it is here that the eco-profiles are most sensitive to change. However, few if any materials exist as practical alternatives to timber for these designated purposes. In contrast, both clay bricks and aerated concrete blocks compete with alternative materials such as dense concrete blocks and provide scope for variation and change.

Other material inputs, although essential to building construction, make a relatively minor contribution to the total gross energy. For many, such as sheet glass, cement and sand, no suitable alternatives are available. In contrast, some materials, such as wooden window frames and doors compete with PVC and aluminium alternatives. Although these materials may be relatively unimportant in terms of their contribution to the total gross energy of building construction, comparisons with competing alternatives are of interest and importance to producers.

In the next chapter alternative building materials will be compared and the effect of their substitution on the eco-profiles of buildings considered.

Chapter 8

A COMPARISON OF ALTERNATIVE BUILDING MATERIALS

8.1 Introduction

Before any comparisons between alternative building materials are made, it is important to re-state the key principle underpinning all life-cycle analysis that any such comparisons must be confined to systems performing identical functions. For example, when comparing PVC and wooden window frames, it is incorrect and meaningless to compare 1 kg of PVC with 1 kg of wood. Rather, it is the behaviour of the extended industrial systems producing PVC and wooden window frames that must be compared. Moreover, unlike the eco-profiles discussed throughout the present work, which omit the use or final disposal of products, in true life-cycle analyses comparisons between alternative building materials should be made over their complete life-cycles. Nonetheless, despite this limitation, where alternative building materials exist, the choice between them may be guided by comparing and contrasting the eco-profiles of their respective production systems, and by applying the principle that *least is best* to the gross inputs and outputs. In an ideal case, one production system will assert its superiority and select itself by virtue of much reduced gross inputs and outputs. However, in many cases the choice is not always clear as competing systems may each have advantageous claims to reduce one or more gross inputs or outputs. In comparing eco-profiles, the accuracy of the reported data should be borne in mind. Given that data are at best correct to within 5 or 10 %, see Section 2.6.4., the preferred production system should offer at least a 20 % reduction in gross inputs and outputs to claim any significant advantage.

Taking the above comments into consideration, the following groups of building materials, each serving equivalent functions, will now be compared. The effect of substituting alternative materials on the eco-profiles of the bungalow house and the two storey detached house will also be considered for those materials offering significant reductions in gross inputs and outputs.

- ◆ Roof tiles: clay and concrete
- ◆ Window frames/doors: timber, aluminium, PVC
- ◆ Sewer pipes/gullies: clay, PVC
- ◆ Roof drainage materials (drainpipes, gutters): aluminium, PVC
- ◆ Lintels: reinforced concrete, timber, steel, combined
- ◆ Building blocks: clay bricks, dense concrete blocks, aerated concrete blocks
- ◆ Insulation materials: glass fibre wool, expanded polystyrene (EPS), polyurethane


Detailed inventories of the gross inputs and outputs for the extended industrial systems producing these materials are contained in the Appendices. Rather than compare all inputs and outputs, selective comparisons will be made as established in Section 5.3. Using gross energy inputs, carbon dioxide and sulphur dioxide emissions, and suspended solid discharges as performance indicators, comparisons will be made by expressing one as a ratio of the other. Using this technique detailed comparisons between the above alternative materials are made in Sections 8.2 - 8.8 below.

8.2 Roof tiles: *clay, concrete*

Clay and concrete are used as alternative materials in the construction of roof tiles. The selected gross inputs and outputs for the systems providing 1 square metre of roof cover from clay and concrete tiles are derived from Appendices 23 and 30 respectively.

These values are used to calculate comparative gross input and output ratios as shown in Table 8.1. The results of this exercise are depicted graphically in Figure 8.1.


Building material	Gross energy		Air emissions				Water emissions	
	MJ	Ratio	Carbon dioxide		Sulphur dioxide		Suspended solids	
			mg	Ratio	mg	Ratio	mg	Ratio
Clay	280.47	2.07	16,755,100	1.17	89,574	1.00	24,646	1.00
Concrete	135.34	1.00	14,329,800	1.00	104,088	1.16	126,953	5.15



From Figure 8.1 it can be seen that when judged in terms of gross energy and carbon dioxide inputs, the performance of the system producing concrete roof tiles is superior to that producing clay roof tiles, but inferior when sulphur dioxide and suspended solid emissions are compared. Clearly, both production systems offer advantages over the other. A more valid comparison can be made, however, by comparing the two systems over the expected lifetime of a modern house (70 years). Using the manufacturer's guaranteed lifetime for clay tiles (30 years) and concrete tiles (50 years), it is evident that three sets of clay tiles and two sets of concrete tiles will be required during this time. Table 8.2 shows

modified gross input and output ratios calculated for the total number of tiles required during this period. The results of this comparison are shown graphically in Figure 8.2.

Building material	Gross energy		Air emissions				Water emissions	
	MJ	Ratio	Carbon dioxide		Sulphur dioxide		Suspended solids	
			mg	Ratio	mg	Ratio	mg	Ratio
Clay	841.41	3.11	50,265,300	1.75	268,722	1.29	73,938	1.00
Concrete	270.68	1.00	28,659,600	1.00	208,176	1.00	253,906	3.43




From Figure 8.2 it is evident that when judged over the expected lifetime of a modern house the performance of the system producing concrete roof tiles is enhanced compared to the system producing clay roof tiles. Moreover, the sulphur dioxide ratio is reversed to give an advantage to the concrete roof tile production system. Nonetheless, the performance of the clay roof tile system is superior when comparing suspended solid emissions. On balance, however, the system producing concrete roof tiles may be judged as the superior of the two systems and to offer distinct advantages, particularly for houses with long lifetimes. These conclusions are of particular interest given the absence of published data in this field.

8.3 Window frames/doors: *timber, aluminium, PVC*

Timber, PVC and aluminium are used extensively as alternative materials for the construction of window frames and doors. The gross inputs and outputs for window frame/door construction will clearly depend on the physical dimensions of the window or door opening. For the purposes of this comparison, two typical products will be considered as shown in Figure 8.3.

a) a two vent casement window frame - (1200 mm x 1200 mm)

b) an external kitchen door/frame - door dimensions (762 mm x 1981 mm)




The gross input and output ratios for the systems producing the above casement window frame and the external kitchen door are derived from Appendices 48, 62, 63, 64, 65, 73, and 74. These ratios are given in Tables 8.3 and 8.4 respectively and graphically illustrated in Figures 8.4 - 8.5 and 8.6 - 8.7.

Table 8.3 Selected gross inputs and outputs for systems producing casement window frames (1200 mm x 1200 mm) - per frame


Building material	Gross energy		Air emissions				Water emissions	
	MJ	Ratio	Carbon dioxide		Sulphur dioxide		Suspended solids	
			mg	Ratio	mg	Ratio	mg	Ratio
Timber	690.10	1.00	33,604,900	1.00	59,656	1.00	9,529	1.00
PVC	1,713.34	2.48	63,885,900	1.90	766,508	12.85	466,790	48.99
Aluminium (painted)	3,021.14	4.38	110,139,600	3.28	878,615	14.73	4,542,100	476.66
Aluminium (anodised)	3,261.14	4.73	128,761,200	3.83	1,206,000	20.22	5,354,000	561.86

Figure 8.4 Gross input and output ratios for systems producing casement window frames (1200 mm x 1200 mm) - per frame



Window frames	Gross energy	Carbon dioxide	Sulphur dioxide
Timber	1.00	1.00	1.00
PVC	2.48	1.90	12.85
Aluminium (painted)	4.38	3.28	14.73
Aluminium (anodised)	4.73	3.83	20.22

Figure 8.5 Gross input and output ratios for systems producing casement window frames (1200 mm x 1200 mm) - per frame




Window frames	Suspended solids
Timber	1.00
PVC	48.99
Aluminium (painted)	476.66
Aluminium (anodised)	561.86

Table 8.4 Selected gross inputs and outputs for systems producing external kitchen door & door frame: door size (762 mm x 1981 mm) - per door/doorframe


Building material	Gross energy		Air emissions				Water emissions	
	MJ	Ratio	Carbon dioxide		Sulphur dioxide		Suspended solids	
			mg	Ratio	mg	Ratio	mg	Ratio
Timber	1,214.57	1.00	59,144,600	1.00	104,995	1.00	16,771	1.00
PVC	2,581.05	2.12	97,607,300	1.65	2,142,900	20.41	2,329,800	138.92
Aluminium (painted)	4,666.63	3.84	167,983,900	2.84	1,399,200	13.33	7,158,600	426.84
Aluminium (anodised)	5,043.34	4.15	197,212,800	3.33	1,913,000	18.22	8,432,900	502.83

Figure 8.6 Gross input and output ratios for systems producing external kitchen door/frames: door size (762 mm x 1981 mm) - per door/frame



Door/frames	Gross energy	Carbon dioxide	Sulphur dioxide
Timber	1.00	1.00	1.00
PVC	2.12	1.65	20.41
Aluminium (painted)	3.84	2.84	13.33
Aluminium (anodised)	4.15	3.33	18.22

Figure 8.7 Gross input and output ratios for systems producing external kitchen door/frames: door size (762 mm x 1981 mm) - per door/frame



Door/frames	Suspended solids
Timber	1.00
PVC	138.92
Aluminium (painted)	426.84
Aluminium (anodised)	502.83

Using the gross input and output ratios as performance indicators, it is apparent from Figures 8.4 - 8.7 that systems using timber consistently outperform the others. When placed in increasing order of superiority the four systems in this study may be judged to read, *aluminium (anodised)*, *aluminium (painted)*, *PVC* and *timber*. This order is in line with Austrian research (1991)⁴⁴ which reaches similar general conclusions. However, despite any similarities with the present work, the Austrian study is limited to a discussion of gross energies, air emissions and solid waste production. It is neither a complete life-cycle analysis nor an exhaustive eco-profile and fails to categorise solid waste, or to include specific air emissions such as carbon dioxide and water emissions. Nonetheless, it is interesting to observe the close agreement between the PVC/timber gross energy ratio of 2.07 and the results of the present work. Of special note, however, is the improved performance quoted for systems producing aluminium window frames. For example, the aluminium/timber gross energy ratio is given as 2.62. This improvement may reflect differences in fuel production efficiencies and in the mix of primary fuels used for electricity generation.


Although the results of the present work suggest that systems producing timber window frames and doors may be judged superior to systems using PVC or aluminium, it must be remembered that if the systems were compared over the lifetime of a house the conclusions may well be different. For example, if the expected lifetimes of softwood, PVC and aluminium window frames and doors are taken as 10, 20 and 70 years respectively, the number of frame/door changes required during the expected lifetime of a modern house (70 years) are 7, 4 and 1 respectively. Modified gross input and output ratios that take account

of these different life expectancies are shown in Tables 8.5 - 8.6 and graphically illustrated in Figures 8.8 - 8.11.

Table 8.5 Selected gross inputs and outputs for systems producing casement window frames (1200 mm x 1200 mm) during the lifetime of a house - per frame

Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Timber	4,830.70	1.60	235,234,300	2.14	417,592	1.00	66,703	1.00
PVC	6,853.36	2.27	255,543,600	2.32	3,066,032	7.34	1,867,160	27.99
Aluminium (painted)	3,021.14	1.00	110,139,600	1.00	878,615	2.10	4,542,100	68.09
Aluminium (anodised)	3,261.14	1.08	128,761,200	1.17	1,206,000	2.89	5,354,000	80.27

Figure 8.8 Gross input and output ratios for systems producing casement window frames (1200 mm x 1200 mm) during the lifetime of a house - per frame



Window frames	Gross energy	Carbon dioxide	Sulphur dioxide
Timber	1.60	2.14	1.00
PVC	2.27	2.32	7.34
Aluminium (painted)	1.00	1.00	2.10
Aluminium (anodised)	1.08	1.17	2.89

Figure 8.9 Gross input and output ratios for systems producing casement window frames (1200 mm x 1200 mm) during the lifetime of a house - per frame





Table 8.6 Selected gross inputs and outputs for systems producing external kitchen door & door frames: door size (762 mm x 1981 mm) during the lifetime of a house - per door/door frame


Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Timber	8,501.99	1.82	414,012,200	2.46	734,965	1.00	117,397	1.00
PVC	10,324.20	2.21	390,429,200	2.32	8,571,600	1.66	9,319,200	79.38
Aluminium (painted)	4,666.63	1.00	167,983,900	1.00	1,399,200	1.90	7,158,600	60.98
Aluminium (anodised)	5,043.34	1.08	197,212,800	1.17	1,913,000	2.60	8,432,900	71.83

Figure 8.10 Gross input and output ratios for systems producing external kitchen door/frames during the lifetime of a house: door size: (762 mm x 1981 mm) - per door/frame



Door/frames	Gross energy	Carbon dioxide	Sulphur dioxide
Timber	1.82	2.46	1.00
PVC	2.21	2.32	1.66
Aluminium (painted)	1.00	1.00	1.90
Aluminium (anodised)	1.08	1.17	2.60

Figure 8.11 Gross input and output ratios for systems producing external kitchen door/frames during the lifetime of a house: door size (762 mm x 1981 mm) - per door/frame



Door/frames	Suspended solids
Timber	1.00
PVC	79.38
Aluminium (painted)	60.98
Aluminium (anodised)	71.83

The noticeable feature of these results is that unlike the earlier results illustrated in Figures 8.4 - 8.7, no one system displays an outright overall advantage. Although the performance of the systems producing aluminium frames and doors are superior when measured in terms of gross energy inputs and carbon dioxide emissions, the systems producing softwood frames and doors retain an advantage when judged in terms of sulphur dioxide and suspended solid emissions. It is interesting to observe that the systems producing PVC frames and doors are consistently outperformed by the other two.

The preceding discussion relates to the use of softwood. If hardwood, with a longer life expectation, was substituted the conclusions would be different. Similarly, if a full life-cycle analysis was applied to these systems different conclusions may be reached. For example, unlike timber, both PVC and aluminium may be re-cycled. Moreover, timber products require regular and frequent maintenance throughout their lifetime, making use of chemical preservatives, paints and varnishes.

8.4 Underground sewer pipes and gullies: *vitrified clay, PVC*

Vitrified clay and PVC compete with each other as alternative materials used to manufacture underground sewerage systems. According to previous studies by Boustead & Hancock,^{32, 36} systems producing vitrified clay pipes outperform equivalent PVC systems. Although these studies focus exclusively on gross energy requirements, they provide a starting point for comparisons in the present study. However, unlike the preceding studies, this analysis is not an exhaustive study of all the variously sized pipes, junctions and bends used to construct complete sewerage systems. Instead, it is restricted to two items commonly used in house construction:


- a) 100 mm (int. diameter) pipes per metre run *(based on data for 1.6 m clay pipes and 4 m PVC pipes)*
- b) yard (bottle) gullies - (195 mm x 335 mm)

The gross input and output ratios for the systems producing the above pipes and gullies are derived from Appendices 24, 25, 77, and 78. These ratios are given in Tables 8.7 and 8.8 respectively and represented graphically in Figures 8.12 and 8.13.

Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Vitrified clay	82.64	1.00	4,261,700	1.00	18,809	1.00	3,614	1.00
PVC	140.43	1.70	4,984,600	1.17	48,886	2.60	23,994	6.64


Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Vitrified clay	137.83	1.36	13,615,900	3.97	61,135	1.86	3,280	1.00
PVC	101.13	1.00	3,434,000	1.00	32,842	1.00	13,314	4.06

Figure 8.12 Gross input and output ratios for systems producing 100 mm (internal diameter) sewer pipes - per metre run



Sewer pipes	Gross energy	Carbon dioxide	Sulphur dioxide	Suspended solids
Vitrified clay	1.00	1.00	1.00	1.00
PVC	1.70	1.17	2.60	6.64

Figure 8.13 Gross input and output ratios for systems producing yard gullies - per gully



Yard gullies	Gross energy	Carbon dioxide	Sulphur dioxide	Suspended solids
Vitrified clay	1.36	3.97	1.86	1.00
PVC	1.00	1.00	1.00	4.06

When judged in terms of gross energy requirements, the results of this exercise confirm Boustead & Hancock's earlier work and the pre-eminence of clay pipes over PVC equivalents; see Table 8.9. Moreover, this supremacy is repeated across the remaining gross inputs and outputs to endorse the overall superiority of the system producing clay pipes.

Material	Present work		Boustead & Hancock³²		Boustead & Hancock³⁶	
	Gross energy MJ	Ratio	Gross energy MJ	Ratio	Gross energy MJ	Ratio
Vitrified clay	82.64	1.00	98.49	1.00	78	1.00
PVC	140.43	1.70	152.00	1.54	175	2.24

However, the advantageous position of clay is challenged when the systems producing yard gullies are examined. From Figure 8.13 it is evident that when measured in terms of gross energy inputs and emissions of carbon dioxide and sulphur dioxide, the system producing vitrified clay yard gullies is inferior to that producing PVC yard gullies but superior when judged in terms of suspended solids emissions. The observed reversal for gross energy inputs and air emissions, places clay gulley systems in a disadvantaged position compared to PVC systems. This reversal may possibly be attributed to the following factors:

- a) low stacking efficiencies during the firing and drying of clay gullies
- b) the use of a less efficient intermittent kiln (c.f. the use of a continuous kiln for pipes).

More convincing conclusions may be drawn, however, by measuring the gross inputs and outputs of replacement pipes and gullies during the 70 year expected lifetime of a modern house. Taking the manufacturers guaranteed lifetimes of clay and PVC pipes and gullies as 100 years and 50 years respectively, revised gross inputs and output ratios may be

calculated. The results are shown in Tables 8.10 and 8.11 and graphically illustrated in Figures 8.14 and 8.15.


Table 8.10 Selected gross inputs and outputs for systems producing 100 mm (internal diameter) underground sewer pipes during the lifetime of a house - per metre run

Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Vitrified clay	82.64	1.00	4,261,700	1.00	18,809	1.00	3,614	1.00
PVC	280.86	3.40	9,969,200	2.34	97,772	5.20	47,988	13.28

Table 8.11 Selected gross inputs and outputs for systems producing yard gullies during the lifetime of a house - per gully


Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Vitrified clay	137.83	1.00	13,615,900	1.98	61,135	1.00	3,280	1.00
PVC	202.26	1.47	6,868,000	1.00	65,684	1.07	26,628	8.12

Figure 8.14 Gross input and output ratios for systems producing 100 mm (internal diameter) sewer pipes during the lifetime of a house - per metre run



Sewer pipes	Gross energy	Carbon dioxide	Sulphur dioxide	Suspended solids
Vitrified clay	1.00	1.00	1.00	1.00
PVC	3.40	2.34	5.20	13.28

Figure 8.15 Gross input and output ratios for systems producing yard gullies during the lifetime of a house - per gulley



Yard gullies	Gross energy	Carbon dioxide	Sulphur dioxide	Suspended solids
Vitrified clay	1.00	1.98	1.00	1.00
PVC	1.47	1.00	1.07	8.12

By comparing Figures 8.12 and 8.14 it is clear that when judged over the expected lifetime of a house, the existing advantage of the system producing vitrified clay pipes is enhanced at the expense of the equivalent PVC system. Similar comparisons between Figures 8.13 and 8.15 show that the system producing vitrified clay yard gullies appears more favourably and with the exception of carbon dioxide emissions outperforms the equivalent PVC system.

Before any firm conclusions are made, however, it should be borne in mind that the above analysis is not a complete life-cycle analysis and does not take account of the possibility that PVC may be re-cycled, nor of the variety of acceptable installation procedures. For example, current practice allows for sewer pipes to be laid on a bed of sand or gravel or encased in concrete. Including additional materials will undoubtedly affect the final overall conclusions.

8.5 Roof drainage materials (*drainpipes & gutters*): aluminium, PVC

Aluminium and PVC are commonly used as alternative materials for the manufacture of drainpipes and gutters. The present work is the first attempt at describing the performance of systems producing these items. The variation in the size and design of drainpipes and gutters make it expedient to focus on one size and design in common use when making comparisons. To complete this exercise the following items will be considered:


- a) a 68 mm (external diameter) drainpipe - per metre run,
(based on data for 1.83 m aluminium and 4 m PVC lengths)
- b) a 100 mm half round gutter - per metre run
(based on data for 1.83 m aluminium and 4 m PVC lengths)

The gross input and output ratios for the systems producing the above drainpipes and gutters are derived from Appendices 66, 67, 75, and 76. These ratios are given in Tables 8.12 and 8.13 respectively, and represented graphically in Figures 8.16 - 8.17.

Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Aluminium	157.39	3.29	4,852,700	2.83	49,338	2.92	354,525	33.42
PVC	47.88	1.00	1,712,100	1.00	16,888	1.00	10,609	1.00


Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Aluminium	192.00	4.47	5,543,200	3.61	52,022	3.43	458,849	48.17
PVC	43.00	1.00	1,537,400	1.00	15,165	1.00	9,526	1.00

Figure 8.16 Gross input and output ratios for systems producing 68 mm (external diameter) drainpipes - per metre run



Drainpipes	Gross energy	Carbon dioxide	Sulphur dioxide	Suspended solids
Aluminium	3.29	2.83	2.92	33.42
PVC	1.00	1.00	1.00	1.00

Figure 8.17 Gross input and output ratios for systems producing 100 mm half round gutters - per metre run



Gutters	Gross energy	Carbon dioxide	Sulphur dioxide	Suspended solids
Aluminium	4.47	3.61	3.43	48.17
PVC	1.00	1.00	1.00	1.00

Again, using the gross input and output totals as performance indicators, it is evident from Figures 8.16 and 8.17 that systems using PVC constantly outperform equivalent aluminium systems. The consistent agreement across the full range of gross input and output ratios,


for both drainpipe and gutter production, confers a significant advantage to systems using PVC.

More accurate conclusions may be reached, however, by studying revised gross input and output ratios calculated to include the replacement drainpipes and gullies required during the expected lifetime of a house (70 years). Taking the expected lifetime of PVC drainpipes and gutters as 35 years, and assuming that aluminium systems last the lifetime of the house, it is clear that two PVC systems are needed for every one aluminium. The revised gross input and output ratios are shown in Tables 8.14 and 8.15 and graphically illustrated in Figures 8.18 and 8.19.

Table 8.14 Selected gross inputs and outputs for systems producing 68 mm (external diameter) drainpipes during the lifetime of a house - per metre run								
Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Aluminium	157.39	1.64	4,852,700	1.42	49,338	1.46	354,525	16.71
PVC	95.76	1.00	3,424,200	1.00	33,776	1.00	21,218	1.00


Table 8.15 Selected gross inputs and outputs for systems producing 100 mm half round gutters during the lifetime of a house - per metre run								
Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Aluminium	192.00	2.23	5,543,200	1.80	52,022	1.72	458,849	24.08
PVC	86.00	1.00	3,074,800	1.00	30,330	1.00	19,052	1.00

Figure 8.18 Gross input and output ratios for systems producing 68 mm (external diameter) drainpipes during the lifetime of a house - per metre run



Drainpipes	Gross energy	Carbon dioxide	Sulphur dioxide	Suspended solids
Aluminium	1.64	1.42	1.46	16.71
PVC	1.00	1.00	1.00	1.00

Figure 8.19 Gross input and output ratios for systems producing 100 mm half round gutters during the lifetime of a house- per metre run



Gutters	Gross energy	Carbon dioxide	Sulphur dioxide	Suspended solids
Aluminium	2.23	1.80	1.72	24.08
PVC	1.00	1.00	1.00	1.00

Comparing Figures 8.16 and 8.17 with Figures 8.18 and 8.19 it is evident that the systems producing PVC drainpipes and gutters maintain their marked superiority over equivalent aluminium systems when judged over the lifetime of a house, albeit with a reduced advantage.

8.6 Lintels - single and combined: *reinforced concrete, timber and steel*

Reinforced concrete, timber and steel are frequently used as alternative materials for lintel construction. Earlier work by Kreijger²² focused attention on the gross energy requirements of beams as a function of span. Since then, no published interest has been shown in extending this work into a full eco-profile describing the performance of lintel production systems. The present study is the first attempt to do so, but unlike Kreijger's work, compares systems producing built-in lintels carrying uniformly distributed loads for one span length only. The three lintel types to be considered are described below:


Single lintels: width x height: (100 mm x 143 mm) and (125 mm x 143 mm)

- a) homogenous rectangular sections manufactured from timber and reinforced concrete:
- b) I-section rolled steel joist: flange and web thickness 7 mm

The dimensions correspond to the width of typical bricks or concrete blocks, and the height of two courses of brick.

Combined lintels: manufactured from galvanised steel, dimensions as in Figure 8.20.


A combined lintel consists of two or more structural elements joined together and acting as one. Figure 8.20 illustrates the lintel under consideration.



For a combined lintel of the given dimensions, the safe working load at a maximum design span of 1.35 m is taken as 17,150 N (manufacturer's specification).

Single lintel systems equivalent to combined lintels: dimensions as shown in Figure 8.21.

Two single lintels produced from reinforced concrete, timber or steel may be positioned alongside each other in a cavity wall to form a single lintel pair. For the purpose of comparison they may be considered as serving the same function as the combined lintel shown in Figure 8.20 and treated as equivalent systems. The configurations to be compared are shown in Figure 8.21.



When comparing these single lintel pairs with the combined lintel, it is assumed that a safe working load of 17,150 N is distributed equally between the two lintels. For consistency, a safe working load of 8,575 N is assumed for single lintels throughout this work.


Using a design span of 1.35 m (lintel length 1.50 m) and the specified safe working loads, it may be shown that all three lintel types function safely below the maximum strength of the materials, and in particular, comply with British Standards safety limits.⁶⁸

The gross input and output ratios for the systems producing (100 mm x 143 mm) single lintels are derived from data in Appendices 36, 45 and 53. These ratios are given in Table 8.16 and represented graphically in Figures 8.22 and 8.23. The gross input and output ratios for the systems producing the combined lintel and equivalent single lintel pairs are derived from Appendices 38 and 57. These ratios are given in Table 8.17 and represented graphically in Figure 8.24.

Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Reinforced concrete	101.54	1.00	8,895,100	3.22	144,790	9.71	161,495	122.9
Timber	227.07	2.24	2,764,000	1.00	14,914	1.00	1,314	1.00
RSJ	890.75	8.77	35,654,000	12.9	3,090,600	207.23	4,618,600	3,514.92


Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Timber	385.38	1.71	12,350,100	1.00	163,432	1.00	163,138	1.00
Reinforced concrete	225.23	1.00	19,897,300	1.61	313,713	1.92	346,447	2.12
RSJ	1,127.72	5.01	4,997,100	4.05	3,705,300	22.67	5,482,300	33.61
Combined - Galvanised steel	550.28	2.44	23,455,500	1.90	1,571,400	9.62	2,289,100	14.03

Figure 8.22 Gross input and output ratios for systems producing (100 mm x 143 mm) single lintels - per 1.50 metre length




Lintels	Gross energy	Carbon dioxide
Reinforced concrete	1.00	3.22
Timber	2.24	1.00
RSJ	8.77	12.90

Figure 8.23 Gross input and output ratios for systems producing (100 mm x 143 mm) single lintels - per 1.50 metre length



Lintels	Sulphur dioxide	Suspended solids
Reinforced concrete	9.71	122.90
Timber	1.00	1.00
RSJ	207.23	3,514.92

Figure 8.24 Gross input and output ratios for systems producing single pair and combined lintels- per 1.50 metre length



With reference to Figures 8.22 and 8.23, it is clear that with the exception of gross energy inputs, the order of increasing performance for single lintel systems reads: *RSJs, reinforced concrete, timber*. However, the use of gross energy inputs as the sole performance indicator, adjusts the order to read *RSJs, timber, reinforced concrete*. Although the system producing RSJs is clearly outperformed, the results are inconclusive with the timber and reinforced concrete production systems both claiming competing advantages.

It is interesting to note that in Kreijger's study, the gross energy requirement for the production of timber lintels is less than that for reinforced concrete lintels. Using his results the order of increasing merit reads: *RSJs, reinforced concrete, timber*. These results differ from the present study. Unfortunately, there is insufficient information in Kreijger's paper to explain the reversed order for reinforced concrete and timber. One possible explanation

is that Kreijger may have failed to include timber feedstock energy in his calculations.

Making this omission in the present work produces similar conclusions.


Figure 8.24 demonstrates that the comparison between systems producing galvanised steel combined lintels and single lintel pair equivalents, reaches similar overall conclusions to those already reached for single lintel systems. Using gross energy inputs, the ascending order of performance (omitting the reinforced concrete outer leaf) reads: *RSJ, galvanised steel (combined), timber, reinforced concrete*. For the remaining gross inputs or outputs, the order becomes: *RSJ, galvanised steel (combined), reinforced concrete, timber*. Clearly these results are inconclusive with the timber and reinforced concrete systems once again claiming competing advantages.

Since the expected lifetimes of a house and the above lintel systems are similar, comparisons over the lifetime of a house will produce identical conclusions. It must be noted, however, that a complete life-cycle analysis might produce different conclusions. For example, RSJs and galvanised steel combined lintels may be re-cycled or used again.

8.7 Building blocks: *clay bricks, dense concrete blocks, aerated concrete blocks*

Clay bricks, dense concrete blocks and aerated concrete blocks may be used as alternatives in the construction of walls. The gross input and output ratios for the systems producing 1 square metre of single leaf wall from these materials are derived from Appendices 21, 32, and 34 respectively. These ratios are given in Table 8.18 and represented graphically in Figure 8.25.

Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Clay bricks	735.41	4.09	58,068,300	3.90	370,692	2.96	54,423	1.00
Aerated concrete blocks	344.38	1.92	35,546,100	2.39	331,128	2.65	143,598	2.64
Dense concrete blocks	179.70	1.00	14,883,200	1.00	125,042	1.00	93,074	1.71



Before the three systems are compared it is important to understand that not all comparisons are necessarily valid as the blocks are designed with different purposes in mind. Load bearing walls take advantage of the superior compressive strength of clay bricks and dense blocks. In contrast, walls carrying relatively low loads and designed as a thermal barrier, such as the inner leaf of a cavity wall, take advantage of the high thermal resistance of aerated blocks. Nonetheless, dense blocks are sometimes substituted for aerated blocks as the inner leaf of cavity walls carrying high loads. Thus, it is valid to consider comparisons between:

- a) dense blocks and clay bricks
- b) dense blocks and aerated blocks,

but not between clay bricks and aerated blocks.

Restricting comparisons to these two cases it may be concluded from Figure 8.25 that:


- a) ignoring suspended solid emissions, the system producing dense concrete blocks has an overall superior performance to the system producing clay bricks
- b) the performance of the system producing dense concrete blocks is superior to that of the system producing aerated concrete blocks. Nonetheless, with superior insulation properties, aerated blocks may claim additional advantages over a full life-cycle.

8.8 Insulation materials: *glass fibre wool, expanded polystyrene foam, polyurethane foam*

To comply with current Building Regulations one or more of the above insulation materials are normally incorporated into the design of a modern house. For a fair comparison these materials must be used for equivalent functions, such as the infill to a cavity wall. Consider the systems producing 1 square metre of the above insulants for a 50 mm cavity. The gross input and output ratios for these systems are derived from Appendices 43, 83 and 85.

These ratios are given in Table 8.19 and represented graphically in Figure 8.26.

Building material	Gross energy		Air emissions				Water emissions	
			Carbon dioxide		Sulphur dioxide		Suspended solids	
	MJ	Ratio	mg	Ratio	mg	Ratio	mg	Ratio
Polyurethane foam	164.81	4.13	7,423,900	3.68	60,405	5.22	62,189	19.06
Expanded polystyrene foam	84.76	2.12	2,673,700	1.33	114,587	9.91	3,262	1.00
Glass fibre wool	39.94	1.00	2,015,200	1.00	11,564	1.00	38,534	11.81



Inspection of these results reveals two noticeable features:

1. the relatively poor performance of the polyurethane foam production system
2. with the exception of suspended solid emissions, the overall superiority of the system producing glass fibre wool.

However, these conclusions are of limited value as they fail to consider the energy saving performance of the insulants during a complete life-cycle. This omission highlights an important difference between the present eco-profile and a full life-cycle analysis.

To illustrate this point further, consider the energy losses over the lifetime of a house, say seventy years, across 1 square metre of insulated and uninsulated 50 mm cavity wall. For the purpose of discussion the following assumptions are made:

- ♦ cavity wall profile: outer leaf - 20 mm cement render/100 mm dense concrete block
inner leaf - 140 mm aerated concrete block
- ♦ all energy losses occur during the six winter months
- ♦ the average winter temperature gradient across the wall is 13° C

Standard U-values are used in Table 8.20 to calculate energy losses with and without insulants. These values are then used to calculate the energy savings arising from the use of

Cavity infill	Thermal transmittance U-values ¹ W/m ² K	Energy losses over 70 years MJ	Energy saving using insulation		Production energy as % of energy saving
			MJ	%	
Air	0.86	12,340	-----	-----	-----
Polyurethane foam	0.34	4,879	7,461	60	2.21
Expanded polystyrene foam	0.43	6,170	6,170	50	1.37
Glass fibre wool	0.45	6,457	5,883	48	0.68

¹ Derived from Digest108: Standard U-values, Building Research Establishment, 1991
Note: Maximum allowed U-value = 0.45 W/m²K (1990 Building Regulations, Approved Document L, England & Wales)

the different insulants. The importance of the gross input and output figures in Table 8.19 gains perspective by comparing the gross production energies with these energy savings. From Table 8.20 it is evident that the gross production energies represent a very small proportion of the energy savings. Moreover, it is clear that any one of these insulants will satisfy Building Regulations and produce the desired energy savings. Thus, in the context of a complete life-cycle the notion of a superior production system loses meaning.

8.9 Effect of substituting alternative materials on house eco-profiles

Comparing the results in Sections 8.2 - 8.8 with the material inputs to house construction in Tables 6.2 and 6.3, it is evident that most of the materials offering significant reductions in gross inputs and outputs are already included. Nonetheless, advantages may be gained by the following substitutions:

- a) dense concrete blocks for clay bricks
- b) timber or reinforced concrete lintels for RSJs and galvanised steel combined lintels.

The sensitivity analysis in Section 7.3 supports the proposed substitution of dense concrete blocks for clay bricks. However, since RSJs and galvanised steel combined lintels make a relatively small contribution to the gross input and output totals, the proposed substitution in b) above will produce even smaller savings and will therefore not be made.

Although life-cycle analysis is not concerned with the competing aesthetic claims of different materials, it is normal building practice to use a cement render to enhance the

appearance of exterior walls constructed from concrete blocks. The proposed use of dense concrete blocks is therefore accompanied by additional mortar inputs.

Finally, although strictly not a substitution, to comply with current Building Regulations it is necessary to include cavity wall and ground floor insulation materials in the inventory of proposed amendments to Tables 6.2 and 6.3. These amendments are summarised in Tables 8.21 and 8.22 below.

Materials	Deletions	Additions	Mass kg
65 mm clay facing and common bricks	31,973 kg		-31,973
Dense concrete blocks (440x215x100) mm		213.2 m ³	41,361
20 mm Ready mixed cement:lime:sand mortar		4,284 kg	4,284
50 mm Expanded polystyrene foam cavity wall and ground floor insulation.		186 m ²	140
		Total	13,812
		Less 5 % waste on bulk items	-651
		Net change	13,161

Materials	Deletions	Additions	Mass kg
65 mm clay facing and common bricks	40,163 kg		-40,163
Dense concrete blocks (440x215x100) mm		267.8 m ³	51,953
20 mm Ready mixed cement:lime:sand mortar		6,930 kg	6,930
50 mm Expanded polystyrene foam cavity wall and ground floor insulation.		178 m ²	134
		Total	18,854
		Less 5 % waste on bulk items	-891
		Net change	17,963

The effect of these amendments on the gross inputs and outputs associated with the construction of the bungalow house and the two storey detached house are detailed in Appendices 90 to 92. A selection of the amended gross inputs and outputs are shown in Table 8.23.

Input/Output	per building			per m ² floor space		
	Bungalow	House	% change	Bungalow	House	% change
Gross inputs						
Energy (GJ)	454.30	536.58	18.08	5.22	4.39	-15.90
<u>Raw materials (g)</u>						
Sand	53,988,900	56,267,000	4.22	620,561	460,074	-25.86
Limestone	138,561,200	145,785,800	5.21	1,592,600	1,192,000	-25.15
Clay	646,225	600,944	-7.01	7,428	4,914	-33.84
Gross outputs (g)						
<u>Air emissions</u>						
Carbon dioxide	31,692,800	39,757,400	25.45	364,281	325,081	-10.76
Sulphur dioxide	285,834	365,746	27.96	3,284	2,991	-8.92
<u>Water emissions</u>						
Suspended solids	621,073	942,345	51.73	7,139	7,705	7.93

In the comparison between the bungalow house and the detached house, these results follow a similar pattern as the original data set in Table 7.1. However, considerable changes to the original gross inputs and outputs per building are noted as shown in Table 8.24.

Input/Output	Bungalow	House
Gross inputs		
Energy (GJ)	-17.80	-19.01
<u>Raw materials (g)</u>		
Sand	7.55	12.00
Limestone	38.62	50.29
Clay	-98.82	-99.13
Gross outputs (g)		
Carbon dioxide	-20.20	-20.07
Sulphur dioxide	-8.47	-9.34
Suspended solids	1.85	-1.60

The marked reduction in gross energy inputs and air emissions is attributed to the relatively low fuel consumption in the production of dense concrete blocks compared to clay brick manufacture. The pronounced reduction in gross clay inputs, paralleled by a corresponding increase in the gross inputs of sand and limestone, is attributed to the substitution of clay

bricks by dense concrete blocks. On balance it may be concluded that the environmental burdens of building construction are significantly reduced by the substitution of dense concrete blocks for clay bricks.

Chapter 9

CONCLUSIONS

9.1 Overview

Primary data from commercial sources have been used in this study to produce eco-profiles containing the latest available information for both new and traditional building materials . In addition, the gross inputs and outputs associated with the production of different materials have been assembled to create detailed eco-profiles for the construction of a three bedroom bungalow house and a four bedroom detached house. Finally, eco-profiles for alternative building materials have been compared and the effect of their substitution on the eco-profiles of house construction considered. The results of this work are recorded in the Appendices and have been discussed in earlier chapters. Nonetheless, attention is drawn to the following major conclusions.

9.2 Eco-profiles of house construction

- ♦ With the exception of emissions of suspended solids, the gross inputs and outputs per square metre of floor space for detached house construction, are significantly less than those for bungalow construction; see Table 7.1.
- ♦ The gross energies for both detached house and bungalow construction fall in the range of published values detailed in Table 7.2. However, it is difficult to make strict comparisons as many of the earlier values relate to other countries, different types of building, or use outdated primary data and fuel production efficiencies.
- ♦ The dominant material inputs to house construction have been identified in Tables 6.2 and 6.3 as belonging to the *minerals, structural clay products, concrete and mortar products*, and *timber* categories, and collectively account for 94 % of the total.

Table 9.1 presents a comparison between these material inputs and the corresponding gross energy inputs in Tables 7.3 and 7.4.

Material inputs	Mass inputs %		Gross energy %	
	Bungalow	Detached house	Bungalow	Detached house
Minerals	23.30	19.45	1.23	0.92
Structural clay products	16.30	18.80	28.99	30.17
Concrete and mortar products	52.50	53.55	27.19	29.59
Timber products	2.13	2.25	19.73	19.44
Total	94.23	94.05	77.14	80.12

It is interesting to note that *structural clay products* and *concrete and mortar products* make approximately similar contributions to the gross energy inputs. In contrast, the total mass inputs attributed to *concrete and mortar products* are approximately three times those of *structural clay products*. These comparisons infer an intrinsic advantage is to be gained by the use of concrete products and confirm earlier results. Despite a significant mass input, *minerals* such as limestone and sand make a minor contribution to the gross energy inputs. For *timber* products the position is reversed; small mass inputs giving rise to significant gross energy inputs, most of which is attributed to wood feedstock energy.

9.3 Eco-profiles of alternative building materials

Alternative building materials have been compared over the expected lifetime of a modern house (70 years). The results of these comparisons, as discussed in Sections 8.2 - 8.8, are summarised in Table 9.2.

Table 9.2 Comparison of alternative building products during the 70 year expected lifetime of a modern house - a summary		
Product	Alternative materials	Materials offering significant reductions in gross inputs and outputs
Roof tiles	Clay, concrete	Concrete
Window frames/doors	Timber (softwood), PVC, aluminium	Inconclusive - softwood or aluminium
Underground drainage: - sewer pipes - yard gullies	Clay, PVC Clay, PVC	Clay Clay
Roof drainage: - drainpipes - gutters	PVC, aluminium PVC, aluminium	PVC PVC
Lintels: - single - combined	RSJ, timber, reinforced concrete RSJ, timber, reinforced concrete, galvanised steel	Timber or reinforced concrete Timber or reinforced concrete
Building blocks	Dense concrete blocks, clay bricks Dense concrete blocks, aerated concrete blocks	Dense concrete block Dense concrete blocks
Insulation materials	Polyurethane foam, expanded polystyrene foam, glass fibre wool	Inconclusive

From these results the following conclusions may be drawn.

- ♦ The use of clay as a building material has considerable disadvantages. As a traditional material for the production of roof tiles and bricks it is challenged by alternative concrete products. Nonetheless, it is the preferred product for underground drainage systems.
- ♦ Wood and aluminium are the preferred materials for window frame construction despite competition from 'easy care' alternatives such as PVC.

- ♦ PVC roof drainage systems offer considerable advantages over aluminium alternatives.
- ♦ Wood or reinforced concrete are the preferred products for lintel construction.
- ♦ Comparisons between insulation materials are inconclusive although expanded polystyrene foam and glass fibre wool are preferred to polyurethane foam. However, when considered over a complete life-cycle, the results are meaningless since any one of the three insulants will produce considerable energy savings far in excess of the initial energy consumed in their production.

9.4 Effect of alternative building materials on house eco-profiles

From the discussion in Chapter 8.9 it is clear that for the two types of house considered, many of the superior building products have already been incorporated into the builder's schedules, thereby reducing the scope for variation. Nonetheless, it is evident from Table 8.24 that significant reductions in the gross inputs and outputs to house construction may be made by substituting dense concrete blocks for clay bricks.

9.5 Recommendations for further work

Although this study has considered in great detail the inventory flows across extended industrial systems producing building materials, it is of necessity a 'snapshot' description of a constantly changing scene. Any conclusions will be sensitive to improvements in the design of industrial processes and fuel production efficiencies. Moreover, most of the primary data have been obtained from single sources and are not necessarily representative of the industry. Furthermore, this investigation has been directed towards an eco-profile of building materials, rather than a life-cycle analysis, and restricted to a comparison between

two building types. These limitations both define the boundaries of the initial project and indicate areas of opportunity for further work. Some possible suggestions for extended study include the following.

- ◆ To study the effect of using updated fuel production efficiencies on the final conclusions.
- ◆ By considering the gross inputs and outputs over a complete life-cycle, to develop the study into a full life-cycle analysis.
- ◆ To extend the database by including additional sources of primary data and to calculate industry average inputs and outputs.
- ◆ To consider other types of building. For example, multi-storey blocks and terrace houses.
- ◆ To consider other building materials and alternative structural designs. For example, the use of traditional stone and timber facade houses.
- ◆ In anticipation of possible regulatory limits to air emissions from transport operations, to disaggregate the gross air emissions and calculate the separate contributions arising from *process* and *transport* operations.

APPENDICES

Introduction

The following Appendices include data sets describing the gross inputs and outputs associated with:

- ♦ the production, delivery and use of fuels
- ♦ road, rail and waterborne transport operations
- ♦ the production and delivery of the different materials used in modern house construction
- ♦ the construction of a three bedroom bungalow house and a four bedroom detached house

The data are presented under the seven main headings, *Energy, Fuels, Feedstocks, Raw materials, Air emissions, Water emissions, and Solid waste production*, as described in Section 2.8. Flow diagrams, where used, refer to the accompanying data set.

Notes

1. Raw material inputs of *air* and *nitrogen* refer to *compressed air* and *separated nitrogen*.
2. The environmental burdens associated with the use of sawdust and chippings as a fuel in Appendix 47 are included in the accompanying data set.
3. The flow charts and data sets for the production and delivery of kiln dried sawn timber, Appendices 44 and 46, are based on the following approximate water content for green timber: ⁶⁹

Sitka spruce 25 %

Redwood 50 %

The water content of kiln dried timber in both cases is 5 %.

Appendix 1

Fuels

Gross inputs and outputs associated with the production, delivery and use of fuels/MJ
 Totals may not agree because of rounding errors

Input/output	Units	Fuel					
		Coal	Coke	Natural gas	Man' gas	Heavy fuel oil	Medium fuel oil
Energy							
Electricity - production & delivery	MJ	—	—	—	—	—	—
Electricity - delivered	MJ	—	—	—	—	—	—
Oil fuels - production & delivery	MJ	—	—	—	—	0.14	0.14
Oil fuels - delivered	MJ	—	—	—	—	1.00	1.00
Oil fuels - feedstock	MJ	—	—	—	—	—	—
Other fuels - production & delivery	MJ	0.04	0.20	0.11	0.21	—	—
Other fuels - delivered	MJ	1.00	1.00	1.00	1.00	—	—
Other fuels - feedstock	MJ	—	—	—	—	—	—
Total energy	MJ	1.04	1.20	1.11	1.21	1.14	1.14
Fuels							
Coal	MJ	1.02	1.10	—	1.11	—	—
Oil	MJ	0.01	0.02	—	0.01	1.09	1.09
Gas	MJ	—	0.07	1.11	0.07	0.05	0.05
Hydro	MJ	—	—	—	—	—	—
Nuclear	MJ	—	0.01	—	0.01	—	—
Lignite	MJ	—	—	—	—	—	—
Total fuels	MJ	1.03	1.20	1.11	1.21	1.14	1.14
Feedstock							
Coal	MJ	—	—	—	—	—	—
Oil	MJ	—	—	—	—	—	—
Total feedstock	MJ	—	—	—	—	—	—
Total fuels & feedstock	MJ	1.04	1.20	1.11	1.21	1.14	1.14
Raw materials							
Bauxite	mg	—	—	—	—	—	—
Brine	mg	—	—	—	—	—	—
Fe-Mn	mg	—	—	—	—	—	—
Iron ore	mg	90	117	—	98	16	16
Limestone	mg	32	41	—	34	6	6
Met coal	mg	37	48	—	40	7	7
Water	mg	82,836	690,116	136	699,800	39,080	39,080
Air emissions							
Dust	mg	478	529	80	208	14	17
CO	mg	68	79	—	12	20	20
CO2	mg	81,265	140,258	52,487	63,115	81,253	80,598
SOx	mg	1,027	1,683	14	1,222	1,451	1,297
NOx	mg	305	424	749	855	382	382
HCl	mg	20	21	—	1	—	—
HF	mg	1	1	—	—	—	—
HC	mg	18	63	474	1	149	149
Metals	mg	—	—	—	—	1	1
CH4	mg	258	362	148,670	367	3	3
Water emissions							
COD	mg	—	5	—	5	1	1
BOD	mg	—	—	—	—	1	1
Acid	mg	—	5	—	5	—	—
Metal ions	mg	—	1	—	1	—	—
Dissolved solids	mg	—	—	—	—	—	—
Suspended solids	mg	32	37	—	35	2	2
Hydrocarbons	mg	—	—	—	10	1	1
Phenol	mg	—	—	—	—	1	1
Solid waste							
Mineral waste	mg	7,132	7,725	7	7,808	51	51
Slags\ash	mg	2,037	23,088	2	3,131	9	9
Industrial waste	mg	1	2	—	2	119	119

Appendix 2

Fuels

Gross inputs and outputs associated with the production, delivery and use of fuels/MJ

Totals may not agree because of rounding errors

Input/output	Units	Fuel					
		Light fuel oil	Gas oil	Kerosine	Diesel	Gasoline	Propane
Energy							
Oil fuels - production & delivery	MJ	0.14	0.14	0.14	0.14	0.14	0.15
Oil fuels - delivered	MJ	1.00	1.00	1.00	1.00	1.00	1.00
Total energy	MJ	1.14	1.14	1.14	1.14	1.14	1.15
Fuels							
Oil	MJ	1.09	1.09	1.09	1.09	1.09	1.09
Gas	MJ	0.05	0.05	0.05	0.05	0.05	0.05
Total fuels	MJ	1.14	1.14	1.14	1.14	1.14	1.15
Feedstock							
Total fuels & feedstock	MJ	1.14	1.14	1.14	1.14	1.14	1.15
Raw materials							
Iron ore	mg	16	16	16	16	16	16
Limestone	mg	6	6	6	6	6	6
Met coal	mg	7	7	7	7	7	7
Water	mg	39,080	39,080	39,080	39,080	39,080	39,157
Air emissions							
Dust	mg	14	7	7	67	67	13
CO	mg	20	20	20	703	703	703
CO2	mg	81,119	76,935	76,935	78,080	66,876	68,354
SOx	mg	1,209	390	100	227	227	47
NOx	mg	382	382	382	889	889	889
HC	mg	149	149	149	279	279	319
Lead	mg	—	—	—	—	4	—
Metals	mg	1	—	—	—	—	—
CH4	mg	3	3	3	3	3	3
Water emissions							
COD	mg	1	1	1	1	1	1
BOD	mg	1	1	1	1	1	1
Suspended solids	mg	2	2	2	2	2	2
Hydrocarbons	mg	1	1	1	1	1	1
Phenol	mg	1	1	1	1	1	1
Solid waste							
Mineral waste	mg	51	51	51	51	51	51
Slag\ash	mg	9	9	9	9	9	9
Industrial waste	mg	119	119	119	119	119	119

Appendix 3

Fuels

Gross inputs and outputs associated with the production, delivery and use of fuels/MJ

Totals may not agree because of rounding errors

Input/output	Units	Fuel			
		Butane	Lubricating oil	Grease	Grid electricity
Energy					
Electricity - production & delivery	MJ	—	—	—	2.36
Electricity - delivered	MJ	—	—	—	1.00
Oil fuels - production & delivery	MJ	0.15	0.14	0.14	—
Oil fuels - delivered	MJ	1.00	1.00	1.00	—
Total energy	MJ	1.15	1.14	1.14	3.36
Fuels					
Coal	MJ	—	—	—	2.10
Oil	MJ	1.09	1.09	1.09	0.33
Gas	MJ	0.05	0.05	0.05	0.07
Hydro	MJ	—	—	—	0.04
Nuclear	MJ	—	—	—	0.82
Total fuels	MJ	1.15	1.14	1.14	3.36
Feedstock	MJ	0.00	0.00	0.00	0.00
Total fuels & feedstock	MJ	1.15	1.14	1.14	3.36
Raw materials					
Iron ore	mg	16	16	16	157
Limestone	mg	6	6	6	62
Met coal	mg	7	7	7	65
Water	mg	39,155	39,078	39,078	197,506
Air	mg	—	—	—	9
Air emissions					
Dust	mg	13	7	7	983
CO	mg	703	3	3	140
CO ₂	mg	69,828	8,246	8,246	192,684
SO _x	mg	47	47	47	2,543
NO _x	mg	889	49	49	784
HCl	mg	—	—	—	41
HF	mg	—	—	—	2
HC	mg	319	249	149	135
CH ₄	mg	3	2	2	601
Water emissions					
COD	mg	1	1	1	—
BOD	mg	1	1	1	—
Acid	mg	—	—	—	5
Metal ions	mg	—	—	—	2
Suspended solids	mg	2	2	2	62
Hydrocarbons	mg	1	21	21	1
Phenol	mg	1	1	1	—
Solid waste					
Mineral waste	mg	51	51	51	14,677
Slags\ash	mg	9	9	9	4,464
Industrial waste	mg	119	119	119	37,069

Appendix 4

Transport

Gross inputs and outputs associated with road transport/vehicle km

Input/output	Units	Vehicle type/payload				
		Rigid 10 - 12 t	Rigid 13 -21 t	Rigid 17.5 t concrete mixer	Rigid 21 t tipper	Articulated 18 - 24 t
Totals may not agree because of rounding errors						
Energy						
Electricity - production & delivery	MJ	0.32	0.51	0.47	0.68	0.51
Electricity - delivered	MJ	0.14	0.22	0.20	0.29	0.22
Oil fuels - production & delivery	MJ	1.33	1.65	2.88	2.03	2.13
Oil fuels - delivered	MJ	9.02	11.00	19.59	13.63	14.40
Oil fuels - feedstock	MJ	0.18	0.42	0.37	0.50	0.39
Other fuels - production & delivery	MJ	0.05	0.06	0.06	0.08	0.06
Other fuels - delivered	MJ	0.33	0.44	0.42	0.50	0.43
Other fuels - feedstock	MJ	0.34	0.49	0.48	0.81	0.55
Total energy	MJ	11.70	14.77	24.46	18.53	18.70
Fuels						
Coal	MJ	0.56	0.74	0.76	1.19	0.84
Oil	MJ	9.79	11.86	21.23	14.71	15.58
Gas	MJ	0.74	0.85	1.28	1.03	1.03
Hydro	MJ	0.01	0.01	0.01	0.01	0.01
Nuclear	MJ	0.09	0.11	0.12	0.16	0.12
Total fuels	MJ	11.17	13.57	23.40	17.10	17.58
Feedstock						
Coal	MJ	0.33	0.46	0.45	0.78	0.52
Total feedstock	MJ	0.33	0.46	0.45	0.78	0.52
Total fuels & feedstock	MJ	11.51	14.03	23.86	17.88	18.11
Raw materials						
Barytes	mg	7	7	7	7	7
Bauxite	mg	148	205	202	347	233
Brine	mg	79	86	86	104	90
Fe-Mn	mg	84	116	115	197	132
Fluorspar	mg	3	4	4	6	4
Iron ore	mg	25,646	35,467	349,934	60,053	40,376
Lead	mg	73	74	74	74	74
Limestone	mg	9,071	12,544	12,377	21,239	14,280
Met coal	mg	10,549	14,589	14,394	24,703	16,609
Water	mg	716,490	926,263	1,254,100	1,367,600	1,126,700
Air	mg	1,672	2,242	2,214	3,668	2,526
Sulphur	mg	110	148	146	241	166
Air emissions						
Dust	mg	804	990	1,566	1,314	1,249
CO	mg	6,289	7,628	13,681	9,465	10,028
CO2	mg	736,100	892,751	1,564,300	1,116,400	1,163,100
SOx	mg	4,296	5,566	7,464	8,261	6,755
NOx	mg	8,290	10,044	17,692	12,517	13,108
HCl	mg	4	6	6	8	6
F	mg	1	1	1	2	1
HC	mg	2,652	3,200	5,598	3,970	4,160
CH4	mg	541	614	631	791	656
Water emissions						
COD	mg	10	12	22	15	16
BOD	mg	9	11	20	14	14
Acid	mg	5	7	7	12	8
Metal ions	mg	1	2	2	3	2
Suspended solids	mg	3,307	4,572	4,512	7,740	5,205
Hydrocarbons	mg	10	12	20	14	15
Phenol	mg	9	11	20	14	14
Solid waste						
Plastics	mg	7	7	7	7	7
Organics	mg	4	4	4	4	4
Mineral waste	mg	38,811	53,453	52,980	90,052	60,834
Slag/ash	mg	2,150	2,905	2,940	4,780	3,303
Industrial waste	mg	1,070	1,297	2,321	1,609	1,703

Appendix 5
Transport
Gross inputs and outputs associated with waterborne transport/tonne km

Input/output	Units	Craft type/deadweight tonnage				
		Oil tanker 65,000 t 13 knots	Oil tanker 100,000 t 13 knots	Oil tanker 250,000 t 13 knots	'Average' bulk carrier 100,000 t 18.5 knots	Coal barge (inland canal) 500 t
Totals may not agree because of rounding errors						
Energy						
Oil fuels - production & delivery	MJ	0.01	—	—	0.01	0.05
Oil fuels - delivered	MJ	0.04	0.03	0.02	0.05	0.31
Total energy	MJ	0.05	0.03	0.02	0.06	0.37
Fuels						
Coal	MJ	—	—	—	—	0.01
Oil	MJ	0.04	0.03	0.02	0.06	0.34
Gas	MJ	—	—	—	—	0.02
Total fuels	MJ	0.05	0.03	0.02	0.06	0.37
Feedstock						
Coal	MJ	—	—	—	—	0.01
Total feedstock	MJ	—	—	—	—	0.01
Total fuels & feedstock	MJ	0.05	0.04	0.02	0.06	0.38
Raw materials						
Bauxite	mg	—	—	—	—	4
Fe-Mn	mg	—	—	—	—	2
Iron ore	mg	66	56	42	40	655
Limestone	mg	23	20	15	14	232
Met coal	mg	27	23	17	16	270
Water	mg	2,439	1,917	1,304	2,681	21,289
Air	mg	4	3	2	2	38
Sulphur	mg	—	—	—	—	3
Air emissions						
Dust	mg	1	1	1	1	25
CO	mg	1	1	—	1	221
CO2	mg	3,241	2,437	1,542	4,488	25,100
SOx	mg	62	47	30	83	127
NOx	mg	15	12	7	21	284
HC	mg	6	4	3	8	89
CH4	mg	1	—	—	—	5
Water emissions						
Suspended solids	mg	9	7	5	5	84
Solid waste						
Mineral waste	mg	99	84	63	61	982
Slags\ash	mg	5	4	3	3	52
Industrial waste	mg	5	4	2	7	37


Appendix 6

Transport

Gross inputs and outputs associated with rail freight transport/tonne km

Input/output	Units	Rail type	
		Network average - diesel & electric	Circuit working diesel
Totals may not agree because of rounding errors			
Energy			
Electricity - production & delivery	MJ	0.11	0.04
Electricity - delivered	MJ	0.05	0.02
Oil fuels - production & delivery	MJ	0.06	0.02
Oil fuels - delivered	MJ	0.43	0.15
Other fuels - delivered	MJ	0.02	0.01
Other fuels - feedstock	MJ	0.01	—
Total energy	MJ	0.68	0.24
Fuels			
Coal	MJ	0.11	0.04
Oil	MJ	0.48	0.17
Gas	MJ	0.04	0.02
Nuclear	MJ	0.04	0.01
Total fuels	MJ	0.68	0.24
Feedstock			
Coal	MJ	0.01	—
Total feedstock	MJ	0.01	
Total fuels & feedstock	MJ	0.69	0.25
Raw materials			
Bauxite	mg	6	1
CaSO4	mg	19	4
Fe-Mn	mg	3	—
Iron ore	mg	1,016	254
Limestone	mg	5,179	1,166
Met coal	mg	418	105
Sand	mg	620	139
Water	mg	42,571	13,097
Shale	mg	53	12
Air	mg	54	15
Sulphur	mg	4	—
Air emissions			
Dust	mg	56	19
CO	mg	17	6
CO2	mg	43,498	15,578
SOx	mg	369	121
NOx	mg	217	81
HCl	mg	2	1
HC	mg	79	31
CH4	mg	56	29
Water emissions			
COD	mg	1	—
Suspended solids	mg	135	34
Solid waste			
Mineral waste	mg	2,250	617
Slags\ash	mg	276	86
Industrial waste	mg	597	140

Production and bulk road delivery of building sand



Gross inputs and outputs associated with the production and bulk road delivery of building sand/kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.05
Electricity - delivered	0.02
Oil fuels - production & delivery	0.01
Oil fuels - delivered	0.04
Total energy	0.11

Primary fuels	MJ
Coal	0.04
Oil	0.05
Nuclear	0.02
Total fuels	0.11
Primary feedstocks	MJ
Total feedstocks	0.00
Total fuels & feedstocks	0.11

Raw materials	mg
Iron ore	76
Limestone	27
Met coal	31
Sand	1,000,000
Water	4,006,300
Air	5


Water emissions	mg
Suspended solids	11

Solid waste	mg
Mineral waste	122,622
Slags/ash	94
Industrial waste	5

Air emissions	mg
Dust	22
CO	19
CO ₂	6,671
SO _x	67
NO _x	41
HCl	1
HC	11
CH ₄	13

Packaging & delivery: Bulk delivery - no packaging
Road transport: rigid vehicle, 20 tonne payload, returning empty, notional return distance 48 km

Production and bulk road delivery of flat glass sand



Gross inputs and outputs associated with the production and bulk road delivery of flat glass sand/kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.07
Electricity - delivered	0.03
Oil fuels - production & delivery	0.01
Oil fuels - delivered	0.04
Total energy	0.14

Primary fuels	MJ
Coal	0.06
Oil	0.05
Nuclear	0.02
Total fuels	0.14
Primary feedstocks	MJ
Total feedstocks	0.00
Total fuels & feedstocks	0.14

Raw materials	mg
Iron ore	79
Limestone	28
Met coal	33
Sand	1,000,000
Water	4,008,100
Air	5


Water emissions	mg
Suspended solids	11

Solid waste	mg
Mineral waste	162,668
Slags/ash	132
Industrial waste	5

Air emissions	mg
Dust	30
CO	20
CO ₂	8,354
SO _x	89
NO _x	48
HCl	1
HC	13
CH ₄	18

Packaging & delivery: Bulk delivery - no packaging
Road transport: rigid vehicle, 20 tonne payload, returning empty, notional return distance 48 km

Production and bulk road delivery of fibre glass sand



Gross inputs and outputs associated with the production and bulk road delivery of fibre glass sand /kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	1.12
Electricity - delivered	0.47
Oil fuels - production & delivery	0.10
Oil fuels - delivered	0.72
Other fuels - production & delivery	0.01
Other fuels - delivered	0.09
Other fuels - feedstock	0.01
Total energy	2.53

Primary fuels	MJ
Coal	1.00
Oil	0.94
Gas	0.18
Hydro	0.02
Nuclear	0.39
Sulphur	0.04
Recovered	-0.04
Total fuels	2.52
Primary feedstocks	MJ
Total feedstocks	0.01
Total fuels & feedstocks	2.53

Raw materials	mg
Bauxite	1
Brine	4
Clay	8
Iron ore	184
Limestone	20,339
Met coal	76
Sand	1,000,000
Water	8,324,500
Wood	320
Nitrogen	2
Air	60,529
Sulphur	3,985


Water emissions	mg
COD	2
BOD	1
Acid	3
Metals	1
Suspended solids	17
HC	1
Phenol	1

Air emissions	mg
Dust	610
CO	326
CO ₂	160,886
SO _x	1,618
NO _x	733
HCl	20
HF	1
HC	220
CH ₄	427

Solid waste	mg
Paper	63
Metals	6
Other ref	115
Mineral waste	128,500
Slags/ash	2,131
Industrial waste	2,358

Packaging & delivery: Bulk delivery - no packaging
Road transport: rigid vehicle, 20 tonne payload, returning empty, notional return distance 48 km

Production and bulk road delivery of limestone



Gross inputs and outputs associated with the production and bulk road delivery of limestone/kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.05
Electricity - delivered	0.02
Oil fuels - production & delivery	0.01
Oil fuels - delivered	0.07
Total energy	0.16

Primary fuels	MJ
Coal	0.05
Oil	0.08
Gas	0.01
Nuclear	0.02
Total fuels	0.16
Primary feedstocks	MJ
Total feedstocks	0.00
Total fuels & feedstocks	0.16

Raw materials	mg
Bauxite	1
Iron ore	180
Limestone	1,000,100
Met coal	74
Water	9,456
Air	11


Water emissions	mg
Suspended solids	24

Solid waste	mg
Mineral waste	1,093
Slags/ash	111
Industrial waste	111,177

Air emissions	mg
Dust	32
CO	51
CO ₂	9,761
SO _x	86
NO _x	80
HCl	1
HC	23
CH ₄	16

Packaging & delivery: Bulk delivery - no packaging
Road transport: articulated vehicle, 25 tonne payload, returning empty, return distance 129 km

Clay winning and on-site delivery - roof tile manufacture



Gross inputs and outputs associated with clay winning - roof tile manufacture/kg
Totals may not agree because of rounding errors

Energy	MJ
Oil fuels - production & delivery	0.01
Oil fuels - delivered	0.04
Total energy	0.05

Primary fuels	MJ
Oil	0.05
Total fuels	0.05
Primary feedstocks	MJ
Total feedstocks	0.00
Total fuels & feedstocks	0.05

Raw materials	mg
Clay	1,000,000
Water	1,732


Water emissions	mg
Negligible	

Air emissions	mg
CO	1
CO ₂	3,477
SO _x	34
NO _x	17
HC	7

Solid waste	mg
Mineral waste	149,402
Industrial waste	5

Packaging & delivery: Bulk delivery - no packaging
Internal transport

Clay winning and on-site delivery - clay brick manufacture



Gross inputs and outputs associated with clay winning - clay brick manufacture/kg
Totals may not agree because of rounding errors

Energy	MJ
Oil fuels - delivered	0.02
Total energy	0.02

Primary fuels	MJ
Oil	0.02
Total fuels	0.02
Primary feedstocks	MJ
Total feedstocks	0.00
Total fuels & feedstocks	0.02

Raw materials	mg
Clay	1,000,000
Water	814


Water emissions	mg
Negligible	

Air emissions	mg
CO ₂	1,602
SO _x	8
NO _x	8
HC	3

Solid waste	mg
Mineral waste	285,701
Industrial waste	2

Packaging & delivery: Bulk delivery - no packaging
Internal transport

Production and bulk road delivery of gypsum⁴⁷



Gross inputs and outputs associated with the production and bulk road delivery of gypsum /kg
 Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.36
Electricity - delivered	0.15
Oil fuels - production & delivery	0.03
Oil fuels - delivered	0.22
Oil fuels - feedstock	0.01
Other fuels - delivered	0.01
Other fuels - feedstock	0.01
Total energy	0.79

Primary fuels	MJ
Coal	0.33
Oil	0.29
Gas	0.03
Hydro	0.01
Nuclear	0.13
Total fuels	0.77
Primary feedstocks	MJ
Coal	0.01
Total feedstocks	0.01
Total fuels & feedstocks	0.78

Raw materials	mg
Bauxite	3
Brine	1
Gypsum	1,000,000
Fe-Mn	2
Iron ore	576
Lead	1
Limestone	205
Met coal	237
Water	46,018
Air	36
Sulphur	2


Water emissions	mg
Suspended solids	94,581

Solid waste	mg
Mineral waste	3,049
Slags/ash	719
Industrial waste	31

Air emissions	mg
Dust	166
CO	159
CO ₂	46,617
SO _x	502
NO _x	305
HCl	6
HC	80
CH ₄	100

Packaging & delivery: Bulk delivery - no packaging
 Road transport: articulated vehicle, 25 tonne payload, returning empty, notional return distance 200 km

Production and bulk road delivery of dolomite⁴⁷



Gross inputs and outputs associated with the production and bulk road delivery of dolomite /kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.11
Electricity - delivered	0.05
Oil fuels - production & delivery	0.02
Oil fuels - delivered	0.12
Total energy	0.30

Primary fuels	MJ
Coal	0.10
Oil	0.14
Gas	0.01
Nuclear	0.04
Total fuels	0.29
Primary feedstocks	MJ
Total feedstocks	0.00
Total fuels & feedstocks	0.30

Raw materials	mg
Bauxite	2
Iron ore	284
Limestone	101
Met coal	117
Water	1,067,400
Dolomite	1,000,000
Air	18
Sulphur	1


Water emissions	mg
Suspended solids	38

Solid waste	mg
Mineral waste	1,001,100
Slags/ash	224
Industrial waste	16

Air emissions	mg
Dust	53
CO	75
CO ₂	18,268
SO _x	187
NO _x	133
HCl	2
HC	38
CH ₄	32

Packaging & delivery: Bulk delivery - no packaging
Road transport: articulated vehicle, 25 tonne payload, returning empty, notional return distance 200 km

Production and bulk delivery of ulexite⁴⁷



Gross inputs and outputs associated with the production and delivery of ulexite/kg
 Totals may not agree because of rounding errors

Energy		MJ
Electricity - production & delivery		0.13
Electricity - delivered		0.05
Oil fuels - production & delivery		0.04
Oil fuels - delivered		0.29
Oil fuels - feedstock		0.01
Other fuels - delivered		0.01
Other fuels - feedstock		0.01
Total energy		0.54

Primary fuels		MJ
Coal		0.12
Oil		0.33
Gas		0.02
Nuclear		0.04
Total fuels		0.52

Primary feedstocks		MJ
Coal		0.01
Total feedstocks		0.01
Total fuels & feedstocks		0.53

Raw materials		mg
Bauxite		4
Brine		2
Fe-Mn		2
Iron ore		699
Lead		1
Limestone		248
Met coal		288
Water		1,131,000
Ulexite		1,000,000
Air		44
Sulphur		3


Water emissions		mg
Suspended solids		10

Solid waste		mg
Mineral waste		1,780
Slags/ash		281
Industrial waste		36

Air emissions		mg
Dust		174
CO		210
CO ₂		33,086
SO _x		254
NO _x		304
HCl		2
HC		90
CH ₄		42

Packaging & delivery: Bulk delivery - no packaging
 Road transport: Articulated vehicles, 24 tonne payload, returning empty, notional return distance 483 km

Production and bulk road delivery of milled granite⁴⁷



Gross inputs and outputs associated with the production and delivery of milled granite/kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.68
Electricity - delivered	0.29
Oil fuels - production & delivery	0.08
Oil fuels - delivered	0.57
Oil fuels - feedstock	0.01
Other fuels - delivered	0.01
Other fuels - feedstock	0.01
Total energy	1.66

Primary fuels	MJ
Coal	0.61
Oil	0.72
Gas	0.06
Hydro	0.01
Nuclear	0.24
Total fuels	1.64
Primary feedstocks	MJ
Coal	0.01
Total feedstocks	0.01
Total fuels & feedstocks	1.65

Raw materials	mg
Bauxite	20
Brine	4
Fe-Mn	2
Iron ore	741
Lead	1
Limestone	264
Met coal	305
Water	240,961
Granite	1,000,000
Air	48
Sulphur	3


Water emissions	mg
COD	1
BOD	1
Acid	2
Metals	1
Suspended solids	9,109
HC	1
Phenol	1

Solid waste	mg
Mineral waste	125,270
Slags /ash	1,334
Industrial waste	79

Air emissions	mg
Dust	1,081
CO	432
CO ₂	100,653
SO _x	919
NO _x	743
HCl	12
HF	1
HC	199
CH ₄	184

Packaging & delivery: Bulk delivery - no packaging
Road transport: Articulated vehicle, 24 tonne payload, returning empty, notional return distance 483 km

Production and road delivery of bagged hydrated lime



Gross inputs and outputs associated with the production and road delivery of bagged hydrated lime /kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.59
Electricity - delivered	0.25
Oil fuels - production & delivery	0.05
Oil fuels - delivered	0.32
Oil fuels - feedstock	0.01
Other fuels - production & delivery	0.50
Other fuels - delivered	4.42
Other fuels - feedstock	0.27
Total energy	6.40

Primary fuels	MJ
Coal	0.53
Oil	0.42
Gas	4.94
Hydro	0.01
Nuclear	0.21
Total fuels	6.11
Primary feedstocks	MJ
Coal	0.02
Wood	0.11
Total feedstock	0.13
Total fuels & feedstock	6.23

Raw materials	mg
Bauxite	9
Brine	235
Clay	557
Fe-Mn	5
Iron ore	1,435
Lead	2
Limestone	1,351,900
Met coal	590
Water	683,386
Wood	21,348
Air	444
Sulphur	29

Water emissions	mg
COD	60
BOD	6
Acid	2
Metals	1
Suspended solids	260
HC	1
Other N	1

Air emissions	mg
Dust	1,871
CO	15,246
CO ₂	898,801
SO _x	8,916
NO _x	3,775
HCl	10
HF	1
HC	2,217
CH ₄	6,722


Solid waste	mg
Plastic containers	3
Paper	4,214
Plastics	27
Metals	373
Other ref	7,635
Mineral waste	6,813
Slags/ash	1,203
Industrial waste	150,274

Packaging & delivery: Packaging in 180 g paper bags on wooden pallets
Road transport: rigid vehicle, 20 tonne payload, returning empty, notional return distance 600 km

Appendix 18

Limestone products

Production and road delivery of block form mastic asphalt - Grade II type F1076, suitable for domestic floors



Gross inputs and outputs associated with the production and road delivery of block form mastic asphalt (notional unit inputs and outputs)/kg Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.08
Electricity - delivered	0.03
Oil fuels - production & delivery	0.98
Oil fuels - delivered	0.54
Oil fuels - feedstock	6.41
Other fuels - delivered	0.01
Other fuels - feedstock	0.16
Total energy	8.21

Primary fuels	MJ
Coal	0.10
Oil	1.14
Gas	0.35
Nuclear	0.03
Total fuels	1.63
Primary feedstocks	MJ
Coal	0.02
Oil	6.40
Wood	0.14
Total feedstock	6.56
Total fuels & feedstock	8.20

Raw materials	mg
Bauxite	7
Brine	2
Fe-Mn	4
Iron ore	1,183
Lead	2
Limestone	850,379
Met coal	486
Water	170,959
Wood	9,450
Air	45
Sulphur	3

Water emissions	mg
COD	8
BOD	7
Suspended solids	150
HC	7
Phenol	7

Air emissions	mg
Dust	100
CO	169
CO ₂	99,466
SO _x	634
NO _x	644
HCl	2
HC	425
CH ₄	44


Solid waste	mg
Paper	1
Plastics	18
Metals	370
Other ref	7,635
Mineral waste	2,740
Slags/ash	270
Industrial waste	95,318

Packaging & delivery: No packaging - delivered on wooden pallets
Road transport: rigid vehicle, 20 tonne payload, returning empty, notional return distance 322 km

Appendix 19

Limestone products

Production, road delivery & laying of mastic asphalt floor - 15 mm deep- Grade II type F1076



Gross inputs and outputs associated with the production, road delivery & laying of mastic asphalt floor - 15 mm deep (notional inputs and outputs)/kg per square metre

Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	2.76
Electricity - delivered	1.17
Oil fuels - production & delivery	36.86
Oil fuels - delivered	31.04
Oil fuels - feedstock	230.82
Other fuels - production & delivery	0.05
Other fuels - delivered	0.35
Other fuels - feedstock	5.67
Total energy	308.71

Raw materials	mg
Barytes	4
Bauxite	263
Brine	74
Clay	6
Fe-Mn	149
Fluorspar	5
Iron ore	42,766
Lead	57
Limestone	30,613,700
Met coal	17,574
Sand	1
Water	6,607,300
Wood	340
Zinc	10
Air	1,625
Sulphur	107

Air emissions	mg
Dust	3,700
CO	6,319
CO ₂	4,472,300
SO _x	27,329
NO _x	27,594
HCl	65
F	1
HF	3
HC	17,014
Metals	1
CH ₄	1,614

Primary fuels	MJ
Coal	3.65
Oil	53.74
Gas	13.33
Hydro	0.07
Nuclear	1.30
Total fuels	72.08
Primary feedstocks	MJ
Coal	0.55
Oil	230.56
Wood	5.13
Total feedstock	236.24
Total fuels & feedstock	308.32

Water emissions	mg
COD	293
BOD	263
Acid	16
Metals	5
Suspended solids	5,441
HC	264
Phenol	263

Solid waste	mg
Paper	48
Plastics	632
Metals	13,334
Organics	3
Other ref	274,857
Mineral waste	99,165
Slags/ash	9,827
Industrial waste	3,432,800


Packaging & delivery: No packaging - delivered on wooden pallets

Road transport: rigid vehicle, 20 tonne payload, returning empty, notional return distance 322 km

Appendix 20

Structural clay products

Production & road delivery of clay facing bricks



Gross inputs and outputs associated with the production & road delivery of clay facing bricks /kg

Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.42
Electricity - delivered	0.18
Oil fuels - production & delivery	0.05
Oil fuels - delivered	0.35
Oil fuels - feedstock	0.02
Other fuels - production & delivery	0.45
Other fuels - delivered	3.25
Other fuels - feedstock	0.18
Total energy	4.90

Primary fuels	MJ
Coal	1.46
Oil	0.46
Gas	2.61
Hydro	0.01
Nuclear	0.16
Total fuels	4.71
Primary feedstocks	MJ
Coal	0.03
Oil	0.01
Wood	0.14
Total feedstock	0.18
Total fuels & feedstock	4.89

Raw materials	mg
Bauxite	17
Brine	4
Clay	1,699,500
Fe-Mn	10
Iron ore	2,688
Lead	2
Limestone	822
Met coal	1,104
Water	789,998
Wood	9,451
Air	72
Sulphur	5

Water emissions	mg
COD	5
Acid	6
Metals	2
Suspended solids	363
HC	1

Air emissions	mg
Dust	1,022
CO	320
CO ₂	387,122
SO _x	2,471
NO _x	2,552
HCl	139
HF	43
HC	1,260
CH ₄	3,839


Solid waste	mg
Paper	2
Plastics	176
Metals	1,218
Other ref	7,635
Mineral waste	499,297
Slags/ash	23,578
Industrial waste	51
Fired clay	220,000
Unregulated chemicals	1

Packaging & delivery: Steel and polypropylene strapping - delivered on wooden pallets
Road transport: rigid vehicle, 20 tonne payload, returning empty, notional return distance 644 km

Appendix 21

Structural clay products

Production & road delivery of clay facing bricks - 65 mm



Gross inputs and outputs associated with the production & road delivery of 65 mm clay facing bricks /kg per square metre single leaf wall Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	63.42
Electricity - delivered	26.87
Oil fuels - production & delivery	7.95
Oil fuels - delivered	52.40
Oil fuels - feedstock	2.78
Other fuels - production & delivery	67.51
Other fuels - delivered	487.84
Other fuels - feedstock	26.63
Total energy	735.41

Raw materials	mg
Barytes	29
Bauxite	2,554
Brine	588
Clay	254,925,000
Fe-Mn	1,443
Fluorspar	46
Iron ore	403,146
Lead	357
Limestone	123,276
Met coal	165,583
Sand	25
Water	118,499,600
Wood	1,417,600
Zinc	45
Shale	2
NaCl	117
Air	10,776
Sulphur	709

Air emissions	mg
Dust	153,341
CO	47,923
CO ₂	58,068,300
SO _x	370,692
NO _x	382,753
HCl	20,922
F	10
HF	6,474
HC	189,030
Metals	9
CH ₄	575,856


Primary fuels	MJ
Coal	219.01
Oil	69.60
Gas	392.01
Hydro	1.18
Nuclear	23.97
Lignite	0.01
Total fuels	705.79
Primary feedstocks	MJ
Coal	5.19
Oil	1.06
Gas	0.23
Wood	21.37
Total feedstock	27.85
Total fuels & feedstock	733.64

Water emissions	mg
COD	822
BOD	65
Acid	891
Metals	236
Cl ⁻	19
F ⁻	1
Dissolved organics	1
Suspended solids	54,423
Detergent/oil	1
HC	83
Phenol	63
Dissolved solids	5
Other organics	6

Solid waste	mg
Paper	226
Plastics	26,342
Metals	182,673
Organics	17
Other ref	1,145,200
Mineral waste	74,894,500
Slags/ash	3,536,700
Industrial waste	7,671
Fired clay	33,000,000
Unregulated chemicals	188

Packaging & delivery: Steel and polypropylene strapping - delivered on wooden pallets
Road transport: rigid vehicle, 20 tonne payload, returning empty, notional return distance 644 km

Production and road delivery of clay roof tiles



Gross inputs and outputs associated with the production and road delivery of clay roof tiles /kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.89
Electricity - delivered	0.38
Oil fuels - production & delivery	0.03
Oil fuels - delivered	0.18
Oil fuels - feedstock	0.01
Other fuels - production & delivery	0.26
Other fuels - delivered	2.28
Other fuels - feedstock	0.17
Total energy	4.19

Raw materials	mg
Barytes	1,066
Bauxite	12
Brine	343
Clay	1,250,000
Fe-Mn	7
Iron ore	1,874
Limestone	766
Met coal	769
Water	168,802
Wood	9,488
Pyrolusite	2,460
Air	22
Sulphur	1

Air emissions	mg
Dust	569
CO	114
CO ₂	250,076
SO _x	1,337
NO _x	2,113
HCl	16
HF	244
HC	1,172
CH ₄	3,605

Primary fuels	MJ
Coal	0.80
Oil	0.33
Gas	2.56
Hydro	0.01
Nuclear	0.31
Total fuels	4.01
Primary feedstocks	MJ
Coal	0.02
Oil	0.01
Wood	0.14
Total feedstocks	0.18
Total fuels & feedstocks	4.19

Water emissions	mg
COD	1
Acid	2
Metals	1
Suspended solids	368


Solid waste	mg
Paper	15
Plastics	175
Metals	1,219
Other ref	7,635
Mineral waste	195,075
Slags/ash	1,931
Industrial waste	37
Fired clay	35,340
Unregulated chemicals	8

Packaging & delivery: Steel and polypropylene strapping - delivered on wooden pallets
Road transport: rigid vehicle, 20 tonne payload, returning empty, return distance 155 km

Appendix 23

Structural clay products

Production and road delivery of clay roof tiles/sq metre - 60 tiles



Gross inputs and outputs associated with the production and road delivery of clay roof tiles /kg per sq m (60 tiles)
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	59.69
Electricity - delivered	25.27
Oil fuels - production & delivery	1.84
Oil fuels - delivered	12.09
Oil fuels - feedstock	0.66
Other fuels - production & delivery	17.24
Other fuels - delivered	152.45
Other fuels - feedstock	11.24
Total energy	280.47

Raw materials	mg
Barytes	71,401
Bauxite	826
Brine	22,992
Clay	83,750,100
Fe-Mn	466
Fluorspar	15
Iron ore	125,573
Lead	55
Limestone	51,327
Met coal	51,543
Sand	22
Water	11,309,700
Wood	635,718
Zinc	20
Shale	2
Pyrolusite	164,820
NaCl	52
Air	1,472
Sulphur	97

Air emissions	mg
Dust	38,129
CO	7,643
CO ₂	16,755,100
SO _x	89,574
NO _x	141,560
HCl	1,052
F	3
HF	16,333
HC	78,499
Metals	11
CH ₄	241,555

Primary fuels	MJ
Coal	53.68
Oil	22.21
Gas	171.29
Hydro	1.00
Nuclear	20.76
Total fuels	268.95
Primary feedstocks	MJ
Coal	1.61
Oil	0.47
Gas	0.10
Wood	9.57
Total feedstocks	11.76
Total fuels & feedstocks	280.70

Water emissions	mg
COD	46
BOD	22
Salt	7
Acid	159
Metals	52
Cl ⁻	31
Suspended solids	24,646
HC	32
Phenol	20
Dissolved solids	18
Other organics	3


Solid waste	mg
Paper	1,000
Plastics	11,757
Metals	81,595
Organics	2
Other ref	511,541
Mineral waste	13,070,000
Slags/ash	129,342
Industrial waste	2,463
Fired clay	2,367,800
Unregulated chemicals	566

Packaging & delivery: Steel and polypropylene strapping - delivered on wooden pallets
Road transport: rigid vehicle, 20 tonne payload, returning empty, return distance 155 km

Appendix 24

Structural clay products

Production and road delivery of 100 mm vitrified clay pipes per metre length



Gross inputs and outputs associated with the production and road delivery of 100 mm vitrified clay pipes - kg /m
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	11.22
Electricity - delivered	4.75
Oil fuels - production & delivery	2.28
Oil fuels - delivered	9.45
Oil fuels - feedstock	6.48
Other fuels - production & delivery	4.71
Other fuels - delivered	40.34
Other fuels - feedstock	3.43
Total energy	82.64

Raw materials	mg
Barytes	2
Bauxite	234
Brine	36
Clay	17,226,100
Fe-Mn	99
Fluorspar	3
Iron ore	27,504
Lead	20
Limestone	8,291
Met coal	11,277
Sand	4
Water	2,521,600
Wood	107,640
Zinc	3
NaCl	740
Air	623
Sulphur	41

Air emissions	mg
Dust	8,163
CO	6,030
CO ₂	4,261,700
SO _x	18,809
NO _x	43,601
HCl	445
F	1
HF	597
HC	23,516
Metals	2
CH ₄	60,831

Primary fuels	MJ
Coal	10.13
Oil	12.45
Gas	46.02
Hydro	0.19
Nuclear	3.92
Total fuels	79.70

Primary feedstocks	MJ
Coal	0.35
Oil	6.39
Gas	1.45
Wood	1.62
Total feedstocks	9.82
Total fuels & feedstocks	82.53

Water emissions	mg
COD	72
BOD	19
Acid	42
NO ₃ ⁻	3
Metals	53
NH ₄ ⁺	1
Cl ⁻	118
Dissolved organics	4
Suspended solids	3,614
Detergent/oil	6
HC	56
Phenol	10
Dissolved solids	30
Other N	1
Phosphate/P ₂ O ₅	3
Other organics	37


Solid waste	mg
Paper	17
Plastics	221
Metals	13,870
Other ref	86,962
Mineral waste	5,026,500
Slags/ash	22,391
Industrial waste	1,834
Fired clay	1,124,200
Regulated chemicals	4
Unregulated chemicals	1,184

Packaging & delivery: Steel strapping - delivered on wooden pallets
Road transport: articulated vehicle, 24 tonne payload, returning empty, notional return distance 322 km

Appendix 25

Structural clay products

Production and road delivery of a vitrified clay gully (width 195 mm, depth 335 mm)



Gross inputs and outputs associated with the production and road delivery of a vitrified clay gully - per gully
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	16.05
Electricity - delivered	6.79
Oil fuels - production & delivery	4.35
Oil fuels - delivered	30.10
Oil fuels - feedstock	0.06
Other fuels - production & delivery	7.96
Other fuels - delivered	70.73
Other fuels - feedstock	1.79
Total energy	137.83

Raw materials	mg
Barytes	2
Bauxite	155
Brine	35
Clay	16,089,200
Fe-Mn	88
Fluorspar	3
Iron ore	24,231
Lead	21
Limestone	7,247
Met coal	9,950
Sand	6
Water	3,272,200
Wood	99,230
Zinc	3
Air	512
Sulphur	34

Air emissions	mg
Dust	12,974
CO	3,118
CO ₂	13,615,900
SO _x	61,135
NO _x	85,671
HCl	1,859
F	1
HF	26,264
HC	39,293
Metals	27
CH ₄	109,433


Primary fuels	MJ
Coal	14.49
Oil	35.11
Gas	80.47
Hydro	0.27
Nuclear	5.63
Total fuels	135.98
Primary feedstocks	MJ
Coal	0.31
Oil	0.01
Wood	1.50
Total feedstocks	1.82
Total fuels & feedstocks	137.80

Water emissions	mg
COD	37
BOD	33
Acid	41
Metals	13
Suspended solids	3,280
IIC	35
Phenol	33

Solid waste	mg
Paper	16
Plastics	204
Metals	12,820
Other ref	80,167
Mineral waste	4,729,900
Slags/ash	32,187
Industrial waste	3,844
Fired clay	1,050,000

Packaging & delivery: Steel strapping - delivered on wooden pallets
Road transport: rigid vehicle, 12 tonne payload, returning empty, notional return distance 322 km

Production and delivery of ready mixed concrete (20 MPa) - suitable for footings and foundations



Gross inputs and outputs associated with the production & delivery of ready mixed concrete (20 MPa) /kg
Totals may not agree because of rounding errors

Energy		MJ
Electricity - production & delivery		0.18
Electricity - delivered		0.08
Oil fuels - production & delivery		0.01
Oil fuels - delivered		0.09
Other fuels - production & delivery		0.01
Other fuels - delivered		0.37
Total energy		0.75

Primary fuels		MJ
Coal		0.53
Oil		0.13
Gas		0.01
Nuclear		0.07
Total fuels		0.74
Primary feedstocks		MJ
Total feedstock		0.00
Total fuels & feedstock		0.75

Raw materials		mg
Bauxite		1
CaSO ₄		4,398
Iron ore		206
Limestone		625,884
Met coal		85
Sand		335,354
Water		1,569,400
Shale		12,450
Air		13

Water emissions		mg
Suspended solids		453


Solid waste		mg
Mineral waste		46,515
Slags/ash		367
Industrial waste		73,114

Air emissions		mg
Dust		560
CO		87
CO ₂		100,902
SO _x		620
H ₂ S		1
NO _x		244
HCl		11
HC		41
CH ₄		143

Packaging & delivery: Bulk delivery - no packaging
Road transport: rigid concrete mixer, 14.4 tonne payload, returning empty, return distance 13 km

Production and delivery of ready mixed concrete (30 MPa) - suitable for

- ♦ floors - light foot and trolley traffic
- ♦ reinforced or pre-stressed concrete (mild exposure)



Gross inputs and outputs associated with the production & delivery of ready mixed concrete (30 MPa) /kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.21
Electricity - delivered	0.09
Oil fuels - production & delivery	0.01
Oil fuels - delivered	0.10
Other fuels - production & delivery	0.02
Other fuels - delivered	0.45
Total energy	0.88

Raw materials	mg
Bauxite	1
CaSO ₄	5,426
Iron ore	219
Limestone	654,124
Met coal	90
Sand	317,156
Water	1,527,400
Shale	15,363
Air	14

Air emissions	mg
Dust	684
CO	96
CO ₂	122,162
SO _x	745
H ₂ S	2
NO _x	283
HCl	13
HF	1
HC	45
CH ₄	173


Primary fuels	MJ
Coal	0.65
Oil	0.14
Gas	0.01
Nuclear	0.08
Total fuels	0.88
Primary feedstocks	MJ
Total feedstock	0.00
Total fuels & feedstock	0.88

Water emissions	mg
Acid	1
Suspended solids	555

Solid waste	mg
Mineral waste	45,397
Slags/ash	428
Industrial waste	76,268

Packaging & delivery: Bulk delivery - no packaging
Road transport: rigid concrete mixer, 14.4 tonne payload, returning empty, return distance 13 km

Production and delivery of ready mixed 1 : 1 : 6 cement : lime : sand mortar (by volume)



Gross inputs and outputs associated with the production & delivery of ready mixed cement : lime : sand mortar /kg Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.23
Electricity - delivered	0.10
Oil fuels - production & delivery	0.01
Oil fuels - delivered	0.10
Other fuels - production & delivery	0.04
Other fuels - delivered	0.64
Total energy	1.12

Raw materials	mg
Bauxite	1
CaSO ₄	5,581
Iron ore	213
Limestone	196,419
Met coal	88
Sand	819,503
Water	3,524,400
Shale	15,799
Air	13

Air emissions	mg
Dust	753
CO	695
CO ₂	159,597
SO _x	1,104
H ₂ S	2
NO _x	421
HCl	13
HC	129
CH ₄	443

Primary fuels	MJ
Coal	0.68
Oil	0.14
Gas	0.21
Nuclear	0.08
Total fuels	1.11
Primary feedstocks	MJ
Total feedstock	0.00
Total fuels & feedstock	1.12

Water emissions	mg
Acid	1
Suspended solids	569


Solid waste	mg
Mineral waste	106,805
Slags/ash	464
Industrial waste	26,546

Packaging & delivery: Bulk delivery - no packaging
Road transport: rigid concrete mixer, 14.4 tonne payload, returning empty, return distance 13 km

Appendix 29

Concrete and mortar products

Production and road delivery of concrete roof tiles/kg



Gross inputs and outputs associated with the production and road delivery of concrete roof tiles/kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.52
Electricity - delivered	0.22
Oil fuels - production & delivery	0.06
Oil fuels - delivered	0.37
Oil fuels - feedstock	0.05
Other fuels - production & delivery	0.04
Other fuels - delivered	0.96
Other fuels - feedstock	0.19
Total energy	2.42

Raw materials	mg
Bauxite	14
Brine	5
CaSO ₄	9,502
Clay	7
Fe-Mn	8
Iron ore	13,550
Lead	1
Limestone	242,449
Met coal	842
Sand	829,582
Water	3,878,000
Wood	9,587
Shale	26,902
NaCl	4
Air	36
Sulphur	2

Air emissions	mg
Dust	1,384
CO	197
CO ₂	255,889
SO _x	1,859
H ₂ S	3
NO _x	697
HCl	28
HF	1
HC	150
CH ₄	416

Primary fuels	MJ
Coal	1.41
Oil	0.50
Gas	0.09
Hydro	0.01
Nuclear	0.19
Total fuels	2.20


Primary feedstocks	MJ
Coal	0.03
Oil	0.05
Gas	0.02
Wood	0.14
Total feedstocks	0.24
Total fuels & feedstocks	2.44

Water emissions	mg
COD	2
BOD	1
Acid	2
Metals	1
Suspended solids	2,267
HC	1

Solid waste	mg
Paper	50
Plastics	19
Metals	1,221
Other ref	7,635
Mineral waste	154,262
Slags/ash	1,429
Industrial waste	27,071
Unregulated chemicals	1

Packaging & delivery: Steel strapping - delivered on wooden pallets
Road transport: rigid vehicle, 20 tonne payload, returning empty, return distance 155 km

Appendix 30 Concrete and mortar products
Production and road delivery of concrete roof tiles/kg per sq.m



Gross inputs and outputs associated with the production and road delivery of concrete roof tiles - kg/sq. m
 Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	29.18
Electricity - delivered	12.35
Oil fuels - production & delivery	3.44
Oil fuels - delivered	20.95
Oil fuels - feedstock	2.99
Other fuels - production & delivery	2.17
Other fuels - delivered	53.84
Other fuels - feedstock	10.43
Total energy	135.34

Raw materials	mg
Barytes	4
Bauxite	779
Brine	286
CaSO ₄	532,112
Clay	370
Fe-Mn	422
Fluorspar	14
Iron ore	758,832
Lead	59
Limestone	13,577,100
Met coal	47,141
Sand	46,456,600
Water	217,167,400
Wood	536,886
Zinc	16
Shale	1,506,500
NaCl	216
Air	2,006
Sulphur	132

Air emissions	mg
Dust	77,521
CO	11,041
CO ₂	14,329,800
SO _x	104,088
H ₂ S	179
NO _x	39,063
NH ₃	1
HCl	1,568
F	3
HF	65
HC	8,401
Metals	7
CH ₄	23,298

Primary fuels	MJ
Coal	79.13
Oil	28.36
Gas	4.83
Hydro	0.51
Nuclear	10.39
Total fuels	123.21

Primary feedstocks	MJ
Coal	1.48
Oil	2.75
Gas	0.98
Wood	8.05
Total feedstocks	13.26
Total fuels & feedstocks	136.47

Water emissions	mg
COD	102
BOD	36
Acid	89
Metals	36
Cl ⁻	4
Dissolved organics	1
Suspended solids	126,953
Detergent/oil	3
HC	35
Phenol	27
Dissolved solids	12
Other N	1


Solid waste	mg
Plastic containers	2
Paper	2,796
Plastics	1,089
Metals	68,374
Organics	2
Other ref	427,556
Mineral waste	8,638,700
Slags/ash	80,007
Industrial waste	1,516,000
Regulated chemicals	2
Unregulated chemicals	62

Packaging & delivery: Steel strapping - delivered on wooden pallets
Road transport: rigid vehicle, 20 tonne payload, returning empty, return distance 155 km

Appendix 31

Concrete and mortar products

Production and road delivery of dense concrete blocks/kg



Gross inputs and outputs associated with the production and road delivery of dense concrete blocks - 7 MPa/kg
 Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.19
Electricity - delivered	0.08
Oil fuels - production & delivery	0.03
Oil fuels - delivered	0.23
Oil fuels - feedstock	0.01
Other fuels - production & delivery	0.01
Other fuels - delivered	0.21
Other fuels - feedstock	0.17
Total energy	0.93

Primary fuels	MJ
Coal	0.38
Oil	0.28
Gas	0.03
Nuclear	0.07
Total fuels	0.75
Primary feedstocks	MJ
Coal	0.03
Wood	0.14
Total feedstocks	0.17
Total fuels & feedstocks	0.92

Raw materials	mg
Bauxite	13
Brine	2
CaSO ₄	2,371
Fe-Mn	7
Iron ore	2,021
Lead	1
Limestone	913,533
Met coal	830
Sand	6,713
Water	268,944
Wood	9,450
Shale	6,713
Air	29
Sulphur	2

Water emissions	mg
Acid	1
Suspended solids	480

Solid waste	mg
Paper	1
Plastics	19
Metals	1,226
Other ref	7,635
Mineral waste	7,312
Slags/ash	499
Industrial waste	119,552

Air emissions	mg
Dust	382
CO	129
CO ₂	76,715
SO _x	645
H ₂ S	1
NO _x	298
HCl	7
HC	77
CH ₄	120

Packaging & delivery: Steel strapping - delivered on wooden pallets
 Road transport: rigid vehicle, 16 tonne payload, returning empty, return distance 129 km

Appendix 32

Concrete and mortar products

Production and road delivery of dense concrete blocks - per m²


Gross inputs and outputs associated with the production and road delivery of dense concrete blocks - per m ² (derived from figures shown in Appendix 31 Totals may not agree because of rounding errors)			
Input/output	Units	(440x215x100) mm 194 kg/sq.m	(440x215x140) mm 271.5 kg/sq.m
Energy			
Electricity - production & delivery	MJ	37.45	52.41
Electricity - delivered	MJ	15.88	22.22
Oil fuels - production & delivery	MJ	6.52	9.12
Oil fuels - delivered	MJ	44.17	61.82
Oil fuels - feedstock	MJ	1.09	1.52
Other fuels - production & delivery	MJ	1.72	2.41
Other fuels - delivered	MJ	40.21	56.28
Other fuels - feedstock	MJ	32.66	45.71
Total energy	MJ	179.7	251.49
Fuels			
Coal	MJ	72.8	101.88
Oil	MJ	53.6	75.01
Gas	MJ	5.38	7.53
Hydro	MJ	0.67	0.93
Nuclear	MJ	13.1	18.34
Total fuels	MJ	145.55	203.69
Feedstock			
Coal	MJ	5.04	7.05
Oil	MJ	0.22	0.30
Wood	MJ	27.64	38.69
Total feedstock	MJ	32.9	46.04
Total fuels & feedstock	MJ	178.45	249.73
Raw materials			
Barytes	mg	15	21
Bauxite	mg	2,546	3,563
Brine	mg	467	654
CaSO ₄	mg	459,974	643,727
Clay	mg	38	53
Fe-Mn	mg	1,444	2,020
Fluorspar	mg	46	65
Iron ore	mg	392,061	548,683
Lead	mg	217	303
Limestone	mg	177,225,400	248,024,200
Met coal	mg	160,952	225,250
Sand	mg	1,302,300	1,822,500
Tin	mg	1	2
Water	mg	52,175,100	73,018,200
Wood	mg	1,833,400	2,565,800
Zinc	mg	57	80
Shale	mg	1,302,300	1,822,500
Air	mg	5,708	7,988
Sulphur	mg	376	526
Air emissions			
Dust	mg	74,046	103,626
CO	mg	25,077	35,095
CO ₂	mg	14,883,200	20,828,800
SO _x	mg	125,042	174,995
H ₂ S	mg	154	216
NO _x	mg	57,762	80,837
HCl	mg	1,424	1,993
F	mg	9	12
HF	mg	62	86
HC	mg	14,987	20,976
Metals	mg	7	10
CH ₄	mg	23,217	32,491
Water emissions			
COD	mg	62	86
BOD	mg	50	70
Acid	mg	154	215
Metal ions	mg	44	62
F	mg	1	2
Suspended solids	mg	93,074	130,255
Hydrocarbons	mg	56	79
Phenol	mg	50	69
Solid waste			
Paper	mg	288	403
Plastics	mg	3,756	5,256
Metals	mg	237,830	333,840
Organics	mg	9	12
Other refuse	mg	1,481,200	2,072,900
Mineral waste	mg	1,418,600	1,985,300
Slags/ash	mg	96,725	135,365
Industrial waste	mg	23,193,200	32,458,500

Packaging & delivery: Steel strapping - delivered on wooden pallets
Road transport: rigid vehicle, 16 tonne payload, returning empty, return distance 129 km

Appendix 33

Concrete and mortar products

Production and road delivery of aerated concrete block /kg



Gross inputs and outputs associated with the production and road delivery of aerated concrete blocks (4.0 MPa)/kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.78
Electricity - delivered	0.35
Oil fuels - production & delivery	0.24
Oil fuels - delivered	1.63
Oil fuels - feedstock	0.03
Other fuels - production & delivery	0.06
Other fuels - delivered	1.32
Other fuels - feedstock	0.18
Total energy	4.59

Raw materials	mg
Bauxite	2,009
Brine	254
CaSO ₄	14,602
Fe-Mn	9
Fluorspar	36
Iron ore	2,444
Lead	2
Limestone	398,043
Met coal	1,004
Sand	41,340
Water	1,098,500
Wood	9,450
Shale	41,340
Sodium chloride	3
Air	287
Sulphur	19

Air emissions	mg
Dust	2,006
CO	858
CO ₂	473,948
SO ₂	4,415
H ₂ S	5
NO _x	1,448
HCl	38
F	3
HF	2
HC	400
Metals	1
CH ₄	669
Hydrogen	56

Primary fuels	MJ
Coal	1.93
Oil	1.90
Gas	0.23
Hydro	0.05
Nuclear	0.27
Total fuels	4.37
Primary feedstocks	MJ
Coal	0.03
Oil	0.02
Gas	0.01
Wood	0.14
Total feedstocks	0.21
Total fuels & feedstocks	4.58

Water emissions	mg
COD	2
BOD	2
Acid	2
Metals	1
F	1
Suspended solids	1,915
HC	2
Phenol	2

Solid waste	mg
Paper	1
Plastics	19
Metals	1,226
Other ref	7,635
Mineral waste	29,061
Slags/ash	1,692
Industrial waste	64,921

Packaging & delivery: Steel strapping - delivered on wooden pallets
Road transport: rigid vehicle, 16 tonne payload, returning empty, return distance 129 km

Appendix 34

Concrete and mortar products

Production and road delivery of aerated concrete blocks - per m²


Gross inputs and outputs associated with the production and road delivery of aerated concrete blocks - per m² (derived from figures shown in Appendix 33 Totals may not agree because of rounding errors)			
Input/output	Units	(440x215x100) mm 75 kg/sq.m	(440x215x140) mm 105 kg/sq.m
Energy			
Electricity - production & delivery	MJ	58.47	81.86
Electricity - delivered	MJ	26.50	37.10
Oil fuels - production & delivery	MJ	17.97	25.16
Oil fuels - delivered	MJ	122.34	171.27
Oil fuels - feedstock	MJ	2.38	3.33
Other fuels - production & delivery	MJ	4.23	5.92
Other fuels - delivered	MJ	98.94	138.51
Other fuels - feedstock	MJ	13.56	18.98
Total energy	MJ	344.38	482.13
Fuels			
Coal	MJ	144.41	202.18
Oil	MJ	142.20	199.08
Gas	MJ	17.06	23.88
Hydro	MJ	3.69	5.17
Nuclear	MJ	20.61	28.86
Total fuels	MJ	327.98	459.18
Feedstock			
Coal	MJ	2.36	3.30
Oil	MJ	1.81	2.53
Gas	MJ	0.65	0.91
Wood	MJ	10.69	14.96
Total feedstock	MJ	15.50	21.70
Total fuels & feedstock	MJ	343.48	480.87
Raw materials			
Barytes	mg	10	14
Bauxite	mg	150,707	210,990
Brine	mg	19,042	26,660
CaSO ₄	mg	1,095,100	1,533,200
Clay	mg	15	21
Fe-Mn	mg	662	927
Fluorspar	mg	2,736	3,830
Iron ore	mg	183,293	256,610
Lead	mg	129	180
Limestone	mg	29,853,200	41,794,500
Met coal	mg	75,271	105,379
Sand	mg	3,100,500	4,340,700
Water	mg	82,388,500	115,343,900
Wood	mg	708,782	992,295
Zinc	mg	22	31
Shale	mg	3,100,500	4,340,700
Sodium chloride	mg	189	264
Nitrogen	mg	22	31
Air	mg	21,503	30,104
Sulphur	mg	1,416	1,982
Air emissions			
Dust	mg	150,438	210,613
CO	mg	64,351	90,092
CO ₂	mg	35,546,100	49,764,600
SO _x	mg	331,128	463,579
H ₂ S	mg	367	514
NO _x	mg	108,599	152,038
HCl	mg	2,855	3,997
F	mg	220	307
HF	mg	120	168
HC	mg	29,966	41,952
Metals	mg	108	152
CH ₄	mg	50,136	70,190
Hydrogen	mg	4,208	5,892
Water emissions			
COD	mg	179	251
BOD	mg	137	191
Acid	mg	169	237
Metal ions	mg	60	83
Cl ⁻	mg	23	32
F ⁻	mg	77	108
Dissolved organics	mg	1	1
Suspended solids	mg	143,598	201,037
Detergent/oil	mg	3	4
Hydrocarbons	mg	144	202
Phenol	mg	132	185
Dissolved solids	mg	11	15
Solid waste			
Paper	mg	111	156
Plastics	mg	1,456	2,039
Metals	mg	91,945	128,723
Organics	mg	6	8
Other refuse	mg	572,620	801,668
Mineral waste	mg	2,179,600	3,051,400
Slag/ash	mg	126,898	177,657
Industrial waste	mg	4,869,100	6,816,700
Regulated chemicals	mg	2	3
Unregulated chemicals	mg	54	75

Packaging & delivery: Steel strapping - delivered on wooden pallets
Road transport: rigid vehicle, 16 tonne payload, returning empty, return distance 129 km

Appendix 35

Concrete and mortar products

Production and road delivery of pre-stressed concrete lintels (255 x 75) mm - per metre length



**Schematic flow diagram for the production of pre-stressed concrete lintels (255x75)mm
All flows are in kg per metre length**

Gross inputs and outputs associated with the production and road delivery of pre-stressed concrete lintels (255x75) mm - per metre length Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	21.39
Electricity - delivered	9.12
Oil fuels - production & delivery	2.40
Oil fuels - delivered	16.29
Oil fuels - feedstock	0.32
Other fuels - production & delivery	1.52
Other fuels - delivered	27.65
Other fuels - feedstock	16.02
Total energy	94.72

Raw materials	mg
Barytes	4
Bauxite	5,948
Brine	788
CaSO ₄	317,376
Clay	3
Fe-Mn	3,370
Fluorspar	108
Iron ore	1,031,800
Lead	42
Limestone	31,423,200
Met coal	424,436
Sand	16,286,400
Water	91,978,200
Wood	183,422
Zinc	47
Shale	898,536
Sodium chloride	10
Air	2,293
Sulphur	151

Air emissions	mg
Dust	51,338
CO	10,513
CO ₂	9,048,600
SO _x	138,974
H ₂ S	106
NO _x	31,292
HCl	910
F	19
HF	39
HC	7,013
Metals	7
CH ₄	17,509

Primary fuels	MJ
Coal	46.11
Oil	21.15
Gas	3.00
Hydro	0.47
Nuclear	7.60
Total fuels	78.34

Primary feedstocks	MJ
Coal	13.29
Oil	0.13
Gas	0.02
Wood	2.77
Total feedstocks	16.21
Total fuels & feedstocks	94.55

Water emissions	mg
COD	24
BOD	20
Acid	230
Metals	60
Cl ⁻	2
F ⁻	3
Suspended solids	154,159
HC	23
Phenol	19


Solid waste	mg
Paper	23
Plastics	2,248
Metals	6,256
Organics	2
Other ref	128,930
Mineral waste	3,808,700
Slags/ash	108,469
Industrial waste	3,470,500
Unregulated chemicals	16

Packaging & delivery: Polypropylene strapping using galvanised steel clips - delivered on wooden pallets
Road transport: articulated vehicle, 25 tonne payload, returning empty, average return distance 200 km

Appendix 36

Concrete and mortar products

Production and road delivery of reinforced concrete lintels (100 x 143) mm - per 1500 mm length



Gross inputs and outputs associated with the production and road delivery of reinforced concrete lintels (100x143) mm - per 1500 mm length Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	21.64
Electricity - delivered	9.23
Oil fuels - production & delivery	3.41
Oil fuels - delivered	23.13
Oil fuels - feedstock	0.50
Other fuels - production & delivery	1.47
Other fuels - delivered	24.54
Other fuels - feedstock	17.63
Total energy	101.54

Primary fuels	MJ
Coal	43.07
Oil	28.55
Gas	3.57
Hydro	0.48
Nuclear	7.65
Total fuels	83.32

Primary feedstocks	MJ
Coal	14.49
Oil	0.15
Gas	0.02
Wood	3.16
Total feedstocks	17.82
Total fuels & feedstocks	101.14

Raw materials	mg
Barytes	6
Bauxite	6,486
Brine	882
CaSO ₄	276,649
Clay	4
Fe-Mn	3,674
Fluorspar	118
Iron ore	1,124,900
Lead	73
Limestone	33,626,800
Met coal	462,739
Sand	16,168,000
Water	94,007,900
Wood	209,464
Zinc	53
Shale	783,233
Sodium chloride	11
Nitrogen	1
Air	3,385
Sulphur	223

Water emissions	mg
COD	32
BOD	27
Acid	247
Metals	64
Cl ⁻	3
F	4
Suspended solids	161,495
HC	31
Phenol	26
Other organics	1

Solid waste	mg
Paper	26
Plastics	2,567
Metals	7,144
Organics	4
Other ref	147,235
Mineral waste	3,888,900
Slags/ash	114,787
Industrial waste	3,713,000
Unregulated chemicals	18


Air emissions	mg
Dust	48,272
CO	14,687
CO ₂	8,895,100
SO _x	144,790
H ₂ S	93
NO _x	36,555
HCl	845
F	21
HF	36
HC	8,969
Metals	7
CH ₄	17,297

Packaging & delivery: Polypropylene strapping using galvanised steel clips - delivered on wooden pallets
Road transport: articulated vehicle, 25 tonne payload, returning empty, average return distance 200 km

Appendix 37

Concrete and mortar products

Production and road delivery of reinforced concrete lintels (125 x 143) mm - per 1500 mm length



Gross inputs and outputs associated with the production and road delivery of reinforced concrete lintels (125x143) mm - per 1500 mm length Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	26.42
Electricity - delivered	11.26
Oil fuels - production & delivery	4.22
Oil fuels - delivered	28.66
Oil fuels - feedstock	0.62
Other fuels - production & delivery	1.76
Other fuels - delivered	30.54
Other fuels - feedstock	20.21
Total energy	123.68

Primary fuels	MJ
Coal	53.27
Oil	35.31
Gas	4.25
Hydro	0.57
Nuclear	9.34
Total fuels	103.39
Primary feedstocks	MJ
Coal	16.28
Oil	0.18
Gas	0.03
Wood	3.94
Total feedstocks	20.44
Total fuels & feedstocks	123.18

Raw materials	mg
Barytes	8
Bauxite	7,289
Brine	999
CaSO ₄	345,987
Clay	4
Fe-Mn	4,130
Fluorspar	132
Iron ore	1,264,100
Lead	91
Limestone	42,019,000
Met coal	520,008
Sand	20,220,300
Water	115,662,500
Wood	261,522
Zinc	67
Shale	979,542
Sodium chloride	14
Nitrogen	1
Air	4,120
Sulphur	271

Water emissions	mg
COD	39
BOD	33
Acid	283
Metals	74
Cl ⁻	3
F ⁻	4
Suspended solids	184,952
HC	38
Phenol	33
Dissolved solids	1
Other organics	1

Air emissions	mg
Dust	59,556
CO	18,130
CO ₂	11,002,200
SO ₂	168,923
H ₂ S	116
NO _x	44,618
HCl	1,045
F	24
HF	45
HC	10,913
Metals	8
CH ₄	20,769

Solid waste	mg
Paper	33
Plastics	3,208
Metals	8,920
Organics	5
Other ref	183,831
Mineral waste	4,666,700
Slags/ash	133,028
Industrial waste	4,643,500
Unregulated chemicals	22

Packaging & delivery: Polypropylene strapping using galvanised steel clips - delivered on wooden pallets
 Road transport: articulated vehicle, 25 tonne payload, returning empty, average return distance 200 km

Appendix 38

Concrete and mortar products


Production and road delivery of dual lintel systems - per 1500 mm

Gross inputs and outputs associated with the production and road delivery of dual lintel systems - per 1500 mm				
Outer leaf: reinforced concrete (100 x 143) mm. Inner leaf as specified below (125 x 143) mm.				
(derived from figures shown in Appendices 36, 37, 45, 53) Totals may not agree because of rounding errors				
Input/output	Units	Inner leaf		
		Reinforced concrete	Timber	Rolled steel joist
Energy				
Electricity - production & delivery	MJ	48.05	30.77	241.47
Electricity - delivered	MJ	20.49	13.10	105.03
Oil fuels - production & delivery	MJ	7.63	8.44	14.75
Oil fuels - delivered	MJ	51.78	57.94	99.87
Oil fuels - feedstock	MJ	1.12	0.60	2.50
Other fuels - production & delivery	MJ	3.22	1.48	26.65
Other fuels - delivered	MJ	55.08	24.65	88.57
Other fuels - feedstock	MJ	37.84	248.40	548.88
Total energy	MJ	225.23	385.38	1,127.72
Fuels				
Coal	MJ	96.34	51.40	246.08
Oil	MJ	63.86	67.68	148.31
Gas	MJ	7.82	5.66	867,738.00
Hydro	MJ	1.06	0.63	8.52
Nuclear	MJ	17.00	10.86	86.40
Lignite	MJ	0.00	0	0.02
Sulphur	MJ	0.00	0	1.46
Recovered	MJ	-0.01	0	-1.62
Total fuels	MJ	186.07	136.23	575.94
Feedstock				
Coal	MJ	30.78	14.64	546.52
Oil	MJ	0.33	0.15	1.90
Gas	MJ	0.05	0.02	0.03
Wood	MJ	7.1	233.79	3.16
Total feedstock	MJ	38.26	248.60	551.61
Total fuels & feedstock	MJ	224.33	384.83	1,127.55
Raw materials				
Barytes	mg	14	8	12
Bauxite	mg	13,775	6,552	245,022
Brine	mg	1,881	906	30,930
CaSO ₄	mg	622,638	276,649	276,652
Clay	mg	8	3	3
Fe-Mn	mg	7,804	3,712	138,830
Fluorspar	mg	250	119	4,448
Iron ore	mg	2,389,000	1,136,400	42,425,400
Lead	mg	163	92	135
Limestone	mg	75,645,900	33,630,900	48,233,500
Met coal	mg	982,747	467,464	17,451,500
Sand	mg	36,388,300	16,168,000	16,168,100
Water	mg	209,670,400	96,265,700	668,774,100
Wood	mg	470,986	15,503,000	209,464
Zinc	mg	120	53	53
Shale	mg	1,762,800	783,233	783,241
NaCl	mg	25	11	15
Nitrogen	mg	2	1	130
Air	mg	7,505	4,100	2,398,700
Sulphur	mg	494	270	157,924
Air emissions				
Dust	mg	107,828	54,371	304,863
CO	mg	32,817	38,971	85,618
CO ₂	mg	19,897,300	12,350,100	49,971,000
SO _x	mg	313,713	163,432	3,705,300
H ₂ S	mg	209	93	93
NO _x	mg	81,173	70,043	380,732
HCl	mg	1,890	1,006	4,825
F	mg	45	21	1,159
HF	mg	82	45	235
HC	mg	19,881	19,090	108,057
Lead	mg	0	2	0
Metals	mg	15	8	101
CH ₄	mg	38,066	19,835	305,223
Water emissions				
COD	mg	71	73	170
BOD	mg	59	63	139
Salt	mg	0	0	1
Acid	mg	530	270	8,005
Metal ions	mg	139	72	1,982
Cl ⁻	mg	6	3	35
F ⁻	mg	7	3	126
Suspended solids	mg	346,447	163,138	5,482,300
Hydrocarbons	mg	69	68	175
Phenol	mg	59	63	139
Dissolved solids	mg	1	0	2
Na ⁺	mg	0	0	1
Other organics	mg	1	1	1
Solid waste				
Paper	mg	59	26	26
Plastics	mg	5,776	2,569	2,574
Metals	mg	16,064	7,144	7,144
Organics	mg	8	5	7
Other refuse	mg	331,067	147,235	147,235
Mineral waste	mg	8,555,700	3,962,100	65,254,300
Slags/ash	mg	247,815	132,935	3,227,800
Industrial waste	mg	8,356,500	3,717,200	3,726,300
Unregulated chemicals	mg	40	18	18

Appendix 39

Gypsum plaster products

Production and road delivery of bagged finishing plaster /kg



Gross inputs and outputs associated with the production and road delivery of bagged finishing plaster /kg
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.65
Electricity - delivered	0.28
Oil fuels - production & delivery	0.09
Oil fuels - delivered	0.59
Oil fuels - feedstock	0.02
Other fuels - production & delivery	0.09
Other fuels - delivered	0.75
Other fuels - feedstock	0.28
Total energy	2.74

Raw materials	mg
Bauxite	13
Brine	236
CaSO ₄	1,268,500
Clay	557
Fe-Mn	7
Iron ore	2,139
Lead	4
Limestone	752
Met coal	879
Water	464,772
Wood	21,348
Air	488
Sulphur	32

Air emissions	mg
Dust	385
CO	416
CO ₂	137,610
SO _x	1,076
NO _x	1,269
HCl	11
HF	1
HC	548
CH ₄	1,276


Primary fuels	MJ
Coal	0.59
Oil	0.73
Gas	0.87
Hydro	0.01
Nuclear	0.23
Total fuels	2.43
Primary feedstocks	MJ
Coal	0.03
Wood	0.25
Total feedstocks	0.28
Total fuels & feedstocks	2.71

Water emissions	mg
COD	60
BOD	6
Acid	2
Metals	1
Suspended solids	120,220
HC	1
Phenol	1

Solid waste	mg
Plastic containers	3
Paper	4,214
Plastics	27
Metals	373
Other ref	7,635
Mineral waste	7,505
Slags/ash	1,358
Industrial waste	80

Packaging & delivery: Packed in paper sacks - delivered on wooden pallets
Road transport (notional): rigid vehicle, 20 tonne payload, returning empty, average return distance 300 km

Appendix 40 Gypsum plaster products
Production and road delivery of 12.5 mm plasterboard - per square metre



Gross inputs and outputs associated with the production and road delivery of 12.5 mm plasterboard - per sq.metre
 Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	9.97
Electricity - delivered	4.30
Oil fuels - production & delivery	0.98
Oil fuels - delivered	6.55
Oil fuels - feedstock	0.21
Other fuels - production & delivery	2.14
Other fuels - delivered	18.96
Other fuels - feedstock	11.93
Total energy	55.04

Primary fuels	MJ
Coal	8.90
Oil	8.55
Gas	21.56
Hydro	0.25
Nuclear	3.60
Total fuels	42.85
Primary feedstocks	MJ
Coal	0.22
Oil	0.05
Gas	0.03
Wood	10.88
Total feedstocks	11.98
Total fuels & feedstocks	54.84

Raw materials	mg
Barytes	3
Bauxite	100
Brine	26,862
CaSO ₄	10,819,900
Clay	56,854
Fe-Mn	57
Fluorspar	2
Iron ore	16,924
Lead	42
Limestone	11,401
Met coal	6,959
Sand	1,897
Water	43,302,900
Wood	1,224,100
Zinc	15
Phosphate	4,732
Nitrogen	2
Air	55,161
Sulphur	2,971

Water emissions	mg
COD	6,102
BOD	705
Salt	1
Acid	28
NO _x	54
Metals	43
Cl ⁻	27
Sulphur	4
Dissolved organics	2
Suspended solids	1,032,800
HC	14
Phenol	7
Dissolved solids	165
Phosphorus	10
Other N	89

Air emissions	mg
Dust	7,080
CO	4,382
CO ₂	2,308,900
SO _x	17,815
H ₂ S	31
Mercaptan	9
NO _x	22,468
HCl	182
F	1
HF	9
HC	11,162
Metals	3
CH ₄	30,631


Solid waste	mg
Plastic containers	283
Paper	430,074
Plastics	959
Metals	1,497
Organics	2
Other ref	7,649
Mineral waste	140,262
Slags/ash	20,043
Industrial waste	940

Packaging & delivery: Steel strapping - delivered on wooden pallets
Road transport(notional): rigid vehicle, 20 tonne payload, returning empty, average return distance 300 km

Appendix 41

Glass products

Production and road delivery of 6 mm flat glass - per square metre



Gross inputs and outputs associated with the production and road delivery of 6 mm flat glass - per square metre
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	18.91
Electricity - delivered	8.00
Oil fuels - production & delivery	13.24
Oil fuels - delivered	91.64
Oil fuels - feedstock	0.22
Other fuels - production & delivery	8.40
Other fuels - delivered	78.99
Other fuels - feedstock	0.27
Total energy	219.69

Primary fuels	MJ
Coal	17.37
Oil	102.41
Gas	87.92
Hydro	0.32
Nuclear	6.69
Other	4.35
Sulphur	0.35
Recovered	-0.38
Total fuels	219.02

Raw materials	mg
Barytes	4
Bauxite	129
Brine	5,009,100
Fe-Mn	73
Fluorspar	2
Iron ore	22,382
Lead	41
Limestone	4,065,500
Met coal	9,200
Sand	11,250,000
Water	73,518,200
Sodium chloride	3
Dolomite	2,700,000
Nitrogen	23
Air	568,707
Sulphur	37,442

Primary feedstocks	MJ
Coal	0.29
Total feedstocks	0.29
Total fuels & feedstocks	219.31

Water emissions	mg
COD	106
BOD	95
Salt	1,481
Acid	55
Metals	17
Cl ⁻	5,192
Suspended solids	316,230
HC	98
Phenol	95
Dissolved solid	3,308
Na ⁺	4
SO ₄ ²⁻	4

Air emissions	mg
Dust	27,803
CO	7,296
CO ₂	12,861,400
SO ₂	159,882
NO _x	202,331
HCl	1,269
F	106
HF	137
HC	50,992
Metals	84
CH ₄	115,806


Solid waste	mg
Plastics	4
Organics	2
Mineral waste	7,981,800
Slags/ash	37,555
Industrial waste	94,580

Packaging & delivery: Bulk delivery, no packaging
Road transport (notional): rigid vehicle, 20 tonne payload, returning empty, average return distance 600 km

Appendix 42

Glass products

Production and road delivery of glass fibre wool 150 mm depth - per square metre



Gross inputs and outputs associated with the production and road delivery of 150 mm glass fibre wool / metre³
Totals may not agree because of rounding errors

Energy		MJ
Electricity - production & delivery		24.73
Electricity - delivered		10.47
Oil fuels - production & delivery		1.09
Oil fuels - delivered		7.25
Oil fuels - feedstock		0.29
Other fuels - production & delivery		7.68
Other fuels - delivered		65.38
Other fuels - feedstock		2.92
Total energy		119.81

Raw materials		mg
Bauxite		44
Brine		1,280,900
Clay		15
Fe-Mn		21
Iron ore		6,409
Lead		9
Limestone		889,366
Met coal		2,636
Sand		1,800,000
Water		31,218,600
Wood		576
Phosphate		21
Sodium chloride		80
Ulexite		180,000
Granite		270,000
Dolomite		630,000
Nitrogen		193
Air		223,141
Sulphur		14,688

Air emissions		mg
Dust		18,867
CO		3,142
CO ₂		6,045,700
SO _x		34,691
NO _x		60,772
NH ₃		9
HCl		470
F		21
HF		22
HC		33,789
CHO		2
Organics		23
Metals		7
H ₂ SO ₄		1
CH ₄		107,325

Primary fuels		MJ
Coal		22.07
Oil		11.71
Gas		74.18
Hydro		0.41
Nuclear		8.61
Sulphur		0.14
Recovered		-0.15
Total fuels		116.96

Primary feedstocks		MJ
Coal		0.08
Oil		0.24
Gas		2.85
Total feedstocks		3.18
Total fuels & feedstocks		120.14

Water emissions		mg
COD		17
BOD		11
Salt		381
Acid		57
Metals		22
Cl ⁻		1,288
Dissolved organics		14
Suspended solids		115,603
Detergent/oil		1
HC		15
Phenol		11
Dissolved solid		857
Na ⁺		70
SO ₄ ²⁻		51
Phosphate/P ₂ O ₅		6
Other organic		1


Solid waste		mg
Paper		114
Plastics		2
Metals		10
Other refuse		206
Mineral waste		1,892,300
Slags/ash		47,189
Industrial waste		5,367
Unregulated chemicals		28

Packaging & delivery: Bulk delivery, no packaging
Road transport (notional): rigid vehicle, 20 tonne payload, returning empty, average return distance 600 km

Appendix 43

Glass products

Production and road delivery of glass fibre wool, 50 mm depth, - per m²



Schematic flow diagram for the production of 50 mm glass fibre wool
All flows are in kg per square metre

Gross inputs and outputs associated with the production and road delivery of glass fibre wool, depth 50 mm, per m²

Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	8.24
Electricity - delivered	3.49
Oil fuels - production & delivery	0.36
Oil fuels - delivered	2.42
Oil fuels - feedstock	0.10
Other fuels - production & delivery	2.56
Other fuels - delivered	21.79
Other fuels - feedstock	0.97
Total energy	39.94

Raw materials	mg
Bauxite	15
Brine	426,964
Clay	5
Fe-Mn	7
Iron ore	2,136
Lead	3
Limestone	296,455
Met coal	879
Sand	600,007
Water	10,406,200
Wood	192
Phosphate	7
Sodium chloride	26
Ulexite	60,000
Granite	90,000
Dolomite	210,000
Nitrogen	64
Air	74,380
Sulphur	4,896

Air emissions	mg
Dust	6,289
CO	1,047
CO ₂	2,015,200
SO _x	11,564
NO _x	20,257
NH ₃	3
HCl	157
F	7
HF	8
HC	11,263
CHO	1
Organics	8
Metals	2
CH ₄	35,775

Primary fuels	MJ
Coal	7.36
Oil	3.90
Gas	24.73
Hydro	0.14
Nuclear	2.87
Sulphur	0.05
Recovered	-0.05
Total fuels	38.99

Primary feedstocks	MJ
Coal	0.03
Oil	0.08
Gas	0.95
Total feedstocks	1.06
Total fuels & feedstocks	40.05

Water emissions	mg
COD	6
BOD	4
Salt	127
Acid	19
Metals	7
Cl ⁻	429
Dissolved organics	5
Suspended solids	38,534
HC	5
Phenol	4
Dissolved solid	286
Na ⁺	23
SO ₄ ²⁻	17
Phosphate/P ₂ O ₅	2

Solid waste	mg
Paper	38
Metals	3
Other refuse	69
Mineral waste	630,769
Slags/ash	15,730
Industrial waste	1,789
Unregulated chemicals	9


Packaging & delivery: Bulk delivery, no packaging

Road transport (notional): rigid vehicle, 20 tonne payload, returning empty, average return distance 600 km

Appendix 44

Timber and timber products

Production and road delivery of kiln dried sawn timber (UK Sitka spruce) - per kg



Gross inputs and outputs associated with the production and road delivery of kiln dried sawn timber (UK Sitka spruce - per kg Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.76
Electricity - delivered	0.32
Oil fuels - production & delivery	0.42
Oil fuels - delivered	2.89
Oil fuels - feedstock	0.01
Other fuels - delivered	0.01
Other fuels - feedstock	19.19
Total energy	23.60

Raw materials	mg
Bauxite	5
Brine	2
Fe-Mn	3
Iron ore	955
Lead	2
Limestone	340
Met coal	393
Water	187,728
Wood	1,271,600
Air	59
Sulphur	4

Air emissions	mg
Dust	507
CO	2,019
CO ₂	287,273
SO _x	1,550
NO _x	2,784
HCl	13
HF	1
HC	842
CH ₄	211

Primary fuels	MJ
Coal	0.69
Oil	3.25
Gas	0.17
Hydro	0.01
Nuclear	0.27
Total fuels	4.40
Primary feedstocks	MJ
Coal	0.01
Wood	19.18
Total feedstocks	19.19
Total fuels & feedstocks	23.59

Water emissions	mg
COD	3
BOD	3
Acid	2
Metals	1
Suspended solids	137
HC	3
Phenol	3

Solid waste	mg
Mineral waste	6,082
Slags/ash	1,509
Industrial waste	356

Packaging & delivery: Bulk delivery, no packaging
Road transport: articulated vehicles returning empty
 a) delivery of green timber to sawmill - 22 tonne payload, return distance 193 km
 b) delivery of kiln dried sawn timber to customer - 23 tonne payload, return distance 322 km

Appendix 45

Timber and timber products


Production and road delivery of kiln dried sawn timber (UK Sitka spruce) lintels - per 1500 mm

Gross inputs and outputs associated with the production and road delivery of kiln dried timber lintels - per lintel (derived from figures shown in Appendix 44) Totals may not agree because of rounding errors			
Input/output	Units	Lintel dimensions/weight	
		(100 x 143) mm	(125 x 143) mm
Energy		9.6216 kg	12.0270 kg
Electricity - production & delivery	MJ	7.31	9.13
Electricity - delivered	MJ	3.09	3.87
Oil fuels - production & delivery	MJ	4.03	5.03
Oil fuels - delivered	MJ	27.85	34.81
Oil fuels - feedstock	MJ	0.08	0.10
Other fuels - production & delivery	MJ	0.01	0.02
Other fuels - delivered	MJ	0.09	0.11
Other fuels - feedstock	MJ	184.61	230.77
Total energy	MJ	227.07	283.84
Fuels			
Coal	MJ	6.66	8.33
Oil	MJ	31.31	39.13
Gas	MJ	1.68	2.09
Hydro	MJ	0.12	0.15
Nuclear	MJ	2.56	3.20
Total fuels	MJ	42.33	52.91
Feedstock			
Coal	MJ	0.12	0.15
Wood	MJ	184.5	230.63
Total feedstock	MJ	184.62	230.78
Total fuels & feedstock	MJ	226.95	283.69
Raw materials			
Barytes	mg	1	2
Bauxite	mg	53	66
Brine	mg	19	24
Fe-Mn	mg	30	38
Fluorspar	mg	0	1
Iron ore	mg	9,189	11,486
Lead	mg	15	19
Limestone	mg	3,270	4,088
Met coal	mg	3,780	4,725
Sand	mg	3	3
Water	mg	1,806,200	2,257,800
Wood	mg	12,234,800	15,293,600
Air	mg	572	715
Sulphur	mg	38	47
Air emissions			
Dust	mg	4,879	6,099
CO	mg	19,428	24,284
CO2	mg	2,764,000	3,455,000
SOx	mg	14,914	18,642
NOx	mg	26,790	33,488
HCl	mg	129	161
HF	mg	6	8
HC	mg	8,097	10
Lead	mg	2	2
Metals	mg	1	1
CH4	mg	2,030	2,538
Water emissions			
COD	mg	33	41
BOD	mg	29	36
Acid	mg	18	23
Metal ions	mg	6	7
Suspended solids	mg	1,314	1,643
Hydrocarbons	mg	30	38
Phenol	mg	29	36
Solid waste			
Plastics	mg	2	2
Organics	mg	0	1
Mineral waste	mg	58,523	73,154
Slags/ash	mg	14,519	18,148
Industrial waste	mg	3,424	4,280

Appendix 46

Timber and timber products

Production and road delivery of kiln dried sawn timber (imported Swedish Redwood) - per kg



Gross inputs and outputs associated with the production and road delivery of kiln dried sawn timber (imported Swedish Redwood) - per kg Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.36
Electricity - delivered	0.33
Oil fuels - production & delivery	0.90
Oil fuels - delivered	5.56
Oil fuels - feedstock	0.01
Other fuels - production & delivery	0.02
Other fuels - delivered	0.11
Other fuels - feedstock	16.95
Total energy	24.25

Raw materials	mg
Bauxite	9
Brine	3
Fe-Mn	5
Iron ore	1,598
Lead	3
Limestone	565
Met coal	657
Water	252,200
Wood	1,928,300
Air	99
Sulphur	7

Air emissions	mg
Dust	400
CO	3,787
CO ₂	453,484
SO _x	1,908
NO _x	4,957
HCl	1
HC	1,681
CH ₄	25

Primary fuels	MJ
Coal	0.15
Oil	6.21
Gas	0.26
Hydro	0.19
Nuclear	0.46
Total fuels	7.27
Primary feedstocks	MJ
Coal	0.02
Wood	16.94
Total feedstocks	16.96
Total fuels & feedstocks	24.23

Water emissions	mg
COD	7
BOD	2
Acid	6
Metals	1
Suspended solids	208
HC	56
Phenol	1

Solid waste	mg
Plastic containers	608
Plastics	2
Mineral waste	3,207
Slags/ash	443
Industrial waste	587

Packaging & delivery: Bulk delivery, no packaging

Road transport: articulated vehicles returning empty

a) delivery of green timber to sawmill - 22 tonne payload, return distance 193 km


b) delivery of kiln dried sawn timber: (sawmill - seaport + UK seaport - customer), 23 tonne payload, return distance 579 km

Sea transport: 100,000 dwt bulk carrier fully loaded, distance one way 1,770 km

Appendix 47

Timber and timber products

Production and road delivery of wooden window frames and doors - Swedish Redwood - per kg



Gross inputs and outputs associated with the production and road delivery of wooden window frames/doors - Swedish Redwood) - per kg Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	0.69
Electricity - delivered	0.57
Oil fuels - production & delivery	1.52
Oil fuels - delivered	9.42
Oil fuels - feedstock	0.04
Other fuels - production & delivery	0.04
Other fuels - delivered	10.18
Other fuels - feedstock	16.98
Total energy	39.43

Raw materials	mg
Bauxite	24
Brine	9
Fe-Mn	14
Iron ore	4,182
Lead	7
Limestone	1,479
Met coal	1,720
Water	454,480
Wood	3,065,400
Air	261
Sulphur	17

Air emissions	mg
Dust	727
CO	7,120
CO ₂	1,920,300
SO _x	3,409
NO _x	10,600
HCl	4
HC	2,846
CH ₄	91

Primary fuels	MJ
Coal	0.36
Oil	10.51
Gas	0.46
Hydro	0.31
Nuclear	0.77
Wood	9.99
Total fuels	22.39
Primary feedstocks	MJ
Coal	0.05
Wood	16.94
Total feedstocks	16.99
Total fuels & feedstocks	39.38

Water emissions	mg
COD	12
BOD	4
Acid	11
Metals	2
Suspended solids	544
HC	90
Phenol	2

Solid waste	mg
Plastic containers	967
Plastics	3
Mineral waste	8,154
Slags/ash	1,016
Industrial waste	1,004

Packaging & delivery: Bulk delivery, no packaging

Road transport: articulated vehicle, 13.5 tonne payload, returning empty, average return distance 644 km

Appendix 48

Timber and timber products

Production and road delivery of kiln dried wooden window frames/doors & door frames - per item

Gross inputs and outputs associated with the production and road delivery of kiln dried wooden window frames/doors & door frames - per item (derived from figures shown in Appendix 47) Totals may not agree because of rounding errors			
Input/output	Units	Overall window/ door frame dimensions/mm : Wood Input/kg	
		Casement window frame (1200 x 1200) mm : 17.5 kg	External kitchen door & door frame (762 x 1981) mm : 30.8 kg
Energy			
Electricity - production & delivery	MJ	12.12	21.33
Electricity - delivered	MJ	9.90	17.42
Oil fuels - production & delivery	MJ	26.53	46.70
Oil fuels - delivered	MJ	164.83	290.10
Oil fuels - feedstock	MJ	0.66	1.17
Other fuels - production & delivery	MJ	0.64	1.13
Other fuels - delivered	MJ	178.22	313.67
Other fuels - feedstock	MJ	297.19	523.06
Total energy	MJ	690.10	1,214.57
Fuels			
Coal	MJ	6.22	10.94
Oil	MJ	183.97	323.79
Gas	MJ	7.97	14.02
Hydro	MJ	5.38	9.47
Nuclear	MJ	13.43	23.64
Wood	MJ	174.81	307.66
Total fuels	MJ	391.78	689.53
Feedstock			
Coal	MJ	0.94	1.66
Oil	MJ	0.01	0.01
Wood	MJ	296.39	521.64
Total feedstock	MJ	297.34	523.31
Total fuels & feedstock	MJ	689.12	1,212.84
Raw materials			
Barytes	mg	12	21
Bauxite	mg	423	744
Brine	mg	158	278
Fe-Mn	mg	240	422
Fluorspar	mg	8	14
Iron ore	mg	73,190	128,814
Lead	mg	128	226
Limestone	mg	25,890	45,566
Met coal	mg	30,106	52,987
Sand	mg	0	2
Water	mg	7,953,400	13,998,000
Wood	mg	53,645,200	94,415,500
Air	mg	4,565	8,034
Sulphur	mg	300	529
Air emissions			
Dust	mg	12,723	22,392
CO	mg	124,606	219,307
CO2	mg	33,604,900	59,144,600
SOx	mg	59,656	104,995
NOx	mg	185,501	326,481
HCl	mg	73	129
F	mg	2	4
HF	mg	3	6
HC	mg	49,801	87,649
Lead	mg	8	14
Metals	mg	8	13
CH4	mg	1,597	2,810
Water emissions			
COD	mg	204	359
BOD	mg	68	120
Acid	mg	186	327
Metal ions	mg	40	71
Suspended solids	mg	9,529	16,771
Hydrocarbons	mg	1,570	2,764
Phenol	mg	29	51
Solid waste			
Plastic containers	mg	16,919	29,778
Paper	mg	3	5
Plastics	mg	49	87
Metals	mg	11	19
Organics	mg	7	12
Mineral waste	mg	142,690	251,134
Slags\ash	mg	17,778	31,290
Industrial waste	mg	17,576	30,934


Packaging & delivery: Bulk delivery, no packaging

Road transport: articulated vehicle, 13.5 tonne payload, returning empty, average return distance 644 km

Appendix 49

Metals and metal products

Production and road delivery of electrolytically refined copper metal - per kg ⁴⁷



Gross inputs and outputs associated with the production and road delivery of electrolytically refined copper metal - per kg Totals may not agree because of rounding error

Energy		MJ
Electricity - production & delivery		14.66
Electricity - delivered		6.20
Oil fuels - production & delivery		4.97
Oil fuels - delivered		34.50
Oil fuels - feedstock		0.01
Other fuels - delivered		0.01
Other fuels - feedstock		0.01
Total energy		60.35

Raw materials		mg
Bauxite		12
Brine		3
Fe-Mn		7
Iron ore		2,081
Lead		2
Limestone		777
Met coal		856
Sand		5
Water		2,580,300
Copper		1,000,000
Air		125
Sulphur		8

Air emissions		mg
Dust		6,615
CO		1,700
CO ₂		3,997,600
SO _x		66,715
NO _x		18,210
HCl		259
HF		13
HC		5,996
Metals		134
CH ₄		3,824

Primary fuels		MJ
Coal		13.15
Oil		39.61
Gas		2.18
Hydro		0.24
Nuclear		5.14
Total fuels		60.32

Primary feedstocks		MJ
Coal		0.03
Total feedstocks		0.03
Total fuels & feedstocks		60.35

Water emissions		mg
COD		42
BOD		37
Acid		634
Metals		61
Suspended solids		550
HC		39
Phenol		37


Solid waste		mg
Mineral waste		3,093,600
Slags/ash		228,046
Industrial waste		4,333

Packaging & delivery: Bulk delivery, no packaging
 Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 50

Metals and metal products

Production and road delivery of lead metal - per kg ⁴⁷



Gross inputs and outputs associated with the production and road delivery of lead metal - per kg

Totals may not agree because of rounding error

Energy	MJ
Electricity - production & delivery	4.73
Electricity - delivered	2.00
Oil fuels - production & delivery	0.54
Oil fuels - delivered	3.73
Oil fuels - feedstock	0.01
Other fuels - production & delivery	4.04
Other fuels - delivered	35.91
Other fuels - feedstock	0.01
Total energy	50.96

Raw materials	mg
Bauxite	5
Brine	2
Fe-Mn	3
Iron ore	928
Lead	1,000,000
Limestone	342
Met coal	382
Sand	2
Water	553,287
Air	57
Sulphur	4

Air emissions	mg
Dust	4,941
CO	504
CO ₂	2,570,100
SO _x	10,688
NO _x	29,989
HCl	84
HF	4
HC	17,895
Metals	4
CH ₄	54,593

Primary fuels	MJ
Coal	4.25
Oil	4.77
Gas	40.18
Hydro	0.08
Nuclear	1.66
Total fuels	50.94
Primary feedstocks	MJ
Coal	0.01
Total feedstocks	0.01
Total fuels & feedstocks	50.95

Water emissions	mg
COD	5
BOD	4
Acid	11
Metals	3
Suspended solids	204
HC	5
Phenol	4

Solid waste	mg
Mineral waste	1,030,600
Slags/ash	9,084
Industrial waste	523


Packaging & delivery: Bulk delivery, no packaging

Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 51

Metals and metal products

Production and road delivery of zinc metal - per kg ⁴⁷



Gross inputs and outputs associated with the production and road delivery of zinc metal - per kg

Totals may not agree because of rounding error

Energy	MJ
Electricity - production & delivery	4.73
Electricity - delivered	2.00
Oil fuels - production & delivery	0.54
Oil fuels - delivered	3.73
Oil fuels - feedstock	0.01
Other fuels - production & delivery	4.04
Other fuels - delivered	35.91
Other fuels - feedstock	0.01
Total energy	50.96

Raw materials	mg
Bauxite	5
Brine	2
Fe-Mn	3
Iron ore	928
Lead	1
Limestone	342
Met coal	382
Sand	2
Water	553,287
Zinc	1,000,000
Air	57
Sulphur	4

Air emissions	mg
Dust	4,941
CO	504
CO ₂	2,570,100
SO _x	10,688
NO _x	29,989
HCl	84
HF	4
HC	17,895
Metals	4
CH ₄	54,593

Primary fuels	MJ
Coal	4.25
Oil	4.77
Gas	40.18
Hydro	0.08
Nuclear	1.66
Total fuels	50.94
Primary feedstocks	MJ
Coal	0.01
Total feedstocks	0.01
Total fuels & feedstocks	50.95

Water emissions	mg
COD	5
BOD	4
Acid	11
Metals	3
Suspended solids	204
HC	5
Phenol	4

Solid waste	mg
Mineral waste	1,030,600
Slags/ash	9,084
Industrial waste	523


Packaging & delivery: Bulk delivery, no packaging

Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 52

Metals and metal products

Production and road delivery of cold rolled steel - per kg ⁴⁷



Gross inputs and outputs associated with the production and road delivery of cold rolled steel - per kg
Totals may not agree because of rounding error

Energy	MJ
Electricity - production & delivery	6.99
Electricity - delivered	3.05
Oil fuels - production & delivery	0.36
Oil fuels - delivered	2.44
Oil fuels - feedstock	0.06
Other fuels - production & delivery	0.80
Other fuels - delivered	2.04
Other fuels - feedstock	16.90
Total energy	32.64

Raw materials	mg
Bauxite	7,587
Brine	956
Fe-Mn	4,299
Fluorspar	138
Iron ore	1,313,600
Lead	2
Limestone	464,589
Met coal	540,356
Sand	3
Water	18,281,400
Nitrogen	4
Air	76,187
Sulphur	5,016

Air emissions	mg
Dust	8,161
CO	2,256
CO ₂	1,306,500
SO _x	113,249
NO _x	10,947
HCl	127
F	36
HF	6
HC	3,152
Metals	3
CH ₄	9,158

Primary fuels	MJ
Coal	6.46
Oil	3.81
Gas	2.65
Hydro	0.26
Nuclear	2.50
Total fuels	15.67
Primary feedstocks	MJ
Coal	16.92
Oil	0.06
Total feedstocks	16.98
Total fuels & feedstocks	32.65

Water emissions	mg
COD	4
BOD	4
Acid	247
Metals	61
Cl ⁻	1
F ⁻	4
Suspended solids	169,237
HC	5
Phenol	4

Solid waste	mg
Mineral waste	1,951,800
Slags/ash	99,013
Industrial waste	426

Packaging & delivery: Bulk delivery, no packaging
Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 53

Metals and metal products


Production and road delivery of I-section rolled steel joists, flange & web thickness 7 mm - per 1500 mm

Gross inputs and outputs associated with the production and road delivery of rolled steel joists - per 1500 mm (derived from figures shown in Appendix 52) Totals may not agree because of rounding errors			
Input/output	Units	RSJ size mm	
		100 x 143	125 x 143
Energy			
Electricity - production & delivery	MJ	190.82	219.84
Electricity - delivered	MJ	83.16	95.80
Oil fuels - production & delivery	MJ	9.85	11.34
Oil fuels - delivered	MJ	66.62	76.74
Oil fuels - feedstock	MJ	1.74	2.00
Other fuels - production & delivery	MJ	21.86	25.18
Other fuels - delivered	MJ	55.58	64.03
Other fuels - feedstock	MJ	461.13	531.24
Total energy	MJ	890.75	1,026.18
Fuels			
Coal	MJ	176.22	203.01
Oil	MJ	103.96	119.76
Gas	MJ	72.22	83.21
Hydro	MJ	6.98	8.04
Nuclear	MJ	68.35	78.74
Lignite	MJ	0.02	0.02
Sulphur	MJ	1.27	1.46
Recovered	MJ	-1.40	-1.62
Total fuels	MJ	427.6	492.62
Feedstock			
Coal	MJ	461.81	532.03
Oil	MJ	1.52	1.75
Gas	MJ	0.01	0.01
Total feedstock	MJ	463.34	533.79
Total fuels & feedstock			
	MJ	890.94	1,026.41
Raw materials			
Barytes	mg	5	6
Bauxite	mg	207,054	238,536
Brine	mg	26,083	30,048
CaSO ₄	mg	3	3
Fe-Mn	mg	117,318	135,156
Fluorspar	mg	3,759	4,330
Iron ore	mg	35,849,600	41,300,500
Lead	mg	55	63
Limestone	mg	12,678,900	14,606,700
Met coal	mg	14,746,600	16,988,800
Sand	mg	89	108
Water	mg	498,908,600	574,766,200
Shale	mg	7	9
NaCl	mg	4	4
Nitrogen	mg	112	129
Air	mg	2,079,200	2,395,300
Sulphur	mg	136,881	157,702
Air emissions			
Dust	mg	222,727	256,591
CO	mg	61,570	70,932
CO ₂	mg	35,654,700	41,075,900
SO _x	mg	3,090,600	3,560,600
NO _x	mg	298,752	344,177
HCl	mg	3,454	3,980
F	mg	988	1,138
HF	mg	172	198
HC	mg	86,011	99,088
Metals	mg	82	95
CH ₄	mg	249,926	287,926
Water emissions			
COD	mg	120	138
BOD	mg	98	112
Salt	mg	1	1
Acid	mg	6,734	7,758
Metal ions	mg	1,664	1,918
Cl ⁻	mg	28	32
F ⁻	mg	106	123
Suspended solids	mg	4,618,600	5,320,800
Hydrocarbons	mg	125	144
Phenol	mg	98	112
Dissolved solids	mg	2	2
Na ⁺	mg	1	1
Solid waste			
Plastics	mg	5	6
Organics	mg	3	3
Mineral waste	mg	53,266,400	61,365,400
Slags/lash	mg	2,702,100	3,113,000
Industrial waste	mg	11,620	13,387

Appendix 54

Metals and metal products

Production and road delivery of pickled hot rolled steel coil - per kg ⁴⁷



Gross inputs and outputs associated with the production and road delivery of pickled hot rolled steel coil - per kg
Totals may not agree because of rounding error

Energy	MJ
Electricity - production & delivery	5.93
Electricity - delivered	2.60
Oil fuels - production & delivery	0.36
Oil fuels - delivered	2.43
Oil fuels - feedstock	0.06
Other fuels - production & delivery	0.80
Other fuels - delivered	1.99
Other fuels - feedstock	16.90
Total energy	31.06

Raw materials	mg
Bauxite	7,587
Brine	956
Fe-Mn	4,299
Fluorspar	138
Iron ore	1,313,600
Lead	2
Limestone	464,561
Met coal	540,327
Sand	3
Water	18,146,200
Nitrogen	4
Air	76,183
Sulphur	5,016

Air emissions	mg
Dust	7,714
CO	2,193
CO ₂	1,216,300
SO _x	112,088
NO _x	10,554
HCl	108
F	36
HF	5
HC	3,066
Metals	3
CH ₄	8,816

Primary fuels	MJ
Coal	5.51
Oil	3.65
Gas	2.56
Hydro	0.24
Nuclear	2.14
Total fuels	14.09
Primary feedstocks	MJ
Coal	16.92
Oil	0.06
Total feedstocks	16.98
Total fuels & feedstocks	31.07

Water emissions	mg
COD	4
BOD	3
Acid	244
Metals	60
Cl ⁻	1
F ⁻	4
Suspended solids	169,209
HC	4
Phenol	3


Solid waste	mg
Mineral waste	1,945,200
Slags/ash	97,004
Industrial waste	408

Packaging & delivery: Bulk delivery, no packaging
Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 55

Metals and metal products

Production and road delivery of hot dip galvanised steel (610 g/m²) - general products - per kg



Gross Inputs and outputs associated with the production and road delivery of hot dip galvanised steel products (610 g/m²) - per kg * Totals may not agree because of rounding error

Energy		Primary fuels	
	MJ		MJ
Electricity - production & delivery	6.55	Coal	6.07
Electricity - delivered	2.86	Oil	4.24
Oil fuels - production & delivery	0.43	Gas	6.46
Oil fuels - delivered	2.90	Hydro	0.25
Oil fuels - feedstock	0.07	Nuclear	2.35
Other fuels - production & delivery	1.19	Total fuels	19.37
Other fuels - delivered	5.46	Primary feedstocks	
Other fuels - feedstock	16.91	Coal	16.93
Total energy	36.36	Oil	0.06
		Total feedstocks	16.99
		Total fuels & feedstocks	36.35
Raw materials		Water emissions	
	mg		mg
Bauxite	7,591	COD	5
Brine	12,000	BOD	4
Fe-Mn	4,301	Acid	246
Fluorspar	138	Metals	61
Iron ore	1,314,300	Cl ⁻	12
Lead	3	F ⁻	4
Limestone	464,823	Suspended solids	169,316
Met coal	540,630	HC	5
Sand	3	Phenol	4
Water	18,455,000	Solid waste	
Zinc	55,670	Mineral waste	2,005,800
Nitrogen	6	Slags/ash	112,421
Air	125,742	Industrial waste	474
Sulphur	8,279		
Air emissions			
	mg		
Dust	8,298		
CO	2,407		
CO ₂	1,485,800		
SO ₂	113,201		
NO ₂	13,664		
HCl	119		
F	36		
HF	6		
HC	4,852		
Metals	3		
CH ₄	14,141		


* Input of zinc ammonium chloride omitted for lack of production data

Packaging & delivery: Bulk delivery, no packaging
 Road transport: articulated vehicle, 20 tonne payload, returning with full load, average return distance 322 km

Appendix 56

Metals and metal products

Production and road delivery of galvanised steel coil (275 g/m²) - suitable for use in combined lintel production - per kg



Gross inputs and outputs associated with the production and road delivery of galvanised steel coil (275 g/m²) - per kg
Totals may not agree because of rounding error


Energy		Primary fuels	
	MJ		MJ
Electricity - production & delivery	7.67	Coal	7.07
Electricity - delivered	3.33	Oil	4.22
Oil fuels - production & delivery	0.40	Gas	4.85
Oil fuels - delivered	2.73	Hydro	0.27
Oil fuels - feedstock	0.07	Nuclear	2.74
Other fuels - production & delivery	1.02	Other	0.04
Other fuels - delivered	4.03	Total fuels	19.18
Other fuels - feedstock	16.90	Primary feedstocks	MJ
Total energy	36.17	Coal	16.93
		Oil	0.06
		Total feedstocks	16.99
		Total fuels & feedstocks	36.17
Raw materials		Water emissions	
	mg		mg
Bauxite	7,591	COD	5
Brine	959	BOD	4
Fe-Mn	4,301	Acid	248
Fluorspar	138	Metals	61
Iron ore	1,314,300	Cr	2
Lead	3	F	4
Limestone	464,819	Suspended solids	169,331
Met coal	540,613	HC	6
Sand	4	Phenol	4
Water	18,344,200		
Zinc	28,099		
Nitrogen	15,739		
Air	76,238		
Sulphur	5,019		
Chromium	1		
Air emissions		Solid waste	
	mg		mg
Dust	8,615	Mineral waste	1,985,000
CO	2,408	Slags/ash	104,498
CO ₂	1,484,800	Industrial waste	475
SO _x	114,225		
NO _x	12,817		
HCl	138		
F	36		
HF	7		
HC	4,188		
Metals	3		
CH ₄	12,242		

Packaging & delivery: Bulk delivery, no packaging
Road transport: articulated vehicle, 23.5 tonne payload, returning empty, average return distance 290 km

Appendix 57

Metals and metal products

Production and road delivery of insulated galvanised steel combined lintels - per 1500 mm length (base 270 mm., inner leaf 125 mm., outer leaf 95 mm., cavity 50 mm., web 143 mm)



Gross inputs and outputs associated with the production and road delivery of insulated galvanised steel box lintels- per 1500 mm length Totals may not agree because of rounding error

Energy		MJ
Electricity - production & delivery		123.26
Electricity - delivered		53.35
Oil fuels - production & delivery		8.14
Oil fuels - delivered		52.77
Oil fuels - feedstock		3.82
Other fuels - production & delivery		15.04
Other fuels - delivered		64.19
Other fuels - feedstock		229.72
Total energy		550.28

Raw materials		mg
Barytes		4
Bauxite		102,641
Brine		12,969
CaSO ₄		2
Fe-Mn		58,133
Fluorspar		1,863
Iron ore		17,764,000
Lead		39
Limestone		6,282,800
Met coal		7,307,100
Sand		56
Water		251,507,700
Zinc		379,758
Shale		5
NaCl		521
Nitrogen		212,706
Air		1,030,500
Sulphur		67,843
Chromium		16

Air emissions		mg
Dust		126,423
CO		45,674
CO ₂		23,455,500
SO _x		1,571,400
NO _x		201,358
HCl		2,215
F		490
HF		110
HC		69,146
Organics		691
Metals		46
Methane		183,073
Pentane		1,033

Primary fuels		MJ
Coal		112.95
Oil		77.34
Gas		78.05
Hydro		3.93
Nuclear		43.86
Lignite		0.01
Other		0.48
Sulphur		0.63
Recovered		-0.70
Total fuels		316.55

Primary feedstocks		MJ
Coal		228.84
Oil		3.65
Gas		1.25
Total feedstocks		233.74
Total fuels & feedstocks		550.29

Water emissions		mg
COD		352
BOD		147
Acid		3,414
Metals		867
NH ₄ ⁺		5
Cl ⁻		88
F ⁻		53
Dissolved organics		971
Suspended solids		2,289,100
Detergent/oil		5
HC		137
Phenol		71
Dissolved solids		48
Na ⁺		112
SO ₄ ²⁻		3


Solid waste		mg
Plastics		4
Organics		2
Mineral waste		26,949,500
Slags/ash		1,449,300
Industrial waste		13,610
Regulated chemicals		10
Unregulated chemicals		209

Packaging & delivery: Bulk delivery, no packaging
Road transport: articulated vehicle, 15 tonne payload, returning empty, average return distance 1127 km

Appendix 58

Metals and metal products

Production and rail delivery of 6063 cast aluminium alloy ingot-per kg⁴⁷



Gross inputs and outputs associated with the production and rail delivery of 6063 cast aluminum alloy Ingot- per kg
Totals may not agree because of rounding error

Energy	MJ
Electricity - production & delivery	25.85
Electricity - delivered	56.54
Oil fuels - production & delivery	7.03
Oil fuels - delivered	21.01
Oil fuels - feedstock	28.49
Other fuels - production & delivery	1.51
Other fuels - delivered	13.29
Other fuels - feedstock	0.04
Total energy	153.74

Raw materials	mg
Bauxite	3,910,500
Brine	491,716
CaSO ₄	9
Fe-Mn	13
Fluorspar	71,030
Iron ore	3,903
Lead	3
Limestone	20,227
Magnesium	5,278
Met coal	1,606
Sand	9,666
Water	41,687,900
Shale	26
NaCl	19
Nitrogen	570
Air	454,018
Sulphur	29,892

Air emissions	
Dust	26,223
CO	515,380
CO ₂	4,349,600
SO _x	42,772
NO _x	23,477
HCl	150
F	5,662
HF	8
HC	11,678
Metals	21
CH ₄	21,903

Primary fuels	MJ
Coal	7.78
Oil	26.49
Gas	17.38
Hydro	70.62
Nuclear	2.98
Sulphur	0.28
Recovered	-0.31
Total fuels	125.22
Primary feedstocks	MJ
Coal	0.05
Oil	28.48
Total feedstocks	28.53
Total fuels & feedstocks	153.75

Water emissions	mg
COD	57
BOD	51
Salt	3
Acid	70
Metals	20
Cl ⁻	502
F ⁻	2,011
Suspended solids	378,480
HCl	52
Phenol	51
Dissolved solids	9
Na ⁺	3
SO ₄ ²⁻	1


Solid waste	mg
Mineral waste	6,050,900
Slags/ash	93,924
Industrial waste	6,401

Packaging & delivery: Bulk delivery, no packaging
Rail freight transport: single journey - distance 483 km

Appendix 59

Metals and metal products

Production and road delivery of extruded 6063 aluminium alloy ingot-per kg



Gross inputs and outputs associated with the production and road delivery of extruded 6063 aluminum alloy Ingot-per kg Totals may not agree because of rounding error

Energy	MJ
Electricity - production & delivery	34.56
Electricity - delivered	60.52
Oil fuels - production & delivery	7.45
Oil fuels - delivered	23.77
Oil fuels - feedstock	28.70
Other fuels - production & delivery	1.67
Other fuels - delivered	14.72
Other fuels - feedstock	0.07
Total energy	171.46

Raw materials	mg
Bauxite	3,936,400
Brine	494,967
CaSO ₄	9
Fe-Mn	22
Fluorspar	71,499
Iron ore	6,873
Lead	7
Limestone	21,425
Magnesium	5,313
Met coal	2,827
Sand	9,732
Water	42,809,500
Shale	26
NaCl	19
Nitrogen	574
Air	457,196
Sulphur	30,101

Air emissions	
Dust	49,942
CO	519,906
CO ₂	5,353,700
SO _x	55,206
NO _x	28,885
HCl	301
F	5,699
HF	15
HC	13,373
Metals	24
CH ₄	26,218

Primary fuels	MJ
Coal	15.44
Oil	30.71
Gas	19.37
Hydro	71.22
Nuclear	5.96
Sulphur	0.28
Recovered	-0.31
Total fuels	142.68
Primary feedstocks	MJ
Coal	0.09
Oil	28.66
Total feedstocks	28.75
Total fuels & feedstocks	171.43

Water emissions	mg
COD	62
BOD	55
Salt	3
Acid	90
Metals	26
Cl ⁻	505
F ⁻	2,024
Suspended solids	381,508
HC	57
Phenol	55
Dissolved solids	9
Na ⁺	3
SO ₄ ²⁻	1


Solid waste	mg
Mineral waste	6,147,300
Slags/ash	110,826
Industrial waste	6,888

Packaging & delivery: Bulk delivery, no packaging
Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 60

Metals and metal products

Production and road delivery of anodised 6063 aluminium profiles-per kg



Gross inputs and outputs associated with the production and road delivery of anodised 6063 aluminum profiles - per kg Totals may not agree because of rounding error

Energy	MJ
Electricity - production & delivery	65.33
Electricity - delivered	73.56
Oil fuels - production & delivery	7.70
Oil fuels - delivered	24.89
Oil fuels - feedstock	29.31
Other fuels - production & delivery	2.82
Other fuels - delivered	21.53
Other fuels - feedstock	0.98
Total energy	226.12

Raw materials	mg
Bauxite	3,937,100
Brine	524,472
CaSO ₄	10
Fe-Mn	33
Fluorspar	71,693
Iron ore	11,366
Lead	8
Limestone	23,654
Magnesium	5,314
Met coal	4,670
Sand	308,017
Water	129,257,300
Phosphate	745,625
Shale	28
NaCl	43,680
Nitrogen	606
Air	2,809,700
Sulphur	80,886

Air emissions	mg
Dust	65,525
CO	522,303
CO ₂	8,608,500
SO _x	95,101
NO _x	43,880
NH ₃	3
HCl	916
F	5,700
HF	44
HC	17,521
Metals	29
CH ₄	41,111
Hydrogen	251

Primary fuels	MJ
Coal	46.40
Oil	36.39
Gas	24.63
Hydro	71.75
Nuclear	16.69
Sulphur	0.75
Recovered	-0.83
Total fuels	195.78
Primary feedstocks	MJ
Coal	0.15
Oil	29.27
Gas	0.88
Total feedstocks	30.30
Total fuels & feedstocks	226.08

Water emissions	mg
COD	88
BOD	61
Salt	3
Acid	195
Metals	57
Cl ⁻	2,681
F ⁻	2,024
Suspended solids	458,084
HC	67
Phenol	61
Dissolved solids	13
Na ⁺	307
SO ₄ ²⁻	290
Al ³⁺	317

Solid waste	mg
Mineral waste	6,546,700
Slags/ash	245,587
Industrial waste	134,116
Regulated chemicals	1
Unregulated chemicals	518


Packaging & delivery: Bulk delivery, no packaging

Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 61

Metals and metal products

Production and road delivery of polyester resin powder coated 6063 aluminium profiles-per kg Al



Gross inputs and outputs associated with the production and road delivery of polyester resin powder coated 6063 aluminum profiles- per kg * Totals may not agree because of rounding error

Energy	MJ
Electricity - production & delivery	43.83
Electricity - delivered	64.45
Oil fuels - production & delivery	7.96
Oil fuels - delivered	25.30
Oil fuels - feedstock	30.74
Other fuels - production & delivery	3.37
Other fuels - delivered	29.02
Other fuels - feedstock	0.90
Total energy	205.56

Raw materials	mg
Barytes	3
Bauxite	3,936,400
Brine	527,534
CaSO ₄	9
Fe-Mn	35
Fluorspar	87,301
Iron ore	10,735
Lead	27
Limestone	29,933
Magnesium	5,313
Met coal	4,403
Rutile	40,195
Sand	9,740
Water	80,893,400
Shale	27
NaCl	341
Nitrogen	703
Air	609,447
Sulphur	40,125
Chromium	1,290

Air emissions	mg
Dust	55,048
CO	522,217
CO ₂	7,013,000
SO _x	67,052
NO _x	44,053
HCl	463
F	5,699
HF	23
HC	22,969
Organics	566
Metals	26
CH ₄	48,639

Primary fuels	MJ
Coal	23.72
Oil	33.87
Gas	35.79
Hydro	71.38
Nuclear	9.19
Sulphur	0.37
Recovered	-0.41
Total fuels	173.90

Primary feedstocks	MJ
Coal	0.14
Oil	30.69
Gas	0.78
Total feedstocks	31.61
Total fuels & feedstocks	205.51

Water emissions	mg
COD	254
BOD	118
Salt	4
Acid	121
Metals	40
Cl ⁻	584
F	2,024
Dissolved organics	791
Suspended solids	388,518
Detergent/oil	1
HC	85
Phenol	57
Dissolved solids	47
Na ⁺	97
SO ₄ ²⁻	5

Solid waste	mg
Plastics	3
Organics	1
Mineral waste	6,266,700
Slags/ash	128,468
Industrial waste	78,574
Regulated chemicals	8
Unregulated chemicals	98


* Input of potassium ferricyanide omitted for lack of data

Packaging & delivery: Bulk delivery, no packaging
Road transport: rigid vehicle, 500 kg tonne payload, returning empty, average return distance 80 km

Appendix 62

Metals and metal products

Production and road delivery of anodised aluminium casement window frames (1200 mm x 1200 mm) -per frame



Gross inputs and outputs associated with the production and road delivery of anodised aluminium casement window frames (1200mm x 1200mm) opening - per frame Totals may not agree because of rounding errors

Energy		MJ	
Electricity - production & delivery		787.98	
Electricity - delivered		872.57	
Oil fuels - production & delivery		120.38	
Oil fuels - delivered		431.11	
Oil fuels - feedstock		401.74	
Other fuels - production & delivery		35.36	
Other fuels - delivered		393.83	
Other fuels - feedstock		218.84	
Total energy		3,261.14	

Raw materials		mg	
Barytes		18	
Bauxite		45,949,100	
Brine		6,785,200	
CaSO ₄		115	
Fe-Mn		574	
Fluorspar		836,708	
Iron ore		190,476	
Lead		198	
Limestone		296,564	
Magnesium		62,014	
Met coal		78,283	
Sand		3,594,800	
Water		1,600,900,000	
Wood		37,425,300	
Phosphate		8,701,900	
Shale		324	
NaCl		509,772	
Nitrogen		7,080	
Air		32,878,200	
Sulphur		949,752	

Air emissions		mg	
Dust		783,100	
CO		6,184,800	
CO ₂		128,761,200	
SO _x		1,206,000	
NO _x		674,459	
NH ₃		41	
CL ₂		1	
HCl		11,050	
F		66,526	
HF		534	
HC		256,953	
Lead		5	
Metals		367	
CH ₄		511,581	
Hydrogen		2,929	

Primary fuels		MJ	
Coal		561.42	
Oil		588.38	
Gas		317.29	
Hydro		841.35	
Nuclear		210.18	
Lignite		0.05	
Wood		121.95	
Sulphur		8.79	
Recovered		-9.75	
Total fuels		2,639.68	

Primary feedstocks		MJ	
Coal		2.46	
Oil		400.78	
Gas		10.33	
Wood		206.77	
Total feedstocks		620.34	
Total fuels & feedstocks		3,260.02	

Water emissions		mg	
COD		1,270	
BOD		845	
Salt		33	
Acid		2,441	
Metals		711	
Cl ⁻		31,957	
F		23,626	
Suspended solids		5,354,000	
HC		1,969	
Phenol		815	
Dissolved solids		154	
Na ⁺		3,582	
SO ₄ ²⁻		3,380	
Al ³⁺		3,700	


Solid waste		mg	
Plastic containers		11,804	
Paper		2	
Plastics		45	
Metals		7	
Organics		11	
Mineral waste		76,620,700	
Slags/ash		2,911,800	
Industrial waste		1,587,800	
Regulated chemicals		17	
Unregulated chemicals		6,048	

Packaging & delivery: Bulk delivery, no packaging
Road transport: rigid vehicle, 5.5 tonne payload, returning empty, average return distance 32 km

Appendix 63

Metals and metal products

Production and road delivery of powder painted aluminium casement window frames (1200 mm x 1200 mm) - per frame



Gross inputs and outputs associated with the production and road delivery of anodised aluminium casement window frames (1200mm x 1200mm) opening - per frame Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	536.97
Electricity - delivered	766.26
Oil fuels - production & delivery	123.41
Oil fuels - delivered	435.89
Oil fuels - feedstock	418.42
Other fuels - production & delivery	41.71
Other fuels - delivered	480.63
Other fuels - feedstock	217.85
Total energy	3,021.14

Raw materials	mg
Barytes	39
Bauxite	45,940,800
Brine	6,821,000
CaSO ₄	110
Fe-Mn	598
Fluorspar	1,018,900
Iron ore	183,107
Lead	417
Limestone	369,835
Magnesium	62,004
Met coal	75,174
Rutile	469,104
Sand	113,683
Water	1,036,400,000
Wood	37,425,300
Shale	311
NaCl	3,985
Nitrogen	8,210
Air	7,200,100
Sulphur	474,035
Chromium	15,059

Air emissions	mg
Dust	660,828
CO	6,183,800
CO ₂	110,139,600
SO _x	878,615
NO _x	676,479
NH ₃	1
CL ₂	1
HCl	5,759
F	66,514
HF	289
HC	320,536
Organics	6,603
Lead	5
Metals	337
CH ₄	599,430

Primary fuels	MJ
Coal	296.69
Oil	558.97
Gas	447.51
Hydro	837.04
Nuclear	122.62
Lignite	0.03
Wood	121.95
Sulphur	4.39
Recovered	-4.86
Total fuels	2,384.34

Primary feedstocks	MJ
Coal	2.36
Oil	417.30
Gas	9.15
Wood	206.77
Total feedstocks	635.59
Total fuels & feedstocks	3,019.92

Water emissions	mg
COD	3,207
BOD	1,514
Salt	49
Acid	1,587
Metals	505
Cl ⁻	7,483
F	23,622
Dissolved organics	9,230
Suspended solids	4,542,100
Detergent/oil	14
HC	2,176
Phenol	776
Dissolved solids	549
Na ⁺	1,138
SO ₄ ²⁻	64


Solid waste	mg
Plastic containers	11,804
Paper	2
Plastics	67
Metals	7
Organics	23
Mineral waste	73,352,100
Slags/ash	1,545,000
Industrial waste	939,611
Regulated chemicals	92
Unregulated chemicals	1,142

Packaging & delivery: Bulk delivery, no packaging
Road transport: rigid vehicle, 5.5 tonne payload, returning empty, average return distance 32 km

Appendix 64

Metals and metal products

Production and road delivery of anodised aluminium external kitchen door and frame (762 mm x 1981 mm) -per door/frame



Gross inputs and outputs associated with the production and road delivery of anodised aluminium external kitchen door and frame, (762mm x 1981mm) opening - per door/frame		Totals may not agree because of rounding errors	
Energy		MJ	
Electricity - production & delivery	1,270.48	Primary fuels	
Electricity - delivered	1,382.60	Coal	912.83
Oil fuels - production & delivery	182.59	Oil	878.62
Oil fuels - delivered	631.18	Gas	520.09
Oil fuels - feedstock	636.95	Hydro	1,319.82
Other fuels - production & delivery	60.18	Nuclear	339.17
Other fuels - delivered	589.17	Lignite	0.08
Other fuels - feedstock	290.18	Wood	145.81
Total energy	5,043.34	Sulphur	13.87
		Recovered	-15.37
		Total fuels	4,114.91
Raw materials		Primary feedstocks	
	mg	Coal	3.73
Barytes	84,196	Oil	635.57
Bauxite	72,123,300	Gas	40.34
Brine	10,429,100	Wood	247.23
CaSO ₄	180	Total feedstocks	926.86
Chalk	94,919	Total fuels & feedstocks	5,041.78
Clay	71		
Fe-Mn	865	Water emissions	
Fluorspar	1,313,300		mg
Iron ore	288,401	COD	3,683
Lead	290	BOD	1,415
Limestone	503,565	Salt	60
Magnesium	97,338	Acid	4,108
Met coal	118,279	NO _x	1
Rutile	89,098	Metals	1,452
Sand	5,644,000	Cl ⁻	116,435
Water	2,519,300,000	F	37,084
Wood	44,746,500	Dissolved organics	2,217
Phosphate	13,658,800	Suspended solids	8,432,900
Shale	510	Detergent/oil	81
NaCl	1,868,500	HC	2,674
Nitrogen	11,117	Organo-chlorine	5
Air	51,709,000	Phenol	1,248
Sulphur	1,497,500	Dissolved solids	934
		Other N	5
		Na ⁺	13,218
		SO ₄ ²⁻	7,679
		Phosphate/P ₂ O ₅	1
		Other organic	11
		Al ³⁺	5,807
Air emissions		Solid waste	
	mg		mg
Dust	1,241,100	Plastic containers	14,113
CO	9,681,900	Paper	525
CO ₂	197,212,800	Plastics	60
SO _x	1,913,000	Metals	9
NO _x	1,036,200	Organics	16
NH ₃	67	Mineral waste	120,581,600
CL ₂	4	Slags/ash	4,637,200
HCl	18,102	Industrial waste	2,508,200
F	104,421	Regulated chemicals	5,567
HF	856	Unregulated chemicals	27,832
HC	418,044		
Lead	6		
Metals	573		
CH ₄	803,020		
Hydrogen	4,598		
Organo-chlorine	807		


Packaging & delivery: Bulk delivery, no packaging

Road transport: rigid vehicle, 5.5 tonne payload, returning empty, average return distance 32 km

Appendix 65

Metals and metal products

Production and road delivery of powder painted aluminium external kitchen door and frame (762 x 1981) mm -per door/frame



Gross inputs and outputs associated with the production and road delivery of powder painted aluminium external kitchen door and frame, (762mm x 1981mm) opening - per door/frame Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	876.48
Electricity - delivered	1,215.73
Oil fuels - production & delivery	187.35
Oil fuels - delivered	638.70
Oil fuels - feedstock	663.13
Other fuels - production & delivery	70.15
Other fuels - delivered	726.48
Other fuels - feedstock	288.62
Total energy	4,666.63

Raw materials	mg
Barytes	84,229
Bauxite	72,110,300
Brine	10,485,200
CaSO ₄	172
Chalk	94,919
Clay	71
Fe-Mn	902
Fluorspar	1,599,200
Iron ore	276,835
Lead	634
Limestone	618,573
Magnesium	97,324
Met coal	113,399
Rutile	825,417
Sand	180,031
Water	1,633,400,000
Wood	44,746,500
Shale	489
NaCl	1,074,600
Nitrogen	12,891
Air	11,403,700
Sulphur	750,797
Chromium	23,637

Air emissions	mg
Dust	1,049,200
CO	9,680,300
CO ₂	167,983,900
SO ₂	1,399,200
NO _x	1,039,300
NH ₃	4
CL ₂	4
HCl	9,797
F	104,403
HF	472
HC	517,846
Organics	10,364
Lead	6
Metals	527
CH ₄	940,911
Organo-chlorine	807

Primary fuels	MJ
Coal	497.30
Oil	832.45
Gas	724.48
Hydro	1,313.05
Nuclear	201.75
Lignite	0.04
Wood	145.81
Sulphur	6.95
Recovered	-7.7
Total fuels	3,714.12

Primary feedstocks	MJ
Coal	3.58
Oil	661.50
Gas	38.49
Wood	247.23
Total feedstocks	950.80
Total fuels & feedstocks	4,664.92

Water emissions	mg
COD	6,724
BOD	2,465
Salt	85
Acid	2,769
NO ₃ ⁻	1
Metals	1,130
Cl ⁻	78,020
F ⁻	37,077
Dissolved organics	16,704
Suspended solids	7,158,600
Detergent/oil	103
HCl	2,999
Organo-chlorine	5
Phenol	1,188
Dissolved solids	1,554
Other N	5
Na ⁺	9,382
SO ₄ ²⁻	2,474
Phosphate/P ₂ O ₅	1
Other organic	11


Solid waste	mg
Plastic containers	14,113
Paper	525
Plastics	94
Metals	9
Organics	34
Mineral waste	115,451,100
Slags/ash	2,491,800
Industrial waste	1,490,700
Regulated chemicals	5,685
Unregulated chemicals	20,132

Packaging & delivery: Bulk delivery, no packaging
Road transport: rigid vehicle, 5.5 tonne payload, returning empty, average return distance 32 km

Appendix 66

Metals and metal products

Production and road delivery of 100 mm half round cast aluminium rainwater guttering -per metre



Gross inputs and outputs associated with the production and road delivery of 100 mm half round cast aluminum guttering- per metre Totals may not agree because of rounding error

Energy		MJ
Electricity - production & delivery		31.34
Electricity - delivered		68.53
Oil fuels - production & delivery		8.55
Oil fuels - delivered		25.71
Oil fuels - feedstock		34.54
Other fuels - production & delivery		2.37
Other fuels - delivered		20.91
Other fuels - feedstock		0.05
Total energy		192.00

Raw materials		mg
Bauxite		4,740,000
Brine		596,021
CaSO ₄		11
Fe-Mn		18
Fluorspar		86,097
Iron ore		5,394
Lead		4
Limestone		24,752
Magnesium		6,398
Met coal		2,219
Sand		11,716
Water		50,549,900
Shale		31
NaCl		23
Nitrogen		691
Air		550,366
Sulphur		36,235

Primary fuels		MJ
Coal		9.45
Oil		32.37
Gas		26.41
Hydro		85.59
Nuclear		3.62
Sulphur		0.34
Recovered		-0.37
Total fuels		157.41

Primary feedstocks		MJ
Coal		0.07
Oil		34.52
Total feedstocks		34.59
Total fuels & feedstocks		192.00

Water emissions		mg
COD		70
BOD		62
Salt		3
Acid		85
Metals		24
Cl ⁻		608
F ⁻		2,437
Suspended solids		458,849
HC		63
Phenol		62
Dissolved solids		11
Na ⁺		4
SO ₄ ²⁻		1

Air emissions		
Dust		104,191
CO		624,869
CO ₂		5,543,200
SO _x		52,022
NO _x		32,266
HCl		183
F		6,863
HF		10
HC		16,500
Metals		26
CH ₄		33,696


Solid waste		mg
Mineral waste		7,335,500
Slags/ash		113,912
Industrial waste		7,787

Packaging & delivery: Bulk delivery, no packaging
 Road transport: rigid vehicle, 20000 kg payload, returning empty, average return distance 322 km

Appendix 67

Metals and metal products

Production and road delivery of 68 mm (external diameter) aluminium drainpipe -per metre




Gross Inputs and outputs associated with the production and road delivery of 68 mm diameter aluminium drainpipe- per metre Totals may not agree because of rounding error	
Energy MJ	
Electricity - production & delivery	30.72
Electricity - delivered	55.66
Oil fuels - production & delivery	6.87
Oil fuels - delivered	21.70
Oil fuels - feedstock	26.67
Other fuels - production & delivery	1.60
Other fuels - delivered	14.12
Other fuels - feedstock	0.06
Total energy	157.39
Raw materials mg	
Bauxite	3,658,700
Brine	460,056
CaSO ₄	9
Fe-Mn	20
Fluorspar	66,456
Iron ore	5,995
Lead	6
Limestone	19,771
Magnesium	4,938
Met coal	2,466
Sand	9,045
Water	39,653,500
Shale	24
NaCl	17
Nitrogen	534
Air	424,926
Sulphur	27,976
Air emissions	
Dust	52,436
CO	483,075
CO ₂	4,852,700
SO _x	49,338
NO _x	26,504
HCl	255
F	5,297
HF	13
HC	12,484
Metals	22
CH ₄	24,659
Primary fuels MJ	
Coal	13.10
Oil	27.92
Gas	18.42
Hydro	66.18
Nuclear	5.06
Sulphur	0.26
Recovered	-0.29
Total fuels	130.65
Primary feedstocks MJ	
Coal	0.08
Oil	26.64
Total feedstocks	26.72
Total fuels & feedstocks	157.37
Water emissions mg	
COD	57
BOD	50
Salt	3
Acid	81
Metals	23
Cl ⁻	470
F	1,881
Suspended solids	354,525
HC	53
Phenol	51
Dissolved solids	8
Na ⁺	3
SO ₄ ²⁻	1
Solid waste mg	
Mineral waste	5,704,600
Slags/ash	100,340
Industrial waste	6,333

Packaging & delivery: Bulk delivery, no packaging
Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 68

Plastics and plastic products

Production and road delivery of suspension PVC granules - per kg



Gross inputs and outputs associated with the production and bulk road delivery of suspension PVC granules - per kg¹
 Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	9.08
Electricity - delivered	3.84
Oil fuels - production & delivery	2.54
Oil fuels - delivered	1.94
Oil fuels - feedstock	16.12
Other fuels - production & delivery	3.20
Other fuels - delivered	14.03
Other fuels - feedstock	14.43
Total energy	65.17

Raw materials	mg
Bauxite	223
Brine	2
Fe-Mn	2
Iron ore	922
Lead	1
Limestone	15,195
Met coal	227
Sand	1,000
Water	20,015,500
NaCl	675,000
Air	35
Sulphur	2

Air emissions	mg
Dust	3,917
CO	2,637
CO ₂	1,762,900
SO ₂	13,092
NO _x	15,179
Cl ₂	1
HCl	240
HC	19,057
Metals	3
CH ₄	9
Organo-chlorine	510

Primary fuels	MJ
Coal	8.15
Oil	4.81
Gas	18.32
Hydro	0.15
Nuclear	3.19
Total fuels	34.62
Primary feedstocks	MJ
Coal	0.02
Oil	16.11
Gas	14.42
Total feedstocks	30.55
Total fuels & feedstocks	65.17

Water emissions	mg
COD	1,100
BOD	80
Acid	170
Metals	200
Cl ⁻	42,000
Dissolved organics	1,400
Suspended solids	2,071
Detergent/oil	50
Organo-chlorine	3
Dissolved solids	420
Other N	3
Na ⁺	4,800
SO ₄ ²⁻	1,500

Solid waste	mg
Mineral waste	60,833
Slags/ash	12,045
Industrial waste	2,023
Regulated chemicals	3,500
Unregulated chemicals	11,000


¹ PVC production data: I. Boustead, *Ecoprofiles of the European polymer industry*, APME Report No. 6, Polyvinylchloride, April 1994.

Packaging & delivery: Bulk delivery, no packaging
 Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 69

Plastics and plastic products

Production and road delivery of a PVC formulation used in the production of window/door frame profiles - per kg



Gross inputs and outputs associated with the production and road delivery of a PVC formulation used in the production of window/door frame profiles- per kg Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	10.16
Electricity - delivered	4.30
Oil fuels - production & delivery	2.93
Oil fuels - delivered	4.14
Oil fuels - feedstock	16.61
Other fuels - production & delivery	2.87
Other fuels - delivered	13.31
Other fuels - feedstock	12.05
Total energy	66.38

Raw materials	mg
Barytes	42,726
Bauxite	189
Brine	46,803
Chalk	48,182
Clay	35
Fe-Mn	7
Iron ore	2,511
Lead	4
Limestone	22,087
Met coal	911
Rutile	45,227
Sand	804
Water	23,995,500
Wood	750
NaCl	542,182
Nitrogen	3
Air	72,508
Sulphur	4,774

Air emissions	mg
Dust	4,724
CO	2,717
CO ₂	2,019,300
SO _x	17,138
NO _x	16,097
NH ₃	2
Cl ₂	1
HCl	248
HF	3
HC	17,090
Metals	5
CH ₄	4,189
Organo-chlorine	410

Primary fuels	MJ
Coal	9.38
Oil	7.39
Gas	17.20
Hydro	0.17
Nuclear	3.57
Sulphur	0.04
Recovered	-0.05
Total fuels	37.70

Primary feedstocks	MJ
Coal	0.04
Oil	16.59
Gas	12.02
Total feedstocks	28.65
Total fuels & feedstocks	66.35

Water emissions	mg
COD	896
BOD	71
Salt	4
Acid	144
Metals	163
Cl ⁻	33,783
Dissolved organics	1,125
Suspended solids	15,693
Detergent/oil	40
Hydrocarbons	7
Organo-chlorine	2
Phenol	7
Dissolved solids	347
Other N	2
Na ⁺	3,856
SO ₄ ²⁻	1,205


Solid waste	mg
Paper	265
Mineral waste	125,302
Slags/ash	20,332
Industrial waste	12,511
Regulated chemicals	2,811
Unregulated chemicals	9,124

Packaging & delivery: Bulk delivery, no packaging
Road transport: articulated tanker, 22.5 tonne payload, returning empty, average return distance 869 km

Appendix 70

Plastics and plastic products

Production and road delivery of a PVC formulation used in the production of surface rainwater drainage systems - per kg



Gross inputs and outputs associated with the production and road delivery of a PVC formulation used in the production of surface rainwater drainage systems- per kg

Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	9.70
Electricity - delivered	4.11
Oil fuels - production & delivery	2.29
Oil fuels - delivered	2.34
Oil fuels - feedstock	13.93
Other fuels - production & delivery	2.79
Other fuels - delivered	12.29
Other fuels - feedstock	12.48
Total energy	59.92

Raw materials	mg
Barytes	21,613
Bauxite	202
Brine	6,916
Chalk	129,500
Clay	18
Fe-Mn	7
Iron ore	2,384
Lead	4
Limestone	18,363
Met coal	849
Sand	864
Water	18,095,900
Wood	379
NaCl	582,748
Nitrogen	1
Air	36,734
Sulphur	2,418

Air emissions	mg
Dust	4,268
CO	2,756
CO ₂	1,747,200
SO _x	13,915
NO _x	14,327
Cl ₂	1
HCl	242
HF	2
HC	16,760
Metals	3
CH ₄	622
Organo-chlorine	440

Primary fuels	MJ
Coal	8.83
Oil	5.12
Gas	15.99
Hydro	0.16
Nuclear	3.40
Sulphur	0.02
Recovered	-0.02
Total fuels	33.50

Primary feedstocks	MJ
Coal	0.04
Oil	13.91
Gas	12.45
Total feedstocks	26.40
Total fuels & feedstocks	59.89

Water emissions	mg
COD	953
BOD	70
Salt	2
Acid	151
Metals	174
Cl ⁻	36,267
Dissolved organics	1,209
Suspended solids	16,753
Detergent/oil	43
Hydrocarbons	1
Organo-chlorine	3
Phenol	1
Dissolved solids	367
Other N	3
Na ⁺	4,144
SO ₄ ²⁻	1,295


Solid waste	mg
Paper	134
Mineral waste	71,725
Slags/ash	16,578
Industrial waste	11,954
Regulated chemicals	3,022
Unregulated chemicals	9,643

Packaging & delivery: Bulk delivery, no packaging
Road transport: articulated tanker, 22.5 tonne payload, returning empty, average return distance 869 km

Appendix 71

Plastics and plastic products

Production and road delivery of a PVC formulation used in the production of sewage pipes - per kg



Gross inputs and outputs associated with the production and road delivery of a PVC formulation used in the production of sewage pipes- per kg. Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	10.07
Electricity - delivered	4.26
Oil fuels - production & delivery	2.39
Oil fuels - delivered	2.40
Oil fuels - feedstock	14.55
Other fuels - production & delivery	2.92
Other fuels - delivered	12.84
Other fuels - feedstock	13.04
Total energy	62.45

Raw materials	mg
Barytes	22,526
Bauxite	210
Brine	7,208
Chalk	90,200
Clay	19
Fe-Mn	7
Iron ore	2,402
Lead	4
Limestone	19,140
Met coal	851
Sand	603
Water	18,894,600
Wood	395
NaCl	608,783
Nitrogen	2
Air	38,284
Sulphur	2,521

Air emissions	mg
Dust	4,428
CO	2,854
CO ₂	1,816,500
SO _x	14,438
NO _x	14,913
Cl ₂	1
HCl	252
HF	2
HC	17,495
Metals	3
CH ₄	631
Organo-chlorine	460

Primary fuels	MJ
Coal	9.16
Oil	5.30
Gas	16.70
Hydro	0.17
Nuclear	3.53
Sulphur	0.02
Recovered	-0.03
Total fuels	34.85

Primary feedstocks	MJ
Coal	0.04
Oil	14.53
Gas	13.01
Total feedstocks	27.57
Total fuels & feedstocks	62.42

Water emissions	mg
COD	996
BOD	73
Salt	2
Acid	158
Metals	182
Cl ⁻	37,887
Dissolved organics	1,263
Suspended solids	13,223
Detergent/oil	45
Hydrocarbons	1
Organo-chlorine	3
Phenol	1
Dissolved solids	384
Other N	3
Na ⁺	4,329
SO ₄ ²⁻	1,353


Solid waste	mg
Paper	140
Mineral waste	74,375
Slags/ash	17,180
Industrial waste	12,031
Regulated chemicals	3,157
Unregulated chemicals	10,073

Packaging & delivery: Bulk delivery, no packaging
Road transport: articulated tanker, 22.5 tonne payload, returning empty, average return distance 869 km

Appendix 72

Plastics and plastic products

Production and road delivery of extruded PVC window/door frame profiles - per kg



Gross inputs and outputs associated with the production and road delivery of extruded PVC window/door profiles - per kg Totals may not agree because of rounding errors

Energy		MJ	
Electricity - production & delivery		22.64	
Electricity - delivered		9.58	
Oil fuels - production & delivery		2.99	
Oil fuels - delivered		4.53	
Oil fuels - feedstock		16.62	
Other fuels - production & delivery		2.87	
Other fuels - delivered		13.33	
Other fuels - feedstock		12.08	
Total energy		84.64	

Raw materials		mg	
Barytes		42,726	
Bauxite		205	
Brine		46,808	
Chalk		48,182	
Clay		35	
Fe-Mn		16	
Iron ore		5,199	
Lead		7	
Limestone		23,072	
Met coal		2,017	
Rutile		45,227	
Sand		809	
Water		25,078,100	
Wood		750	
NaCl		542,182	
Nitrogen		3	
Air		72,673	
Sulphur		4,785	

Air emissions		mg	
Dust		9,950	
CO		3,726	
CO ₂		3,067,500	
SO _x		30,796	
NO _x		20,590	
NH ₃		2	
Cl ₂		1	
HCl		466	
HF		14	
HC		17,915	
Metals		6	
CH ₄		7,391	
Organo-chlorine		410	

Primary fuels		MJ	
Coal		20.47	
Oil		9.56	
Gas		17.62	
Hydro		0.38	
Nuclear		7.89	
Sulphur		0.04	
Recovered		-0.05	
Total fuels		55.92	


Primary feedstocks		MJ	
Coal		0.07	
Oil		16.59	
Gas		12.02	
Total feedstocks		28.69	
Total fuels & feedstocks		84.61	

Water emissions		mg	
COD		899	
BOD		73	
Salt		4	
Acid		173	
Metals		172	
Cl ⁻		33,783	
Dissolved organics		1,125	
Suspended solids		16,260	
Detergent/oil		40	
Hydrocarbons		11	
Organo-chlorine		2	
Phenol		9	
Dissolved solids		347	
Other N		2	
Na ⁺		3,856	
SO ₄ ⁺		1,205	

Solid waste		mg	
Paper		265	
Plastics		1	
Mineral waste		205,484	
Slags/ash		44,018	
Industrial waste		12,753	
Regulated chemicals		2,811	
Unregulated chemicals		9,124	

Packaging & delivery: Bulk delivery, no packaging

Road transport: 7.5t rigid vehicle, 5.5 tonne payload, returning empty, average return distance 322 km

Appendix 73
Plastics and plastic products
Production and road delivery of PVC casement window frames (1200 x 1200 mm) - per frame

Gross Inputs and outputs associated with the production and road delivery of PVC casement window frames (1200mm x 1200mm) opening - per frame Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	475.57
Electricity - delivered	201.34
Oil fuels - production & delivery	62.21
Oil fuels - delivered	103.04
Oil fuels - feedstock	337.56
Other fuels - production & delivery	52.88
Other fuels - delivered	252.21
Other fuels - feedstock	228.53
Total energy	1,713.34

Raw materials	mg
Barytes	744,353
Bauxite	11,740
Brine	1,366,200
CaSO ₄	5
Chalk	839,403
Clay	611
Fe-Mn	4,908
Fluorspar	158
Iron ore	1,504,900
Lead	142
Limestone	902,357
Met coal	616,904
Rutile	787,927
Sand	14,121
Water	531,978,300
Wood	13,060
Zinc	59,456
Shale	15
NaCl	9,445,600
Nitrogen	60
Air	1,468,900
Sulphur	96,708

Air emissions	mg
Dust	215,018
CO	73,079
CO ₂	63,885,900
SO _x	766,508
NO _x	420,146
NH ₃	30
Cl ₂	14
HCl	9,544
F	41
HF	308
HC	335,126
Metals	143
CH ₄	183,983
Organo-chlorine	7,138

Primary fuels	MJ
Coal	429.06
Oil	208.55
Gas	335.38
Hydro	8.03
Nuclear	165.82
Lignite	0.04
Sulphur	0.90
Recovered	-0.99
Total fuels	1,146.79

Primary feedstocks	MJ
Coal	19.46
Oil	337.03
Gas	209.41
Wood	0.12
Total feedstocks	566.01
Total fuels & feedstocks	1,712.79

Water emissions	mg
COD	15,761
BOD	1,363
Salt	72
Acid	3,445
Metals	3,122
Cl ⁻	589,095
F ⁻	4
Dissolved organics	19,591
Suspended solids	466,790
Detergent/oil	700
Hydrocarbons	286
Organo-chlorine	42
Phenol	237
Dissolved solids	6,039
Other N	43
Na ⁺	67,169
SO ₄ ²⁻	20,990


Solid waste	mg
Plastic containers	3
Paper	4,624
Plastics	24
Metals	3
Organics	8
Mineral waste	6,192,200
Slags/ash	1,027,800
Industrial waste	232,021
Regulated chemicals	48,977
Unregulated chemicals	158,958

Packaging & delivery: Bulk delivery, no packaging
Road transport: 7.5t rigid vehicle, 5.5 tonne payload, returning empty, average return distance 32 km

Appendix 74

Plastics and plastic products

Production and road delivery of PVC external kitchen door and frame (762 mm x 1981 mm) -per door/frame



Gross inputs and outputs associated with the production and road delivery of PVC external kitchen door and frame (762mm x 1981mm) opening - per door/frame Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	681.55
Electricity - delivered	289.43
Oil fuels - production & delivery	84.23
Oil fuels - delivered	161.78
Oil fuels - feedstock	434.11
Other fuels - production & delivery	80.46
Other fuels - delivered	381.23
Other fuels - feedstock	468.25
Total energy	2,581.05

Raw materials	mg
Barytes	964,042
Bauxite	92,555
Brine	1,849,000
CaSO ₄	8
Chalk	1,087,100
Clay	792
Fe-Mn	50,183
Fluorspar	1,609
Iron ore	15,341,500
Lead	221
Limestone	5,905,100
Met coal	6,307,900
Rutile	1,020,500
Sand	18,321
Water	871,488,200
Wood	16,915
Zinc	644,197
Shale	22
NaCl	12,233,400
Nitrogen	139
Air	3,178,200
Sulphur	209,249

Air emissions	mg
Dust	362,464
CO	119,338
CO ₂	97,607,300
SO ₂	2,142,900
NO _x	681,699
NH ₃	39
Cl ₂	18
HCl	13,552
F	423
HF	458
HC	482,487
Metals	215
CH ₄	380,484
Organo-chlorine	9,243

Primary fuels	MJ
Coal	616.62
Oil	311.57
Gas	498.68
Hydro	12.91
Nuclear	238.33
Lignite	0.06
Sulphur	1.94
Recovered	-2.15
Total fuels	1,677.96
Primary feedstocks	MJ
Coal	197.72
Oil	433.26
Gas	271.21
Wood	0.15
Total feedstocks	902.35
Total fuels & feedstocks	2,580.31

Water emissions	mg
COD	20,456
BOD	1,801
Salt	94
Acid	6,965
Metals	4,661
Cl ⁻	763,038
F ⁻	46
Dissolved organics	25,373
Suspended solids	2,329,800
Detergent/oil	906
Hydrocarbons	415
Organo-chlorine	54
Phenol	342
Dissolved solids	7,823
Other N	56
Na ⁺	86,994
SO ₄ ²⁻	27,186


Solid waste	mg
Plastic containers	4
Paper	5,989
Plastics	35
Metals	4
Organics	12
Mineral waste	28,451,200
Slags/ash	2,474,600
Industrial waste	304,716
Regulated chemicals	63,432
Unregulated chemicals	205,872

Packaging & delivery: Bulk delivery, no packaging
Road transport: 7.5t rigid vehicle, 5.5 tonne payload, returning empty, average return distance 32 km

Appendix 75

Plastics and plastic products

Production and road delivery of a 68 mm (external diameter) PVC drainpipe - per metre



Gross inputs and outputs associated with the production and road delivery of a 68 mm diameter PVC drainpipe - per metre Totals may not agree because of rounding errors

Energy		MJ
Electricity - production & delivery		13.59
Electricity - delivered		5.75
Oil fuels - production & delivery		1.44
Oil fuels - delivered		1.67
Oil fuels - feedstock		8.54
Other fuels - production & delivery		1.71
Other fuels - delivered		7.54
Other fuels - feedstock		7.66
Total energy		47.88

Raw materials		mg
Barytes		13,238
Bauxite		133
Brine		4,239
Chalk		79,319
Clay		11
Fe-Mn		10
Iron ore		3,107
Lead		4
Limestone		11,851
Met coal		1,198
Sand		532
Water		11,746,900
Wood		232
NaCl		356,933
Air		22,602
Sulphur		1,488

Air emissions		mg
Dust		5,815
CO		2,306
CO ₂		1,712,100
SO _x		16,888
NO _x		11,527
Cl ₂		1
HCl		282
HF		8
HC		10,771
Metals		3
CH ₄		2,342
Organo-chlorine		270

Primary fuels		MJ
Coal		12.20
Oil		4.47
Gas		10.05
Hydro		0.23
Nuclear		4.73
Sulphur		0.01
Recovered		-0.02
Total fuels		31.68

Primary feedstocks		MJ
Coal		0.04
Oil		8.52
Gas		7.63
Total feedstocks		16.19
Total fuels & feedstocks		47.86

Water emissions		mg
COD		586
BOD		44
Salt		1
Acid		110
Metals		112
Cl ⁻		22,213
Dissolved organics		740
Suspended solids		10,609
Detergent/oil		26
Hydrocarbons		3
Organo-chlorine		2
Phenol		2
Dissolved solids		225
Other N		2
Na ⁺		2,538
SO ₄ ²⁻		793


Solid waste		mg
Paper		82
Mineral waste		93,043
Slags/ash		24,662
Industrial waste		7,470
Regulated chemicals		1,851
Unregulated chemicals		5,906

Packaging & delivery: Bulk delivery, no packaging
Road transport: 7.5t rigid vehicle, 5.5t payload, returning empty, average return distance 322 km

Appendix 76

Plastics and plastic products

Production and road delivery of a 100 mm half round PVC rainwater gutter - per metre



Gross inputs and outputs associated with the production and road delivery of a 100 mm half round PVC rainwater gutter - per metre Totals may not agree because of rounding errors

Energy		MJ
Electricity - production & delivery		12.20
Electricity - delivered		5.16
Oil fuels - production & delivery		1.29
Oil fuels - delivered		1.50
Oil fuels - feedstock		7.67
Other fuels - production & delivery		1.54
Other fuels - delivered		6.77
Other fuels - feedstock		6.88
Total energy		43.00

Raw materials		mg
Barytes		11,887
Bauxite		120
Brine		3,806
Chalk		71,225
Clay		10
Fe-Mn		9
Iron ore		2,790
Lead		4
Limestone		10,642
Met coal		1,075
Sand		478
Water		10,548,200
Wood		209
NaCl		320,511
Air		20,296
Sulphur		1,336

Air emissions		mg
Dust		5,222
CO		2,071
CO ₂		1,537,400
SO ₂		15,165
NO _x		10,351
HCl		253
HF		7
HC		9,672
Metals		2
CH ₄		2,103
Organo-chlorine		242

Primary fuels		MJ
Coal		10.95
Oil		4.01
Gas		9.03
Hydro		0.20
Nuclear		4.25
Sulphur		0.01
Recovered		-0.01
Total fuels		28.44

Primary feedstocks		MJ
Coal		0.04
Oil		7.65
Gas		6.85
Total feedstocks		14.54
Total fuels & feedstocks		42.98

Water emissions		mg
COD		526
BOD		40
Salt		1
Acid		99
Metals		101
Cl ⁻		19,947
Dissolved organics		665
Suspended solids		9,526
Detergent/oil		24
Hydrocarbons		3
Organo-chlorine		1
Phenol		2
Dissolved solids		202
Other N		1
Na ⁺		2,279
SO ₄ ²⁻		712


Solid waste		mg
Paper		74
Mineral waste		83,549
Slags/ash		22,145
Industrial waste		6,708
Regulated chemicals		1,662
Unregulated chemicals		5,304

Packaging & delivery: Bulk delivery, no packaging
Road transport: 7.5t rigid vehicle, 5.5t payload, returning empty, average return distance 322 km

Appendix 77

Plastics and plastic products

Production and road delivery of a 110 mm (external diameter) PVC sewer pipe - per metre



Gross inputs and outputs associated with the production and road delivery of a 110 mm (external diameter) PVC sewer pipe - per metre Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	39.23
Electricity - delivered	16.60
Oil fuels - production & delivery	4.25
Oil fuels - delivered	4.85
Oil fuels - feedstock	25.33
Other fuels - production & delivery	5.08
Other fuels - delivered	22.36
Other fuels - feedstock	22.72
Total energy	140.43

Raw materials	mg
Barytes	39,196
Bauxite	393
Brine	12,550
Chalk	156,948
Clay	32
Fe-Mn	27
Iron ore	8,857
Lead	13
Limestone	35,019
Met coal	3,404
Sand	1,578
Water	34,760,400
Wood	688
Shale	1
NaCl	1,059,300
Nitrogen	3
Air	66,902
Sulphur	4,405

Air emissions	mg
Dust	16,799
CO	6,721
CO ₂	4,984,600
SO _x	48,886
NO _x	33,767
Cl ₂	2
HCl	817
HF	22
HC	31,877
Metals	8
CH ₄	6,669
Organo-chlorine	800

Primary fuels	MJ
Coal	35.23
Oil	13.01
Gas	29.79
Hydro	0.65
Nuclear	13.66
Sulphur	0.04
Recovered	-0.05
Total fuels	92.34

Primary feedstocks	MJ
Coal	0.12
Oil	25.28
Gas	22.63
Total feedstocks	48.04
Total fuels & feedstocks	140.38

Water emissions	mg
COD	1,738
BOD	131
Salt	4
Acid	325
Metals	333
Cl ⁻	65,923
Dissolved organics	2,197
Suspended solids	23,994
Detergent/oil	78
Hydrocarbons	9
Organo-chlorine	5
Phenol	5
Dissolved solids	668
Other N	5
Na ⁺	7,533
SO ₄ ²⁻	2,354


Solid waste	mg
Paper	244
Plastics	2
Mineral waste	268,931
Slags/ash	71,107
Industrial waste	21,354
Regulated chemicals	5,493
Unregulated chemicals	17,527

Packaging & delivery: Bulk delivery, no packaging
Road transport: 7.5t rigid vehicle, 5.5t payload, returning empty, average return distance 322 km

Appendix 78

Plastics and plastic products

Production and road delivery of a PVC bottle gulley - per gulley



Gross inputs and outputs associated with the production and road delivery of a PVC bottle gulley - per gulley		Totals may not agree because of rounding errors	
Energy		MJ	
Electricity - production & delivery		25.76	
Electricity - delivered		10.90	
Oil fuels - production & delivery		3.94	
Oil fuels - delivered		4.75	
Oil fuels - feedstock		23.22	
Other fuels - production & delivery		3.30	
Other fuels - delivered		14.39	
Other fuels - feedstock		14.88	
Total energy		101.13	
Raw materials		mg	
Barytes		21,490	
Bauxite		316	
Brine		6,882	
Chalk		86,051	
Clay		25	
Fe-Mn		16	
Iron ore		5,354	
Lead		7	
Limestone		19,409	
Met coal		2,041	
Sand		867	
Water		20,082,700	
Wood		377	
NaCl		582,009	
Nitrogen		1	
Air		36,717	
Sulphur		2,417	
Air emissions		mg	
Dust		10,984	
CO		4,085	
CO ₂		3,434,000	
SO _x		32,842	
NO _x		22,051	
Cl ₂		1	
HCl		511	
HF		15	
HC		20,869	
Metals		6	
CH ₄		4,440	
Organo-chlorine		439	
Primary fuels		MJ	
Coal		23.14	
Oil		10.81	
Gas		19.65	
Hydro		0.43	
Nuclear		8.98	
Sulphur		0.02	
Recovered		-0.02	
Total fuels		63.01	
Primary feedstocks		MJ	
Coal		0.07	
Oil		23.19	
Gas		14.82	
Total feedstocks		38.09	
Total fuels & feedstocks		101.10	
Water emissions		mg	
COD		1,052	
BOD		87	
Salt		2	
Acid		207	
NO ₃ ⁻		5	
Metals		258	
NH ₄ ⁺		2	
Cl ⁻		36,341	
Dissolved organics		1,212	
Suspended solids		13,314	
Detergent/oil		53	
Hydrocarbons		80	
Organo-chlorine		3	
Phenol		3	
Dissolved solids		415	
Other N		5	
Na ⁺		4,130	
SO ₄ ²⁻		1,291	
Phosphate/P ₂ O ₅		5	
Other organic		62	
Solid waste		mg	
Paper		134	
Plastics		1	
Mineral waste		170,260	
Slags/ash		46,024	
Industrial waste		12,748	
Regulated chemicals		3,019	
Unregulated chemicals		11,578	


Packaging & delivery: Bulk delivery, no packaging

Road transport: 7.5t rigid vehicle, 5.5t payload, returning empty, average return distance 322 km

Appendix 79

Plastics and plastic products

Production and road delivery of polyethylene granules (all grades) - per kg



Gross inputs and outputs associated with the production and bulk road delivery of polyethylene granules (all grades) - per kg¹ Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	5.55
Electricity - delivered	2.35
Oil fuels - production & delivery	4.40
Oil fuels - delivered	7.59
Oil fuels - feedstock	23.58
Other fuels - production & delivery	4.31
Other fuels - delivered	14.14
Other fuels - feedstock	24.17
Total energy	86.08

Raw materials	mg
Bauxite	303
Brine	2
Clay	20
Fe-Mn	3
Iron ore	753
Lead	1
Limestone	351
Met coal	227
Sand	2
Water	1,815,400
NaCl	7,000
Air	74
Sulphur	5

Air emissions	mg
Dust	2,017
CO	937
CO ₂	2,240,900
SO _x	7,093
NO _x	11,179
HCl	60
HF	1
HC	21,057
CHO	5
Organics	5
Metals	1
CH ₄	9
Hydrogen	1

Primary fuels	MJ
Coal	5.09
Oil	11.10
Gas	20.06
Hydro	0.09
Nuclear	1.99
Total fuels	38.33
Primary feedstocks	MJ
Coal	0.02
Oil	23.57
Gas	24.16
Total feedstocks	47.75
Total fuels & feedstocks	86.08

Water emissions	mg
COD	1,000
BOD	150
Acid	70
NO ₃ ⁻	5
Metals	300
NH ₄ ⁺	5
Cl ⁻	120
Dissolved organics	20
Suspended solids	471
Detergent/oil	100
Hydrocarbons	100
Phenol	1
Dissolved solids	400
Other N	10
Sulphate	10
Phosphate/P ₂ O ₅	5

Solid waste	mg
Mineral waste	22,835
Slags/ash	7,045
Industrial waste	3,124
Regulated chemicals	70
Unregulated chemicals	2,000


¹ Polyethylene production data: I. Boustead, *Ecoprofiles of the European polymer industry*, APME Report No. 3, Polyethylene and polypropylene, May 1993.

Packaging & delivery: Bulk delivery, no packaging
 Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 80

Plastics and plastic products

Production and road delivery of polyethylene damp proof course - per m²



Gross inputs and outputs associated with the production and bulk road delivery of polyethylene damp proof course - per m² Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	6.88
Electricity - delivered	2.91
Oil fuels - production & delivery	2.50
Oil fuels - delivered	3.81
Oil fuels - feedstock	13.90
Other fuels - production & delivery	2.09
Other fuels - delivered	6.86
Other fuels - feedstock	11.72
Total energy	50.66

Raw materials	mg
Bauxite	154
Brine	3
Clay	10
Fe-Mn	6
Iron ore	1,630
Lead	3
Limestone	629
Met coal	631
Sand	3
Water	1,342,800
NaCl	3,392
Air	115
Sulphur	8

Air emissions	mg
Dust	2,758
CO	910
CO ₂	1,456,300
SO _x	7,989
NO _x	7,168
HCl	102
HF	4
HC	10,638
CHO	2
Organics	2
Metals	1
CH ₄	1,088

Primary fuels	MJ
Coal	6.20
Oil	6.31
Gas	9.98
Hydro	0.12
Nuclear	2.42
Total fuels	25.03
Primary feedstocks	MJ
Coal	0.02
Oil	13.88
Gas	11.71
Total feedstocks	25.61
Total fuels & feedstocks	50.64

Water emissions	mg
COD	488
BOD	76
Acid	44
NO ₃ ⁻	2
Metals	148
NH ₄ ⁺	2
Cl ⁻	58
Dissolved organics	10
Suspended solids	466
Detergent/oil	48
Hydrocarbons	52
Phenol	4
Dissolved solids	194
Other N	5
Sulphate	5
Phosphate/P ₂ O ₅	2

Solid waste	mg
Mineral waste	38,554
Slags/ash	11,403
Industrial waste	1,886
Regulated chemicals	34
Unregulated chemicals	969


Packaging & delivery: Bulk delivery, no packaging

Road transport (notional): articulated vehicle, 10 tonne payload, returning empty, average return distance 644 km

Appendix 81

Plastics and plastic products

Production and road delivery of polyethylene damp proof membrane (1200 gauge) - per kg



Gross inputs and outputs associated with the production and bulk road delivery of polyethylene damp proof membrane (1200 gauge) - per kg Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	14.10
Electricity - delivered	5.96
Oil fuels - production & delivery	4.54
Oil fuels - delivered	8.05
Oil fuels - feedstock	24.06
Other fuels - production & delivery	4.39
Other fuels - delivered	14.43
Other fuels - feedstock	24.66
Total energy	100.19

Raw materials	mg
Bauxite	318
Brine	5
Clay	20
Fe-Mn	8
Iron ore	2,299
Lead	3
Limestone	923
Met coal	862
Sand	5
Water	2,580,700
NaCl	7,140
Air	170
Sulphur	11

Air emissions	mg
Dust	5,590
CO	1,664
CO ₂	2,996,700
SO _x	16,447
NO _x	14,470
HCl	209
HF	8
HC	22,045
CHO	5
Organics	5
Metals	2
CH ₄	2,169
Hydrogen	1

Primary fuels	MJ
Coal	12.68
Oil	12.84
Gas	20.74
Hydro	0.24
Nuclear	4.95
Total fuels	51.45
Primary feedstocks	MJ
Coal	0.04
Oil	24.04
Gas	24.64
Total feedstocks	48.72
Total fuels & feedstocks	100.17

Water emissions	mg
COD	1,022
BOD	155
Acid	91
NO ₃ ⁻	5
Metals	312
NH ₄ ⁺	5
Cl ⁻	122
Dissolved organics	20
Suspended solids	827
Detergent/oil	102
Hydrocarbons	105
Phenol	3
Dissolved solids	408
Other N	10
Sulphate	10
Phosphate/P ₂ O ₅	5

Solid waste	mg
Mineral waste	77,050
Slags/ash	23,171
Industrial waste	3,354
Regulated chemicals	71
Unregulated chemicals	2,040


Packaging & delivery: Bulk delivery, no packaging

Road transport (notional): articulated vehicle, 20 tonne payload, returning empty, average return distance 322 km

Appendix 82

Plastics and plastic products

Production and road delivery of expanded polystyrene (EPS) foam - per kg



Gross inputs and outputs associated with the production and bulk road delivery of expanded polystyrene (EPS) foam - per kg¹ Totals may not agree because of rounding errors

Energy		MJ	
Electricity - production & delivery		3.22	
Electricity - delivered		1.36	
Oil fuels - production & delivery		7.63	
Oil fuels - delivered		25.62	
Oil fuels - feedstock		28.03	
Other fuels - production & delivery		4.74	
Other fuels - delivered		17.03	
Other fuels - feedstock		25.40	
Total energy		113.01	

Raw materials		mg	
Barytes		4	
Bauxite		1,835	
Brine		52	
Clay		21	
Fe-Mn		76	
Fluorspar		2	
Iron ore		23,493	
Lead		42	
Limestone		8,374	
Met coal		9,467	
Water		11,067,400	
NaCl		12,766	
Air		1,440	
Sulphur		95	

Air emissions		mg	
Dust		6,138	
CO		8,269	
CO ₂		3,565,000	
SO _x		152,783	
H ₂ S		5	
NO _x		53,215	
HCl		46	
F		1	
HC		25,775	
Metals		21	
CH ₄		374	
Pentane		85,104	

Primary fuels		MJ	
Coal		3.39	
Oil		30.66	
Gas		24.30	
Hydro		0.06	
Nuclear		1.17	
Total fuels		59.48	

Primary feedstocks		MJ	
Coal		0.31	
Oil		27.81	
Gas		25.08	
Total feedstocks		53.20	
Total fuels & feedstocks		112.68	

Water emissions		mg	
COD		2,881	
BOD		136	
Acid		90	
Metals		1,065	
NH ₄ ⁺		426	
Cl ⁻		106	
Dissolved organics		340	
Suspended solids		4,350	
Detergent/oil		319	
Hydrocarbons		647	
Phenol		8	
Dissolved solids		426	
Other N		21	

Solid waste		mg	
Plastics		4	
Organics		2	
Mineral waste		46,422	
Slags/ash		6,138	
Industrial waste		3,737	
Regulated chemicals		1	
Unregulated chemicals		7,447	


¹ Polystyrene production data: I. Boustead, *Ecoprofiles of the European polymer industry*, APME Report No. 4, Polystyrene, May 1993.

Packaging & delivery: Bulk delivery, no packaging
 Road transport (notional): articulated vehicle, 480 kg payload, returning empty, average return distance 322 km

Appendix 83

Plastics and plastic products

Production and road delivery of expanded polystyrene (EPS) foam insulation slab, 50 mm depth - per m²



Gross inputs and outputs associated with the production and bulk road delivery of expanded polystyrene (EPS) foam insulation slab, depth 50 mm, - per m² Totals may not agree because of rounding errors

Energy		MJ	
Electricity - production & delivery		2.41	
Electricity - delivered		1.02	
Oil fuels - production & delivery		5.72	
Oil fuels - delivered		19.21	
Oil fuels - feedstock		21.02	
Other fuels - production & delivery		3.56	
Other fuels - delivered		12.77	
Other fuels - feedstock		19.05	
Total energy		84.76	

Raw materials		mg	
Barytes		3	
Bauxite		1,376	
Brine		39	
Clay		16	
Fe-Mn		57	
Fluorspar		2	
Iron ore		17,620	
Lead		32	
Limestone		6,280	
Met coal		7,100	
Water		8,300,600	
NaCl		9,574	
Air		1,080	
Sulphur		71	

Air emissions		mg	
Dust		4,604	
CO		6,202	
CO ₂		2,673,700	
SO ₂		114,587	
H ₂ S		4	
NO _x		39,911	
HCl		35	
HC		19,331	
Metals		16	
CH ₄		281	
Pentane		63,828	

Primary fuels		MJ	
Coal		2.47	
Oil		23.00	
Gas		18.22	
Hydro		0.04	
Nuclear		0.88	
Total fuels		44.61	

Primary feedstocks		MJ	
Coal		0.23	
Oil		20.86	
Gas		18.81	
Total feedstocks		39.90	
Total fuels & feedstocks		84.51	

Water emissions		mg	
COD		2,161	
BOD		102	
Acid		67	
Metals		799	
NH ₄ ⁺		319	
Cl ⁻		80	
Dissolved organics		255	
Suspended solids		3,262	
Detergent/oil		239	
Hydrocarbons		485	
Phenol		6	
Dissolved solids		319	
Other N		16	


Solid waste		mg	
Plastics		3	
Organics		2	
Mineral waste		34,817	
Slags/ash		4,604	
Industrial waste		2,803	
Unregulated chemicals		5,585	

Packaging & delivery: Bulk delivery, no packaging
 Road transport (notional): articulated vehicle, 480 kg payload, returning empty, average return distance 322 km

Appendix 84

Plastics and plastic products

Production and road delivery of rigid polyurethane foam - per kg



Schematic flow diagram for the production of rigid PU foam. All flows are in kg (notional values)

Gross Inputs and outputs associated with the production and road delivery of rigid polyurethane foam - per kg¹
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	17.17
Electricity - delivered	7.27
Oil fuels - production & delivery	3.59
Oil fuels - delivered	9.07
Oil fuels - feedstock	16.25
Other fuels - production & delivery	5.20
Other fuels - delivered	25.46
Other fuels - feedstock	25.87
Total energy	109.87

Raw materials	mg
Bauxite	836
Brine	78
Fe-Mn	345
Fluorspar	11
Iron ore	106,610
Lead	2
Limestone	274,791
Met coal	43,345
Sand	943
Water	191,958,000
Phosphate	3,590
NaCl	874,692
Air	6,186
Sulphur as SO ₂	54,781
Sulphur	3,344

Air emissions	mg
Dust	9,968
CO	2,936
CO ₂	4,949,200
SO _x	40,270
H ₂ S	4
NO _x	23,328
NH ₃	109
HCl	302
F	3
HF	11
HC	18,677
Organics	302
Metals	18
CH ₄	1,641
H ₂	590
Pentane	3,000
Organo-chlorine	120

Primary fuels	MJ
Coal	15.41
Oil	13.76
Gas	32.25
Hydro	0.30
Nuclear	6.02
Total fuels	67.73
Primary feedstocks	MJ
Coal	2.30
Oil	16.24
Gas	23.21
Biomass	0.39
Total feedstocks	42.13
Total fuels & feedstocks	109.86

Water emissions	mg
COD	5,966
BOD	1,081
Acid	182
NO ₃ ⁻	2,355
Metals	50,758
Cl ⁻	504,188
Dissolved organics	714
Suspended solids	41,459
Detergent/oil	60
Hydrocarbons	588
Organo-chlorine	81
Phenol	8
Dissolved solids	212
Other N	889
Na ⁺	30,985
SO ₄ ⁻	7,943
Phosphate/P ₂ O ₅	540

Solid waste	mg
Mineral waste	563,340
Slags/ash	45,292
Industrial waste	92,392
Regulated chemicals	3,229
Unregulated chemicals	5,605


¹ MDI and polyol precursor production data: I. Boustead, *Ecoprofiles of the European plastics industry*, A Report for the European Isocyanate Producers Association (ISOPA), Polyurethane precursors (TDI, MDI, polyols), February 1996.

Packaging & delivery: Bulk delivery, no packaging
Road transport (notional): 15t rigid vehicle, 10t payload, returning empty, average return distance 200 km

Appendix 85

Plastics and plastic products

Production and road delivery of rigid polyurethane foam insulation, 50 mm depth - per m²



Schematic flow diagram for the production of rigid PU foam. All flows are in kg (notional values)

Gross Inputs and outputs associated with the production and road delivery of rigid polyurethane foam - per kg¹
Totals may not agree because of rounding errors

Energy	MJ
Electricity - production & delivery	25.75
Electricity - delivered	10.91
Oil fuels - production & delivery	5.38
Oil fuels - delivered	13.61
Oil fuels - feedstock	24.37
Other fuels - production & delivery	7.80
Other fuels - delivered	38.19
Other fuels - feedstock	38.80
Total energy	164.81

Raw materials	mg
Bauxite	1,254
Brine	117
Fe-Mn	517
Fluorspar	18
Iron ore	159,914
Lead	2
Limestone	412,187
Met coal	65,018
Sand	1,415
Water	287,937,100
Phosphate	5,385
NaCl	1,312,000
Air	9,279
Sulphur as SO ₂	82,171
Sulphur	5,015

Air emissions	mg
Dust	14,952
CO	4,404
CO ₂	7,423,900
SO _x	60,405
H ₂ S	6
NO _x	34,992
NH ₃	163
HCl	454
F	4
HF	16
HC	28,016
Organics	454
Metals	27
CH ₄	2,461
H ₂	884
Pentane	4,500
Organo-chlorine	181

Primary fuels	MJ
Coal	23.11
Oil	20.63
Gas	48.38
Hydro	0.45
Nuclear	9.03
Total fuels	101.60
Primary feedstocks	MJ
Coal	3.45
Oil	24.36
Gas	34.81
Biomass	0.58
Total feedstocks	63.19
Total fuels & feedstocks	164.79

Water emissions	mg
COD	8,948
BOD	1,621
Acid	273
NO ₃ ⁻	3,532
Metals	76,137
Cl ⁻	756,282
Dissolved organics	1,071
Suspended solids	62,189
Detergent/oil	90
Hydrocarbons	882
Organo-chlorine	122
Phenol	12
Dissolved solids	318
Other N	1,332
Na ⁺	46,477
SO ₄ ⁻	11,915
Phosphate/P ₂ O ₅	811

Solid waste	mg
Mineral waste	845,010
Slags/ash	67,938
Industrial waste	138,588
Regulated chemicals	4,843
Unregulated chemicals	8,408


¹ MDI and polyol precursor production data: I. Boustead, *Ecoprofiles of the European plastics industry*, A Report for the European Isocyanate Producers Association (ISOPA), Polyurethane precursors (TDI, MDI, polyols), February 1996.

Packaging & delivery: Bulk delivery, no packaging
Road transport (notional): 15t rigid vehicle, 10t payload, returning empty, average return distance 200 km

Appendix 86

Miscellaneous

Production and road delivery of pulverised fuel ash - per kg⁴⁷



Gross inputs and outputs associated with the production and road delivery of pulverised fuel ash - per kg
 Totals may not agree because of rounding errors

Energy		MJ
Electricity - production & delivery		0.33
Electricity - delivered		0.14
Oil fuels - production & delivery		0.13
Oil fuels - delivered		0.87
Total energy		1.47

Raw materials		mg
Bauxite		2
Fe-Mn		1
Iron ore		310
Limestone		111
Met coal		128
Water		64,874
Air		19
Sulphur		1

Air emissions		mg
Dust		156
CO		103
CO ₂		96,496
SO _x		1,394
NO _x		492
HCl		6
HF		1
HC		162
Metals		1
CH ₄		89

Primary fuels		MJ
Coal		0.30
Oil		0.99
Gas		0.06
Hydro		0.01
Nuclear		0.11
Total fuels		1.46

Primary feedstocks		MJ
Total feedstocks		0.00
Total fuels & feedstocks		1.47

Water emissions		mg
COD		1
BOD		1
Acid		1
Suspended solids		46
Hydrocarbons		1
Phenol		1

Solid waste		mg
Mineral waste		2,464
Slags/ash		641
Industrial waste		108

Packaging & delivery: Bulk delivery, no packaging
 Road transport: 24t articulated vehicle, 20t payload, returning empty, average return distance 161 km

Appendix 87

Building construction


Construction of a three bedroom bungalow and a four bedroom detached house - per building

Gross inputs and outputs associated with the construction of a bungalow and a detached house - per building			
Totals may not agree because of rounding errors			
Energy GJ	bungalow	house	
Electricity - production & delivery	69.41	85.45	
Electricity - delivered	29.89	37.05	
Oil fuels - production & delivery	15.40	17.69	
Oil fuels - delivered	77.00	103.04	
Oil fuels - feedstock	30.01	19.20	
Other fuels - production & delivery	20.35	24.94	
Other fuels - delivered	206.09	253.88	
Other fuels - feedstock	104.16	121.27	
Total energy	552.30	662.52	
Raw materials - g	bungalow	house	
Barytes	39,995	55,821	
Bauxite	29,204	53,001	
Brine	548,661	705,377	
CaSO ₄	5,076,800	8,123,000	
Chalk	3,577	6,064	
Clay	54,984,300	68,858,000	
Fe-Mn	2,416	3,088	
Fluorspar	530	962	
Iron ore	815,080	994,102	
Lead	157,693	105,238	
Limestone	99,960,400	97,004,400	
Met coal	297,020	379,635	
Sand	50,200,500	50,239,200	
Tin	0	1	
Water	330,050,300	367,149,000	
Wood	7,396,600	9,033,200	
Zinc	8,198	14,302	
Copper	27,000	36,000	
Phosphate	1,090	1,298	
Shale	2,321,700	2,857,500	
NaCl	18,071	33,663	
Ulexite	15,660	10,980	
Granite	23,490	16,470	
Dolomite	99,522	111,006	
Nitrogen	2,452	4,216	
Air	203,574	268,737	
Sulphur	13,251	17,512	
Air emissions - g	bungalow	house	
Dust	156,409	193,147	
CO	53,279	69,993	
CO ₂	39,716,100	49,738,500	
SO _x	312,146	403,472	
H ₂ S	284	349	
Mercaptan	2	3	
NO _x	190,034	235,802	
NH ₃	1	1	
HCl	6,875	8,554	
F	59	97	
HF	1,659	1,983	
HC	74,840	91,526	
Organics	10	15	
Lead	1	1	
Metals	38	58	
CH ₄	195,646	237,716	
H ₂	701	1,337	
Pentane	12	20	
Organo-chlorine	13	25	
Primary fuels GJ	bungalow	house	
Coal	167.08	205.82	
Oil	97.65	127.67	
Gas	120.38	145.32	
Hydro	1.90	2.70	
Nuclear	25.24	31.15	
Lignite	0.01	0.01	
Wood	5.63	8.94	
Other	0.08	0.13	
Sulphur	0.12	0.16	
Recovered	-0.14	-0.18	
Total fuels	417.95	521.70	
Primary feedstocks GJ	bungalow	house	
Coal	9.30	11.90	
Oil	29.11	18.10	
Gas	1.89	1.98	
Wood	92.93	107.37	
Biomass	0.18	0.22	
Total feedstocks	133.42	139.55	
Total fuels & feedstocks	551.37	661.26	
Water emissions - g	bungalow	house	
COD	2,050	2,573	
BOD	309	374	
Salt	58	64	
Acid	459	579	
NO ₃ ⁻	13	15	
Metals	151	187	
Cl ⁻	1,667	2,799	
F ⁻	15	27	
S	1	1	
Dissolved organics	51	91	
Dissolved solids	200	226	
Suspended solids	609,786	927,472	
Detergent/oil	6	7	
HIC	180	227	
Phenol	110	124	
Phosphorus	3	3	
Other N	25	32	
Na ⁺	133	244	
SO ₄ ²⁻	44	78	
Phosphate/P ₂ O ₅	1	1	
Other organics	2	3	
Solid waste - g	bungalow	house	
Plastic containers	623	964	
Paper	118,571	149,761	
Plastics	6,752	8,469	
Metals	77,373	98,571	
Organics	22,709	31,511	
Other refuse	532,169	669,684	
Mineral waste	25,166,300	29,722,700	
Slags/ash	912,180	1,143,600	
Industrial waste	11,745,700	11,631,000	
Fired clay	7,075,200	8,873,800	
Regulated chemicals	95	176	
Unregulated chemicals	467	721	

Appendix 88

Building construction

Construction of a three bedroom bungalow - per m² floor space



Gross inputs and outputs associated with the construction of a three bedroom bungalow - per m² floor space
Totals may not agree because of rounding errors

Energy	GJ
Electricity - production & delivery	0.80
Electricity - delivered	0.34
Oil fuels - production & delivery	0.18
Oil fuels - delivered	0.89
Oil fuels - feedstock	0.34
Other fuels - production & delivery	0.23
Other fuels - delivered	2.37
Other fuels - feedstock	1.20
Total energy	6.35

Raw materials	g
Barytes	460
Bauxite	336
Brine	6,307
CaSO ₄	58,355
Chalk	41
Clay	632,004
Fe-Mn	28
Fluorspar	6
Iron ore	9,369
Lead	1,813
Limestone	1,149,000
Met coal	3,414
Sand	577,017
Water	3,793,700
Wood	85,019
Zinc	94
Copper	310
Phosphate	12
Shale	26,686
NaCl	208
Ulexite	180
Granite	270
Dolomite	1,144
Nitrogen	28
Air	2,340
Sulphur	152

Air emissions	g
Dust	1,798
CO	612
CO ₂	456,507
SO _x	3,588
H ₂ S	3
NO _x	2,184
HCl	79
F	1
HF	19
HC	860
CH ₄	2,249
H ₂	8

Primary fuels	GJ
Coal	1.92
Oil	1.12
Gas	1.38
Hydro	0.02
Nuclear	0.29
Lignite	0.00
Wood	0.06
Total fuels	4.80

Primary feedstocks	GJ
Coal	0.11
Oil	0.33
Gas	0.02
Wood	1.07
Total feedstocks	1.53
Total fuels & feedstocks	6.34


Water emissions	g
COD	24
BOD	4
Salt	1
Acid	5
Metals	2
Cl ⁻	19
Dissolved organics	1
Dissolved solids	2
Suspended solids	7,009
HC	2
Phenol	1
Na ⁺	2
SO ₄ ²⁻	1

Solid waste	g
Plastic containers	7
Paper	1,363
Plastics	78
Metals	889
Organics	261
Other refuse	6,117
Mineral waste	289,268
Slags/ash	10,485
Industrial waste	135,009
Fired clay	81,324
Regulated chemicals	1
Unregulated chemicals	5

Appendix 89

Building construction

Construction of a four bedroom detached house - per m² floor space



Gross inputs and outputs associated with the construction of a four bedroom detached house - per m² floor space
Totals may not agree because of rounding errors

Energy	GJ
Electricity - production & delivery	0.70
Electricity - delivered	0.30
Oil fuels - production & delivery	0.15
Oil fuels - delivered	0.84
Oil fuels - feedstock	0.16
Other fuels - production & delivery	0.20
Other fuels - delivered	2.08
Other fuels - feedstock	0.99
Total energy	5.42

Raw materials	g
Barytes	456
Bauxite	433
Brine	5,768
CaSO ₄	66,419
Chalk	50
Clay	563,025
Fe-Mn	25
Fluorspar	8
Iron ore	8,128
Lead	860
Limestone	793,168
Met coal	3,104
Sand	410,787
Water	3,002,000
Wood	73,861
Zinc	117
Copper	294
Phosphate	11
Shale	23,365
NaCl	275
Ulexite	90
Granite	135
Dolomite	908
Nitrogen	34
Air	2,197
Sulphur	143

Air emissions	g
Dust	1,579
CO	572
CO ₂	406,692
SO _x	3,299
H ₂ S	3
NO _x	1,928
HCl	70
F	1
HF	16
HC	748
CH ₄	1,944
H ₂	11

Primary fuels	GJ
Coal	1.68
Oil	1.04
Gas	1.19
Hydro	0.02
Nuclear	0.25
Lignite	0.00
Wood	0.07
Total fuels	4.27

Primary feedstocks	GJ
Coal	0.10
Oil	0.15
Gas	0.02
Wood	0.88
Total feedstocks	1.14
Total fuels & feedstocks	5.41

Water emissions	g
COD	21
BOD	3
Salt	1
Acid	5
Metals	2
Cl ⁻	23
Dissolved organics	1
Dissolved solids	2
Suspended solids	7,584
HC	2
Phenol	1
Na ⁺	2
SO ₄ ²⁻	1

Solid waste	g
Plastic containers	8
Paper	1,225
Plastics	69
Metals	806
Organics	258
Other refuse	5,476
Mineral waste	243,032
Slags/ash	9,351
Industrial waste	95,103
Fired clay	72,558
Regulated chemicals	1
Unregulated chemicals	6


Appendix 90

Building construction

Construction of a three bedroom bungalow and a four bedroom detached house - per building

Revised gross inputs and outputs associated with the construction of a bungalow and a detached house - per building			Totals may not agree because of rounding errors		
Energy GJ	bungalow	house	Primary fuels GJ	bungalow	house
Electricity - production & delivery	65.31	80.53	Coal	139.28	171.80
Electricity - delivered	281.54	34.97	Oil	99.12	128.45
Oil fuels - production & delivery	16.22	18.42	Gas	42.26	46.49
Oil fuels - delivered	79.23	104.92	Hydro	1.81	2.60
Oil fuels - feedstock	33.57	22.50	Nuclear	23.44	28.96
Other fuels - production & delivery	7.15	8.20	Lignite	0.01	0.01
Other fuels - delivered	115.80	140.74	Wood	5.63	8.94
Other fuels - feedstock	109.00	126.29	Other	0.08	0.13
Total energy	454.43	536.58	Sulphur	0.12	0.16
			Recovered	-0.14	-0.18
			Total fuels	311.61	387.36
Raw materials - g	bungalow	house	Primary feedstocks GJ	bungalow	house
Barytes	39,992	55,818	Coal	9.33	11.91
Bauxite	29,463	53,252	Oil	32.81	21.58
Brine	548,664	705,354	Gas	5.34	5.27
CaSO ₄	5,198,800	8,284,900	Wood	94.27	109.05
Chalk	3,577	6,064	Biomass	0.18	0.22
Clay	646,225	600,944	Total feedstocks	141.93	148.03
Fe-Mn	2,430	3,103	Total fuels & feedstocks	453.55	535.39
Fluorspar	530	962			
Iron ore	816,926	995,746	Water emissions - g	bungalow	house
Lead	157,670	105,208	COD	2,291	2,755
Limestone	138,561,200	145,785,800	BOD	326	389
Met coal	297,736	380,266	Salt	58	64
Sand	53,988,900	56,267,000	Acid	317	398
Tin	1	1	NO ₃ ⁻	13	15
Water	332,557,900	375,291,900	Metals	260	279
Wood	7,485,400	9,144,600	NH ₄ ⁺	60	57
Zinc	8,200	14,306	Cl ⁻	1,678	2,809
Copper	27,000	36,000	F ⁻	15	27
Phosphate	1,090	1,298	S	1	1
Shale	2,667,000	3,315,600	Dissolved organics	98	136
NaCl	19,827	35,336	Dissolved solids	258	282
Ulexite	15,660	10,980	Suspended solids	621,073	942,345
Granite	23,490	16,470	Detergent/oil	51	49
Dolomite	99,522	111,006	HC	266	307
Nitrogen	2,452	4,216	Phenol	109	123
Air	202,751	267,664	Phosphorus	3	3
Sulphur	13,197	17,441	Other N	28	35
			Na ⁺	133	244
			SO ₄ ²⁻	44	78
			Phosphate/P ₂ O ₅	1	1
			Other organics	1	1
Air emissions - g	bungalow	house	Solid waste - g	bungalow	house
Dust	143,911	177,951	Plastic containers	623	964
CO	52,542	69,799	Paper	118,584	149,778
CO ₂	31,692,800	39,757,400	Plastics	1,938	2,422
SO ₂	285,834	365,746	Metals	89,141	113,339
H ₂ S	325	404	Organics	22,708	31,509
Mercaptan	2	3	Other refuse	603,844	759,627
NO _x	129,990	158,804	Mineral waste	9,968,800	10,795,700
NH ₃	1	1	Slags/ash	181,795	226,608
HCl	2,783	3,432	Industrial waste	16,803,100	18,023,400
F	59	97	Fired clay	41,150	37,926
HF	294	270	Regulated chemicals	95	176
HC	41,890	49,258	Unregulated chemicals	1,466	1,665
Organics	10	15			
Lead	1	1			
Metals	40	60			
CH ₄	79,801	92,865			
H ₂	701	1,337			
Pentane	11,884	11,382			
Organo-chlorine	13	25			

Appendix 91 Building construction
Construction of a three bedroom bungalow - per m² floor space



Revised gross inputs and outputs associated with the construction of a three bedroom bungalow - per m² floor space Totals may not agree because of rounding errors

Energy	GJ
Electricity - production & delivery	0.75
Electricity - delivered	0.32
Oil fuels - production & delivery	0.19
Oil fuels - delivered	0.91
Oil fuels - feedstock	0.39
Other fuels - production & delivery	0.08
Other fuels - delivered	1.33
Other fuels - feedstock	1.25
Total energy	5.22

Raw materials	g
Barytes	460
Bauxite	339
Brine	6,306
CaSO ₄	59,756
Chalk	41
Clay	7,428
Fe-Mn	28
Fluorspar	6
Iron ore	9,390
Lead	1,812
Limestone	1,592,600
Met coal	3,422
Sand	620,561
Water	3,822,500
Wood	86,038
Zinc	94
Copper	310
Phosphate	13
Shale	30,655
NaCl	228
Ulexite	180
Granite	270
Dolomite	1,144
Nitrogen	28
Air	2,331
Sulphur	152

Air emissions	g
Dust	1,651
CO	604
CO ₂	364,281
SO _x	3,284
H ₂ S	4
NO _x	1,494
HCl	32
F	1
HF	3
HC	481
CH ₄	917
H ₂	8
Pentane	137


Primary fuels	GJ
Coal	1.60
Oil	1.14
Gas	0.49
Hydro	0.02
Nuclear	0.27
Lignite	0.00
Wood	0.06
Total fuels	3.58

Primary feedstocks	GJ
Coal	0.11
Oil	0.34
Gas	0.06
Wood	1.08
Total feedstocks	1.63
Total fuels & feedstocks	5.21

Water emissions	g
COD	26
BOD	4
Salt	1
Acid	4
Metals	3
NH ₄ ⁺	1
Cl ⁻	19
Dissolved organics	1
Dissolved solids	3
Suspended solids	7,139
Detergent/oil	1
HC	3
Phenol	1
Na ⁺	2
SO ₄ ²⁻	1

Solid waste	g
Plastic containers	7
Paper	1,363
Plastics	22
Metals	1,025
Organics	261
Other refuse	6,940
Mineral waste	114,583
Slags/ash	2,090
Industrial waste	193,134
Fired clay	473
Regulated chemicals	1
Unregulated chemicals	17

Appendix 92 **Building construction**
Construction of a four bedroom detached house - per m² floor space



Revised gross inputs and outputs associated with the construction of a four bedroom detached house - per m² floor space Totals may not agree because of rounding errors

Energy	GJ
Electricity - production & delivery	0.66
Electricity - delivered	0.29
Oil fuels - production & delivery	0.15
Oil fuels - delivered	0.86
Oil fuels - feedstock	0.18
Other fuels - production & delivery	0.07
Other fuels - delivered	1.15
Other fuels - feedstock	1.03
Total energy	4.39

Raw materials	g
Barytes	456
Bauxite	435
Brine	5,767
CaSO ₄	67,742
Chalk	50
Clay	4,914
Fe-Mn	25
Fluorspar	8
Iron ore	8,142
Lead	860
Limestone	1,192,000
Met coal	3,109
Sand	460,074
Water	3,068,600
Wood	74,772
Zinc	117
Copper	294
Phosphate	11
Shale	27,111
NaCl	289
Ulexite	90
Granite	135
Dolomite	908
Nitrogen	34
Air	2,189
Sulphur	143

Air emissions	g
Dust	1,455
CO	571
CO ₂	325,081
SO ₂	2,991
H ₂ S	3
NO _x	1,299
HCl	28
F	1
HF	2
HC	403
CH ₄	759
H ₂	11
Pentane	93

Primary fuels	GJ
Coal	1.40
Oil	1.05
Gas	0.38
Hydro	0.02
Nuclear	0.24
Lignite	0.00
Wood	0.07
Total fuels	3.17

Primary feedstocks	GJ
Coal	0.10
Oil	0.18
Gas	0.04
Wood	0.89
Total feedstocks	1.21
Total fuels & feedstocks	4.38

Water emissions	g
COD	23
BOD	3
Salt	1
Acid	3
Metals	2
NH ₄ ⁺	0
Cl ⁻	23
Dissolved organics	1
Dissolved solids	2
Suspended solids	7,705
Detergent/oil	0
HC	3
Phenol	1
Na ⁺	2
SO ₄ ²⁻	1

Solid waste	g
Plastic containers	8
Paper	1,225
Plastics	20
Metals	927
Organics	258
Other refuse	6,211
Mineral waste	88,272
Slags/ash	1,853
Industrial waste	147,371
Fired clay	310
Regulated chemicals	1
Unregulated chemicals	14

REFERENCES

References

1. *'Resources and man, A Study and Recommendations'*, National Academy of Sciences and National Research Council, ISBN 7167 0244 4, W.H. Freeman, San Francisco, 1969
2. Meadows D. et al, *'The limits to growth'* ISBN 0-330-241699, 1972
3. Club of Rome, *'A blueprint for survival'*, The Ecologist, Vol. 2, 1972
4. Smith H. *'The cumulative energy requirements of some final products of the chemical industry'*, Transactions of the World Energy Conference, Vol. 18, Section E, 1969.
5. Makhijani A.B. & Lichtenberg A.J. *'Energy and well being'*, Environment, Vol. 14, No. 5, June 1972, pp 10-18
6. MacKillop A. *'Low energy housing'*, The Ecologist, Vol. 2, No. 12, 1972
7. Leach G. & Slessor M. *'The energy equivalents of network inputs to food producing industries'*, University of Strathclyde, 1973
8. Brown G. & Stellon P. *'The material account'*, Built Environment, August 1974, pp 415-417
9. Chapman P.F. *'Energy costs: a review of methods'*, Energy Policy, June 1974, pp 91-103
10. Chapman P.F., Leach G., & Slessor M. *'The energy cost of fuels'* Energy Policy, Sept. 1974, pp 231-243
11. Whittemore O.J. *'Energy consumption in ceramic processes'* Bulletin of the American Ceramic Society, pp 456-457, Vol. 53, No. 5, 1974
12. Barnes D. & Rankin L. *'The energy economics of building construction'*, Build International, Vol. 8, 1975, pp 31-42
13. Chapman P.F. *'The energy cost of materials'*, Energy Policy, March 1975, pp 47-57
14. Kegel R.A. *'The energy intensity of building materials'*, Heating/Piping/Air Conditioning, June 1975, pp 37-41
15. Maddox K.P. *'Energy analysis'*, Mineral Industries Bulletin, Colorado School of Mines Research, Vol. 18, No. 4, July 1975, pp 1-16
16. Addleson L. *'Materials & energy'*, Building, 11 July 1975, pp 94-97
17. Haseltine B.A. *'Comparison of energy requirements for building material and structures'*, The Structural Engineer, Vol. 53, No. 9, Sept' 1975, pp 357-365

18. Bullard C.W. & Herendeen R.A. *'The energy cost of goods and services'*, Energy Policy, Dec' 1975, pp 268-278
19. Ballantyne E.R. *'Energy cost of dwelling'*, (Reprint from 5th Australian Building Research Congress), 1975, pp 1-7
20. Leach G. *'Energy and food production'*, ISBN 0 902852 55 8, IPC Science & Technology Press Ltd, 1975
21. Pick H.J. & Becker P.E. *'Direct and indirect uses of energy and materials in engineering and construction'*, Applied Energy, Vol.1, 1975, pp 31-51
22. Kreiger P.C. *'Energy analysis of materials and structures in the building industry'*, Proceedings of the 9th International TNO Conference, Rotterdam, February 1976, pp 141-160
23. Gartner E.M. & Smith M.A. *'Energy costs of house construction'*, Energy Policy, June 1976, pp 144-157
24. Noble J., Clarke R.B., & Naylor T. *'Energy Use in the Kilning, Drying and Heat Curing Industries'*, New Zealand Energy Research & Development Committee, Report No. 11 Sept' 1976
25. Stein R. *'Energy Cost of Building Construction'*, Energy and Buildings, Vol 1, 1977, pp 27-29
26. Slessor M. & Marcus T. *'Energy costs of house construction. A reply'*, Energy Policy, March 1977, pp 76-77
27. Department of Energy & Department of Industry, *'Building Brick Industry'*, Energy Audit Series No. 2, 1977
28. Morris E.N., *'Housing Energy Economics'*, Building and Environment, Vol. 13, 1978, pp 11-19
29. Wright C. & Gardiner P. *'Energy and Housing'*, Built Environment, Vol. 5, No. 4, 1979, pp 287-297
30. Kindler H. & Nikles A. *'Energy requirements in the production and processing of plastics'*, Chem.-Ing.-Tech. Vol 51, 1979, pp 1125-1127
31. Department of Energy & Department of Industry, *'Glass Industry'*, Energy Audit Series No. 5, 1979
32. Boustead I. & Hancock G.F. *'Energy requirements of a vitrified clay pipe drainage system'*, Resources & Conservation, Vol.6, 1981, pp 241-261

33. Kindler H. & Nikles A. *'Energy requirements in the production of materials -Fundamentals and energy equivalent values for plastics'*, Kunststoffe, Vol. 70, 1980, pp. 802-807
34. Department of Energy & Department of Industry, *'The Cement Industry'*, Energy Audit Series No. 11, 1980
35. Wong Y.C. & Sauer H.J. *' Total Energy Costs of Building Construction and Operation'*, Thermal Insulation, Materials, and Systems for Energy Conservation in the '80s, American Society for Testing and Materials, Spec. Tech. Publ., 1983, pp 149-160
36. Boustead I. & Hancock G.F *'Energy Requirement for Vitrified Clay Drainage and Sewerage Systems'*, Informations de la Fédération Européenne des Fabricants de Tuyaux en Grès, No. 8 1983
37. Baird G. & Aun C.S *'Energy Cost of Houses and Light Construction Buildings'*, New Zealand Energy Research and Development Committee, Report No. 76, Nov. 1983
38. Energy Audit No. 5 *'Clay brick industry in the European Economic Community'*, Report No. EUR 9469, ISBN 92 825 4902 X, British Ceramic Research Association Ltd. 1985.
39. Urien R., de Vesvrotte F., & Canela D. *'Energy analysis of the building production system in Tunisia'*, CIB Congress on Advancing Building Technology, Washington DC 21 Sept. 1986, Report No. CONF-860901, pp 1562-1568
40. EC Directive 85/339: *'Containers of liquids for human consumption'*, 1985
41. *'This Common Inheritance'* - Britain's Environmental Strategy, HMSO, ISBN 0-10-112002-8, 1990
42. EC Directive 94/62: *'Packaging and packaging waste'*, 1994
43. Boustead I. & Hancock G.F. *'Handbook of industrial energy analysis'*, ISBN 0-85312-064-1. Ellis Horwood, Chichester, John Wiley, New York, 1979.
44. Österreichisches Forschungsinstitut für Chemie und Technik. *Ökologische Betrachtung der Fenster-Profil-Werkstoffe Kunststoffe, Aluminium, Holz'*, Wien 1991
45. Marcea R.L. & Lau K.K., *'Carbon dioxide implications of building materials'*, Journal of Forest Engineering, 1992, pp 37-43
46. Christophersen E., Dinesen J., Nielsen, P. *'Life-cycle based building design performance'*, Building physics in the Nordic countries, 3rd Symposium, Copenhagen, ISBN 87 984610 2 8, Sept' 1993, pp 481-489
47. The Boustead Model for life-cycle inventory calculations, 1996

48. Boustead I. *'Eco-profiles of the European polymer industry'*, Association of Plastic Manufacturerers in Europe (APME), Report 3, Polyethylene and Polypropylene, May 1993
49. Boustead I. *'Eco-profiles of the European polymer industry'*, Association of Plastic Manufacturerers in Europe (APME), Report 4, Polystyrene, May 1993
50. Boustead I. *'Eco-profiles of the European polymer industry'*, Association of Plastic Manufacturerers in Europe (APME), Report 6, Polyvinylchloride, April 1994
51. Boustead I. *'Eco-profiles of the European plastics industry'*, A Report for the European Isocyanate Producers Association (ISOPA), Polyurethane precursors (TDI, MDI, polyols), February 1996
52. *'A technical framework for life cycle assessment'*, Society of Environmental Toxicology and Chemistry, Washington DC, 1991.
53. Boustead I. *'Eco-balance methodology for commodity thermoplastics'*, A Report for Plastics in the Environment (PWMI), Brussels, December 1992.
54. Odum, E.P. *'Fundamentals of ecology'*, ISBN 0-7216-6941-7, W.B. Saunders Co. Philadelphia, 1971, p 39
55. Beardmore C. *'Fuel usage in the manufacture of clay building bricks'* Research paper 783, British Ceramic Research Ltd., ISBN 0-948593-42-3, November 1989,
56. Pauls N. *'Survey of the emission of pollutants in brick and tile production'*, Ziegelindustrie International, 1989, pp 69 - 76
57. Kolkmeier H. *'Emissions'*, Ziegelindustrie International, 1991, pp 544 - 548
58. *'Energy Yearbook 1992'*, The Institute of Energy, London
59. Mortimer, N.D. *'Energy analysis of burner reactor power systems'*, Open University, 1974
60. Mortimer, N.D. ; *The energy cost of road and rail freight transport systems in the U.K. in 1968'*, Energy Research Group Report No. 4, Open University, 1974
61. Hirst, E *'Energy consumption for transportation in the U.S.'*, Oak Ridge National Laboratory Report ORNL-NSF-EP-15, 1968
62. Clemow, C.J *'Understanding energy systems'*, Paper presented to the joint conference of the Operational Research Society and the Institute of Fuel, London, April 1975.
63. Commercial Motor, *'Tables of Operating Costs'*, Reed Business Publishing, 1994
64. Motor Transport, *'Cost tables'*, 28 October 1993, Reed Business Publishing

65. Personal communication, Avon Tyres Ltd. Melksham, Wiltshire.
66. Duda, W.H. '*Cement Data Book*', Vol 1, 3rd edition, ISBN 3-7625-2137-9, Bauverlag GmbH, Berlin 1985.
67. BPM 1, Appendix 4, *Best practicable means: general principles and practice*, Her Majesty's Inspectorate of Pollution, January 1988
68. B.S. 5977: Part 2: 1983, British Standards Institution
69. Lynch, Charles T. '*Handbook of Materials Science*', Volume 1, *General Properties*, CRC Press, 1974, Table 4-61, p556