



Citation for published version:

McClymont, D, Kolaczowski, ST & Molloy, KC 2010, 'Catalyst system design for the control of NO_x using hydrogen' DTC Summer Showcase 2010, Bath, UK United Kingdom, 8/07/10 - 9/07/10, .

Publication date:
2010

Document Version
Peer reviewed version

[Link to publication](#)

University of Bath

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Catalyst System Design for the Control of NO_x Using Hydrogen

David W. J. McClymont^a, Stan T. Kolaczowski^b, Kieran C. Molloy^c

^aDoctoral Training Centre ^bDepartment of Chemical Engineering ^cDepartment of Chemistry
Centre for Sustainable Chemical Technologies, University of Bath, BA2 2AY, UK.

E-mail: D.W.J.McClymont@bath.ac.uk: URL: <http://www.bath.ac.uk/csct>

1. What is NO_x?

- Nitric Oxides - highly reactive gases; primarily NO (>90 %) and NO₂
- Pollutants, involved in many atmospheric processes e.g. formation of smog
- Produced as a result of the high temperatures during combustion of fossil fuels
- Legislation is in place to reduce NO_x emissions




Figure 1 – Pd/Al₂O₃ monoliths





Figure 2 – 1 wt% Pd/Al₂O₃ pellets

3. H₂-SCR

- H₂ is already present in many systems e.g. diesel engines, biomass gasification combined heat and power (CHP) plants
- Could replace NH₃/urea processes:



Target Chemistry



- Removes the need for additional chemicals and their associated costs

2. Current De-NO_x Processes

- NH₃/urea-Selective Catalytic Reduction (SCR) is an efficient, established method



BUT it requires additional toxic chemicals:

- Intrinsic safety issues
- Extra system costs
- NH₃/urea infrastructure necessary

4. Catalyst

- Pd/Al₂O₃ catalyst prepared using an incipient wetness impregnation technique
- Supported on honeycomb monoliths (Figure 1)
 - Outer diameter = 14 mm
 - Channel size = 1 mm x 1 mm (x 80)
- Compared to commercially available 1 wt% Pd/Al₂O₃ pellets (Figure 2)
 - Diameter = 3 mm




Figure 3 – Experimental set-up

5. Experimental Conditions

- Gas composition supplied to catalysts:
 - 1000 ppm NO
 - 1000 ppm H₂
 - Air (12.5 % O₂) or N₂
- Temperature varied from 50-250 °C (Figure 3)

7. Conclusions

- In the absence of O₂, Pd/Al₂O₃ catalysts can effectively reduce NO_x using H₂
- However, Pd/Al₂O₃ strongly promotes the reaction between H₂ and O₂, even at low temperatures
- Conditioning of the catalyst may be necessary to achieve maximum activity
- Some selectivity of products was seen at varying temperatures

6. Experimental Results

