



Miskolc Mathematical Notes
Vol. 1 (2000), No 2, pp. 167-170

HU e-ISSN 1787-2413
DOI: 10.18514/MMN.2000.30

Solutions of a system of second-order ordinary differential equations

Kurt W. Tomantschger

SOLUTIONS OF A SYSTEM OF SECOND-ORDER ORDINARY DIFFERENTIAL EQUATIONS

KURT W. TOMANTSCHGER

Department of Mathematics, Technical University of Graz

Steyrergasse 30, A-8010 Graz, Austria

toman@weyl.math.tu-graz.ac.at

[Received March 24, 2000]

Abstract. A general solution of a coupled system of second-order ordinary differential equations is obtained. The solution is represented by modified Bessel functions of the first and second kind. The corresponding boundary conditions are also given. The boundary value problem describes the motion of a micropolar suspension between two coaxial cylinders, and the two unknown functions are, respectively, the velocity and the velocity of microrotation of the micropolar theory.

Mathematical Subject Classification: 34B05, 33C10

Keywords: Coupled linear ordinary differential equations, modified Bessel functions, MacDonald functions

1. Introduction

Classical continuum mechanics is not sufficient to describe the behaviour of certain materials (granular materials, fluid suspensions, liquid crystals, blood flow, polymeric substances, composite materials, etc.). For this reason the continuum with microstructure was introduced [1]. The new model is called the micropolar continuum, and it possesses two independent kinematic quantities: the velocity vector \vec{v} (macromotion) and the spin, or microrotation vector $\vec{\nu}$.

Since 1965, the micropolar theory has attracted a great deal of attention.

Paper [2] considers the stationary motion of a suspension between two coaxial cylinders. The inner cylinder with the radius R_1 is immobile, while the outer one with the radius R_2 ($R_2 > R_1$) rotates with angular velocity Ω . The axis of rotation is horizontal.

Applying the basic relations and balance laws of micropolar theory, the following result was obtained: The behaviour of the micropolar suspension between the two coaxial cylinders is described by the system of the following two coupled differential equations [2]:

$$(\mu + k)[r^2 v'' + rv' - v] - kr^2 \nu' = 0, \quad (1)$$

$$\gamma [r\nu'' + \nu'] + k(vr)' - 2kr\nu = 0, \quad R_1 \leq r \leq R_2. \quad (2)$$

Hence, $v(r)$ represents the velocity of the suspension (macromotion); $\nu(r)$ is the microrotational velocity r is one of the coordinates of the cylindrical system; γ , μ , and k denote viscosity coefficients of the micropolar continuum (they are positive constants).

We treat this kind of motion of suspension when the suspension flows down the walls of the cylinders, so that the boundary conditions for the velocity $v(r)$ and the microrotation velocity $\nu(r)$ are

$$v(R_1) = 0, \quad v(R_2) = \Omega R_2 \quad \text{and} \quad \nu(R_1) = 0, \quad \nu(R_2) = 0. \quad (3)$$

In this paper, the general solution $v(r)$ and $\nu(r)$ of the differential equations (1) and (2) are determined. The arbitrary constants of this solution are calculated on the basis of the boundary conditions (3). Finally, we show, that in a special case, we obtain from our result the same velocity $v(r)$ which we would have got if we solved this technical problem taking into account the laws of classical physics.

2. Solution of the coupled system

After multiplying (2) by r , the terms in the brackets of (1) and (2) are brought to the form $r^n y^{(n)}$, $y = y(r)$. These expressions may be reduced to derivatives with constant coefficients if we substitute

$$r = R_2 e^{-t}, \quad \text{resp.} \quad t = \ln R_2 - \ln r. \quad (4)$$

If the change of variable (4) is applied to $v(r)$ and $\nu(r)$, we determine the resulting functions

$$V(t) = v(R_2 e^{-t}) = v(r) \quad \text{and} \quad U(t) = \nu(R_2 e^{-t}) = \nu(r). \quad (5)$$

Substituting (4), (5), $rv' = -\dot{V}$, $r^2 v'' = \ddot{V} + \dot{V}$ and the analogous ν derivatives into equations (1) and (2) then multiplying by r , we obtain

$$\ddot{V} - V = -kR_2(\mu + k)^{-1} e^{-t} \dot{U}, \quad (6)$$

$$\ddot{U} - 2k\gamma^{-1} R_2^2 e^{-2t} U = k\gamma^{-1} R_2 e^{-t} (\dot{V} - V). \quad (7)$$

After multiplying the above equation by $\gamma e^t / (kR_2)$ and differentiating it, we have

$$\dot{V} - V = \frac{\gamma}{kR_2} e^t \ddot{U} - 2R_2 e^{-t} U, \quad \ddot{V} - \dot{V} = \frac{\gamma}{kR_2} \frac{d(e^t \ddot{U})}{dt} - 2R_2 \frac{d(e^{-t} U)}{dt}. \quad (8)$$

These two equations and equation (6) are a system of three independent differential equations. Consequently, V , \dot{V} and \ddot{V} can be eliminated. In this way we obtain

$$\ddot{U} + 2\dot{U} - M^2 e^{-2t} U = 0, \quad M = \left[\frac{k}{\gamma} \left(\frac{2\mu + k}{\mu + k} \right) \right]^{1/2} R_2. \quad (9)$$

Suppose the Laplace transform of $U(t)$ is denoted by $\Upsilon(s)$. Then we take the Laplace transform of both sides of equation (9). Dividing the transformed equation by $s^2(s+2)$, then using the method of partial fraction and taking into account the boundary conditions $U(0) = \nu(R_2) = 0$, we get

$$\Upsilon(s) - \frac{M^2}{s^2} \Upsilon(s+2) = \frac{1}{s^2} \dot{U}(0) + \left(-\frac{1}{4s} + \frac{1}{2s^2} + \frac{1}{4(s+2)} \right) \ddot{U}(0).$$

Applying to this relation the inverse Laplace transform on this relation, we obtain the integral equation

$$U(t) - M^2 \int_0^t \int_0^{t_1} e^{-2t_2} U(t_2) dt_2 dt_1 = t \dot{U}(0) + [-1 + 2t + e^{-2t}] \frac{\ddot{U}(0)}{4}.$$

Introducing the new variables

$$t_1 = \ln(M/x_1), \quad t_2 = \ln(M/x_2), \quad t = \ln(M/x) \tag{10}$$

and setting

$$w(\xi) = U[\ln(M/\xi)]$$

we bring the integral equation to the form

$$w(x) - \int_M^x \int_M^{x_1} x_2 w(x_2) dx_2 \frac{dx_1}{x_1} = \ln\left(\frac{M}{x}\right) \dot{U}(0) + [-1 + 2 \ln \frac{M}{x} + \frac{x^2}{M^2}] \frac{\ddot{U}(0)}{4}.$$

If we apply to the transformed integral equation the differential operator $d/dx (x d/dx)$, we obtain the modified inhomogeneous Bessel equation with zero order

$$xw'' + w' - xw = xM^{-2}\ddot{U}(0), \quad w = w(x).$$

The general solution of this differential equation is defined by

$$w(x) = C_1 I_0(x) + C_2 K_0(x) - M^{-2} \ddot{U}(0). \tag{11}$$

I_n (resp. K_n) is called the *modified Bessel function of the first* (resp., *second kind*) of order n . K_n is also known as *MacDonald function*.

Substituting $x = Me^{-t}$ (see (10)) and (11) into the first equation (8), we get

$$x\tilde{V}'(x) + \tilde{V}(x) = \frac{kR_2}{\mu + k} \frac{x}{M} (C_1 I_0(x) + C_2 K_0(x)) - 2R_2 \frac{x}{M^3} \ddot{U}(0). \tag{12}$$

By variation of constants we obtain a particular solution of the form $\tilde{V}_p = C(x)x^{-1}$. The general solution of equation (7) (resp. (12)) is now explicitly expressed:

$$\tilde{V} = -\frac{R_2}{M^3} \ddot{U}(0) x + C_3 \frac{1}{x} + \frac{kR_2}{\mu + k} \frac{1}{M} (C_1 I_1(x) - C_2 K_1(x)). \tag{13}$$

Substituting $e^{-t} = x/M$ into (4), using (5), $x = Me^{-t}$, (11) and (13), we find

$$v = -\frac{\ddot{U}(0)}{M^2} r + \tilde{C}_3 \frac{1}{r} + \frac{k}{\mu + k} \frac{1}{N} (C_1 I_1(Nr) - C_2 K_1(Nr)), \quad (14)$$

$$\nu = C_1 I_0(Nr) + C_2 K_0(Nr) - \frac{\ddot{U}(0)}{M^2}, \quad N = M/R_2. \quad (15)$$

These two functions satisfy equations (1) and (2) identically. To determine the arbitrary constants, we apply the boundary conditions (3) to (14) and (15). This yields

$$\begin{aligned} C_1 &= \frac{\Omega R_2^2}{H} [K_0(a_2) - K_0(a_1)], & C_2 &= \frac{\Omega R_2^2}{H} [I_0(a_2) - I_0(a_1)], \\ \frac{\ddot{U}(0)}{M^2} &= \frac{\Omega R_2^2}{H} [I_0(a_1)K_0(a_2) - I_0(a_2)K_0(a_1)], & a_j &= NR_j, \quad j = 1, 2, \\ \tilde{C}_3 &= \frac{\Omega R_1 R_2^2}{H} (I_1(a_1)[K_0(a_1) - K_0(a_2)] + K_1(a_1)[I_0(a_1) - I_0(a_2)] + \\ &\quad + R_1 [I_0(a_1)K_0(a_2) - I_0(a_2)K_0(a_1)]), \\ H &= (R_1^2 - R_2^2)[I_0(a_1)K_0(a_2) - I_0(a_2)K_0(a_1)] + [K_0(a_1) - K_0(a_2)] * \\ &\quad * [R_1 I_1(a_1) - R_2 I_1(a_2)] + [I_0(a_1) - I_0(a_2)][R_1 K_1(a_1) - R_2 K_1(a_2)]. \end{aligned}$$

3. Conclusion

The classic case of suspension motion is obtained if the material constant k of the micropolar suspension is equal to zero. In that case, the relation for the velocity of suspension motion is reduced to the well-known form

$$v = \frac{\Omega}{R_2^2 - R_1^2} \left[R_2^2 r - \frac{R_1^2 R_2^2}{r} \right]; \quad \nu = 0.$$

REFERENCES

- [1] ERINGEN, A.C. and SUHUBI, E.S.: *Nonlinear theory of simple microelastic solids*, Int. J. Engng. Sci., **2** (1964), 189-202.
- [2] CVETKOVIĆ, P., TOMANTSCHGER, K.W., KUZMANOVIĆ, D. and GOLUBOVIĆ, Z.: *The motion of a suspension between two coaxial cylinders*, Facta Universitatis, in press.
- [3] ERINGEN, A.C.: *Simple microfluids*, Int. J. Engng. Sci., **2**, (1964), 205-217.
- [4] TOMANTSCHGER, K.W., CVETKOVIĆ, P., KUZMANOVIĆ, D. and GOLUBOVIĆ, Z.: *Solving the problem of motion of a micropolar suspension*, ZAMM, in press.