

Oral presentation

Open Access

Neural networks with small-world topology are optimal for encoding based on spatiotemporal patterns of spikes

Petra E Vertes*¹ and Tom Duke²

Address: ¹Cavendish Laboratory, University of Cambridge, Cambridge, CB3 0HE, UK and ²London Centre for Nanotechnology, University College London, London, WC1H 0AH, UK

Email: Petra E Vertes* - pv226@cam.ac.uk

* Corresponding author

from Eighteenth Annual Computational Neuroscience Meeting: CNS*2009
Berlin, Germany. 18–23 July 2009

Published: 13 July 2009

BMC Neuroscience 2009, **10**(Suppl 1):O11 doi:10.1186/1471-2202-10-S1-O11

This abstract is available from: <http://www.biomedcentral.com/1471-2202/10/S1/O11>

© 2009 Vertes et al; licensee BioMed Central Ltd.

Despite a wealth of knowledge at the micro- and macroscopic scales in neuroscience, the way information is encoded at the mesoscopic level of a few thousand neurons is still not understood. Polychronization is a newly proposed [1] mechanism of neuronal encoding that attempts to bridge this gap and that has been suggested to underlie a wide range of cognitive phenomena, from associative memory to attention and cross-modal binding. This encoding is based on millisecond-precision spatiotemporal firing patterns, corresponding to so-called polychronous groups, that have been shown to emerge spontaneously in networks of spiking neurons with axonal conduction delays and spike-timing-dependent plasticity.

Here, we investigate the effect of network topology on the ease and reliability with which input stimuli can be distinguished by such a network based on their encoding in the form of polychronous groups. We find that, while scale-free networks are unreliable in their performance, small-world and modular architectures perform an order of magnitude better than random networks at such discrimination tasks in a variety of situations. Furthermore, we find that these topologies introduce biologically realistic constraints on the optimal input stimuli for the system, performing best with inputs consistent with the topographic organization known to exist in many cortical areas. Finally, we investigate the capacity of such networks to distinguish between signals involving overlapping sets of input neurons and suggest that, for optimal perform-

ance, the network should be locally as well as globally small-world but should only show large-scale modularity.

These topological constraints on both networks and stimuli seem consistent with the first experimental findings on the cortical network architecture (see review [2] and references therein), suggesting that these are optimal for information processing through polychronization.

Acknowledgements

We thank Eugene Izhikevich and Danielle Bassett for helpful advice and discussion.

References

1. Izhikevich E: **Polychronization: computation with spikes.** *Neural Computation* 2006, **18**:245-282.
2. Bassett D, Bullmore E: **Small-world brain networks.** *The Neuroscientist* 2006, **12**:512-523.