

**Engineering Conferences International
ECI Digital Archives**

Ultra-High Temperature Ceramics: Materials For
Extreme Environmental Applications II

Proceedings

Spring 5-14-2012

Microstructure, tribological response, and mechanical properties of fiber bonded silicon carbide ceramics

M.C. Vera
Universidad de Sevilla

J. Ramirez
Universidad de Sevilla

J. Martinez
Universidad de Sevilla

M. Singh
Ohio Aerospace Institute


Follow this and additional works at: <http://dc.engconfintl.org/uhtc>

 Part of the [Materials Science and Engineering Commons](#)

Recommended Citation

M.C. Vera, J. Ramirez, J. Martinez, and M. Singh, "Microstructure, tribological response, and mechanical properties of fiber bonded silicon carbide ceramics" in "Ultra-High Temperature Ceramics: Materials For Extreme Environmental Applications II", W. Fahrenholtz, Missouri Univ. of Science & Technology; W. Lee, Imperial College London; E.J. Wuchina, Naval Service Warfare Center; Y. Zhou, Aerospace Research Institute Eds, ECI Symposium Series, (2013). <http://dc.engconfintl.org/uhtc/30>

This Conference Proceeding is brought to you for free and open access by the Proceedings at ECI Digital Archives. It has been accepted for inclusion in Ultra-High Temperature Ceramics: Materials For Extreme Environmental Applications II by an authorized administrator of ECI Digital Archives. For more information, please contact franco@bepress.com.



MICROSTRUCTURE, TRIBOLOGICAL RESPONSE, AND MECHANICAL PROPERTIES OF FIBER BONDED SILICON CARBIDE CERAMICS

M. C. Vera¹, J. Ramírez-Rico¹, J. Martínez-Fernandez¹, M. Singh²


¹Dpto. Física de la Materia Condensada-ICMS

Universidad de Sevilla-CSIC, Sevilla, Spain


²Ohio Aerospace Institute, Cleveland, OH




Fiber bonded Silicon carbide Ceramics



Sheets of Si-Al-C-O
amorphous fibers



SA-Tyrannohex™
(Ube Industries, Ltd.)




Hot-pressing

Fiber bonded SiC ceramics

14 May 2012_1

Microstructure





Main Results

Microstructural Stability:

- Thermal treatments in vacuum at temperatures ranging 1400-2000°C during 5-30 h

Mechanical Properties:

- Hardness
- Tribological response



Thanks

