


ENVIRONMENTALLY SUSTAINABLE BIOFUELS - BIODIESEL

P.T. Vasudevan
Chemical Engineering Department
University of New Hampshire
USA


Rio de Janeiro, 2009 3/12/2009

World Oil Production (million barrels per day)






U.S. Power Generation





Non-OPEC Countries



How much oil and gas is really left?

- EIA estimates that in 2025, countries around the globe will still have more than 900 billion barrels of oil remaining to be discovered. EIA estimates total world oil resources at more than 2.9 trillion barrels of oil.
- Demand is expected to rise to 119 million barrels per day. Oil can be expected to last another 65 years.




WHAT ARE WE FORGETTING?

- Assume we have 85 more years of oil.
- Assume we are sold on the notion of energy security and independence.
- Are we forgetting something?





The Wedge Concept




The Wedge Concept

- End-user efficiency and conservation
 - Increase fuel economy of 2 billion cars from 30 to 60 mpg
- Power Generation
 - Raise efficiency of coal-fired plants
- Carbon Capture and Storage
 - Install CCS in coal-fired power plants (IGCC)
- Alternative Energy Sources
- Agriculture and Forestry
 - Stop deforestation




Managing the Climate Problem

Each wedge represents a reduction of 25 billion tons in 50 years



Cumulative Amount of CO₂

Each ppm of CO₂ corresponds to a total of 2.1 billion tons of atmospheric CO₂



Background

- ▶ Due to diminishing petroleum reserves and the deleterious environmental consequences of exhaust gases from petroleum diesel, biodiesel has attracted attention during the past few years as a renewable and environmentally friendly fuel.
- ▶ Biodiesel is made entirely from vegetable oil or animal fats; hence it is renewable and biodegradable.



Properties

- ▶ Biodiesel contains very little sulfur, polycyclic aromatic hydrocarbons, and metals. Diesel fuels can contain up to 20% polycyclic aromatic hydrocarbons.
- ▶ Biodiesel is most often blended with petroleum diesel in ratios of 2 percent (B2), 5 percent (B5), or 20 percent (B20). It can also be used as pure biodiesel (B100).



United Nations Report

“The global rush to switch from oil to energy derived from plants will drive deforestation, push small farmers off the land and lead to serious food shortages and increased poverty unless carefully managed.”




Current Technology

- The majority of biodiesel today is produced by alkali-catalyzed transesterification with methanol, which results in a relatively short reaction time.
- However, free fatty acids and water in this feedstock results in the production of soap. Thus, additional steps to remove any water and either the free fatty acids or soap from the reaction mixture are required.



Transesterification Reaction



Fatty Acid + Alcohol \longrightarrow Fatty acid ester + Water



Challenges

- Produce triglyceride feedstock in sufficient quantities and economical prices.
- Develop better catalysts.
- Resolve the “glycerol saturation” problem
- Improve the source of mono-hydroxy alcohol used for transesterification



Feedstock for Biodiesel Production

- Current biofuels are produced with yields on the order of 50 to a few hundred gallons per acre-year (~60 gallons per acre-year for soy-biodiesel, about twice that for canola biodiesel.)
- US Gasoline demand is 140 billion gals per year (or energy equivalent of 200 billion gals ethanol). Diesel demand is about half. Current US demand for diesel would require 1 billion acres of soy farming!
- Soybeans yield soy meal that is heavily used in both human foods, and to a greater extent, animal feed.



Biodiesel Production

- US production increased from 250 million gallons in 2006 to 450 million gallons (1.5 million tons) in 2007 – an increase of 55.6%.
- European countries produced 1.5 billion gallons (4.9 million tons) with Germany producing 790 million gallons (2.7 million tons) in 2007
- Total demand for diesel in the US and Europe – 490 million tons (147 billion gallons). Total world production of vegetable oil for all purposes in 2005/06 was about 110 million tons, with about 34 million tons each of palm oil and soybean oil.




Alternate feedstocks

- Non-edible sources like *Jatropha curcas*, *Pongamia*, Castor, Sal etc. Focus is on crops that grow in sandy soils – greening the desert. *Jatropha* trees can capture four tons of carbon dioxide per acre and the fuel emits negligible greenhouse gases. Some varieties of *Jatropha* can produce 1600 gals per acre year – Roy Beckford
- Waste oil – restaurant grease.
- Animal fats including tallow, lard, yellow grease, chicken fat, and the by-products of the production of Omega-3 fatty acids from fish oil.
- Oil from halophytes such as *salicornia bigelovii*, which can be grown using saltwater in coastal areas where conventional crops cannot be grown, with yields equal to the yields of soybeans grown using freshwater irrigation

- Microalgae



Photosynthetically Available Radiation



Photosystems in plants are made of an antenna of photosynthetic pigments, leading to a chemical reaction center. Only a portion of the spectrum of light from the sun can be used by the pigments. PAR, the spectrum of light usable by pigments is roughly the same as the visible light spectrum.

Photosynthetically active region accounts for 43% of the solar energy reaching the earth's surface. It takes 8 photons to split a water molecule and CO₂ molecule to make a base carbohydrate, CH₂O.

Average energy of PAR photon is 2.25 eV and the overall efficiency of converting the energy in the photons to chemical energy in the carbohydrates is 27%.

Photosynthesis

- In the US, the average daily incident solar energy (across the entire spectrum) reaching the earth's surface ranges from 12,000-22,000 kJ/m²
- Chemical process efficiency ~27%, max photosynthetic efficiency ~11.6% - equivalent to 28,000 gge/acre-year (assuming 100% conversion of algae biomass to biodiesel).
- Water and nutrient limitations, photosaturation, and photorespiration limit avg. photosynthetic efficiency of terrestrial plants to <1%.



Microalgae

- Potential for significantly higher average photosynthetic efficiency due to their aquatic environment providing them with better access to water, CO₂, and nutrients .
- Algae produce their highest oil concentrations when stressed – in particular due to nutrient restriction.
- Algae strains with higher oil content grow slower than lower oil content strains. The result is that open systems inoculated initially with a high oil algae are rapidly taken over by native low oil strains.
- Also, the desired goals of high reproduction rate and high oil yield are mutually exclusive.



Photobioreactors

- Prevention of culture collapse or take over by low oil strains can be accomplished through photobioreactors. However, they are expensive.
- A source of CO₂ rich air is needed. Combine with aerobic or anaerobic digestors?
- Hybrid approach of Huntley and Redalje appears to be attractive.
- Genetic engineering of Acetyl-CoA carboxylase - enzyme that regulates fatty acid synthesis to enhance enzyme activity



Economics of Algal Biodiesel

- Photobioreactors essential to achieve high oil content.
- PETC Study in open ponds – Assumes 40% oil content with biomass production of 30 g/m²-day using flue gas CO₂. This puts the cost at \$67/bbl
- Problem is 40% is too high! Reducing nutrients would result in lower biomass yields. Huntley and Redalje extrapolated the cost with their system to \$84/bbl.



Challenges

- Produce triglyceride feedstock in sufficient quantities and economical prices.
- Develop better catalysts.
- Resolve the “glycerol saturation” problem
- Improve the source of mono-hydroxy alcohol used for transesterification



Catalyst Systems

- ZrO_2 , ZnO , and $\text{KNO}_3/\text{ZrO}_2$ are some solid catalysts that have been studied.
- Sulfonated catalysts derived from amorphous carbon.
- Zinc and calcium oxides, calcium and barium acetates, Mg-Al hydrotalcites, NaX faujasites, titanosilicate structure-10, calcium carbonate rock, tungstated zirconia-alumina. Almost all of the catalysts require temperatures in excess of 200°C to achieve conversions greater than 90% within the time scale of the experiment.
- Mesoporous silica multifunctionalized with both organosulfonic acid and hydrophobic organic groups such as allyl and phenyl has been shown to be effective.

Enzyme Catalyzed Transesterification

- New biochemical routes to biodiesel production, based on the use of enzymes, have become very interesting.
- Most of the research has focused on the use of virgin oils such as rice bran oil, canola, sunflower oil, soybean oil and castor oil.
- Emphasis should be on waste oil.
- Advantage of enzyme transesterification is that there is **no soap** formation.



Objectives of Enzyme Catalysis


- ▶ Ensure that enzyme retains activity
- ▶ Minimize enzyme denaturation
- ▶ Evaluate long-term performance
- ▶ Investigate used-oil utilization
- ▶ Scale-up and kinetics



Waste Oil Studies




Effect of Molar Ratio on Yield



60C, 150 rpm, 500 U enzyme




Effect of Stepwise Addition on Yield




150 rpm, 500 U enzyme, 40C




Step-wise Addition of Methanol




Effect of Mixing Speed on Yield




Effect of Temperature



Effect of Solvent/Acyl Acceptor



Effect of Enzyme Reutilization



Results from Enzyme Studies

- External mass transfer resistance is insignificant at 150 rpm
- The relatively small difference in yields at the beginning of the reaction is followed by a much larger difference in yields at the two temperatures as the reaction proceeds.
- In the case of step-wise addition of methanol, the productivity was substantially higher compared to the 'single-addition' runs, with an average value of 1.3×10^{-5} g biodiesel/U-h.



Challenges

- Produce triglyceride feedstock in sufficient quantities and economical prices.
- Develop better catalysts.
- Improve the source of mono-hydroxy alcohol used for transesterification
- Resolve the “glycerol saturation” problem



The Choice of Acyl Acceptor and Solvent

- Solvent/ acyl acceptor should be from a renewable source
- Enzyme activity in organic media is correlated with solvent hydrophobicity. Generally, highest activities are found at high log P (>2) values.
- Methanol has poor solubility in hydrophobic solvents resulting in deactivation of the enzyme.
- Use a combination of solvents, that is co-solvents that results in better distribution of methanol.



Solvent Engineering Studies

- Preliminary screening based on solvent characteristics and reaction conditions.
- $\log P$ – Solvents with low $\log P$ exhibit strong hydrophilicity triggering enzyme deactivation.
- Typical reaction temperature 35-45C. Thus solvents with low boiling point such as dimethyl ether, pentane etc. were eliminated.
- Viscosity – Dynamic viscosity of biodiesel is 4-6 cP at 20-40C. Desirable solvent viscosity is < 4 cP. Thus solvents in the alcohol group with carbon number > 5 were not considered.



Challenges

- Produce triglyceride feedstock in sufficient quantities and economical prices.
- Develop better catalysts.
- Improve the source of mono-hydroxy alcohol used for transesterification
- Resolve the “glycerol saturation” problem



Glycerol Conversion to Methanol

- Ongoing research to convert glycerol to 1,3-propanediol, 1,2-propanediol, propylene glycol etc.
- Solvay's epichlorohydrin process - Epicerol
- Cost of methanol required for transesterification is high.
- Aqueous phase reforming (ACR) of glycerol over Pt catalyst $C_3H_5(OH)_3 \rightarrow 3CO + 4H_2$ at 600K followed by
 - $CO + 2H_2 \rightarrow CH_3OH$ over Cu/ZnO catalyst
 - More research is needed to develop better catalysts



Acknowledgements

Current and Former Students

- Fernando Sanchez
- Robert Coggon
- Xiangping Shen
- Michael Briggs
- Boyi Fu

