

## Engineering Conferences International ECI Digital Archives

---

Composites at Lake Louise (CALL 2015)

Proceedings

---

Fall 11-9-2015

# Bicontinuous networks of metal and elastomer for shape morphing composites

Robert Sheperd

Cornell University, [rfshepherd@gmail.com](mailto:rfshepherd@gmail.com)

Follow this and additional works at: [http://dc.engconfintl.org/composites\\_all](http://dc.engconfintl.org/composites_all)

 Part of the [Materials Science and Engineering Commons](#)

---

### Recommended Citation

Robert Sheperd, "Bicontinuous networks of metal and elastomer for shape morphing composites" in "Composites at Lake Louise (CALL 2015)", Dr. Jim Smay, Oklahoma State University, USA Eds, ECI Symposium Series, (2016). [http://dc.engconfintl.org/composites\\_all/36](http://dc.engconfintl.org/composites_all/36)

This Conference Proceeding is brought to you for free and open access by the Proceedings at ECI Digital Archives. It has been accepted for inclusion in Composites at Lake Louise (CALL 2015) by an authorized administrator of ECI Digital Archives. For more information, please contact [franco@bepress.com](mailto:franco@bepress.com).

## BICONTINUOUS NETWORKS OF METAL AND ELASTOMER FOR SHAPE MORPHING COMPOSITES

Robert Shepherd  
Cornell University  
USA

[rfpshepherd@gmail.com](mailto:rfpshepherd@gmail.com)

A composite of two entangled foams—silicone and a low melting temperature eutectic metal alloy will be presented. At room temperature, the material is stiff and thin sections (~1 cm) can handle loads in bending excess of 0.5 kg. Above 60°C, the melting temperature of the metal ( $T_m$ ), the composite is rubbery and can undergo large deformation according to the properties of the elastomer foam. We have demonstrated this change in mechanical properties using standard mechanical testing techniques. Exploiting the dramatic tunability in stiffness, we have demonstrated that this material can: 1) vary in stiffness dramatically 1) take on multiple configurations, 2) be preprogrammed with shape memory, 3) heal with application of heat, and 4) be assembled into larger continuous structures from smaller sub-components.